MIL-F-80057C
5 August 1981
SUPERSEDING
MIL-F-80057B
23 January 1976

MILITARY SPECIFICATION

FORMING MACHINES, SHEET METAL, CLEAT AND LOCK FORMING

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers electric motor driven, sheet metal, cleat and lock forming machines of the progressive forming roll type.

1.2 Classification. This specification covers machines of the following types and classes and of the sizes specified in tables I and II. The type, class, and size supplied shall be as specified (see 6.2.1).

Type I - Machines with built-in lock rolls and single extended shafts for mounting auxiliary rolls

Class 1 - Built-in Pittsburgh lock rolls
Class 2 - Built-in Snap lock rolls

Type II - Machines with built-in cleat rolls and double extended shafts for mounting auxiliary rolls

Class 1 - Built-in drive cleat rolls
Class 2 - Built-in "S" cleat rolls

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Defense Industrial Plant Equipment Center, Memphis, Tennessee 38114, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or letter.

FSC 3441

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:35Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 Military publications. The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

STANDARDS

FEDERAL

FED-STD-H28 - Screw Thread Standards for Federal Services

MILITARY

MIL-STD-1188 - Commercial Packaging of Supplies and Equipment

(Copies of specifications, standards, drawings, and the publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on the date of invitation for bids or request for proposal shall apply.

U. S. DEPARTMENT OF LABOR

OSHA 2206 - General Industry, OSHA Safety and Health Standards (29 CFR 1910)

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington,DC 20402.)

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA)

NFPA No. 79 - Electrical Standard for Metalworking Machine Tools

(Application for copies should be addressed to the National Fire Protection Association, 470 Atlantic Avenue, Boston, MA 02210.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:35Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2.1), the contractor shall furnish a sample unit for first article inspection and approval (see 4.2 and 6.2.1).

3.2 Design. The machine shall be new and one of the manufacturer's current models, capable of forming cleat and lock forms in sheet metal of the gauge shown as capacity and at the required speeds shown in tables I and II. The machine shall be designed to progressively form the cleat and lock forms as the sheet metal passes from one roll station to the next. The built-in, or inboard rolls, shall be considered the primary rolls of the machine and shall be capable of forming sheet metal shown as capacity in the built-in rolls section of tables I and II. The auxiliary, or outboard, rolls shall be capable of forming sheet metal shown as capacity in the auxiliary rolls section of table I and II. The machine shall include all components, parts, and features necessary to meet the performance requirements specified herein. All parts subject to wear, breakage, or distortion shall be accessible for adjustment, replacement or repair.

3.2.1 Safety and health requirements. Covers, guards, or other safety devices shall be provided for all parts of the machine that present safety hazards. The safety devices shall not interfere with operation of the machine. The safety devices shall prevent unintentional contact with the guarded part, and shall be removable to facilitate inspection, maintenance and repair. All machine parts, components, mechanisms, and assemblies furnished on the machine, whether or not specifically required herein, shall comply with all of the requirements of OSHA that are applicable to the machine itself. Additional safety and health requirements shall be as specified (see 6.2.1 and 6.3).

3.2.2 Controls. All operating controls shall be located convenient to the operator at his normal work station.

3.2.3 Lubrication. Means shall be provided to insure adequate lubrication for all moving parts. Each recirculating system, when used, shall include a filter which is cleanable or replaceable. Each lubricant reservoir, when used, shall have means for determing fluid level. All oil holes, grease fittings and filler caps shall be accessible.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:35Z
Check the source to verify that this is the current version before use.

3.2.4 Interchangeability. To provide for replacement of worn parts, all parts shall be manufactured to definite dimensions and tolerances which will permit installation of replacement parts without modification of part or machine.

3.2.5 Reclaimed materials. The machine shall contain reclaimed materials to the maximum extent possible without jeopardizing its intended use and performance. The reclaimed materials shall have been reprocessed, remanufactured, or recycled in a manner which restores them to the same chemical composition and physical properties as the materials originally selected for use on the machine. Reclaimed materials shall include iron, steel, copper, brass, aluminum, fiber products, plastics, and elastomers that have been collected from discarded solid, liquid, semi-solid, or gaseous waste such as garbage, refuse, or sludge.

3.3 Construction. The machine shall be constructed of parts which are new, without defects, and free of repair. The structure shall be capable of withstanding all forces encountered during operation of the machine to its maximum rating and capacity without permanent distortion.

3.3.1 Castings and forgings. All castings and forgings shall be free of scale and mismatching. No process such as welding, peening, plugging, or filling with solder or paste shall be used for reclaiming any defective part.

3.3.2. Welding, brazing, or soldering. Welding, brazing, or soldering shall be employed only where specified in the original design. None of these operations shall be employed as a repair measure for any defective part.

3.3.3 Fastening devices. All screws, pins, bolts and other fasteners shall be installed in a manner to prevent change of tightness. Those subject to removal or adjustment shall not be swaged, peened, staked, or otherwise permanently installed.

3.3.4 Surfaces. All surfaces shall be cleaned and free of sand, dirt, fins, sprues, flash, scale, flux and other harmful or extraneous materials. All edges shall be either rounded or beveled unless sharpness is required to perform a necessary function. Except as otherwise specified herein, the condition and finish of all surfaces shall be in accordance with the manufacturer's standard commerical practice.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:35Z
Check the source to verify that this is the current version before use.

3.3.5 Painting. Unless otherwise specified (see 6.2.1), the machine shall be painted in accordance with the manufacturer's standard commercial practice.

3.3.6 Threads. All threaded parts used on the machine and its related attachments and accessories shall conform to FED-STD-H28 and the applicable "Detailed Standard" section referenced therein.

3.3.7 Plates. All words on instruction and indicating plates shall be in the English language. Characters shall be engraved, etched, embossed, or stamped in boldface on a contrasting background and the plate shall be securely affixed to the machine.

3.3.8 Gears. All gears shall be constructed of a material suitable for their application. Gears shall be applied in a manner to preclude either premature damage, wear or failure.

3.4 Components. The machines covered herein shall consist basically of the components described in 3.4.1 through 3.4.4.1. Any additional components necessary to the operation of the machine shall be furnished to the manufacturer's standard design and specifications.

3.4.1 Base. The machine shall have a cabinet style base constructed to support the top plate and forming head and shall enclose the drive motor and drive mechanism. Means shall be provided in the base for securely fastening the machine to the floor or a foundation.

3.4.2 Top plate. The top plate shall be mounted to the top of the cabinet style base and shall serve as a working surface and for mounting the entrance and exit guides, and other accessories used in aligning the workpiece with the forming rolls.

3.4.2.1 Guides. The machine shall have entry guides to align the sheet metal workpiece with the entry end of the forming rolls. The machine shall also have exit guides that guide the workpiece as it leaves the exit end of the forming rolls. The guides shall have all necessary adjustments required to maintain alignment of workpiece with the forming head assembly.

3.4.3 Forming head assembly. The machine shall have a forming head assembly capable of producing the cleat and lock forms listed in tables I and II, as applicable to the machine being procured. The forming head assembly shall consist essentially of rolls, roll shafts, bearings, roll shaft support plates, roll drive system, and related adjusting mechanisms.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:35Z
Check the source to verify that this is the current version before use.

3.4.3.1 Built-in rolls. The machine shall have a set of built-in rolls capable of forming the "built-in roll" profiles required by tables I and II, as applicable, for the type, class and size machine being procured. The set of built-in rolls shall consist of a series of mating upper and lower rolls that are contoured to progressively form the required profile as a sheet metal workpiece is fed from one pair of rolls to the next pair. The rolls shall have adequate strength to withstand all forces encountered while the machine is forming the rated capacity thickness of sheet metal specified in tables I and II, as applicable. The built-in rolls shall be mounted on the center section of the roll shafts between the roll shaft support plates.

3.4.3.2 Auxiliary rolls. The machine shall have provision for mounting and utilizing auxiliary rolls capable of forming all of the "auxiliary roll" profiles required by tables I and II for the type, class and size machine being procured. It shall be possible to install and remove the auxiliary rolls without disturbing the built-in rolls. The auxiliary rolls shall conform to all the requirments specified in 3.4.3.1 for built-in rolls with the following exceptions. The auxiliary rolls shall be mounted on shaft extensions that project beyond the sides of the roll shaft support plates. All auxiliary rolls shall be permanently and legibly marked to indicate the position in which they are installed on the machine. All of the types of auxiliary rolls specified in tables I and II, for the type, class, and size machine being procured, shall be available from the machine manufacturer. When specified (see 6.2.1), a complete set of auxiliary rolls of the type specified shall be furnished with the machine.

3.4.3.3 Roll shafts. Each built-in roll shall have a shaft that supports the roll and its drive gear (see 3.4.3.6). The shafts shall have adequate strength to withstand all forces encountered while the machine is forming the rated capacity thickness of sheet metal specified in tables I and II. The section of the shafts between the shaft support plates shall support the built-in rolls and the roll drive gears. The shafts, rolls, and gears shall have either splines or keys that allow full motor torque to be transmitted to the rolls and gears. On type I machines, one end of all shafts shall extend beyond the shaft support plates to allow a set of auxiliary rolls to be installed. On type II machines, the roll shafts shall have extensions on both ends to allow two sets of auxiliary rolls to be installed onto the extensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:35Z
Check the source to verify that this is the current version before use.

The shaft extension shall have either splines or keys that prevent the rolls from rotating on the shaft extensions. The shaft extensions shall also have suitable means for securely holding the auxiliary rolls onto the shaft extensions.

3.4.3.4 Bearings. All roll shafts and idler gears shall be supported by ball, roller or needle bearings. Needle bearings, if utilized, shall be of a type having a cup, or cage, that serves as a roller retainer and race.

3.4.3.5 Roll shaft support plates. The upper roll shafts shall be supported on a pair of upper roll shaft support plates, and the lower roll shafts shall be supported on a pair of lower roll shaft support plates. The support plates shall be adequate in strength to withstand all forces encountered while the machine is operating at its full rated capacity. The support plates shall accept the roll shaft bearings and idler gear shafts and hold all bearings, shafts, idler gears, and rolls in alignment. The upper support plates shall be attached to the lower support plates in a manner that allows the upper rolls to be positioned closer to or farther away from the lower rolls to allow workpiece thickness variation and for increasing and decreasing workpiece feed force. The adjusting mechanism shall have means for locking.

3.4.3.6 Roll drive system. The machine shall be powered by an electric motor conforming to 3.4.4.1 and table I or II, as applicable. The electric motor shall either power a belt drive, chain drive, or a gear train. If a belt or chain drive is utilized, means shall be provided for adjusting and maintaining proper belt or chain alignment and tension. The forming head shall have a gear train that drives each upper and lower roll in a direction that will feed the sheet metal workpiece into the entry end and out of the exit end of the machine.

3.4.3.7 Adjusting mechanisms. The forming head components shall have adjusting mechanisms necessary to enable the machine to produce all standard profiles of the types shown under "built-in rolls" and "auxiliary rolls" in tables I and II for type, class, and size machine.

3.4.4 Electrical system. Unless otherwise specified (see 6.2.1), the electrical system shall conform to all requirements in this paragraph. The system shall conform to the requirements of NFPA-79. Each machine shall draw all of its electrical power from a single 230/460 volt, 3 phase, 60 Hz

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:35Z
Check the source to verify that this is the current version before use.

circuit having a fused safety disconnect switch. The machine shall be initially wired for operation on 230 volts. An identified terminal for grounding the machine when installed shall be mounted in or near the disconnect switch. The terminal shall be suitable for connecting the size grounding conductor specified in table 240-A of NFPA-79 for the disconnect fuse rating.

3.4.4.1 Motors. Motors shall have ball or roller bearings. Unless otherwise specified (see 6.2.1), each motor shall meet the requirements of a dripproof enclosure. Motor horsepower shall conform to the requirements of tables I and II.

3.5 Sizes and capacities. The machine shall meet, or exceed, the applicable requirements of tables I and II. In the tables, "capacity thickness" is the thickest gauge steel that the machine is capable of forming into the indicated type and size of profile. Where "rolling speed" is shown, the machine shall be capable of forming the indicated type, size, and gauge of profile workpiece at the specified rolling speed.

3.6 Performance. The machines covered by this specification shall be capable of forming the indicated type, size, and gauge of profile at the indicated rolling speed as specified in tables I and II, as applicable to the machine being procured. The completed profiles shall be true and uniform to the extent that assembly can be accomplished manually without the use of tools except where they are required to close the seams.

3.7 Standard equipment. Unless otherwise specified (see 6.2.1), the machine shall be furnished with all standard equipment normally furnished by the manufacturer.

3.8 Optional equipment. Optional equipment shall be furnished as specified and as fully described (see 6.2.1).

3.9 Lubrication chart or plate. Unless otherwise specified (see 6.2.1), a lubrication chart or plate shall be permanently and securely attached to each machine. If a chart is furnished, it shall be placed in a transparent plastic folder, or permanently sealed between clear plastic sheets with suitable means for mounting. The following information shall be furnished on the chart or plate:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:35Z
Check the source to verify that this is the current version before use.

TABLE I

SIZES AND CAPACITIES

TYPE I MACHINES
BUILT-IN LOCK ROLLS AND SINGLE EXTENDED SHAFT

Class 1, Built-in Pittsburgh Lock Rolls

Size, Gauge Capacity and Speed by use of Built-in Rolls :

	Size 14	Size 16	Size 18	Size 20	Size 20A	Size 22
Capacity, Thickness, USS Gauge	14	16	18	20	20	22
Size of Lock Pocket, Inch	1/2	1/2	3/8	5/16	5/16	5/16
Rolling Speed, Ft. Per Min.	30	30	30	23	75	23
Drive Motor Horsepower	5	.2	1-1/2	3/4	2	1/2

Type, Size and Gauge Capacity by use of Auxiliary Rolls (see 3.4.3.2 and 6.2.1):

	Size 14	Size 16	Size 18	Size 20	Size 20A	Size 22
Pittsburgh Lock, Inch	5/16	5/16	5/16	*	*	*
USS Gauge	22	22	22			
Double Seam, Inch	7/16	3/8	3/8	3/8	3/8	3/8
USS Gauge	16	16	18	20	20	22
Drive Cleat, Inches	1-1/8	1-1/8	1-1/8	1-1/8	1-1/8	1-1/8
USS Gauge	20	20	20	22	22	22
Standing Seam, Inch	3/4	3/4	3/4	*	*	*
USS Gauge	16	16	18			
Right Angle Flange, Inch	7/16	7/16	7/16	3/8	3/8	3/8
USS Gauge	16	16	18	22	22	20

Class 2, Built-in Snap Lock Rolls

Size, Gauge Capacity and Speed by use of Built-in Rolls:

	Size 20	Size 24	Size 24A	Size 26
Capacity, Thickness, USS Gauge	20	24	24	26
Type of Snap Lock	Button	Button	Reeves	Reeves
Size of Lock Pocket, Inch	1/2	1/2	7/16	7/16
Rolling Speed, Ft. Per Min.	60	60	35	30
Drive Motor Horsepower	3	2	2	1

Type, Size, and Gauge Capacity by use of Auxiliary Rolls (see 3.4.3.2 and 6.2.1):

	Size 20	Size 24	Size 24A	Size 26
Button Lock (Male) Inch	1/2	7/16	*	*
USS Gauge	20	24		
Reeves Lock (Male) Inch	*	*	7/16	7/16
USS Gauge			24	26

* This type roll not available on this size machine.

NOTE: Requirements are not less than those shown.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:35Z
Check the source to verify that this is the current version before use.

TABLE II

SIZES AND CAPACITIES

TYPE II MACHINES

BUILT-IN CLEAT ROLLS AND DOUBLE EXTENDED SHAFT

Class 1, Built-in Drive Cleat Rolls

Size, Gauge Capacity and Speed by Use of Built-in Rolls:

	Size 20	Size 22
Capacity, Thickness, USS Gauge	20	22
Size of Cleat, Inches	1-1/8	1-1/8
Rolling Speed, Ft. Per Min.	100	100
Drive Motor Horsepower	5	3

Type, Size, and Gauge Capacity by Use of Auxiliary Rolls (see 3.4.3.2 and 6.2.1):

	Size 20	Size 22
Pittsburgh Lock, Inch	5/16	5/16
USS Gauge	20	20
Double Seam, Inch	3/8	3/8
USS Gauge	20	20
Standing Seam, Inch	5/8	3/4
USS Gauge	22	20
Right Angle Flange, Inch	9/16	7/16
USS Gauge	20	20

Class 2, Built-in "S" Cleat Rolls

Size, Gauge Capacity and Speed by Use of Built-in Rolls:

	Size 20	Size 22
Capacity, Thickness, USS Gauge	22	22
Size of Cleat, Inches	1-1/16	1-1/16
Rolling Speed, Ft. Per Min.	100	100
Drive Motor Horsepower	5	3

Type, Size, and Gauge Capacity by Use of Auxiliary Rolls (see 3.4.3.2 and 6.2.1):

	Size 20	Size 22
Pittsburgh Lock, Inch	5/16	5/16
USS Gauge	20	22
Double Seam, Inch	3/8	3/8
USS Gauge	20	20
Standing Seam, Inch	5/8	3/4
USS Gauge	22	20
Right Angle Flange, Inch	9/16	7/16
USS Gauge	20	20

NOTE: Requirements are not less than those shown

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:35Z
Check the source to verify that this is the current version before use.

Points of application

Service interval

Type of lubricant

Viscosity

If there are no points on the machine requiring lubrication, the chart or plate shall be inscribed "No lubrication necessary" in lieu of the above required information.

3.10 Nameplate. Unless otherwise specified (see 6.2.1), a corrosion-resistant metal nameplate shall be securely attached to each machine. The nameplate shall contain the information listed below. If the machine is a special model, the model designation shall include the model of the basic standard machine and a suffix identified to the manufacturer's permanent record. The captions listed may be shortened or abbreviated, provided the entry for each caption is clear as to its identity.

Nomenclature

Manufacturer's name

Manufacturer's model designation

Manufacturer's serial number

Power input (volts, total amps, phase, frequency)

Contract Number or Order Number

National Stock Number or Plant Equipment Code

Date of manufacture

3.11 Technical data. Technical data shall be furnished as specified (see 6.2.2).

3.12 Workmanship. Workmanship of the machine and accessories shall be of a quality equal to that of the manufacturer's commercial equipment of the type specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:35Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirments specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspections. The inspections requirements specified herein are classified as follows:

1. First article inspection (see 4.2.1)
2. Quality conformance inspection (see 4.2.2).

4.2.1 First article inspection. When first article approval is required under 3.1, first article inspection shall be performed. Unless otherwise specified (see 6.2.1), first article inspection shall comprise the examination in 4.3 and all tests in 4.4. Failure of the item to pass any examination or test shall be casuse for disapproval of the first article.

4.2.2 Quality conformance inspection. Each item shall be subjected to quality conformance inspection prior to being offered for acceptance. Unless otherwise specified (see 6.2.1), quality conformance inspection shall consist of the examination in 4.3, the test in 4.4.1 and the inspection 4.5. Failure of the item to pass any examination, test, or inspection shall be cause for rejection.

4.3 Examination. The machine and equipment shall be examined to determine compliance with the requirements in 3.2 through 3.5 and 3.7 through 3.12.

4.4 Tests.

4.4.1 Operational test. The machine shall be operated at no load for not less than 15 minutes, during which time the controls and all operating components shall be actuated and observed to determine that they operate properly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:35Z
Check the source to verify that this is the current version before use.

4.4.2 Performance test. Each machine shall be used to form six test pieces with each set of rolls furnished with the machine. Each test piece shall be not less than two feet long and of the gauge shown as "capacity thickness" in table I or II, as applicable. The completed test pieces shall be straight, the formed edges shall be uniform, and there shall be no evidence of cracks or tears. The formed edges shall permit assembly of mating pieces without the use of tools except those required to close the seams.

4.5 Packaging inspection. Packaging shall be inspected to determine compliance with the requirements of Section 5.

5. PACKAGING

5.1 Preservation, packing and marking. Unless otherwise specified (see 6.2.1), preservation, packing and marking shall conform to the requirements of MIL-STD-1188.

6. NOTES

6.1 Intended use. Forming machines covered by this specification are intended for use in sheet metal shops to form, seam, cleat, and lock profiles in sheet metal, for assembly into various products such as sheet metal ducts used in heating and air conditioning installations.

6.2 Ordering data.

6.2.1 Procurement requirements. Purchasers should specify their requirements in procurement documents, including whether each choice is required or not required, by entering an appropriate statement identified to each of the following:

a. Title, number, and date of this specification.

b. Type, class, and size machine required (see 1.2 and tables I and II).

c. First Article approval, if required (see 3.1).

d. Specify exceptions and additional safety and health requirements (see 3.2.1 and 6.3).

e. Painting, if different (see 3.3.5).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:35Z
Check the source to verify that this is the current version before use.

f. Auxiliary rolls as selected from table I or II, if required. Specify each set required by type of lock or cleat, and specify depth of pocket, height of flange, or width of cleat required (see 3.4.3.2 and tables I and II).

g. Electrical system, if different (see 3.4.4).

h. Motor enclosure, if different (see 3.4.4.1).

i. Standard equipment, if different (see 3.7).

j. Optional equipment, if required; fully describe (see 3.8).

k. Lubrication chart or plate, if different (see 3.9).

l. Nameplate, if different (see 3.10).

m. First Article inspection, if different (see 4.2.1).

n. Quality conformance inspection, if different (see 4.2.2).

o. Preservation, packing and marking, if different (see 5.1).

6.2.2 Contract data requirements. Required technical data, such as operators manuals, parts lists, wiring diagrams, and other instruction for operation and maintenance as identified on a numbered DD Form 1664 should be specified on a DD Form 1423 incorporated into the contract.

6.3 Safety and health requirements. Paragraph 3.2.1 requires compliance only with those OSHA requirements that concern "the machine in its operating environment" such as noise levels, radiation levels, electromagnetic emissions, noxious vapors, air contaminants, heat, etc. Since OSHA limits the total hazard level of these hazards in the environment (and does not limit the hazard level of individual machines in the environment) the procuring agency is advised to analyze the additional requirements supplied by the requesting activity pertaining to the existing hazard levels in the proposed operating environment, and specify additional machine requirements that will integrate the new machine into its future operating environment. If specific point-of-operation guarding is required as in most cases, the guard configuration is dependent on the size and configuration of the workpieces. The above, and any other additional safety and health requirements should be specified in detail under 6.2.1(d).

Source: https://assist.dla.mil - Downloaded: 2026-10-23T04:35Z
Check the source to verify that this is the current version before use.

6.4 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodians:

Army - AL
Navy - SH
Air Force - 99

Review Activities:
Army - AL
Navy - SH, YD
Air Force - 99
DLA - GS

User Activities:

Navy - MC

Preparing Activity:

DLA-IP

Project Number:

3441-0104

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:35Z
Check the source to verify that this is the current version before use.

FOLD

DEFENSE LOGISTICS AGENCY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL

FIRST CLASS PERMIT NO. 4966 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEFENSE LOGISTICS AGENCY

Commander
Defense Industrial Plant Equipment Center
ATTN: DIPEC-TF
Memphis, Tennessee 38114

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:35Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-F-80057C, Forming Machines, Sheet Metal, Cleat and Lock Forming

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426

EDITION OF 1 JAN 72 MAY BE USED UNTIL EXHAUSTED

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:35Z
Check the source to verify that this is the current version before use.