MIL-H-81500A(AS)
15 October 1982
SUPERSEDING
MIL-H-81500(AS)
23 September 1966

MILITARY SPECIFICATION

HOOD, ANTI-EXPOSURE COVERALL

This specification is approved for use by the Naval Air Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers requirements for one type and size of an anti-exposure coverall hood.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. Unless otherwise specified, the following specifications, standards, and handbooks of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

PPP-B-636	-	Boxes, Shipping, Fiberboard.
PPP-T-45	-	Tape, Gummed, Paper, Reinforced and Plain, for Sealing and Securing.

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables For Inspection by Attributes.
MIL-STD-129	-	Marking for Shipment and Storage.
MIL-STD-130	-	Identification Marking of U.S. Military Property.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Engineering Specifications and Standards Department (Code 93), Naval Air Engineering Center, Lakehurst, NJ 08733, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:31Z
Check the source to verify that this is the current version before use.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

DRAWINGS

NAVAL AIR SYSTEMS COMMAND

1414AS101 - Hood Assembly, Anti-Exposure Coverall.

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.1.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 First article. When specified, a sample shall be subjected to first article inspection (see 4.3 and 6.2.1).

3.2 Materials and components. Materials and components shall conform to applicable specifications, standards, and drawings as listed or required herein. Unless otherwise specified, the materials and components, except for the metallic parts, used in the construction of the anti-exposure coverall hoods shall have been manufactured not more than 12 months prior to the date of delivery of the anti-exposure coverall hoods.

3.3 Design and construction. The design and construction of the anti-exposure coverall hood shall be in accordance with Drawing 1414AS101.

3.3.1 Cutting. The hood shall be cut in strict accordance with the patterns furnished by the Government (see 6.4), which show direction of the cloth, size, shape, placement of the loop, patch, oral inflation assembly, snap fasteners, sewn eyelet, pile fastener tape and notches or markings for the proper assembly of all the parts. The directional lines shall be in the warp direction. The Government patterns shall not be altered in any manner and shall be used for making the working patterns. The working patterns shall be identical to the Government furnished patterns. The component parts of each hood shall be cut from the same ply of the lay.

3.3.2 Shade marking. The component parts shall be marked or ticketed, by any commercial method, or bundled with the top ply of each individual component part marked with the bundle number, to insure a uniform shade and proper assembly throughout the hood. Metal fastening devices or sewn-on tickets shall not be used. Shade markings may be accomplished by the use of ink pad numbering machine, rubber stamp, or pencil, provided the markings do not show through to the outerside of the hood and are not deleterious to the cloth. Markings placed on the seam allowance shall not be visible on the outerside. Adhesive tape shade tickets may be used for the shade markings (see 3.3.2.1). The assembled hood shall not contain any shade marking tickets.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:31Z
Check the source to verify that this is the current version before use.

3.3.2.1 Adhesive shade tickets. Adhesive shade tickets shall be fabricated from paper with a thermo-activated adhesive applied on one side. The adhesive shall not discolor the cloth and the adhesive mass shall not adhere to the cloth upon removal of the ticket. The heat used to attach the thermo-activated adhesive tickets shall not stiffen, harden, sear or damage the cloth in any manner.

3.3.3 Use of adhesive. In all the cementing operations, the surface to which the adhesive is to be applied shall be thoroughly cleaned with a suitable solvent in such a manner that the dusting materials (zinc stearate or talc) and any other surface contaminant is removed. The surface shall be clean prior to cementing. Care should be exercised to insure that the coating and the base undercloth are not damaged and the adhesion between both is not impaired in any way by prolonged exposure to the solvent. The solvent used shall evaporate completely prior to the application of the adhesive and shall leave no residue. Cemented areas shall not contain trapped air, channels or wrinkles. The adhesive shall be controlled to insure that old adhesive or adhesive which has partly or completely polymerized is not used. A fresh batch of adhesive shall be used at least every 8 hours during the course of manufacture. Containers shall be free from congealed adhesive before being refilled.

3.3.4 Cementing of the seams and attaching of the component parts. The cementing of the seams and the attaching of the reinforcing patch, pile fastener tape and oral inflation assembly shall be undertaken utilizing the technique and precautions outlined in 3.3.3 so that, prior to the inspection of the assembled hood, the adhesive shall have developed its optimum bonding properties and the adherence of all the seams and attachment of all the component parts shall conform to the requirements of this specification. The seams shall be formed and the components attached without any tension. The internal diameter of the opening in the oral inflation assembly reinforcing patch shall coincide with the opening in the base of the oral inflation assembly tube. The adhesive shall be applied in a straight line parallel to the edges of the seams and components and shall extend from just being visible to a maximum of one half inch beyond the seams and components. The adhesive when dry or cured shall present a neat and uniform appearance. The adhesive shall not be allowed to remain in clots nor permitted to extend in such a manner as to result in localized stiffness, which might result in discomfort to the wearer, when the hood is deflated or inflated. The adhesive upon drying or curing shall not cause the cloth and attachment to shrink or pucker at any point on the hood. The adhesive shall not be allowed to run over the edges of the hood to form stiff or hard needle points and all the edges around the periphery of the hood, both inside and out, shall be free from sharp points or ragged edges. The external portion of the oral inflation valve and the hood shall be free from congealed masses of the adhesive and spots or stains resulting from excess adhesive.

3.3.5 Seams and stitching. No stitching shall be used in any of the hood seams or through the cloth of the inflatable portion. Sewing shall be used only in the sewn eyelet. The sewn eyelet shall contain a minimum of 25 stitches. The number of stitches per eyelet shall be determined by counting the number of needle penetrations in the outer diameter of the eyelet. The overlapping stitches shall also be included, when determining the number of stitches per eyelet. The eyelets shall be constructed with Stitch Type 401, 502 or 503. When Stitch Type 401 is used, the

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:31Z
Check the source to verify that this is the current version before use.

purling shall be located on the innerside of the hood. When Stitch Type 502 or 503 is used, the outerside purling shall be located on the outer diameter of the eyelet and the innerside purling shall not be pulled to the outerside of the hood. The thread ends shall be on the innerside of the hood. The size and location of the eyelet shall be as specified in Drawing 1414AS101 and the patterns.

3.4 Color. The color of the anti-exposure hood and the components shall be as specified on the applicable drawing. The color shall be compared to the standard as specified in 4.6.1.

3.5 Markings. The markings on the hood shall be in accordance with MIL-STD-130 and Drawing 1414AS101.

3.5.1 Serial numbers. Serial numbers (required by Drawing 1414AS101) shall be assigned by the manufacturer. Serialization shall be by a block of consecutive numbers to cover the entire acquisition document quantity (see 6.2.1e).

3.6 Performance inspection.

3.6.1 Leakage. When inspected as specified in 4.6.3, the pressure in the hood shall not drop below 1.5 inches (water column). The seams and attachments shall remain perfectly intact and shall show no indication of separation. There shall be no evidence of constructional or material failure in any respect. There shall be no evidence that the air entering the hood chamber is hindered by the misplacement of the reinforcing patch or that the front or back of the oral inflation valve or the opening in the oral inflation tube is blocked by excess adhesive, zinc stearate, talc, or other foreign matter. The oral inflation valve shall operate without difficulty, shall shut off the flow of air completely, and shall not be blocked by an excess adhesive, talc, zinc stearate, or other foreign matter, or by damage to the oral inflation valve due to clamping together of the oral inflation valve and tube. The attachment of the flange end of the oral inflation tube to the hood, and the bond between the oral inflation valve and tube shall remain perfectly intact.

3.7 Workmanship. The snap fasteners shall be securely clinched without distortion, cracking, splitting, or cutting of the cloth. The hood shall be free of holes, tears, cuts, mends, spots, or stains. The metal components shall not be misaligned or contain any nicks, burrs, metal slivers, cracks, or sharp edges. Because of the emergency and life support use of this hood, the importance of providing a product of uniformly excellent quality cannot be overemphasized. The hoods shall be uniform in quality and shall be free from irregularities or defects which could adversely affect performance, reliability, or durability. The hoods shall conform to the quality and grade of product established by this specification. The occurrence of defects shall not exceed the acceptance criteria established herein.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:31Z
Check the source to verify that this is the current version before use.

4.1.1 Test equipment and inspection facilities. The manufacturer shall insure that test and inspection facilities of sufficient accuracy, quality and quantity are established and maintained to permit performance of required inspections.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection. First article inspection consists of examinations and tests performed on samples which are representative of the production item after the award of a contract to determine that the production item meets the requirements of this specification (see 4.3).

b. Quality conformance inspection. Quality conformance inspection consists of examinations and tests performed on individual products or lots to determine conformance of the products or lots with the requirements set forth in this specification (see 4.4).

4.3 First article inspection. The first article inspection of the anti-exposure coverall hoods shall consist of examinations and tests for all of the requirements of this specification.

4.3.1 First article samples. Unless otherwise specified, as soon as practicable after the award of the contract or order, the manufacturer shall submit three hoods. The samples shall be representative of the construction, workmanship, components and materials to be used during production. When a contractor is in continuous production of these hoods from contract to contract, submission of further first article samples on the new contract may be waived at the discretion of the acquiring activity (see 6.2.1d). Approval of the first article samples or the waiving of the first article inspection does not waive the requirements for performing the quality conformance inspection. The first article samples shall be forwarded as specified in the contract or order (see 6.2.1f). The samples shall be plainly identified by securely attached durable tags marked with following information:

Samples submitted by (name) (date) for first article inspection in accordance with the requirements of MIL-H-81500A(AS) under contract no.

4.3.2 First article sample approval. Upon completion of the first article inspection program, pertinent comments and recommendations will be forwarded by the cognizant Government activity responsible for conducting the inspection program (see 6.2.1f) to the contracting officer. One approved hood will be returned to the manufacturer for use in monitoring production. The other two hoods will be consumed or destroyed in the first article inspection and shall not be considered as part of the quantity to be delivered under contract or order.

4.4 Quality conformance inspection. The sampling and inspection levels shall conform to MIL-STD-105. The quality conformance inspection shall consist of the following:

Visual examination
Leakage
Packaging

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:31Z
Check the source to verify that this is the current version before use.

4.4.1 Sampling.

4.4.1.1 Inspection lot.

4.4.1.1.1 Hoods. An inspection lot size shall be expressed in units of one hood made under essentially the same conditions and from the same materials and components. The sample unit shall be one hood.

4.4.1.1.2 Packaging. An inspection lot size shall be expressed in units of one fully prepared shipping container, containing hoods, fully prepared for delivery from essentially the same materials and components. The sample unit shall be one shipping container, containing hoods, fully prepared for delivery with the exception that it need not be sealed.

4.4.1.2 Sampling for tests and examinations of the hoods and packaging. The sample size, acceptance criteria, tests and examinations required for the hoods shall be as specified in Table I.

4.5 Inspection conditions.

4.5.1 Atmospheric conditions. Unless otherwise specified, all inspections required by this specification shall be conducted at an atmospheric pressure of 28 to 32 inches of mercury, at a temperature of $77^{\circ} \pm 18^{\circ}F$ ($25^{\circ} \pm 10^{\circ}C$) and a relative humidity of 80 percent or less. When the inspections are conducted at an atmospheric pressure or temperature different from the above values, proper correction shall be made for the change in instrument reading.

4.5.2 Air. Where air is specified to be used in an inspection, the air used shall be oil and liquid water free.

4.5.3 Inspection area and equipment. The area in which the hoods are inspected shall be adequately protected to preclude damage to the units. The area and inspection equipment shall be free of sharp or rough edges, burrs, protrusions, etc., which will cut, tear, or damage the hood or the components.

4.6 Inspection methods.

4.6.1 Color matching. The color shall match the approved standard shade under natural (north sky) daylight or articifial daylight having a color temperature of 7500 degrees Kelvin.

4.6.2 Visual examination.

4.6.2.1 Hoods. Every hood shall be examined visually for major defects to determine conformance to this specification. Each hood, selected as a sample unit from the lot, shall be examined visually for minor defects to determine conformance to this specification. The classification of defects, Table II, shall be used to classify the defects found.

4.6.2.2 Packaging. Each of the fully prepared shipping containers, containing hoods, selected as a sample unit from the lot, shall be visually examined to determine that the packaging, packing, and marking conform to this specification. The list of defects, Table III, shall be used to enumerate the defects found.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:31Z
Check the source to verify that this is the current version before use.

4.6.3 Leakage. After a minimum time of 24 hours has elapsed from the last cementing operation, the hood shall be inflated with air (see 4.5.2) to a pressure of 2 inches (water column). The air supply shall be completely shut off and after a minimum of 5 minutes, the pressure in the hood shall be cheked and readjusted, if necessary, to the original pressure of 2 inches (water column). At the end of a minimum of 5 minutes after the readjustment and disconnecting of the air supply, the pressure in the hood air chamber shall be not less than 1.5 inches (water column). While inflated, the hood shall be examined for material failure and construction failure of the seams and attachments (see 3.6.1). The air from the hood chamber shall be discharged through the oral inflation assembly by depressing the mouthpiece, in order to determine that there is no restriction of air flow or blockage from talc, zinc stearate, adhesive or other foreign matter, misplacement of the reinforcing patch or by damage to the oral inflation assembly from the clamping together of the oral inflation valve and tube. The mouthpiece, when released, shall return to the closed position without difficulty and completely shut off the air flow.

5. PACKAGING

5.1 Preparation. All parts of the hood shall be lightly dusted with zinc stearate or talc to prevent the adhering of unrelated cloth surfaces and cemented areas during normal storage and transportation conditions. Care shall be exercised so that the zinc stearate or talc shall not clog the oral inflation assembly nor interfere with the operation of the hood. The hood shall be completely evacuated of air and the oral inflation valve shall be locked in the closed position by the knurled ring. The snap fasteners shall be snapped closed. There shall not be any trapped air in the folds and rolls of the hood. The hood shall be folded and rolled as follows:

a. The hood shall be folded in half so that the snap fasteners are located at the fold on one side.

b. Lay the hood flat with the oral inflation assembly in the up position.

c. Fold the bottom of the hood over at the reinforcing patch of the oral inflation assembly.

d. Fold the top of the hood over at the mouthpiece of the oral inflation assembly.

e. Starting at the side of the oral inflation assembly, roll the hood tightly without bending or distorting any component of the oral inflation assembly.

f. The hood shall be held in the rolled position by neatly winding the tie cord around the rolled hood. The end of the tie cord shall be tucked under the turns. The tie cord shall not contain any snarls or knots.

5.2 Preservation. Preservation shall be Level A or Industrial, as specified (see 6.2.1d).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:31Z
Check the source to verify that this is the current version before use.

5.2.1 Level A. A paper label shall be inserted (see 5.4.1) and each hood, prepared as specified in 5.1, shall be heat sealed within a clear polyethylene film bag of 0.00125 ± 20 percent inch thick material. The film bag shall be formed with heat sealed seams that are continuous, straight, and parallel to each other and to the edges of the bag. The closing heat seal seam of the bag shall be as close as possible to the edge of the bag. No part of the hood shall be distorted nor caught in the heat seal. Prior to or during the heat sealing operation, excess air shall be exhausted to the extent necessary to permit packaging of the required quantity in the fiberboard box. Twelve bagged hoods shall be placed within a snug fitting fiberboard box conforming to PPP-B-636, Type CF or SF, Domestic Class, Variety SW, Grade 275. All the seams and joints shall be sealed with a 3 inch minimum wide tape conforming to PPP-T-45, Type III, Grade A, B. or C. The container shall be constructed and closed in accordance with the appendix to PPP-B-636.

5.2.2 Industrial. The hoods shall be packaged to afford the minimum degree of protection necessary to prevent deterioration or damage during shipment under normal environmental conditions and commercial modes of transportation.

5.3 Packing. Packing shall be Level A, B, or Industrial, as specified (see 6.2.1d).

5.3.1 Level A. Eight boxes, ninety-six hoods, packaged as specified in 5.2.1, shall be packed within a snug fitting fiberboard container conforming to PPP-B-636, Type CF or SF, Weather Resistant Class, Variety SW, Grade V3c or V3s. Each container shall be constructed, closed, and reinforced with flat strapping or tape banding in accordance with the appendix to PPP-B-636.

5.3.2 Level B. Eight boxes, ninety-six hoods, packaged as specified in 5.2.1, shall be packed within a snug fitting fiberboard shipping container conforming to PPP-B-636, Type CF or SF, Domestic Class, Variety SW, Grade 275. Each container shall be constructed and closed in accordance with the appendix to PPP-B-636.

5.3.3 Industrial. The packaged hoods, which require packing for acceptance by the carrier, shall be packed within exterior type shipping containers in a manner that shall insure safe transportation at the lowest rate to the point of delivery. The shipment shall conform to the minimum requirements of the rules and regulations applicable to the mode of transportation selected.

5.4 Marking. In addition to any special markings required by the contract or order (see 6.2.1g), the interior and exterior containers shall be marked in accordance with MIL-STD-129 and shall include the date of manufacture (month and year) and specification number.

5.4.1 Film bag. Prior to heat sealing, a white paper label with black letters and numerals shall be placed inside each film bag. The label shall be placed so that it may be read through the bag and shall contain the same markings as required in 5.4.

6. NOTES

6.1 Intended use. The anti-exposure coverall hood covered by this specification is intended to be used to protect the head of the wearer from exposure to cold

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:31Z
Check the source to verify that this is the current version before use.

wind and spray as a result of emergency ditching of an aircraft at sea. The hood is used with anti-exposure coveralls.

6.2 Ordering data.

6.2.1 Acquistion requirements. Acquisition documents should specify the following:

a. Title, number and date of this specification (including amendments).

b. Government part number, national stock number and quantity desired.

c. Applicable drawings, including revisions (see 2.1.2).

d. Whether first article inspection may be waived (see 4.3.1).

e. Serial numbers to be assigned by the manufacturer (see 3.5.1).

f. Name and address of first article inspection laboratory (see 4.3.1) and the name and address of the Government activity responsible for conducting the first article inspection program (see 4.3.2).

g. Selection of applicable levels of preservation and packing (see 5.2 and 5.3).

h. Whether any special markings are required (see 5.4).

i. Data requirements (see 6.2.2).

6.2.2 Data requirements. When this specification is used in an acquisition which incorporates a DD Form 1423, Contract Data Requirements List (CDRL), the data requirements identified below shall be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved CDRL incorporated into the contract. When the provisions of DAR 7-104.9 (n) (2) are invoked and the DD Form 1423 is not used, the data specified below shall be delivered by the contractor in accordance with the contract or purchase order requirements. Deliverable data required by this specification is cited in the following paragraphs:

Paragraph no.	Data requirements	Applicable DID no.
3.2	Certificate of compliance for the age of materials and components.	DI-E-2121
4.3.2	First article inspection reports.	DI-T-5329

(Copies of data item descriptions required by contractors in connection with specific acquisition functions should be obtained from the Naval Publications and Forms Center or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:31Z
Check the source to verify that this is the current version before use.

6.3 First article. When a first article inspection is required, the hood will be tested and should be a first production item. The contracting officer should include specific instructions in all acquisition documents regarding arrangements for examinations, test and approval of the first article.

6.4 Patterns. The patterns for the hood will be furnished by the contracting officer to the contractor for use in cutting working patterns (see 3.3.1).

6.5 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Preparing activity:
Navy - AS

(Project 8475-N182)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:31Z
Check the source to verify that this is the current version before use.

TABLE I. Sample size, acceptance criteria, tests and examinations of the hoods and packaging.

Inspection	Paragraph		Sample size	Acceptance criteria
	Requirement	Method		
Visual Examination	Section 3 and applicable drawings	4.6.2.1	Every hood for major defects. Inspection Level II for minor defects.	Reject all units with any major defect and an Acceptable Quality Level of 6.5 defects per hundred units for minor defects.
Leakage 1/	3.6.1	4.6.3	Every hood	Reject all defective units
Packaging	Section 5	4.6.2.2	Inspection Level S-2	An Acceptable Quality Level of 2.5 percent defective

1/ The results of the hood leakage inspection shall be identifiable by the assigned serial numbers (see 6.2.1e) which shall be marked on the hood as specified in 3.5.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:31Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of defects for the visual examination of the hoods.

Defect	Major	Minor
GENERAL		
a. Any hole, scissors or knife cut, tear, burn, mend or weakening defect such as smash, multiple float, loose slub needle chew, etc.	X	
b. Cloth stiffened, hardened, seared by heat, or otherwise damaged, where the thermo-activated shade marking tickets were attached.	X	
c. Color of any component not as specified, any part shaded, or any shade bar.		X
d. Coated side of the cloth on the outerside of the hood.	X	
e. Any spot or stain, any shade ticket not removed, or any shade identification stamping visible on the outerside of the hood.		X
f. Any metal fastening device or sewn on ticket.	X	
g. Faulty adhesion, i.e., any portion of the seams or any attachment separating.	X	
h. Any trapped air, wrinkles, or creases in the seam or attachments.		X
i. Cement on the cloth surface along the seam edge not visible or in excess of 1/2 inch.		X
j. Movement on the knurled ring interfered with by excess adhesive. 1/	X	
METALLIC COMPONENTS 2/		
a. Any surface rough, misaligned, distorted, or containing nicks, burrs, sharp edges, cracks, or metal slivers.	X	
b. Any surface unclean or containing embedded foreign matter.		X
c. Any component loose or otherwise not securely retained.	X	
d. Any functioning part that works with difficulty.	X	

Source: https://assist.dla.mil - Downloaded: 2026-10-23T05:31Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of defects for the visual examination of the hoods. - Continued

Defect	Major	Minor
COMPONENT AND ASSEMBLY		
a. Any component not as specified or any defect of a component or defect of assembly not herein classified.	3/	
b. Any component, component part, or required operation omitted, or any operation improperly performed not herein classified.	3/	
c. Any component part not cut in accordance with the patterns.	3/	
MARKINGS		
a. Missing, Incomplete, incorrect, illegible, or located on the outerside of the hood.		X

1/ The knurled ring shall be checked for proper function by locking the mouthpiece in the closed position and then unlocking.

2/ The snap fasteners shall be checked for proper function and attaching by snapping closed and unsnapping each of the snap fasteners at least 3 times.

3/ The defect shall be classified as major, when it seriously affects the appearance or serviceability, otherwise it shall be classified as a minor defect.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:31Z
Check the source to verify that this is the current version before use.

TABLE III. List of defects for packaging.

Item	Defect
Exterior and interior markings	Missing, incorrect, incomplete, illegible; of improper size, location, sequence, or method of application; markings not the same on the interior and exterior containers; information on the label in the polyethylene bag not read able through the film or no label in the film bag.
Materials	Any non-conforming component; any component missing, damaged, or otherwise defective.
Workmanship	Inadequate application of the components, such as incomplete closure of the container flaps, film bag, loose strapping, etc.; bulging or distortion of the containers; any portion of the hood dis torted or caught in the heat sealed seam.
Content	Number per container is more or less than re- quired; gross or net weight exceeds the require ments.

* U.S. GOVERNMENT PRINTING OFFICE: 1982—605-034/5074
Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:31Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER (Number) AND TITLE

MIL-H-81500A(AS) Hood, Anti-Exposure Coverall

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY (Printed or typed name and address — Optional)

TELEPHONE NO.

DATE

DD FORM 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: http://assist.dla.mil - Downloaded: 2020-10-23T05:01Z
Check the source to verify that this is the current version before use.