MILITARY STANDARD

TEST EQUIPMENT FOR THE
STANDARD ELECTRONIC MODULES PROGRAM

TO ALL HOLDERS OF MIL-STD-1665:

1. THE FOLLOWING PAGES OF MIL-STD-1665 HAVE BEEN REVISED AND SUPERSEDE THE PAGES LISTED:

NEW PAGE	DATE	SUPERSEDED PAGE	DATE
i	20 January 1978	Reprinted without change	20 January 1978
ii	16 January 1984	ii	20 January 1978
1	16 January 1984	1	20 January 1978
2	20 January 1978	Reprinted without change	20 January 1978
5	16 January 1984	5	19 November 1980
6	16 January 1984	6	20 March 1980
J04-1	20 January 1978	Reprinted without change	20 January 1978
J04-2	16 January 1984	J04-2	20 January 1978
V04-1	16 January 1984	V04-1	20 January 1978
W05-1	16 January 1984	W05-1	20 January 1978

2. The following pages are to be added:

NEW PAGE	DATE
G11-1	16 January 1984
G11-2	16 January 1984
J04-3	16 January 1984
W08-1	16 January 1984

3. RETAIN THIS NOTICE AND INSERT BEFORE TABLE OF CONTENTS.

4. Holders of MIL-STD-1665 will verify that additions indicated above have been entered. This notice page will be retained as a check sheet. This issuance, together with the appended pages is a separate publication. Each notice is to be retained by stocking points until the Military Standard is completely revised or canceled.

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - AT
Navy - AS, SH
Air Force - 13, 17, 19
DLA - ES

User activities:
Army - MI
Navy -
Air Force -

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5963-0025)

FSC 5963

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:51Z
Check the source to verify that this is the current version before use.

MIL-STD-1665
20 January 1978
SUPERSEDING
(See 6.2)

MILITARY STANDARD

TEST EQUIPMENT
FOR THE
STANDARD ELECTRONIC MODULES PROGRAM



FSC 5963

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:51Z
Check the source to verify that this is the current version before use.

DEPARTMENT OF DEFENSE

WASHINGTON, D.C. 20301

Test Equipment for the Standard Electronic Modules Program

MIL-STD-1665

1. This Military Standard is approved for use by all Departments and Agencies of the Department of Defense.

2. Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Naval Electronic Systems Command, ATTN: ELEX 8111, Washington, D.C. 20363 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Supersedes page ii of
20 January 1978

Source: https://assist.dla.mil -- Downloaded: 202610-24T00:51Z
Check the source to verify that this is the current version before use.

1. SCOPE

1.1 Scope. This standard establishes the capabilities of electronic test equipment needed for testing of Standard Electronic Modules (as specified in MIL-M-28787). It specifies equipment performance parameters and lists representative test equipment.

2. REFERENCED DOCUMENTS.

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this standard to the extent specified herein.

SPECIFICATION

MILITARY

MIL-M-28787 - Modules, Standard Electronic, General Specification For.

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. DEFINITIONS

3.1 Not applicable.

4. GENERAL REQUIREMENTS

4.1 Substitution of equivalent equipment. With the concurrence of the procuring activity, equipment other than that listed herein may be used provided that the substitute equipment has capabilities and performance characteristics at least equal to the listed equipment with respect to test data to be taken. Tests shall be performed as required to verify correlation between the substitute and the listed equipment.

4.2 Significance of asterisk. Test equipment marked with an asterisk (*) shall be considered as reference equipment to be used in the event of conflicting data.

4.3 Arrangement of data and requirements. The requirements and pertinent data pertaining to the specific equipment are arranged as follows:

TITLE - - - - - - - - - - - - - - - - - -	Lists the item number referenced and specified in detail specifications, tests, etc., and the generic name of the equipment.
TYPE OF EQUIPMENT - - - - - - - - - - - -	Generic name of the equipment.
FUNCTION PERFORMED- - - - - - - - - - - -	Defines types of tests within the capability of the equipment.
SPECIFICATIONS- - - - - - - - - - - - - -	This section lists the performance parameters and specifications required for the equipment.
EQUIPMENT MEETING ALL SPECIFICATIONS- - - - - - - - - - - - - -	This section lists specific equipment by manufacturer's name or trade name and model number that complies with or surpasses the minimum requirements listed under specifications.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:51Z
Check the source to verify that this is the current version before use.

EQUIPMENT MEETING SPECIFICATIONS WITH EXCEPTIONS - - - - - - - - - - - - - This section lists specific test equipment by manufacturer's name or trade name and model number, together with deviations from the specification, and other pertinent information. Except for the specified deviations, the equipment complies with the specification requirements. The term "exceptions" is construed to mean only those deviations which limit the measurement capability of the equipment.

4.4 General purpose test equipment. Miscellaneous test equipment suitable for general bench testing, and for incorporation in factory production testing equipment, is listed and described under item number designations in the remainder of this document.

4.5 Test equipment application criteria. The choice of test equipment to perform a given measurement should be determined on the basis of the following application criteria. The detailed requirements for maintenance and calibration of inspection and test equipment are defined in MIL-M-28787.

4.5.1 Parameter. The parameter to be measured determines the family of test equipment (ac voltmeters, ohmmeters, frequency meters, etc.) which should be investigated for a specific instrument to perform the measurement.

4.5.2 Range. This criteria determines the qualitative range that the instrument must have in order to measure the magnitude of the parameter.

4.5.3 Accuracy. Once the type of instrument and range have been determined, it is necessary to consider the measurement accuracy required. The accuracy required is a function of the specified parameter tolerance and the required ratio of that tolerance to the test equipment accuracy. The ratio of specification tolerance to test equipment accuracy shall be 10:1 for tolerances of 3 percent or greater and at least 4:1 for tolerances of less than 3 percent.

4.5.4 Other selection criteria. After the necessary considerations of test equipment parameter, range and accuracy have been made, the final selection of a particular manufacturer's instrument is determined as a matter of judgement and compromise of the following:

a. Secondary features of the instrument.

b. Multiple usage to satisfy the requirements of other item numbers.

c. Effect of the instrument on the parameter being measured.

d. Cost.

4.6 Specifying new test equipment. This document is not intended to be a catalog of manufacturer's general purpose test equipment. Therefore, potential users and contributors to this document, when specifying equipment for the testing of an electronic module, should attempt to restrict their choice to the item numbered equipment in this document. If a suitable test equipment item cannot be found in this document, the user should evaluate his requirements and search for a suitable commerical instrument. After finding a suitable instrument the user should make a written request to the SEMP-QAA to have his test equipment requirements incorporated under an item number in this document.

Source: https://assist.dla.mil -- Downloaded: 202610-24T00:51Z
Check the source to verify that this is the current version before use.

INDEX

Equipment	Item No.
Ammeter, dc	X01
Ammeter, dc	X02
Ammeter, dc	X03
Ammeter, dc	X04
Ammeter, dc	X05
Amplifier, low noise	A03
Amplifier, power	A01
Analyzer, distortion	B01
Analyzer, spectrum	B03
Analyzer, wave	B02
Analyzer, wave	B04
Attenuator	R08
Attenuator, balanced	R09
Bridge, capacitance	C01
Bridge, capacitance	C03
Bridge, capacitance	C04
Bridge, capacitance, rf	C02
Bridge, inductance	L01
Bridge, inductance	L02
Bridge, inductance, rf	L03
Bridge, megohm	R06
Bridge, resistance	R02
Bridge, resistance, rf	R03
Counter-timer	T01
Decade, synchro/resolver standard	F03
Digital multifunction meter	M02
Filter, tunable	N01
Frequency meter	T02
Frequency meter	T03
Generator, function	G05
Generator, function	G06
Generator, function	G10
Generator, pulse	J01
Generator, pulse	J02
Generator, pulse	J04
Generator, pulse	J05
Generator, pulse	J06
Generator, power	Q01
Generator, random noise	K03
Generator, rf signal	G11
Generator, sine wave	G01
Generator, sine wave	G02
Generator, sine wave	G03
Generator, sine wave	G04
Generator, sine wave	G08
Generator, power sine wave	G07
Generator, power sine wave	G09
Generator, square wave	H01
Generator, square wave	H02
Generator, time-mark	K01
Generator, word	J03
Leakage tester, high voltage dc	U01
Leakage tester, high voltage ac	U02
Load, electronic	EL01
Meter, capacitance	C05
Multifunction meter, analog	M03
Multimeter (VOM)	M01
Ohmmeter	R01
Ohmmeter	R04
Ohmmeter	R05
Ohmmeter	R07
Ohmmeter	R10

Supersedes page 5 of
19 November 1980

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:51Z
Check the source to verify that this is the current version before use.

MIL-STD-1665
16 January 1984

INDEX - Continued

Equipment	Item No.
Oscilloscope, high frequency	D01
Oscilloscope, high frequency	D03
Oscilloscope, high frequency	D06
Oscilloscope, high frequency	D07
Oscilloscope, high gain	D02
Oscilloscope, UHF sampling system	D04
Oscilloscope, UHF sampling system	D05
Phasemeter	Z03
Photometer, digital	K02
Power supply, constant current	P05
Power supply, dc	P01
Power supply, dc	P02
Power supply, dc	P03
Power supply, dc	P04
Power supply, dc	P06
Power supply, dc	P07
Probe, oscilloscope current	Y03
Probe, oscilloscope current	Y05
Probe, oscilloscope voltage	Y02
Probe, oscilloscope voltage	Y04
Probe, oscilloscope voltage	Y06
Probe, wide band	Y01
Resolver/synchro bridge	F04
Standard, dc voltage	P08
Standard, dc voltage and null meter	P09
Tester, LSI	U03
Transformer, isolation	E01
Transformer, isolation	E02
Transformer, isolation	E03
Transformer, isolation	E05
Transformer, ratio	F01
Transformer, ratio	F02
Transformer, ratio	F05
Transformer, Scott "T"	E04
Voltmeter, ac	W01
Voltmeter, ac	W02
Voltmeter, ac	W03
Voltmeter, ac	W04
Voltmeter, ac	W05
Voltmeter, ac	W06
Voltmeter, dc	V01
Voltmeter, dc	V02
Voltmeter, dc	V03
Voltmeter, dc	V04
Voltmeter, dc	V05
Voltmeter, dc	V06
Voltmeter, differential ac/dc	V07
Voltmeter, phase angle	Z01
Voltmeter, phase angle	Z02
Voltmeter, rf	W08
Voltmeter, true rms	W07
Wattmeter, ac	S01
Wattmeter ac/dc	S02

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:51Z
Check the source to verify that this is the current version before use.

GENERATOR, RF SIGNAL

TYPE OF EQUIPMENT - - - - - - - - - - - - - - RF signal generator

FUNCTION PERFORMED- - - - - - - - - - - - - - Provides accurate (stable) variable frequency and amplitude sine waves.

SPECIFICATIONS

Frequency
- Range- - - - - - - - - - - - - - - - - - - 1 MHz to 520 MHz.
- Resolution - - - - - - - - - - - - - - - - 1 kHz.
- Accuracy - - - - - - - - - - - - - - - - - ±0.001 percent.
- Stability- - - - - - - - - - - - - - - - - <0.2 ppm/hour.
- Programmability- - - - - - - - - - - - - - Frequency is programmable via rear-panel input connector.

Amplitude
- Power level range- - - - - - - - - - - - - +13 dBm to -127 dBm (1V to 0.1 μV into 50Ω.
- Total level accuracy - - - - - - - - - - - ±1.5 dB (+13 to -7 dBm).
±1.95 dB (-7 to -77 dBm).
±2.75 dB (-77 to -137 dBm).
- Level flatness - - - - - - - - - - - - - - ±1 dB.
- Leakage- - - - - - - - - - - - - - - - - - <1 μV is induced in a two-turn, 2.5 cm diameter loop which is held 2.5 cm away from the front surface. (Loop feeds a 50 ohm receiver).

Spectral purity
- Harmonic output- - - - - - - - - - - - - - >26 dB below signal.
- Subharmonics - - - - - - - - - - - - - - - None detectable.
- Non-harmonics- - - - - - - - - - - - - - - >55 dB below signal for fundamental and non-harmonics <350 MHz.
>35 dB below signal for fundamental and non-harmonics >350 MHz.
- Residual AM- - - - - - - - - - - - - - - - >65 dB below carrier (50 Hz to 15 kHz post detection noise bandwidth).
- Residual FM- - - - - - - - - - - - - - - - <200 Hz (50 Hz to 15 kHz post detection noise bandwidth).

Amplitude modulation (for carrier ≤+3dBm)
- Frequency
  - Internal - - - - - - - - - - - - - - - - 400 Hz and 1 kHz ±5 percent.
  - External - - - - - - - - - - - - - - - - 25 Hz to 20 kHz.
- Range- - - - - - - - - - - - - - - - - - - 0 to 90 percent.
- Modulation indicator accuracy- - - - - - ± (5 percent of reading ±5 percent).
- Distortion - - - - - - - - - - - - - - - - <3 percent to 70 percent AM (5 percent to 90 percent AM) at 1 kHz.

Frequency modulation
- Frequency
  - Internal - - - - - - - - - - - - - - - - 400 Hz and 1 KHz, ±5 percent.
  - External - - - - - - - - - - - - - - - - 50 Hz to 25 kHz.
- Deviation peak - - - - - - - - -

Center frequency (f_c)	Maximum Peak Deviation 1/ (Δf_{pk})	
	Rates ≥60 Hz	Rates <60 Hz
0.1-123.5 MHz	99 kHz	1600 x Rate
123.5-247 MHz	25 kHz	400 x Rate
247-494 MHz	50 kHz	800 x Rate
494-990 MHz	99 kHz	1600 x Rate

1/ FM not specified for $f_c - \Delta f_{pk}$ < 100 kHz.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:51Z
Check the source to verify that this is the current version before use.

ITEM G11 - Continued

Accuracy	±500 Hz to 10 kHz. ±5 kHz to 100 kHz.
Distortion	<2 percent for 10 kHz to 100 kHz deviations at 1 kHz. <4 percent for 3 kHz to 10 kHz deviations at 1 kHz.
Specified operating range	25°C ±5°C.

EQUIPMENT MEETING ALL SPECIFICATIONS

Manufacturer	Hewlett Packard Model 8656A.
Manufacturer	Wavetek Model 3001.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:51Z
Check the source to verify that this is the current version before use.

ITEM J04

GENERATOR, PULSE

TYPE OF EQUIPMENT	Pulse generator.
FUNCTION PERFORMED	Generator of single pulses on pulse trains with controlled parameters.
SPECIFICATIONS	
Modes of operation	Internal, external trigger, gate, manual (one-shot pushbutton) single pulse (pulse 1 only), delayed pulse (pulse 2 only), double pulse.
Frequency data	
Pulse repetition rate (PRR)	1 Hz to 25 MHz (at reduced amplitudes). Higher effective (PRR) in double pulse mode. At least 3 MHz repetition rate at 100 V. Continuously variable.
Frequency jitter	0.1 percent of period +0.5 ns.
Pulse width data	
Range	20 ns to 500 ms less than 25 V; 20 ns to 5 ms @ 50 V; 30 ns to 0.1 ms @ 100 V.
Variation	Continuously variable; independent range and vernier control for pulse 1 and pulse 2.
Stability	0.1 percent of setting +0.5 ns.
Pulse delay data	
Range	15 ns to 500 ms (pulse 2 position with respect to leading edge of pulse 1). 45 ns to 500 ms, pulse 2 position with respect to sync.
Variation	Continuously variable.
Stability	0.1 percent of setting +0.5 ns.
Control	(Double pulse mode) controls pulse 1 to pulse 2 spacing.
Delayed pulse mode	Controls delay of output with respect to sync out and trigger in pulse 2 only output.
Input data	
Gate/trigger input	May be gated or trigger at rates to 25 MHz.
Internal sync	Internal clock may be synchronized by an external pulse; frequency ratio to 100:1 may be used to sync.
Threshold	-2 V to +2 V; continously variable through zero.
Sensitivity	Less than 0.1 V, 5 ns or wider input.
Impedance	Low (50Ω) or high (225Ω) switch selector.
Slope	Positive or negative; switch selector.
Delays	Trigger to sync, less than 15 ns; trigger to output less than 60 ns; sync to output, 45 ns.

Source: https://assist.dla.mil -- Downloaded: 202610-24T00:51Z
Check the source to verify that this is the current version before use.

Output data	Output source impedance 50Ω (voltage source) or 850Ω (current source). Positive or negative pulse polarity.
Amplitude	
Current mode	±10 mA to ±2 A.
Source impedance	850Ω.
Maximum voltage	110 V into open circuit.
Voltage mode	±20 mV to ±100 V from 50Ω. (±10 mV to 50 V into 50Ω.
Duty cycle	10 percent @ 2 A, 0.1 ms maximum width; high duty cycles for gated bursts; 50 percent @ 1 A, 5 ms maximum width; 100 percent @ 0.5 A and below; no duty cycle limitation below 25 V.
Overload protection	Operates into open or short circuit. Protection fully automatic. May drive inductive or capacitive loads.
Waveshape data	
Rise time	Less than 10 ns to greater than 50 ms; continuously variable.
Fall time	Less than 10 ns to greater than 50 ms; continuously variable.
Linearity	2 percent nonlinearity in rise time/fall time over 10 percent to 90 percent amplitude, any range.
Overshoot	Less than 5 percent of amplitude, maximum, of each range.
Distortion	Preshoot, undershoot, droop or other waveform anomalies less than 5 percent at full output.
Baseline offset data.	
Range	-100 mA to +100 mA; -5 V to +5 V into 50Ω; continuously variable.
Control	ON-OFF and continuous variation through zero. Baseline control not affected by output amplitude setting.
Sync output data	
Repetition rate	Same as clock frequency or trigger frequency.
Amplitude	+1 V into 50Ω.
Width	5 ns, minimum.
Rise/fall time	Less than 2 ns.

EQUIPMENT MEETING ALL SPECIFICATIONS

Manufacturer	Chronetics Model PG-13A, pulse generator.

EQUIPMENT MEETING SPECIFICATIONS
WITH EXCEPTIONS AS NOTED

Manufacturer	Hewlett Packard Model 2148.
Exceptions	1. Only one pulse output. 2. Frequency data. Pulse repetition rate: 10 Hz to 10 MHz (at reduced amplitudes). At least 4 MHz repetition rate on all amplitude ranges.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:51Z
Check the source to verify that this is the current version before use.

ITEM J04 - Continued

3. Pulse width data.
   Range:
   25 ns to 10 ms on all ranges.
4. Pulse delay data.
   Range:
   100 ns to 10 ms pulse 1 with respect to pulse 2 (double pulse mode). 60 ns to 10 ms output with respect to trigger.
5. Input data.
   Gate/trigger input:
   May be gated or trigger at rates to 10 MHz.
   Internal sync - no synchronization. of internal trigger available.
   Sensitivity - less than 0.5 V pp, 10 ns or wider input.
   Impedance - 10 kΩ nominal.
6. Output data.
   Output source impedance fixed 50 ohm on ranges up to 10 V. Selectable 50 ohm nominal or high impedance on 30 V and 100 V ranges.
7. Amplitude.
   Current mode not available.
   Voltage mode 300 mV to 50 V into 50Ω from 50Ω.
   Duty cycle - ≥10 percent maximum for 30-100 V ranges; ≥50 percent maximum for other ranges.
8. Transition time - ≤15 ns, not adjustable.
9. Offset - not adjustable.

Source: https://assist.dla.mil -- Downloaded: 202610-24T00:51Z
Check the source to verify that this is the current version before use.

ITEM V04

VOLTMETER, DC

TYPE OF EQUIPMENT	Digital dc voltmeter.
FUNCTION PERFORMED	DC voltage measurement.
SPECIFICATIONS	
Range	1.0000 V full scale +20 percent over-range. 10.000 V full scale +20 percent over-range. 100.000 V full scale +20 percent over-range. 1,000.0 V full scale.
Accuracy	±0.01 percent of reading ±0.01 percent of full scale; above 500 V ±0.01 percent of reading ±0.027 percent of full scale.
Resolution	100 μV (1 V range.
Input impedance	1 V: > 1,000 MΩ. 10 V: > 1,000 MΩ. 100 V: > 10 MΩ. 1,000 V: > 10 MΩ.
Temperature coefficient	±0.002 percent of reading ±0.008 percent of full scale/°C.
Voltage coefficient	±0.00005 percent/V if input exceeds 500 V.
Temperature range	+5°C to +45°C.
Normal mode rejection	>30 dB at 60 Hz. >40 dB at 120 Hz. >50 dB at 400 Hz.
EQUIPMENT MEETING ALL SPECIFICATIONS	
Manufacturer	Fairchild Model 7000 Digital Multimeter.
EQUIPMENT MEETING SPECIFICATIONS WITH EXCEPTIONS AS NOTED	
Manufacturer	*Fluke Model 8600 Digital Multimeter.*
Exceptions	Accuracy ±0.02 percent of reading ±0.005 percent of full scale; on 1,000 V scale ±0.04 percent of reading ±0.01 percent of full scale.

Supersedes page V04-1 of
20 January 1978

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:51Z
Check the source to verify that this is the current version before use.

ITEM W05

VOLTMETER, AC

TYPE OF EQUIPMENT	AC voltmeter.
FUNCTION PERFORMED	Meter measures the rms value (heating value) of the input signal for all waveforms.
SPECIFICATIONS	
Voltage range	12 full scale ranges from 1 mV to 300 V in a 1, 3, 10 sequence.
Frequency range	10 Hz to 10 MHz.
Accuracy	±5 percent of full scale from 10 to 50 Hz. ±1 percent of full scale from 50 Hz to 1 MHz. ±2 percent of full scale from 1 to 2 MHz. ±3 percent of full scale from 2 to 10 MHz. ±5 percent of full scale from 3 to 10 MHz.
Input impedance	10 MΩ shunted by 40 pF for 0.001 to 0.3 V range. 10 MΩ shunted by 40 pF for 1 to 300 V range.
Crest factor	(Ratio of peak amplitude to rms amplitude): 10:1 at full scale except where limited by maximum input.
EQUIPMENT MEETING ALL SPECIFICATIONS	
Manufacturer	Hewlett-Packard Model 3400A.
EQUIPMENT MEETING SPECIFICATIONS WITH EXCEPTIONS AS NOTED	
Manufacturer	John Fluke. Models 931A, 931B, 931P, and 931B rms ac differential voltmeters.
Exceptions	Input voltage range: 0.01 to 1,100 V rms, in five ranges of 0.1, 1, 10, 100, and 1,100 V rms, each with 10 percent over-ranging. Frequency range is from 10 Hz to 1 MHz. Input impedance is 1 MΩ in parallel with 8 pF.
Manufacturer	Boonton Electronics Model 93A.
Exceptions	Accuracy - 300 V scale is not calibrated above 100 kHz; 100 V scale is ±2 percent of full scale from 100 kHz to 1 MHz and not calibrated above 1 MHz; 30 V scale is ±2 percent of full scale from 100 kHz to 5 MHz and not calibrated above 5 MHz. Input impedance is 2 MΩ in parallel with ≤25 pF. Frequency response extends to 20 MHz with ±5 percent of full scale accuracy for 1 mV to 3 V ranges. Frequency response can be limited to 100 kHz by means of a selector switch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:51Z
Check the source to verify that this is the current version before use.

VOLTMETER, RF

TYPE OF EQUIPMENT - - - - - - - - - - - - - - - RF voltmeter.

FUNCTION PERFORMED- - - - - - - - - - - - - - - Measures high frequency ac voltages (true rms <30 mV, indication proportional to peak >30 mV).

SPECIFICATIONS

Voltage range - - - - - - - - - - - - - - - - 1 mV rms full scale to 3 V rms full scale in 1, 3, 10 sequence (8 ranges).

Frequency range - - - - - - - - - - - - - - - Calibrated 10 kHz to 2.4 GHz.

Accuracy- - - - - - - - - - - - - - - - - - - ± (1 percent full scale +1 percent reading) 10 kHz to 150 MHz
± (1 percent full scale +3 percent reading) 150 MHz to 700 MHz.
1 mV to 300 mV scales: ± (1 percent full scale +7 percent reading) 700 MHz to 1.2 GHz.
1 V to 3 V scales: ± (1 percent full scale +10 percent) 700 MHz to 1.2 GHz.

Input impedance - - - - - - - - - - - - - - -

	10 mV range	3 V range
100 KHz	100 kΩ min 2.8 pF max	1 MΩ min 1.8 pF max
1 MHz, 10 MHz	100 kΩ min	1 MΩ min
100 MHz	5 kΩ min	50 kΩ min

Crest factor- - - - - - - - -- - - - - - - - 420 to 42 on 1 mV scale.
42 to 14 on 3 mV scale.
14 to 4.2 on 10 mV scale.
4.2 to 1.4 on 30 mV scale.

EQUIPMENT MEETING ALL SPECIFICATIONS

Manufacturer- - - - - - - - - - - - - - - - - Ballantine Model 3440A with option 40.
Boonton Models 9200, 92B, or 92BD.

Source: https://assist.dla.mil -- Downloaded: 202610-24T00:51Z
Check the source to verify that this is the current version before use.