MILITARY SPECIFICATION

WRENCH, COUPLING, MEDIUM CABLEWAY

1. SCOPE

1.1 This specification covers a spanner type coupling wrench used in the medium cableway.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-621	- Boxes, Wood, Nailed and Lock Corner.

STANDARDS

Federal

FED. STD. No. 595	- Colors.

Military

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.

DRAWINGS

ME

DL13208E5074	- Wrench, Coupling, Medium Cableway.

(Copies of specifications, standards, and drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

FSC 5420

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:14Z
Check the source to verify that this is the current version before use.

PWER UNIT shall be fabricated 3.3.1 Material identification and control. The

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification.

(Application for copies should be addressed to the Tariff Publishing Officer, Room 202, Union Station, 516 West Jackson Boulevard, Chicago, Illinois 60606.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., ATTN: Tariff Order Section, 1616 P Street NW, Washington, D. C. 20036.)

3. REQUIREMENTS

3.1 Description. The coupling wrench shall be as shown on DL13208E5074 and as specified herein.

3.1.1 Drawings. The drawings forming a part of this specification are engineering design drawings. No deviation from the prescribed dimensions or tolerances is permissible without prior approval of the contracting officer. Any data (e.g., shop drawings, layouts, flow sheets, processing procedures, etc.) prepared by the supplier or obtained from a vendor to support fabrication and manufacture of the production item shall be made available, upon request, for inspection by the contracting officer or his designated representative.

3.2 First article (preproduction model). The supplier shall furnish one coupling wrench for examination within the time frame specified, to prove prior to starting production, that his production methods will produce coupling wrenches that comply with the requirements of this specification. Examination shall be as specified in section 4 and shall be subject to surveillance and approval by the Government (see 6.3).

3.3 Material. Material shall be as specified herein and as shown on the drawings. Materials not specified shall be selected by the supplier and shall be subject to all provisions of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:14Z
Check the source to verify that this is the current version before use.

3.4 Identification marking. The coupling wrench shall be metal-die stamped as shown on the drawings. Die stamping shall be legible after painting.

3.5 Cleaning, treatment, and painting. The coupling wrench shall be cleaned, treated, and painted as specified on the drawings, except that the color number designation shall be 24087 or 34087 in accordance with FED. STD. No. 595.

3.6 Workmanship.

3.6.1 Steel fabrication. Steel used in the fabrication of the coupling wrench shall be free from laminations, kinks, and sharp bends. The straightening of material shall be done by methods that will not cause injury to the metal. Shearing and chipping shall be done neatly and accurately. Corners shall be square and true. Flame cutting with a tip suitable for the thickness of metal may be employed instead of shearing or sawing. Burned surfaces of flame-cut material shall be ground or machined sufficiently to remove ash and cooling checks. All bends shall be made with metal dies or fixtures to insure uniformity of size and shape. Precautions shall be taken to avoid overheating, and heated metal shall be allowed to cool slowly. All burrs and rough edges shall be ground smooth.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Component and material inspection. The supplier is responsible for insuring that components and materials used are manufactured, examined, and tested in accordance with referenced specifications and standards.

4.1.2 Parts and components. Parts and components detailed on the drawings shall be inspected in accordance with the Supplementary Quality Assurance Provisions (SQAP) shown on the drawings. The drawings specify the characteristscs requiring SQAP inspection, the sampling plan, and the basis for acceptance or rejection (see 6.4 and 6.5).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:14Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspection. Inspection shall be classified as follows:

(a) Preproduction inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).
(c) Inspection of preparation for delivery (see 4.6).

4.3 Preproduction inspection.

4.3.1 Examination. The preproduction coupling wrench shall be examined for the defects specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.4 Quality conformance inspection.

4.4.1 Sampling for examination. Sampling for examination shall be in accordance with MIL-STD-105.

4.4.2 Examination. Samples selected in accordance with 4.4.1 shall be examined for the major and minor defects specified in 4.5.1. AQL shall be 2.5 percent defective for major defects and 4.0 percent defective for minor defects.

4.5 Inspection procedure.

4.5.1 Examination. The coupling wrench shall be examined for the following defects:

Major

101. Any part or component not in accordance with the SQAP requirements shown on the drawings.
102. Material not as specified.
103. Workmanship not as specified.

Minor

201. Dimensions other than those identified by SQAP data not as specified.
202. Identification marking incorrect, missing, or illegible.
203. Cleaning, treatment, and painting not as specified.

4.6 Inspection of preparation for delivery.

4.6.1 Quality conformance inspection of pack.

4.6.1.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:14Z
Check the source to verify that this is the current version before use.

4.6.1.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.6.1.3 Examination. Samples selected in accordance with 4.6.1.2 shall be examined for the following defects. AQL shall be 2.5 percent defective.

104.	Wrenches not packed in multiples of four or boxes containing more than 100 wrenches for level A, B, or C.
105.	Boxes not as specified for level A or B.
106.	Contents not secured to prevent movement for level A or B.
107.	Strapping not zinc coated for level A.
108.	Marking missing, illegible, incorrect, or incomplete for level A, B, or C.

5. PREPARATION FOR DELIVERY

5.1 Packing. Packing shall be level A, B, or C as specified.

5.1.1 Level A. The wrenches shall be packed in multiples of four, not to exceed 100, in close-fitting boxes conforming to PPP-B-621, class 2, style optional, or PPP-B-601, overseas type, style optional. The contents shall be secured within the box to prevent movement. The boxes shall be closed and strapped in accordance with the appendix to the applicable box specification. Strapping shall be zinc coated.

5.1.2 Level B. The wrenches shall be packed as specified in 5.1.1 for level A, except the boxes shall be domestic type or class as applicable. Strapping is not required to be zinc coated.

5.1.3 Level C. The wrenches shall be packed in multiples of four, not to exceed 100, in containers that will assure carrier acceptance and safe delivery to destination at lowest rating in compliance with Uniform Freight Classification rules or National Motor Freight Classification rules.

5.2 Marking. Packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The coupling wrench is intended to be used for tightening the cable coupling when splicing the track cable of the medium cableway.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:14Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Time frame required for submission of preproduction model (see 3.2).
(c) Level of packing required (see 5.1).

6.3 Preproduction model. Any changes or deviations of production coupling wrenches from the approved preproduction model during production will be subject to the approval of the contracting officer. Approval of the preproduction model will not relieve the supplier of his obligation to furnish coupling wrenches conforming to this specification.

6.4 Supplementary Quality Assurance Provisions (SQAP). The contracting officer should require the supplier to maintain records of all SQAP inspections. A suggested paragraph is as follows:

"The supplier shall maintain complete records of all examinations and tests performed to verify the requirements of classified SQAP characteristics. The records shall include as a minimum, lot size, sample size, drawing requirement, actual measurement, number and type of deficiencies found, quantity approved, quantity rejected, corrected action taken when applicable."

6.5 Definitions.

6.5.1 Supplementary Quality Assurance Provisions (SQAP). A SQAP is a contractual requirement that supplements section 4 of the specification. SQAP indicates the minimum requirement which must be inspected on the product drawings to verify the design objectives of the product and assure interchangeability of repair parts.

Custodian:

Army - ME

Preparing activity:

Army - ME

Project No. 5420-A214

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:14Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

MIL-W-52319A(ME) Wrench, Coupling, Medium Cableway

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 20261O-22T21:14Z
Check the source to verify that this is the current version before use.

 Finish not as specified

FOLD

DEPARTMENT OF THE ARMY
U. A. ARMY MOBILITY EQUIPMENT COMMAND
RESEARCH, DEVELOPMENT AND ENGINEERING DIRECTORATE
ATTN: AMSME-RZG
FORT BELVOIR, VIRGINIA 22060

OFFICIAL BUSINESS

POSTAGE AND FEES PAID

DEPARTMENT OF THE ARMY
U. S. ARMY MOBILITY EQUIPMENT COMMAND
RESEARCH, DEVELOPMENT AND ENGINEERING DIRECTORATE
ATTN: AMSME-RZG
FORT BELVOIR, VIRGINIA 22060

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:14Z
Check the source to verify that this is the current version before use.