DATA ITEM DESCRIPTION

TITLE: PLANNED MAINTENANCE SYSTEM (PMS) MAINTENANCE INDEX PAGE (MIP)

Number: DI-SESS-80992A
AMSC Number: N9174
DTIC Applicable: N/A
Office of Primary Responsibility: SH/SEA 04RM.
Applicable Forms: N/A

Approval Date: 20100923
Limitation: N/A
GIDEP Applicable: N/A

Use/Relationship:
The Planned Maintenance System (PMS) Maintenance Index Page (MIP) provides a concise index and cross-reference to all MRCs within the MIP set.

This Data Item Description (DID) contains the format, content, preparation instructions and intended use for the PMS Maintenance Index Page (MIP) resulting from the work described in paragraph 5.1.12 of MIL-STD-3034.

This DID is related to DI-SESS-80991A, Planned Maintenance System (PMS) Maintenance Requirement Card (MRC).

This DID supersedes DI-MNTY-80992.

Requirements:

1. Reference documents. The applicable issue of documents cited herein, including approval dates and dates of any applicable amendments, notices, and revisions, shall be as cited in the contract.

2. Format. The Planned Maintenance System (PMS) Maintenance Index (MIP) shall be documented using contractor format.

3. Content. The MIP shall contain all the information specified in Figure 1 of this did as follows:

3.1. Block 1. SYSCOM MIP Control Number. This number is provided by the PMS coordinating activity.

3.2. Block 2. Date. Leave blank unless provided by PMS coordinating activity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:42Z
Check the source to verify that this is the current version before use.

3.3. Block 3. Ship system, system, subsystem, or equipment. Enter the nomenclature and ESWBS number for the lowest level to which all the listed requirements apply.

3.4. Block 4. Reference publications. Enter the identifying number of the publication providing the most comprehensive maintenance information for the system or equipment for which the PMS documentation is being prepared; for example, Operational Procedures (Ops), NAVSEA instruction books, manufacturers' pamphlets, NAVSEA technical manuals, and so forth. If additional space is required, enter the phrase: "See Note." A note shall be entered in the Maintenance Requirements (MR) description area to provide the additional referenced publications.

3.5. Block 5. Configuration. Maintenance index pages that index MRs for group Expanded Ship Work Break-Down Structure (ESWBS) levels 1, 2, or 3 or those that combine more than one ESWBS level 4 grouping, shall contain the level 4 ESWBS numbers and nomenclatures. The level 5 item numbers and nomenclature shall be included; this may include military designation or manufacturer name (CAGE) and part number. Level 5 items are typically subassemblies of the equipment under analysis, and normally designated as a sub-group of the equipment. When directed by the PMS coordinating activity, enter the change configuration of system or equipment for which documentation is intended. Each FIELD CHANGE, SHIPALT, ORDALT, or other officially authorized hardware change considered in the development shall be included. Each change that affects maintenance procedures shall be preceded by an asterisk; for example, ORDALTS: *7176, 7380, *7662. When individual elements which make up the system or equipment being documented are not readily identifiable as part of the system or equipment, these and their individual change configurations shall be listed in this area. When other information regarding the composition of the system or equipment being documented will facilitate maintenance or management it will be included in this area. Use brief statements such as Level of Repair Analysis (LORA) configuration or serial numbers 7-30 only. If additional space is required, the configuration data shall be continued in the MR description area by use of a note. When the configuration data is so voluminous as to be impractical to include on the MIP, enter the identification of the publication from which configuration data can be obtained. In those cases where configuration data is not required, this area shall not be included on the MIP.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:42Z
Check the source to verify that this is the current version before use.

3.6. Block 6. Scheduling aids. All notations affecting the scheduling of MRs shall be located in the MR column preceding the first MR description. When scheduling aids include more than one topic, they shall be typed in boldface and numbered under a scheduling aid heading; for example:

a. Scheduling aids:

(1) Schedule MRC A-3 for accomplishment during annual crypto reload.

(2) Review MRCs A-9 and A-11. Omit requirement if not applicable to your configuration; no feedback report required.

b. Asterisks and the symbol # shall be used to call attention to specific scheduling information as follows:

(1) * Safety of ship items

(2) ** For scheduling purposes only; no MRC is provided.

(3) # Mandatory scheduling required.

3.7. Column 7. Other. Enter the specialized management code, as applicable, listed below. If the MRC is also classified, a two-character code will be entered. The second character space shall identify the MRCs security classification. If there is no applicable specialized management code but the MRC is classified, the classification code shall be in this column.

R – Denotes a MR on Deep Submergence Recovery Vehicles (DSRV) system and equipment that is within the scope of certification.

RC – Denotes a MR on DSRV systems and equipment that is within the scope of certification and is also a confidential MRC.

K – Denotes a MR (no test) developed under the cognizance of SMMSO.

C – Confidential

S – Secret

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:42Z
Check the source to verify that this is the current version before use.

3.8. Column 8. SYSCOM MRC control number. Enter the control number as recorded on the MRC. In the case of newly developed MRs, the control number will be applied by the PMS coordinating activity.
3.9 Column 9. Maintenance requirement description. The MR description shall appear exactly as it appears on the applicable MRC. The first line of the first maintenance description shall be two spaces below the scheduling aid or column border if no scheduling aids apply. When the MRCs aggregated on a MIP are applicable to a number of systems or equipment or units lower than the one shown in the MIP heading, the specific system or equipment unit shall be entered in boldface type (or underlined) on the line preceding the actual MR. Both item names and nomenclature designation shall be provided.

3.9.1. Notes. Notes shall be used to define “R” requirements in the operational maintenance section of the MIP and to continue entries too numerous for the space provided in the reference publication and configuration areas. In addition, notes shall be used to provide management information applicable to a specific MRC; for example, “NOTE: This MRC is applicable to Mod 1 only”. The note(s) shall be placed immediately after the last MR description for that MRC and shall be unnumbered. If more than one note is required for the same MRC, the note defining the R requirement shall be listed first.

3.9.2. Scheduling notations. The first scheduling notation shall be located at least two spaces below the top line which borders the MR column. Two spaces shall be allowed between each scheduling entry.

3.10. Column 10. Periodicity. Enter the periodicity code as shown on the MRCs. The MRCs shall be listed in the following sequence of decreasing frequency: D, 2D, 3D, W, 2W, M, 2M, Q, 4M, S, 8M, 9M, A, 18M, 24M, 30M, 36M, 48M, 54M, 60M, R, and U. Within each periodicity group, list the MRCs in numerical sequence, for example: D-1, D-2, D-3, W-1, W-2, M-1, M-2, Q1R, Q-2, A-1, 18M-1, R-1, R-2, U-1, U-2. When reapplying previously developed MRCs, the condition may occur where the existing MRC is applicable but the number associated with the periodicity falls out of consecutive order. Skipping of sequential code numbers is acceptable; for example: Q-1, Q-3, Q-4, Q-7. Asterisks are used in the periodicity column to call attention to scheduling information applicable to a specific MR. The standard use of the asterisk is listed below.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:42Z
Check the source to verify that this is the current version before use.

3.10.1. Use a single asterisk (*) to indicate safety of ship items. The use of the term “safety of ship” is restricted to submarines. The designation of safety of ship items will be recommended by Maintenance Requirement Development Activity (MRDA) by annotation on the verification copy of MIP; for example, Q-1*. The safety of ship notation shall be entered on the verification copy.

3.10.2. Use the double asterisk (**) to indicate that the requirement is listed for scheduling purposes only and there is no MRC. The double asterisk shall be placed beneath the applicable periodicity code in this column, and the notation shall be entered in the MR column.

3.11. Column 11. Rates. Enter the rates required as shown on the MRCs.

3.12. Column 12. Man-hours. Enter the man-hours for each rate shown on the MRCs.

3.13. Column 13. Related maintenance. Enter the periodicity codes for MRCs which are identified as related during the procedure evaluation process. Entries in the related maintenance column shall be listed only with the MRC of the longest periodicity; for example, if a weekly and a monthly MRC are related, only the monthly MRC would indicate the related maintenance. If two MRCs of the same frequency are related, the related MRCs shall be entered with both MRCs. When the related MRC is from the same MIP, list only the periodicity code, for example, M-3. When it is of another MIP, list the MIP series of the code also; for example, “5600016: M-3”. When the accomplishment of the related MRC is mandatory, # shall be placed after the periodicity code; for example “M-3#”. When the related MRC is merely a convenience, the # shall be omitted. When there is no related maintenance, the word “None” shall be entered.

3.14. Column 14. Unscheduled Maintenance. Entries for columns Other, SYSCOM MRC control number, periodicity, and related maintenance shall follow the convention set forth in their respective paragraphs above. These requirements shall be separated from the maintenance requirements by a horizontal line and use of boldface print. The MR description shall be written exactly as it appears on the applicable MRC. The first line of the first maintenance description shall be two spaces below the column border. A note shall be included for each unscheduled

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:42Z
Check the source to verify that this is the current version before use.

maintenance task to identify the situational requirement necessitating the unscheduled maintenance. Entries for rates and man-hours are not required.

3.15. Column 15. Inactive Equipment Maintenance Requirements. Entries for columns Other, SYSCOM MRC control number, periodicity, rates, man-hours, and related maintenance shall follow the convention set forth in their respective paragraphs above. Enter SYSCOM control numbers from the applicable MRCs, in the case of newly developed IEM requirements, the control number will be applied by the PMS coordinating activity. The IEM requirements shall be listed on the MIP following the unscheduled maintenance requirements. The requirements shall be separated from the unscheduled requirements by a horizontal line and use of boldface print. The IEM section shall be titled Inactive Equipment Maintenance. The first entry following the title shall be: “The following requirements will be scheduled when equipment is inactive for periods of prolonged idleness”. When no IEM requirements are justified during IEM analysis, enter the words, “None required.” The IEM requirements shall be entered as follows:

3.15.1. The IEM requirements shall be grouped under the following subheads: Lay up Maintenance, Periodic Maintenance, Start-Up Maintenance, and Operational Test. The subheads shall be initial caps, underlined or boldface print.

3.15.2. When Lay Up Maintenance (LU) MRCs are prepared to support system or equipment periods of prolonged idleness, Start-Up (SU) MRCs shall be required suitable for system or equipment operation or activation.

3.15.3. Within each subheading, IEM MRCs will either be a scheduling "pointer" MRC, a step-by-step procedure MRC, or a combination of both. Pointer MRCs must reference a complete MRC. If only one MRC is referenced, the Maintenance Requirement (MR) will duplicate the MR on the MRC being referenced. If the “Pointer MRC” references a complete MRC with one or more MRs, the MIP entry will be a generic MR that encompasses all of the MRC tasks. If the “Pointer MRC” references multiple MRCs, the MIP entry will be a generic MR that encompasses all of the MRCs tasks.

3.15.4. The word “None” shall be entered for any subhead where IEM does not apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:42Z
Check the source to verify that this is the current version before use.

3.15.5. Inactive equipment maintenance-periodicity column. For new MRCs developed exclusively to satisfy IEM requirements, enter the periodicity code as shown on the IEM MRC. IEM pointer MRCs will be given an IEM periodicity code applicable to the action being taken. The MRCs shall be listed in the following sequence: LU, PM, SU and OT.

3.15.6. Inactive equipment maintenance rates column. MRCs with procedural steps shall include the rate(s) required to perform those steps. MRC pointer cards shall include only the highest rate that is required to perform and MRC listed.

3.15.7. Man-hours inactive equipment maintenance. Inactive equipment MRs making reference to equipment operational MRCs shall contain 0.1 hr in the man-hours column. MRCs with procedural steps shall include the man-hours to perform those steps. If MRC is a blend of reference to operational MRCs and procedural steps, only include the man-hours to perform the procedural steps.

3.16. Page number. All pages of a MIP shall be identified by completing the entry “Page _ of _” on the bottom of the sheet.

4. End of DI-SESS-80992A.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:42Z
Check the source to verify that this is the current version before use.

1. SYSCOM MIP CONTROL NUMBER:	2. DATE:
3. NOMENCLATURE:	
4. REFERENCE PUBLICATIONS:	
5. CONFIGURATION:	
6. SCHEDULING AIDS:	

7. OTHER	8. MRC NO.	9. MAINTENANCE REQUIREMENT DESCRIPTION	10. PERIO-DICITY CODE	11. RATES	12. MAN-HOURS	13. RELATED MAINT
		14. UNSCHEDULED MAINTENANCE				
		15. INACTIVE EQUIPMENT MAINTENANCE				

PAGE OF

MAINTENANCE INDEX PAGE

FIGURE 1. MAINTENANCE INDEX PAGE

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:42Z
Check the source to verify that this is the current version before use.