NOTE: The document identifier and heading has been changed on this page to reflect that this is a performance specification. There are no other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised.

INCH-POUND

MIL-PRF-39016/54C
AMENDMENT 1
22 June 1992

PERFORMANCE SPECIFICATION SHEET

RELAYS, ELECTROMAGNETIC, ESTABLISHED RELIABILITY, HERMETICALLY SEALED, 4PDT, LOW-LEVEL TO 2 AMPERES (0.150-INCH TERMINAL SPACING) WITH INTERNAL DIODE FOR COIL TRANSIENT SUPPRESSION AND POLARITY REVERSAL PROTECTION

This amendment forms a part of MIL-R-39016/54C, dated 20 July 1988, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

FIGURE 1, note 9, delete in its entirety and substitute:

"9. Finish shall be gold plated in accordance with MIL-G-45204, type II, class 1, grade C, except that Knoop hardness shall be 130 to 240. Nickel underplating shall be in accordance with QQ-N-290 (50 to 150 microinches thick)."

PAGE 3

Under load ratings, high level, entry for "Resistive": Delete "400 Hz life test not required for qualification testing."

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - AR
Navy - AS, OS, SH
Air Force - 99
DLA - ES

User activities:
Navy - MC
Air Force - 19

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5945-0894-01)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:53Z
Check the source to verify that this is the current version before use.