INCH-POUND

MIL-R-39016/50B
AMENDMENT 1
21 September 1992

MILITARY SPECIFICATION

RELAYS, ELECTROMAGNETIC, HIGH SHOCK AND HIGH VIBRATION, ESTABLISHED RELIABILITY, DPDT, LOW LEVEL TO 1.0 AMPERE WITH INTERNAL DIODE FOR COIL TRANSIENT SUPPRESSION

This amendment forms a part of MIL-R-39016/50B, dated 20 July 1988, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 7

QUALIFICATION INSPECTION, group A testing for relays supplied with spreader pads (-013 through -018), shall be tested as specified below, delete and substitute:

"Perform seal test immediately, preceding the subgroup 3 electrical tests. Relay leads shall be formed and the mounting pad removed before the seal test. After the seal test, the mounting pad shall be rigidly attached to the relay and the remaining group A tests performed."

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Navy - AS
Air Force - 99
DLA -ES
NSA - NS

User activities:
Army - AR
Navy - MC, OS, SH

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5945-0900-20)


DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:52Z
Check the source to verify that this is the current version before use.