INCH-POUND

MIL-R-39017/1N
19 March 1991
SUPERSEDING
MIL-R-39017/1M
12 January 1990

MILITARY SPECIFICATION

RESISTORS, FIXED, FILM (INSULATED), ESTABLISHED RELIABILITY STYLE RLR07

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the detail requirements for style RLR07, established reliability, insulated, film, fixed resistors.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

* 2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATION

MILITARY

MIL-R-39017 - Resistors, Fixed, Film, (Insulated), Established Reliability, General Specification For.

* (Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Requirements. Requirements shall be in accordance with MIL-R-39017, and as specified herein.

3.2 Design, construction, and physical dimensions. Resistors shall be of the design, construction, and physical dimensions specified on figure 1.

3.3 Power rating. The power rating shall be 0.25 watt.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Laboratory Command (LABCOM), ATTN: SLCET-R-S, Fort Monmouth, NJ 07703-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 5905

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:58Z
Check the source to verify that this is the current version before use.

3.4 Voltage rating. The continuous working voltage shall not exceed 250 volts.

* 3.5 Resistance. Minimum and maximum resistance values for temperature characteristics of ±100 PPM and ±350 PPM shall be as follows:

	100 PPM	350 PPM
Minimum resistance	10Ω	11 MΩ
Maximum resistance	10 MΩ	22 MΩ

3.6 Maximum weight. The maximum weight shall not exceed 0.5 gram.

3.7 Marking. Due to size limitations this style resistor shall be marked with the following minimum information:


603AJ - Year and week manufactured, lot code (letters "O" and "I" excluded), JAN marking.

RLR7C - Partial style ("0" deleted for partial marking), terminal.

1002F - Resistance value, tolerance.

M* - Failure rate designator and manufacturer's code (see qualified products list for manufacturer's code symbols).

Full marking is required on the unit package.



Inches	mm
.002	0.05
.008	0.20
.016	0.41
.025	0.64
.031	0.79
.046	1.17
.090	2.29
.125	3.18
.250	6.35
.300	7.62
1.500	38.10

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Maximum length is "clean lead" to "clean lead".
4. The end of the body shall be that point at which the body diameter equals the nearest drill size larger than 250 percent of the nominal lead diameter.
5. Lead length for tape and reel packaging shall be 1 inch minimum.

FIGURE 1. Style RLR07 resistor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:58Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. Sampling and inspecton shall be in accordance with MIL-R-39017.

4.2 Power conditioning. The maximum voltage applied shall not exceed 250 volts, ac or dc.

4.3 Dielectric withstanding voltage. The test voltages applicable to style RLR07 are as follows:

Atmospheric pressure - 500 volts rms.
Barometric pressure - 250 volts rms.

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-R-39032.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Notes. The notes specified in MIL-R-39017 are applicable to this specification.

6.2 Substitution data.

6.2.1 MIL-R-22684. Resistors of this specification, regardless of their failure rate designation are substitutes for resistors of the same resistance value and tolerance specified in the inactivated specification sheet MIL-R-22684/1.

6.2.2 MIL-R-11. Resistors of this specification of resistance tolerance "G" are substitutes for style RC12 of MIL-R-11/9 in the following resistance range: 10 ohms through .300 megohm inclusive. Use MIL-R-39008/1, style RCR07 resistance tolerance "G" for RC12 values from 2.7 ohms through 9.1 ohms and .330 megohm through 22 megohms inclusive.

6.3 Changes from previous issue. The margins of this specification are marked with asterisks to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on he entire content irrespective of the marginal notations and relationship to the last previous issue.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - AR
Navy - AS, OS
Air Force - 17, 99

User activites:
Army - AT, AV, ME
Navy - CG, MC

Preparing activity:
Army - ER

Agent:
DLA - ES

(Project 5905-1229)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:58Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-R-39017/1N	2. DOCUMENT DATE (YYMMDD) 19 March 1991

3. DOCUMENT TITLE
Resistors, Fixed, Film (Insulated), Established Reliability Style RLR07

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME Commander LABCOM	b. TELEPHONE (Include Area Code) (1) Commercial (908) 544-3441	(2) AUTOVON 995-3441
c. ADDRESS (Include Zip Code) ATTN: SLCET-RS Ft. Monmouth, NJ 07703-5000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

DD Form 1426, OCT 89 — Previous editions are obsolete. — 198-290

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:58Z
Check the source to verify that this is the current version before use.