INCH-POUND

MIL-R-39016/619
AMENDMENT 1
24 April 1990

MILITARY SPECIFICATION

RELAYS, ELECTROMAGNETIC, ESTABLISHED RELIABILITY, DPDT, LOW LEVEL TO 1 AMPERE WITH INTERNAL DIODES FOR COIL TRANSIENT SUPPRESSION AND POLARITY REVERSAL PROTECTION, TERMINALS 0.100-INCH GRID PATTERN INCLUDING INSPECTIONS OF APPENDIXES A AND B

This amendment forms a part of MIL-R-39016/619, dated 24 August 1989 and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Figure 1: Delete ".370 SQ MAX" and substitute ".375 SQ MAX".

PAGE 2

Figure 1: Delete ".370 SQ MAX" and substitute ".375 SQ MAX".

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - AR
Navy - AS, OS, SH
Air Force - 99
DLA - ES

User activities:
Navy - MC
Air Force - 11

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5945-0831-09)

AMSC N/A

FSC 5945

DISTRIBUTION STATEMENT A Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:55Z
Check the source to verify that this is the current version before use.