

MILITARY SPECIFICATION SHEET

RELAYS, ELECTROMAGNETIC, ESTABLISHED RELIALBILITY, DPDT, LOW LEVEL TO 1.0 AMPERE, TERMINALS 0.100-INCH GRID PATTERN (SENSITIVE, 60 MILLIWATTS, COIL OPERATE AT 25°C), INCLUDING INSPECTIONS OF APPENDIXES A AND B


This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-R-39016.





CIRCUIT DIAGRAM
TERMINAL VIEW



TERMINAL VIEW
APPLICABLE TO
-025 THRU -032 ONLY
(SEE NOTE 7)


Inches	mm
.001	0.03
.002	0.05
.003	0.08
.017	0.43
.031	0.79
.035	0.89
.100	2.54
.335	8.51
.370	9.40
.375	9.52


NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ±.010 (0.25 mm).
4. Terminal numbers shown above are for reference only. Numbers do not appear on relay.
5. Coil symbol optional in accordance with MIL-STD-1285.
6. Circuit diagram on part is the terminal view.
7. Dash numbers -025 through -032 shall be supplied with a case grounding pin welded to the header as shown.

FIGURE 1. Dimensions and configuration.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.


Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:56Z
Check the source to verify that this is the current version before use.






MOUNTING PAD

Inches	mm	Inches	mm
.001	0.03	.047	1.19
.002	0.05	.100	2.54
.003	0.08	.170	4.32
.005	0.13	.335	8.51
.014	0.36	.370	9.40
.017	0.43	.375	9.52
.031	0.79	.400	10.16
.035	0.89	.500	12.70



TERMINAL VIEW
APPLICABLE TO
-033 THRU -040 ONLY
(SEE NOTE 9)



CIRCUIT DIAGRAM
TERMINAL VIEW

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ±.010 (0.25 mm).
4. Terminal numbers shown above for reference only. Numbers do not appear on relay.
5. Relays shall have a plus (+) sign placed on the circuit diagram as shown.
6. Coil symbol optional in accordance with MIL-STD-1285.
7. Circuit diagram shown on part is the terminal view.
8. Mounting pad shall be a polyester film in accordance with MIL-I-631, type G, class I.
9. Dash numbers -033 through -040 shall be supplied with a case grounding pin welded to the header as shown.

FIGURE 2. Dimensions and configuration (relay with mounting pad).

Source: https://assist.dla.mil -- Downloaded: 202610-21T17:56Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Cleaning and small particle inspection: Applicable.

CONTACT DATA:

Load ratings:

High level (relay case grounded):

Resistive:

1.0 ampere at 28 V dc.

500 milliamperes at 115 V ac 400 Hz case not grounded.

250 milliamperes at 115 V ac 60 Hz case not grounded.

100 milliamperes at 115 V ac 60 Hz case grounded.

Inductive load: 0.2 ampere at 28 V dc with 0.32 henry inductance.

Lamp: 0.10 ampere at 28 V dc.

Low level: 10 to 50 µA at 10 to 50 mV dc or peak ac.

Intermediate current: Applicable.

Contact resistance or voltage drop:

Initial: 0.10 ohm maximum (0.110 ohm maximum with spacer pad).

High level:

During life: Not more than 5 percent of open circuit voltage.

After life: 0.20 ohm maximum (0.210 ohm maximum with spacer pad).

Low level:

During life: 100 ohms maximum.

After life: 0.15 ohm maximum (0.160 ohm maximum with spacer pad).

Intermediate current:

During: 3 ohms maximum.

After: 0.20 ohm maximum (0.210 ohm maximum with spacer pad).

Contact bounce: 1.5 milliseconds (ms) maximum (applicable for after high level rated load life and intermediate current tests).

Contact stabilization time: 2.5 milliseconds maximum.

Overload (high level only): Two times rated current.

COIL DATA: See table I.

Operate time: 4.0 ms maximum over temperature range with rated coil voltage.

Release time: 7.5 ms maximum over temperature range with rated coil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:56Z
Check the source to verify that this is the current version before use.

ELECTRICAL DATA:

Insulation resistance: 10,000 megohms minimum at 500 V dc, except the resistance between coil and case at high temperature shall be 1,000 megohms minimum.

Dielectric withstanding voltage:

	Sea level V rms (60 Hz)	Altitude V rms (60 Hz)
Between case, frame, or enclosure and all contacts both in the energized and deenergized positions	500	125 All terminals to case
Between case, frame, or enclosure and coils	500	
Between all contacts and coils	500	
Between open contacts in the energized and deenergized positions	500	
Between contact poles	500	
Between coils of dual coil relays	---	

ENVIRONMENTAL DATA:

Temperature range: -65°C to +125°C.

Vibration (sinusoidal): MIL-STD-202, method 204. Contact chatter shall not exceed 10 microseconds maximum for closed contacts, and 1 microsecond maximum closure for open contacts.

Vibration (random): MIL-STD-202, method 214, test condition IG. Contact chatter shall not exceed 10 microseconds maximum for closed contacts, and 1 microsecond maximum closure for open contacts. Applicable to qualification, group C, and group A inspection testing.

Shock (specified pulse): MIL-STD-202, method 213, test condition B (75 g's). Contact chatter shall not exceed 10 microseconds maximum for closed contacts, and 1 microsecond maximum closure for open contacts.

Magnetic interference: Applicable.

Resistance to soldering heat: Applicable.

Acceleration: Applicable.

Salt atmosphere (corrosion): In accordance with MIL-STD-750, method 1041.

Particle impact noise detection: Applicable.

PHYSICAL DATA:

Terminal:

Terminal strength: 1 pound pull minimum.

Terminal twist test: As specified in MIL-R-39016.

Dimensions and configuration: See figure 1 and table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:56Z
Check the source to verify that this is the current version before use.

TABLE I. Dash numbers and characteristics 1/

Dash numbers 2/					Coil voltages V dc 3/		At +25°C				Over temperature range		
Lead length .500 min	Lead length .187 ±.010	Mounting pads (fig. 2) 4/	Lead length .500 with ground pin 5/	Mounting pads (fig. 2) with ground pin 4/5/	Rated	Max	Coil resistance ohms ±10%	Specified pickup value (voltage) (V dc)	Specified hold value (voltage) (V dc)	Specified dropout value (voltage) (V dc)	Specified pickup value (voltage) (V dc)	Specified hold value (voltage) (V dc)	Specified dropout value (voltage) (V dc)
001	009	017	025	033	5.0	7.5	100	2.6	1.4	0.23	3.5	2.5	0.12
002	010	018	026	034	6.0	10.0	200	3.4	2.0	0.28	4.5	3.2	0.18
003	011	019	027	035	12.0	20.0	800	7.0	4.0	0.64	9.0	6.5	0.41
004	012	020	028	036	26.5	40.0	3,200	14.0	8.0	1.4	18.0	13.0	0.89
005	013	021	029	037	36.0	57.0	6,500	20.0	10.0	1.8	27.0	19.0	1.25
006	014	022	030	038	48.0	75.0	11,000	25.8	13.0	2.47	36.0	26.0	1.60
007	015	023	031	039	9.0	15.0	400	4.85	3.0	0.55	6.8	4.9	0.35
008	016	024	032	040	18.0	30.0	1,600	9.8	6.0	0.92	13.5	10.0	0.59

1/ Each relay possesses high level and low level capabilities. However, relays previously tested or used above 10 mA resistive at 6 V dc maximum or peak ac open circuits not recommended for subsequent use in low level applications.

2/ The suffix letter M, P, or R to designate the applicable failure rate level shall be added to the applicable listed dash number. Failure rate level (percent per 10,000 cycles): M, 1.0; P, 0.1; R, 0.01.

Example, 033M - - - - - 040R.

3/ Caution: The use of any coil voltage less than the rated coil voltage will compromise the operation of the relay.

4/ Relays supplied with mounting pads (-017 through -024 and -033 through -040) shall have the pad rigidly attached.

5/ Dash numbers -025 through -040 shall be supplied with a case grounding pin welded to the relay header (see figures 1 and 2).

Source: https://assist.dla.mil -- Downloaded: 202610-21T17:56Z
Check the source to verify that this is the current version before use.

Terminations: See figure 1 and table I.

Weight: 4.30 grams (0.15 ounce) maximum.

Solderability: Applicable.

Seal: Hermetic, adjunct sealant shall not be used.

Minimum marking: Military PIN, "J" with the date code (example J8830), circuit diagram, manufacturers' name or source code.

LIFE TEST REQUIREMENTS:

High level: 100,000 cycles per relay.

Low level: 100,000 cycles plus 900,000 cycles mechanical life.

Part or Identifying Number (PIN): M39016/641- (dash number from table I and suffix letter designating failure rate level).

QUALIFICATION INSPECTION:

Qualification inspection and sample size: See table II.

Failure rate qualification: The manufacturer shall qualify his products to failure rate level "M" initially.

TABLE II. Qualification inspection and sample size. 1/

Single submission	Group submission	
33 units plus 1 open unit for level M at C = 0 2/ Qualification inspection as applicable	M39016/641-004	33 units plus 1 open unit for level M at C = 0 2/ Qualification inspection as applicable
	M39016/641-001 M39016/641-002 M39016/641-003 M39016/641-005 M39016/641-006 M39016/641-007 M39016/641-008	2 units each PIN Qualification inspection, group I, group II
	M39016/641-028	1 unit terminal strength and solderability
	M39016/641-020	2 units each PIN 3/

1/ For retention of qualification or extension of qualification to lower failure rate levels, all life test data accumulated on (or specified in) MIL-R-39016/41, MIL-R-39016/642 and MIL-R-39016/643 may be used in addition to MIL-R-39016/641. Prior to performance of retention of qualification testing, the relay manufacturer shall preselect the sampling plan.

2/ The number of units required for qualification testing shall be increased as required in group V, table II, MIL-R-39016, if the contractor elects to test the number of units permitting one or more failures. Prior to performance of qualification inspection, the relay manufacturer shall preselect the sampling plan.

3/ Qualification inspection of relays supplied with spreader pads shall be tested as specified in the qualification inspection table of MIL-R-39016 in the order shown on the next page.

Source: https://assist.dla.mil -- Downloaded: 2026l0-21T17:56Z
Check the source to verify that this is the currentversion before use.

Before installation of the pad:

Vibration (sinusoidal) test duration shall be 10 minutes, vibration (random), particle impact noise detection, screening.

After installation of the pad:

Insulation resistance, dielectric withstanding voltage, static contact resistance, specified pickup, hold, and dropout values (voltages), coil resistance, operate and release time, contact dynamic characteristics, coil transient suppression (when specified), solderability, seal, visual and mechanical inspection (external).

Group A inspection: Group A inspection for relays supplied with spreader pads shall be as specified below:

Before installation of the pad: Perform subgroups 1 and 2 of the group A inspection table.

After installation of the pad: Perform subgroups 3 and 4 of the group A inspection table.

Qualification inspection (reduced testing) and sample size: If the relays produced for MIL-R-39016/641 are similar in construction and design, except for the additional inspections specified herein, to the relays produced for MIL-R-39016/41, then reduced testing may be performed concurrent with or subsequent to successful qualification of MIL-R-39016/41 at the "M" failure rate level. See table III.

TABLE III. Qualification inspection (reduced testing).

Examination of test
2 units each coil voltage, group A inspection table. 1 unsealed sample unit for internal examination.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Navy - AS
Air Force - 99
DLA - ES
NASA - NS

User activities:
Army - AR
Navy - MC, OS, SH
Air Force - 11, 19

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5945-0766-14)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:56Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:56Z
Check the source to verify that this is the current version before use.