MIL-D-50720(MU)
AMENDMENT 2
3 August 1973
SUPERSEDING
AMENDMENT 1
11 January 1973

MILITARY SPECIFICATION

DUMMY CARTRIDGE, 20MM: PLASTIC, XM254

This amendment forms a part of Military Specification MIL-D-50720(MU), dated 10 May 1971, and is approved for use by all Departments and Agencies of the Department of Defense.

Para 2.1, under DRAWINGS (Cont), add the following:

"D11075790 - Head Stem"

Para 4.2.1.a, delete entire paragraph and substitute the following:

"a. For visual and dimensional inspection:

(1) Two piece Head and Stem Assembly, Dwg. D7259296.

50 Stems
50 Heads
50 Head and Stem Assemblies
100 Cartridges

(2) One piece Head Stem, Dwg. D11075790.

50 Head Stems
100 Cartridges"

Para 4.3.2.1, at end of paragraph, delete "(see 6.4)" and substitute "(see 6.3)."

Para 4.3.3, Classification of defects 1/, delete "The classification of defects shall be as follows:" and substitute the following:

"The classification of defects shall be as specified herein. Paragraphs 4.3.3.1, 4.3.3.2, 4.3.3.3 and 4.3.3.4 are applicable to cartridges having a two piece head and stem assembly, Dwg. D7259296. Paragraphs 4.3.3.4 and 4.3.3.5 are applicable to cartridges having a one piece head stem, Dwg. D11075790."

FSC 1305

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:35Z
Check the source to verify that this is the current version before use.

Para 4.3.3.4, delete the following: "Dummy Cartridge (see Dwg. D7259254 or C7259255, a detail of Dwg. D7259254, as applicable)" and substitute the following:

"Dummy Cartridge (see Dwg. D7259254, D11075790 or C7259255, a detail of Dwg. D7259254, as applicable)."

Para 4.3.3.4, under Major: 118. Step or gap, junction of head and body ---------- Visual, add "/Gage 5/."

Para 4.3.3.4, under Major: Add the following:

"122. Diameter, body forward of head, min. ---------- Gage"

After para 4.3.3.4 (Cont), insert the following:

"4.3.3.5 Head stem (see Dwg. D11075790).

Categories and Defects	Method of Inspection
Critical: None defined.	
Major:	
101. Diameter, datum surface C	Gage
102. True position, head rim, with datum surface C	Gage
103. Spherical radius missing, head face	Visual
104. Diameter, stem, forward portion	Gage
105. Runout, stem with datum surface A	Gage
106. Foreign matter (including corrosion)	Visual
Minor:	
201. Length, head face to end of datum surface C, min.	Gage
202. Surface finish, head portion (larger diameters)	Visual
203. Diameter, datum surface A	Gage
204. Length, head stem, max.	Gage
*205. Diameter, undercut in datum surface A	Gage
*206. Width, undercut in datum surface A	Gage"

Para 4.3.3.5, under Minor: Add the following:

"207. Diameter, forward of datum surface A ---------- Gage"

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:35Z
Check the source to verify that this is the current version before use.

Para 4.3.3, after footnote 4/, add the following:

"5/ If a gap at the junction of the head and plastic body is greater than .005, the cartridge shall be classed defective."

Custodian:

Army - MU

Preparing Activity:

Army - MU

Project No. 1305-A741

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:35Z
Check the source to verify that this is the current version before use.