MILITARY SPECIFICATION

FUZES, ROCKET, M423, M427 AND M433
LOADING, ASSEMBLING AND PACKING

This amendment forms a part of Military Specification MIL-F-50253A(AR), dated 10 November 1978.

PAGE 2

2.1: Add to PRODUCT AND PACKAGE DRAWINGS: "9260925 - Umbilical Test Set" Delete "9260701 - Fuze, Rocket, M433 with Booster and Booster Lead" and substitute "9260701 - Fuze, Rocket, M433".

PAGE 4

4.3.1: Delete "Fuze, Rocket, M433 with Booster and Booster Lead" and substitute "Fuze, Rocket, M433".

PAGE 7

4.4.1: Delete "a. One metal parts lot from one manufacturer" and substitute "Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, each inspection lot of boostered fuzes shall contain:

"a. Fuzes bearing the same metal parts lot interfix number from one metal parts manufacturer"

PAGE 9

4.4.2.2, Major 105: Delete "0.40%" and substitute "100%".

PAGE 10

4.5.2: Delete in its entirety and substitute: "Umbilical Continuity Test.-Each fuze umbilical shall be connected to an Umbilical Test Set (9260925). Each umbilical must meet the acceptance requirements. Any umbilical that does not meet the acceptance requirements shall be classed as defective. If one or more defective samples are found, the fuze lot shall be rejected.

PAGE 11

4.5.3.2, line 8: Delete "functional" and substitute "functioned".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:18Z
Check the source to verify that this is the current version before use.

4.5.3.3: Delete in its entirety and substitute: "M433 Fuze.-Live boosters will be assembled into a government-approved simulated M433 fuze, an M423 Fuze Assembly or an M427 Fuze Assembly. When a simulated M433 fuze is used, the test fixture must simulate an M433 explosive train in the armed condition. Functional (electrical) energy of not less than 750 ergs shall be applied to the detonator electrical contacts in the simulated test fixture. High order detonation shall be determined by a 0.25 inch minimum dent in a cylindrical witness block (1.5 inch minimum height by 2.0 inch minimum diameter of 2011-T3 aluminum). When M423/427 Fuze Assemblies are used, the test procedure of 4.5.3.2 applies.

"WARNING: This test is dangerous and must be performed behind a suitable barricade.".

PAGE 13

6.3: Delete "DRDAR-QAR-I" and substitute "DRDAR-QAF-I".

Custodian:
ARMY-AR

Preparing Activity
ARMY-AR

Project Number: 1340-A565

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:18Z
Check the source to verify that this is the current version before use.