INCH-POUND
A-A-59957
October 04, 2017

COMMERCIAL ITEM DESCRIPTION

SEMITRAILER, DROP DECK BREAKBULK/CONTAINER TRANSPORTER, 22-1/2 TON – M871A3

The General Services Administration has authorized the use of this Commercial Item Description for all federal agencies.

1. SCOPE.

This commercial item description (CID) covers a commercial, drop deck semitrailer. The semitrailer has a 22.5 ton capacity and is capable of carrying breakbulk loads, as well as 20-foot intermodal International Organization Standardization (ISO) containers. The semitrailer is capable of being towed by M1088 series, M915 series, M931 series, M932 series, and M818 series trucks.

2. SALIENT CHARACTERISTICS.

2.1 Semitrailer description. The semitrailer is the CID equivalent of the M871A3 tactical trailer. The semitrailer shall be constructed in accordance with SAE AS8090, "General Requirements for Towed Aerospace Ground Equipment Mobility," and SAE ARP1247, "General Requirements for Aircraft Ground Support Equipment." In the event of a conflict between either of these standards and the text of this document, this document shall take precedence.

2.2 Design and construction. The design shall promote cost effective, life-cycle sustainability by addressing considerations such as incorporating open standards while satisfying system performance requirements. It shall be designed and constructed so that no parts will work loose in service, and to withstand the strains, jars, vibrations, and other conditions incident to shipping, storage, installation, and service. It shall be weatherproof and designed to prevent the intrusion of water, sand, and dust into critical operating components.

2.2.1 Materials, protective coatings, and finish.

2.2.1.1 Protective coatings. Materials that deteriorate when exposed to sunlight, weather, or operational conditions normally encountered during the service life of the item shall not be used or shall have means of protection against such deterioration that does not prevent compliance with the performance characteristics specified herein. Protective coatings that chip, crack, or scale with age or extremes of climatic conditions or when exposed to heat shall not be used. Exposed surfaces

Beneficial comments, recommendations, additions, deletions, clarifications and any data that may improve this document should be sent to: **U.S. AIR FORCE - AFLCMC/WNZ-M-SERIES TACTICAL VEHICLE**, Robins AFB GA 31098 or emailed to SPEC99@us.af.mil.

AMSC N/A FSC 2330
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:31Z
Check the source to verify that this is the current version before use.

of fasteners, handles, and fittings shall also be primed and painted. See 2.2.4.1 for prohibited hazardous materials.

2.2.1.2 Corrosion Protection. The semitrailer shall have a protective coating system for steel components consisting of a zinc phosphate pretreatment (with performance characteristics equivalent to TT-C-490, Type I), followed by an zinc-rich, solvent-borne, epoxy-based primer (with performance characteristics equivalent to MIL-PRF-26915, Type I). Aluminum components shall be protected with a coating system consisting of a conversion pretreatment (with performance characteristics equivalent to MIL-DTL-5541, Class 1A), followed by a solvent-borne, epoxy primer (with performance characteristics equivalent to MIL-PRF-23377). The final topcoat shall be a two-component, solvent-borne, polyurethane (with performance characteristics equivalent to MIL-PRF-85285).

2.2.1.3 Finish. The exterior finishcolor of the semitrailer and the inner surfaces of compartments shall be Olive Drab Green Color Number 34064 of SAE AMS-STD-595.

2.2.1.4 Fluid traps and faying surfaces. There shall be no fluid traps on the semitrailer. Faying surfaces of all structural joints, except welded joints, shall be sealed to preclude fluid intrusion.

2.2.1.5 Drainage. Drain holes shall be provided to prevent collection or entrapment of water or other unwanted fluid in areas where exclusion is impractical. All designs shall include considerations for the prevention of water or fluid entrapment and ensure that drain holes are located to effect maximum drainage of accumulated fluids. The number and location of drain holes shall be sufficient to permit drainage of all fluids when the semitrailer is on a 10-degree longitudinal slope facing both up and down and on a 5-degree side slope in each direction (right and left side facing up the slope). The minimum size of the drain holes shall be 0.25 inch.

2.2.2 Markings. All external devices which require an operational or maintenance interface shall be marked in accordance with MIL-STD-130. Markings shall be applied with decals and shall be 1-inch high block letters unless prohibited by the available space. In such cases, the markings shall be the largest size possible. Markings, Information/Caution shall be Lusterless Black, Color Number 37038 of SAE AMS-STD-595, and Markings, Warning/Danger shall be Lusterless Red, Color Number 31136 of SAE AMS-STD-595. The center of gravity of the semitrailer shall be stenciled on the unit within 1-inch of the calculated center of gravity.

2.2.3 Identification and information plates.

2.2.3.1 Identification plate. An identification plate in accordance with MIL-STD-130 shall be securely attached to the semitrailer in a readily accessible location. The identification plate shall contain the following information: nomenclature, part number, serial number, date of manufacture, manufacturer's name, Commercial and Government Entity (CAGE) code, date of warranty expiration, and National Stock Number (NSN), payload in kg (pounds), and contract number. The semitrailer and any of its components for which the Government's unit cost is more than $5,000, is serially managed, or the procuring agency determines is mission essential, shall have Unique Identification (UID) (also known as Item Unique Identification (IUID)) information permanently affixed on or near the respective identification plate(s), marked in accordance with

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:31Z
Check the source to verify that this is the current version before use.

MIL-STD-130. UID information shall be included as both a bar code and human readable markings.

2.2.3.2 Transportation data plate. A transportation data plate shall be securely attached to the semitrailer in a readily accessible location. The plate shall contain at least the following information:

a. Side and rear silhouette views of the semitrailer.

b. Horizontal and vertical location of the center of gravity of the semitrailer in air transportable configuration, marked on the silhouette views.

c. Shipping weight.

d. Loading cubage.

e. Overall height, width, and length.

f. Axle loads.

g. Tie down information.

2.2.3.3 Lubrication data plate. The semitrailer shall be provided with a permanently-marked lubrication data plate constructed of a non-corroding metal, mounted on the exterior surface of the semitrailer that shall direct attention to all lubrication fittings and components that require lubrication. The plate shall identify the type and grade of lubricant required for operational temperatures specified in 2.3.1.

2.2.4 Environment, Safety, and Occupational Health (ESOH).

2.2.4.1 Hazardous material. The design shall minimize and control hazards associated with the inclusion or use of hazardous or toxic materials and the generation of toxic or noxious gases. The semitrailer shall not generate or use Class I or Class II Ozone Depleting Substances (ODS) during operation, maintenance, or disposal. The semitrailer shall not contain or use hexavalent chromium. The semitrailer shall not contain or use cadmium without written approval by the procuring activity. For the purposes of this requirement, the Class I ODS and controlled substances identified in AFI 32-7086 shall not be used in any system, component, or process.

2.2.4.2 Component protection. All wires, cables, tubes, and hoses shall be supported and protected to minimize chafing and abrasion and shall be located so as to provide adequate clearance from moving parts and high operational temperatures. Grommets shall be provided wherever wires, cables, tubes, or hoses pass through bulkheads, partitions, or structural members.

2.2.4.3 Foreign object damage (FOD). All loose metal parts, such as pins or connector covers, shall be securely attached to the semitrailer with wire ropes or chains. "Dog tag" style beaded

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:31Z
Check the source to verify that this is the current version before use.

chains shall not be provided. Removable panels, if provided, shall be attached with captive fasteners. Tire valve stem caps shall be made of plastic.

2.2.5 Human systems integration. The semitrailer shall be designed in accordance with MIL-STD-1472 for ease of operation, inspection, and maintenance, including the use of arctic mittens and Mission-Oriented Protective Posture (MOPP) Level 4 Chemical Warfare Gear. Chemical Warfare Gear is not required for preventive maintenance.

2.2.6 Welders and welding. All welders shall be certified to weld in accordance with AWS D1.1 and AWS D1.2, as applicable. Welding procedures and all welding on the semitrailer shall be in accordance with AWS D1.1 and AWS D1.2, as applicable. The surface parts to be welded shall be free from rust, scale, paint, grease, and other foreign matter. Welds shall be of sufficient size and shape to develop the full strength of the welded parts. Welds shall transmit stress without cracking or permanent distortion when the parts connected by the welds are subjected to test, proof, and service loadings.

2.3 Environmental conditions.

2.3.1 Operating temperature range. The semitrailer shall be capable of operating in ambient temperatures ranging from -40° F to 125° F.

2.3.2 Storage temperature range. The semitrailer shall be capable of being stored in ambient temperatures ranging from -65° F to 160° F.

2.4 Weight and dimensions. Overall weight and dimensions in air transport configuration (see 2.5.2) shall not exceed the following in Table I:

Table I. Air transport dimensions.

DIMENSION	PROPORTION
Unloaded Weight	18,000 pounds (C-130)
Loaded Weight	63,000 pounds (C-17, C-5)
Length	506 inches
Width	96 inches
Height	103 inches

2.5 Transportability.

2.5.1 Surface transportability. The semitrailer shall be transportable via all modes of surface shipment (highway, rail, and water) in accordance with MIL-STD-1366, and shall be capable of withstanding the mechanical shock and vibration characteristics of highway, rail, and water transport, except that design for rail impact testing (see 5.2.5 of MIL-STD-1366) is not required.

2.5.2 Air transportability. The loaded/unloaded semitrailer shall be transportable on C-5 and C-17 aircraft, and the unloaded semitrailer shall be transportable on the C-130 in accordance with MIL-STD-1791, without reconfiguration. The semitrailer shall be capable of being restrained and

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:31Z
Check the source to verify that this is the current version before use.

withstanding, without loss of serviceability, 2.0 G up and 4.5 G down accelerations, and shall be capable of being restrained and withstanding, without loss of structural integrity, 3.0 G forward, 1.5 G aft, and 1.5 G lateral accelerations. The semitrailer shall be equipped with pressure relief devices or configured for air transport to prevent any part from becoming a projectile in the event of catastrophic loss of aircraft cabin pressure. The semitrailer shall roll on and off the aircraft, negotiating the required maximum ramp angles.

2.5.2.1 Shoring. The use of shoring to load the aircraft (referred to as approach shoring and step-up shoring) and during flight (referred to as load shoring, parking shoring, and sleeper shoring) is permitted, but not desired. The use of shoring, especially in loading the aircraft, is not an alternative to a good design. The semitrailer shall be designed to the maximum extent possible with adequate clearances for the semitrailer to roll on and off the aircraft, negotiating the required maximum ramp angles without shoring.

2.5.2.2 Winch points. Winch points shall be provided at the front and rear of the semitrailer for aircraft loading using the aircraft's winch.

2.5.3 Tie downs. The semitrailer shall be restrained during air and ground transport. Tie down points shall have a clear opening compatible with MIL-DTL-25959 and MIL-PRF-27260 tie down devices. Each end of each tie down device shall terminate at a tie down point and not pass through any other tie down point. There shall be no interference between tie down devices and the semitrailer. The tie down provisions shall be in accordance with 4.1 through 4.12 of MIL-STD-209. The tie down locations and types shall be as follows:

a. 36 D-Ring cargo tie downs located on the upper and lower deck rated for 15,000 pounds.

b. 4 D-Ring ammo tie downs located on the lower deck and rated to 30,000 pounds.

c. 8 D-Ring rail/transportability tie downs, 4 located on the front drop frame and 4 located to the rear under ride protection.

2.5.4 Lifting provisions. The semitrailer shall be equipped with sufficient attachment points so located that it can be lifted by crane; each attachment point shall be marked "Lift Point". The lifting provisions shall be in accordance with 5.1 through 5.1.4 of MIL-STD-209.

2.6 Maintainability. The semitrailer shall be designed for maintainability in accordance with 5.9 through 5.9.18 of MIL-STD-1472; forces shall not exceed those specified for both males and females.

2.7 Performance.

2.8 Mobility. The semitrailer shall be in accordance with SAE AS8090 for Type III, Group D mobility except as otherwise specified herein.

2.8.1 Terrain.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:31Z
Check the source to verify that this is the current version before use.

2.8.1.1 Paved surfaces. The semitrailer shall be towable at speeds up to 55-miles per hour (mph) over paved surfaces.

2.8.1.2 Graded gravel. The semitrailer shall be towable at speeds up to 35-mph over graded gravel.

2.8.1.3 Off road. The semitrailer shall be towable at speeds up to 10-mph off road.

2.8.2 Suspension. The semitrailer shall have a suspension system in accordance with 3.4.1.2 of SAE AS8090.

2.8.3 Brakes.

2.8.3.1 Parking brakes. The semitrailer shall have parking brakes in accordance with 3.6.1 of SAE AS8090.

2.8.3.2 Service brakes. The semitrailer shall have service brakes in accordance with 3.6.2 of SAE AS8090.

2.8.4 Bumper. The semitrailer shall have a rear bumper in accordance with 3.7 of SAE AS8090.

2.8.5 Fenders. The semitrailer shall have fenders in accordance with 3.9 of SAE AS8090.

2.8.6 Mudflaps. The semitrailer shall have mudflaps in accordance with 3.12 of SAE AS8090.

2.8.7 Tires and wheels. The semitrailer shall be equipped with single or dual tubeless steel belted radial tires with on/off-road type tread mounted on steel disc wheel assemblies. Tire and wheel assemblies shall be identical at all wheel positions. Tires and wheels shall be in accordance with the *Tire and Rim Association Year Book* requirements for this application.

2.8.7.1 Tire pressure. Tire pressure shall not exceed 120 pounds per square inch (psi). Tire inflation pressures shall be marked above all wheel well openings, with ½" high letters/numbers that are black in color. A decal shall be adhered near the top of each wheel well opening that warns personnel of the dangers of placing any part of the body into the wheel well area.

2.8.7.2 Spare tire and carrier. The semitrailer shall have a spare tire and wheel assembly secured on the underside, behind the landing legs.

2.9 Electrical system. The semitrailer shall have a 12/24-volt, negative ground electrical system in accordance with 3.13.1.2 of SAE ARP1247 except as otherwise specified herein. The electrical system shall include tail, stop, turn, blackout, clearance LED lights, as well as an anti-lock braking system (ABS) warning light.

2.9.1 Reflectors. The semitrailer shall have an amber reflector on each of the front corners and each side. The semitrailer shall have a red reflector on each rear corner.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:31Z
Check the source to verify that this is the current version before use.

2.10 Semitrailer dimensions. The unloaded semitrailer shall have the following nominal dimensions in Table II:

Table II. Overall Dimensions

DIMENSION	PROPORTION
Overall Length	506 inches
Width	96 inches
Upper Deck Height	78.5 inches
Drop Deck Height	55.5 inches

2.11 Curb weight. The unloaded semitrailer shall have an approximate curb weight of 17,600 pounds.

2.12 Payload. The semitrailer shall be capable of carrying a total payload of 45,000 pounds as either break bulk cargo or a 20-foot ISO container.

2.13 Bulkhead. The semitrailer shall have a front bulkhead 25 inches tall.

2.14 Fording. The semitrailer shall be capable of fording depths of up to 30 inches.

2.15 Stakes and side panels. The semitrailer shall have stakes, stake pockets, and side panels to allow for transportation of break bulk cargo.

2.16 Landing legs. The semitrailer shall have scissor type landing legs with a static capacity of 170,000 lbs. The legs shall have a retracted height of 40 inches, and an extended height of 57.5 inches. The crank shall have a high and low operating speed.

2.17 Tool box. The semitrailer shall have a tool box, with lock and keys, mounted under the chassis, large enough for the included tools and accessories.

2.18 Tools and accessories. The semitrailer shall come equipped with the following tools and accessories:

a. Two-piece, 48 inch, galvanized breaker bar for tire wrench.

b. Wheel lug nut socket wrench and handle.

c. One 20-ton hydraulic jack.

d. Two rubber chock blocks.

e. Two ground boards.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:31Z
Check the source to verify that this is the current version before use.

2.18.1 Special tools. The design of the semitrailer shall minimize the requirement for special tools (see 6.3.4). Any special tools required to operate or maintain the semitrailer (see 6.3.4) shall be provided with, and stored on, the semitrailer.

2.19 Kingpin. The semitrailer shall have a 2 inch diameter kingpin, located 24 inches from the front of the trailer and 85 inches to the center line of the landing gear.

2.20 Floor decking. The semitrailer's deck shall be composed of hardwood and fastened with floor screws.

2.21 Axles. The semitrailer shall have 2 dual tandem axles, 5 inches in diameter, with 5/8 inch tube wall thickness, and a load capacity of 25,000 pounds each.

2.22 Workmanship. The semitrailer, including all parts and accessories, shall be constructed and finished in a thoroughly workmanlike manner. Workmanship objectives shall include freedom from blemishes, defects, burrs and sharp corners and edges; accuracy of dimensions, surface finish, and radii of fillets; thoroughness of welding, painting, and riveting; marking of parts and assemblies; and proper alignment of parts and tightness of assembly fasteners.

2.22.1 Bolted connections. Bolt holes shall be accurately punched or drilled and shall be deburred. Threaded fasteners shall be tight and shall not work loose during testing or service usage.

2.22.2 Riveted connections. Rivet holes shall be accurately punched or drilled and shall be deburred. Rivets shall be driven with pressure tools and shall completely fill the holes. Rivet heads shall be full, neatly made, concentric with the rivet holes, and in full contact with the surface of the component.

2.22.3 Gear and lever assemblies. Gear and lever assemblies shall be properly aligned and meshed and shall be operable without interference, tight spots, loose spots, or other irregularities. Where required for accurate adjustment, gear assemblies shall be free of excessive backlash.

2.22.4 Cleaning. The semitrailer shall be thoroughly cleaned. Loose, spattered, or excess solder; welding slag; stray bolts, nuts, and washers; rust; metal particles; pipe compound; and other foreign matter shall be removed during and after final assembly.

3. REGULATORY REQUIREMENTS.

3.1 Recycled, recovered materials. Recycled, recovered, or environmentally preferable materials should be used to the maximum extent possible provided that the material meets or exceeds the operational and maintenance requirements, and promotes economically advantageous life cycle costs. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with 23.403 of the Federal Acquisition Regulation (FAR). However, used, rebuilt, or refurbished items shall not be provided.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:31Z
Check the source to verify that this is the current version before use.

3.2 Green Procurement Program. Green Procurement Program (GPP) is a mandatory federal acquisition program that focuses on the purchase and use of environmentally preferable products and services. GPP requirements apply to all acquisitions using appropriated funds, including services and new requirements. FAR 23.404(b) applies and states the GPP requires 100% of EPA designated product purchase that are included in the Comprehensive Procurement Guidelines list that contains recovered materials, unless the item cannot be acquired: a) competitively within a reasonable timeframe; b) meet appropriate performance standards, or c) at a reasonable price. The prime contractor is responsible for ensuring that all subcontractors comply with this requirement.

4. PRODUCT CONFORMANCE PROVISIONS.

The products provided shall meet the salient characteristics of this CID, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial marketplace, modified as necessary to comply with the requirements herein. The Government reserves the right to require proof of such conformance.

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First production inspection (see 4.2).

b. Conformance inspection (see 4.3).

4.2 First production inspection. The first production semitrailer shall be subjected to the analyses, demonstrations, examinations, and tests described in 4.5.1 through 4.5.5.5.

4.3 Conformance inspection. Each production semitrailer shall be subjected to the examination described in 4.5.1.

4.4 Inspection requirements.

4.4.1 General inspection requirements. Apparatus used in conjunction with the inspections specified herein shall be laboratory precision type, calibrated at proper intervals to ensure laboratory accuracy.

4.4.2 Data. During all testing specified herein, at least the following data, unless not applicable, shall be recorded at intervals not to exceed 30 minutes. Additional data or shorter intervals shall be provided as appropriate for any specific test.

a. Date.

b. Time started.

c. Time finished.

d. Ambient temperature.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:31Z
Check the source to verify that this is the current version before use.

e. Ambient humidity.

4.4.3 Test rejection criteria. Throughout all tests specified herein, the semitrailer shall be closely observed for the following conditions, which shall be cause for rejection.

a. Failure to conform to design or performance requirements specified herein or in the contractor's technical proposal.

b. Any spillage or leakage of any liquid, such aslubricant,under any condition, except as allowed herein.

c. Structural failure of any component, including permanent deformation, or evidence of impending failure.

d. Evidence of excessive wear. If excessive wear is suspected, the original equipment manufacturer’s (OEM’s) specifications or tolerances shall be utilized for making a determination.

e. Evidence of corrosion or deterioration.

f. Misalignment of components.

g. Conditions that present a safety hazard to personnel during operation, servicing, or maintenance.

h. Interference between the semitrailer components or between the semitrailer, the ground, and all required obstacles, with the exception of normal contact by the tires.

i. Evidence of undesirable mobility characteristics, including instability in handling during cornering, braking, and while traversing all required terrain.

4.5 Test methods.

4.5.1 Examination of product. Each semitrailer shall be examined to verify compliance with the requirements herein prior to accomplishing any other demonstrations or tests listed in 4.5. A contractor-generated, Government-approved checklist (part of the test procedure) shall be used to identify each requirement not verified by an analysis, certification, demonstration, or test, and shall be used to document the examination results. Particular attention shall be given to materials, workmanship, dimensions, surface finishes, protective coatings and sealants and their application, welding, fastening, and markings. Proper operation of each semitrailer function shall be verified. Certifications and analyses shall be provided in accordance with Table III. Each production semitrailer shall be inspected to a Government-approved reduced version of the checklist.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:31Z
Check the source to verify that this is the current version before use.

TABLE III. Certifications and analyses.

Paragraph	Required Certifications and Analyses
2.5.1 Surface transportability.	Contractor surface transportability analysis (see 4.5.3.1.1) and certification that the semitrailer is transportable via all modes of surface shipment (highway, rail, and water) in accordance with MIL-STD-1366, and shall be capable of withstanding the mechanical shock and vibration characteristics of highway, rail, and water transport.
2.5.2 Air transportability.,2.5.2.1 Winch points.	Contractor air transportability analysis (see 4.5.3.2).
2.5.3 Tie downs.	Contractor tie down provision analysis (see 4.5.3.3.1).
2.5.4 Lifting provisions.	Contractor lifting provision analysis (see 4.5.3.4.1).
2.3.1 Operating temperature range.	Contractor operating temperature analysis (see 4.5.4.1).
2.3.2 Storage temperature range.	Contractor storage temperature analysis (see 4.5.4.2).

4.5.2 Weight and dimension tests.

4.5.2.1 Weight and center of gravity test. The weight, center of gravity, and axle weights of a first production semitrailer shall be measured to demonstrate compliance with the weight requirement of 2.4 and the axle weight requirement of 2.21.

4.5.2.2 Dimension measurement. A first production semitrailer shall be measured to demonstrate compliance with the dimensional requirements of 2.10.

4.5.3 Transportability verification.

4.5.3.1 Surface transportability verification.

4.5.3.1.1 Surface transportability analysis. An engineering analysis shall be performed to demonstrate compliance with 2.5.1. The engineering analysis shall utilize the data for road transportation in accordance with MIL-STD-810, Method 514.7, Table 514.7C-II.

4.5.3.2 Air transportability analysis. An engineering analysis shall be performed to demonstrate compliance with the air transportability requirements of 2.5.2 and 2.5.2.1. The analysis shall include the tie downs and all major components and their ability to withstand the accelerations

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:31Z
Check the source to verify that this is the current version before use.

specified in 2.5.2. The analysis shall demonstrate the accessibility and structural adequacy of the winch points specified in 2.5.2.1. The evaluation shall also include a dimensional analysis for the semitrailer while traversing the ramp and while loaded aboard C-5, C-17, and C-130 aircraft.

4.5.3.3 Tie down provision verification.

4.5.3.3.1 Tie down provision analysis. An engineering analysis shall be performed to demonstrate compliance with the tie down provision requirements of 2.5.3.

4.5.3.3.2 Tie down provision test. A first production semitrailer shall be tested to demonstrate compliance with the tie down provision requirements of 2.5.3.

4.5.3.4 Lifting provision verification.

4.5.3.4.1 Lifting provision analysis. An engineering analysis shall be performed to demonstrate compliance with the lifting provision requirements of 2.5.4.

4.5.3.4.2 Lifting provision test. A first production semitrailer shall be tested to demonstrate compliance with the lifting provision requirements of 2.5.4.

4.5.4 Environmental testing.

4.5.4.1 Operating temperature analysis. An engineering analysis shall be performed to demonstrate compliance with the operating temperature requirement of 2.3.1.

4.5.4.2 Storage temperature analysis. An engineering analysis shall be performed to demonstrate compliance with the storage temperature requirement of 2.3.2.

4.5.5 Mobility tests. A first production semitrailer shall be tested in accordance with Table VIII of SAE AS8090 to demonstrate compliance with the mobility requirements of 2.8. Note that the maximum towing force is 75 pounds per ton of gross weight, in accordance with 3.3.4 of SAE AS8090, rather than 50 pounds per ton of gross weight as stated in Table VIII of SAE AS8090.

4.5.5.1 Parking brake test. A first production semitrailer shall be tested in accordance with 4.5.7.1 of SAE AS8090 to demonstrate compliance with 2.8.3.1.

4.5.5.2 Service brake test. A first production semitrailer shall be tested in accordance with 4.5.7.2 and 4.5.8 of SAE AS8090 to demonstrate compliance with 2.8.3.2.

4.5.5.3 Maximum speed. A first production semitrailer, loaded to its Gross Vehicle Weight Rating (GVWR), shall be towed at 55 mph on a dry level paved surface to demonstrate compliance with 2.8.1.1.

4.5.5.4 Graded roads. A first production semitrailer, loaded to its GVWR, shall be towed at 35 mph on a dry level graded surface to demonstrate compliance with 2.8.1.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:31Z
Check the source to verify that this is the current version before use.

4.5.5.5 Off road. A first production semitrailer, loaded to its GVWR, shall be towed at 10 mph on a dry level off road surface to demonstrate compliance with 2.8.1.3.

5. PACKAGING. Preservation, packing, and marking shall be as specified in the contract or order.

6. NOTES.

6.1 Source of documents.

6.1.1 Military Specifications and Standards referenced herein may obtained online at http://quicksearch.dla.mil/ or from the DLA Document Services, 700 Robbins Avenue, Building 4D, Philadelphia PA 19111-5094.

6.1.2 AFI. Copies of AFIs are available online at http://www.e-publishing.af.mil/.

6.1.3 FAR. The FAR may be obtained from the Superintendent of Documents, P.O. Box 371954, Pittsburgh PA 15250-7954. Electronic copies of the FAR may be obtained from https://www.acquisition.gov/far/.

6.1.4 AWS documents. Application for copies should be addressed to American Welding Society, 550 N.W. LeJeune Road, Miami FL 33126, http://www.aws.org/.

6.1.5 SAE documents. Application for copies should be addressed to SAE International, 400 Commonwealth Drive, Warrendale PA 15096, http://www.sae.org/.

6.1.6 Tire and Rim Association documents. Application for copies should be addressed to The Tire and Rim Association, Inc., 175 Montrose West Ave., Suite 150, Copley OH 44321, http://www.us-tra.org/.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this CID.

b. If a spare tire and wheel assembly is required (see 2.8.7.2).

c. Packaging requirements (see 5).

6.2.1 National Stock Number NSN. The following is a list of NSN's assigned that correspond to this CID. The list may not be indicative of all possible NSN's associated with this CID.

NSN	2330-01-458-6865

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:31Z
Check the source to verify that this is the current version before use.

6.3 Definitions.

6.3.1 Common hand tool. A non-powered tool that is likely to be found in a typical mechanic's toolbox. Common hand tools include open end, boxed end, combination, socket (both 6- and 12-point in both standard and deep-well), and hex key wrenches, in SAE sizes up to and including 1-inch and metric sizes up to and including 25-mm; ratchet handles, extensions, and swivels; slotted and Phillips-head screwdrivers; regular and snap-ring pliers; and a ball-peen hammer.

6.3.2 Cross-country terrain. Cross-country terrain consists of unimproved open fields, broken ground, loose sand, and gravel road encountered by tactical vehicles supporting an army in the field.

6.3.3 Gravel road. A gravel road is a level or rolling gravel trail.

6.3.4 Special tool. A tool that is not commercially and readily available from a source other than the semitrailer contractor.

6.4 Key words.

Breakbulk loads
Container
Drop deck configuration
M871A3
Tactical

Conculding Material

Custodians:
Army - AT
Air Force - 184

Preparing Activity:
Air Force – 184

Reviewers:
Army – AV, MI

Agent:
Air Force – 99
(Project 2330-2017-005)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil .

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:31Z
Check the source to verify that this is the current version before use.