METRIC
A-A-59975
June 17, 2016

COMMERCIAL ITEM DESCRIPTION

CLEANER, OVEN

The General Services Administration has authorized the use of this commercial item description for all federal agencies.

1. SCOPE. This commercial item description (CID) covers oven cleaners suitable for removing heavy, baked-on grease, and carbonized soil deposits on grills, ovens, fryers, other kitchen equipment (including stainless steel), and vertical and horizontal surfaces where such deposits might occur.

2. SALIENT CHARACTERISTICS.

2.1 General. The cleaner shall be a uniform solution, free of sediment and foreign materials. Liquid type products shall be either a concentrate or ready-to-use (RTU) solution.

2.2 Prohibited materials. The cleaner shall not contain any materials above the threshold for trace amount that have a severity category of either catastrophic or critical in the prohibited and restricted chemicals tables in the NAVSEA List of Targeted Chemicals (N-LTC) appendix of T9070-AL-DPC-020/077-2, NAVSEA Hazardous Material Avoidance Process. The threshold for trace amount is defined as less than 1 percent for non-carcinogenic compounds and less than 0.1 percent for carcinogenic compounds.

2.3 Volatile organic compound (VOC) levels. VOC levels of the cleaner shall be stated as a percent of VOCs by weight when prepared in the dilution ratio as directed on the manufacturer's label and shall not exceed the California Air Resources Board (CARB) 17 CCR § 94509 VOC standard for oven and grill cleaners.

2.4 pH. The pH of a RTU solution shall be a minimum of 11.0 and a maximum of 14.0 when tested in accordance with ASTM E70.

2.5 Flash point. The flash point shall be greater than 93.3 °C (200 °F) when tested in accordance with ASTM D56.

2.6 Eutrophication and phosphate. The cleaner shall comply with the U.S. Environmental Protection Agency (EPA) Safer Choice Standard eutrophication and phosphate criteria.

2.7 Aquatic toxicity. The cleaner, when used as directed on the label in a use-dilution solution, shall not be toxic to aquatic life in accordance with the United Nations Economic Commission for Europe (UNECE) Globally Harmonized System of Classification and Labelling of Chemicals (GHS) criteria for acute and chronic aquatic toxicity. More specifically, the cleaner at use-dilution shall not have an acute toxicity within GHS Categories 1 and 2 for short-term (acute) aquatic hazard, and shall not have a chronic toxicity within GHS Categories 1 and 2 for long-term aquatic hazard.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data that may improve this document should be sent to: Commander, Naval Sea Systems Command, ATTN: SEA 05S, 1333 Isaac Hull Avenue, SE, Stop 5160, Washington Navy Yard DC 20376-5160 or emailed to CommandStandards@navy.mil, with the subject line "Document Comment". Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil.

FSC 7930

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:32Z
Check the source to verify that this is the current version before use.

2.8 Cleaning efficiency. The oven cleaner shall completely remove a soil of the composition shown in table I when tested as follows, or following other equivalent or comparable test methods.

TABLE I. Soil composition.

Soil composition	Weight percent
Corn oil	84
Sugar (granulated)	8
Flour (standard, bleached)	8

a. While stirring, heat corn oil to 65.5 to 93 °C (150 to 200 °F). While continuing to stir, add sugar and flour and mix thoroughly. Allow mixture to cool to room temperature before use.

b. While constantly stirring the soil mixture, paint two porcelain enamel test panels and two stainless steel Grade 430 test panels. The test panels shall be approximately 7.62 centimeters by 7.62 centimeters (3 inches by 3 inches). Bake panels in a horizontal position for 20 minutes at 218 to 232 °C (425 to 450 °F).

c. After panels have cooled to room temperature, place them in a horizontal position. Apply the oven cleaner to the soiled panels until the cleaner completely covers the surface of the panels. Allow panels to sit for 30 minutes in a horizontal position at room temperature.

d. Wipe the panel with a lightly dampened sponge and flush with water to remove the soil. Dry panels and apply oven cleaner again and repeat the procedure.

e. After using the damp sponge and flushing with water, the oven cleaner shall, by visual observation, completely remove all the soil on the panel and leave no visible film.

2.9 Aerosol delivery rate. The aerosol type oven cleaner shall have a delivery rate at 21 °C (70 °F) of 1.0 to 3.5 grams per second when tested in accordance with ASTM D3069, or other equivalent or comparable test methods.

3. REGULATORY REQUIREMENTS. The offeror/contractor is encouraged to use recovered materials or biobased materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4. PRODUCT CONFORMANCE PROVISIONS. The products provided shall meet the salient characteristics of this CID, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial marketplace. The government reserves the right to require proof of such conformance.

5. PACKAGING. Preservation, packing, and marking shall be as specified in the contract or order.

6. NOTES.

6.1 Source of documents.

6.1.1 ASTM International. ASTM standards are available from ASTM International, 100 Barr Harbor Dr., P.O. Box C700, West Conshohocken, PA 19428-2959 or online at www.astm.org.

6.1.2 California Code of Regulations (CCR). The CCR may be obtained online at http://www.oal.ca.gov/CCR.htm.

6.1.3 EPA. The U.S. EPA Safer Choice may be obtained from the Environmental Protection Agency, Ariel Rios Building, 1200 Pennsylvania Avenue, N.W., Washington, DC 20460 or online at https://www.epa.gov/saferchoice/standard.

6.1.4 FAR. The FAR may be obtained from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402 or online at https://www.acquisition.gov/far.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:32Z
Check the source to verify that this is the current version before use.

6.1.5 GHS. The UNECE GHS criteria may be obtained online at http://www.unece.org/trans/danger/publi/ghs/ghs_rev06/06files_e.html.

6.1.6 Naval Sea Systems Command (NAVSEA) Publications. Copies of T9070-AL-DPC-020/077-2 are available online via Technical Data Management Information System (TDMIS) at https://mercury.tdmis.navy.mil/ by searching for the document number without the suffix. Refer questions, inquiries, or problems to: DSN 296-0669, Commercial (805) 228-0669. T9070-AL-DPC-020/077-2 is available for ordering (hard copy) via the Naval Logistics Library https://nll.ahf.nmci.navy.mil. For questions regarding the NLL, contact the NLL Customer Service at nllhelpdesk@navy.mil, (866) 817-3130, or (215) 697-2626/DSN 442-2626.

6.2 Ordering data. The contract or order should specify the following:

a. CID document number and revision letter.
b. Quantity required.
c. Product conformance provisions.
d. Packaging requirements.

MILITARY INTERESTS:

Custodians:
Army – MI
Navy – SH

Review Activities:
Army – AV, GL
Navy – AS, CG, MC, SA

CIVIL AGENCY COORDINATING ACTIVITY:
GSA – FAS

Preparing Activity:
Navy – SH
(Project 7930-2015-013)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:32Z
Check the source to verify that this is the current version before use.