INCH-POUND
A-A-59981
28 April 2017

COMMERCIAL ITEM DESCRIPTION

DOLLY SET MOBILIZER, 7-1/2 TON

The General Services Administration has authorized the use of this commercial item description (CID) for all federal agencies.

1. SCOPE. This CID describes a dolly set mobilizer that is capable of lifting, loading, and transporting an International Standard Organization (ISO) container or shelter with a payload of 7-1/2 U.S. tons (15,000 lbs) and has an overload capacity of 10 U.S. tons (20,000 lbs), to be carried for a limited amount of time. The mobilizer consists of a front-steerable dolly and a rear-trailer dolly with interconnecting brake lines and electrical harnesses that can be towed across all surfaces, including primary roads, secondary roads, and cross country. Each dolly half is equipped with a diesel-powered, hydraulic lift system, which allows the mobilizer to act as a shelter-handling device for lifting, and truck or aircraft loading. The mobilizer can be towed by any tactical vehicle that can meet the appropriate towing capacity and connections of the mobilizer. The system is designed to be loaded onto a C-130, C-17, and C-5 aircraft using its own power and the aircraft winch.

2. SALIENT CHARACTERISTICS.

2.1 Mobilizer description. The dolly set mobilizer shall be used as a method of lifting, loading, and transporting ISO containers or shelters with a maximum payload of 15,000 lbs (6,818 kg) and 20,000 lbs (9,090 kg) overload capacity. The mobilizer shall be compatible with any tactical, towing vehicle with a 10,000-lb rating or higher and an authorized towing capacity of at least 21,000 lbs. The mobilizer shall travel on primary roads, secondary roads, and off-road, and shall be air transportable. The mission-essential functions of the mobilizer can be separately identified as (1) loading (and unloading), (2) side loading, and (3) mobility.

2.1.1 Loading/unloading. The mobilizer load and unload function equipment shall include attaching the dolly set to the shelter, lifting the shelter for transport, securing shelter in the transport mode, and returning the mobilizer to its uncoupled and original configuration.

2.1.2 Side loading. The side load and unload function shall include those items utilized in uncoupling the unloaded mobilizer, attachment of specified payload, lifting to the specified height, and loading and unloading to and from the flatbed trucks or trains (or cross loading between modes of transportation).

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any data that may improve this document should be sent to: WR-AFLCMC/WNZEB, 235 Byron St., Suite 19A, Robins AFB GA 31098-1813. Since contact information can change, you may want to verify the currency of this information using the ASSIST Online database at https://assist.dla.mil.

AMSC N/A FSC 2330

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:32Z
Check the source to verify that this is the current version before use.

2.1.3 Mobility. The mobility function equipment shall include all items exclusive of the load and unload function and side load and unload function specified above.

2.2 Design and construction. The mobilizer design shall promote cost-effective, life-cycle sustainability by addressing considerations, such as incorporating open standards, reducing pollutant emissions and wastes, and increasing fuel economy, while satisfying system performance requirements. It shall be designed and constructed so that no parts will work loose in service, and to withstand the strains, jars, vibrations, and other conditions incident to shipping, storage, installation, and service. It shall be weatherproof and designed to prevent the intrusion of water, sand, and dust into critical operating components.

2.2.1 Materials, protective coatings, and finish.

2.2.1.1 Protective coatings. Materials that deteriorate when exposed to sunlight, weather, or operational conditions normally encountered during the service life of the item shall not be used, or shall have means of protection against such deterioration that does not prevent compliance with the performance requirements specified herein. Protective coatings that chip, crack, or scale with age or extreme climate conditions, or when exposed to heat shall not be used. Exposed surfaces of fasteners, handles, and fittings shall also be primed and painted. See 2.2.4.1 for prohibited hazardous materials.

2.2.1.2 Finish. The exterior finish color of the mobilizer shall be Lusterless Olive Drab Green, color number 34088 of SAE-AMS-STD-595.

2.2.1.3 Exclusion of water. The design of the mobilizer shall be such as to prevent water leaking into, or being driven into, any part of the mobilizer interior when either in an operating or travelling configuration. All panels, covers, etc., shall be provided with sealing arrangements such that the entry of water is minimized when these items are correctly closed. Particular care shall be taken to prevent wetting of equipment and heat and sound proofing materials. Sharp corners and recesses shall be avoided so that moisture and solid matter cannot accumulate to initiate localized attack. Sealed floors with suitable drainage shall be provided for storage compartments, engine compartments, and other areas in the mobilizer that could collect and retain water.

2.2.1.3.1 Fluid traps and faying surfaces. There shall be no fluid traps on the mobilizer. Faying surfaces of all structural joints, except welded joints, shall be sealed to preclude fluid intrusion.

2.2.1.3.2 Ventilation. Ventilation shall be sufficient to prevent moisture retention and buildup.

2.2.1.3.3 Drainage. Drain holes shall be provided to prevent collection or entrapment of water or other unwanted fluid in areas where exclusion is impractical. All designs shall include considerations for the prevention of water or fluid entrapment, and ensure that drain holes are located to effect maximum drainage of accumulated fluids. The number and location of drain holes shall be sufficient to permit drainage of all fluids when the mobilizer is on a 20-degree longitudinal slope facing both up and down, and on an 11.5-degree side slope in each direction (right and left side facing up the slope). The minimum size of the drain holes shall be 0.375 inch.

2.2.2 Markings. All external devices which require an operational or maintenance interface shall be marked in accordance with MIL-STD-130. Markings shall be applied with decals and shall be 1-inch high block letters, unless prohibited by the available space. In such cases, the markings shall be the largest size possible. Information and Caution markings shall be Lusterless Black, color

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:32Z
Check the source to verify that this is the current version before use.

number 37038 of SAE-AMS-STD-595, and Warning and Danger markings shall be Lusterless Red, color number 31136 of SAE-AMS-STD-595. Tire inflation pressure shall be marked as near to each tire as practicable.

2.2.3 Identification and information plates. All data plates shall be permanently marked and constructed of a non-corrosive metal in accordance with MIL-STD-130. All data plates shall be attached using stainless steel or anodized aluminum screws or rivets, or with stainless steel or aluminum banding, if attached to hydraulic cylinders. Attachments shall be in a conspicuous location which is readily viewable to service personnel standing on a level ground during all stated procedures. The size of the plates shall not exceed the structure to which it is attached.

2.2.3.1 Identification plate. The mobilizer shall have three identification plates: one for the rear-dolly half, one for the front-dolly half, and one for the mobilizer as a whole. The identification plates for the rear and front dolly, individually, shall include the following: nomenclature, registration number, manufacturer's name, manufacturer's serial number, and contract number. The identification plate for the mobilizer as a whole shall be securely attached to the mobilizer in a readily-accessible location and shall contain the following information: nomenclature, registration number, part number, manufacturer's name, manufacturer's serial number, date of manufacture, date of warranty expiration, Commercial and Government Entity (CAGE) code, National Stock Number (NSN), technical manual number, and contract number. The mobilizer and any of its components, for which the Government's unit cost is more than $5,000 or the procuring agency determines is mission essential, is serially managed and shall have Unique Identification (UID) (also known as Item Unique Identification (IUID)) information permanently affixed on or near the respective identification plate(s), marked in accordance with MIL-STD-130. UID information shall be included as both a bar code and legible markings.

2.2.3.2 Transportation data plate. Two transportation data plates shall be securely attached to the mobilizer in a readily-accessible location for a standard configuration and for a mobilizer with the side lift kit. Each plate shall contain at least the following information for both the fully-loaded (with 15,000-lb ISO container) and unloaded (in tandem) configurations with all weights rounded to the nearest 50 lbs.

a. Side and rear silhouette views of the mobilizer.

b. Horizontal and vertical location of the center of gravity (CG) of the mobilizer in air-transportable configuration, marked on the silhouette views. Use differentiated markings of the CG for each aircraft configuration.

c. Shipping weight.

d. Loading cubage.

e. Overall height, width, and length.

f. Front and rear axle loads and locations.

g. Axle springs.

h. Lunette load.

i. Ground clearance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:32Z
Check the source to verify that this is the current version before use.

j. Tie down information.

2.2.3.3 Lubrication data plate. The mobilizer shall be provided with a permanently-marked lubrication data plate constructed of a non-corroding metal, mounted on the exterior surface of the mobilizer that shall direct attention to all lubrication fittings and components that require lubrication. The plate shall identify the type and grade of lubricant required for operational temperatures specified in 2.3. The lubrication data plate shall be placed adjacent to the identification plate for the whole mobilizer.

2.2.3.4 Uncoupling plate. The uncoupling plate shall give instruction for the uncoupling of the mobilizer halves in tandem.

2.2.3.5 Coupling plate. The coupling plate shall give instruction for the coupling of the mobilizer to the container, lifting and preparation for shipment, lowering and uncoupling from shelter, and preparation for unloaded mobilizer movement.

2.2.3.6 Side loading plate. The side loading plate shall provide instruction for coupling of the mobilizer halves to the container, lifting of the container, maneuvering of the container, and lowering and uncoupling of the mobilizer halves from the container when the side loading kit is in use.

2.2.4 Environmental, Safety, and Occupational Health (ESOH).

2.2.4.1 Hazardous material. The design shall minimize and control hazards associated with the inclusion or use of hazardous or toxic materials and the generation of toxic or noxious gases. The mobilizer shall not generate or use class I or class II ozone-depleting substances (ODS) during operation, maintenance, or disposal. Class I ODS and hazardous materials shall not be used in any system, component, or process. The mobilizer shall not contain or use either hexavalent chromium or cadmium without written approval by the procuring activity. Hazardous materials are defined in Air Force Instruction 32-7086, and class I and class II ODS are defined in Title 40 of the Code of Federal Regulations (40 CFR), part 82.

2.2.4.2 Component protection. All space in which work is performed during operation, service, and maintenance shall be free of hazardous protrusions, sharp edges, or other features which may cause injury to personnel. All rotating and reciprocating parts, and all parts subject to high operational temperatures or subject to being electrically energized that are of such nature or so located as to be hazardous to personnel, shall be guarded or insulated to eliminate the hazard. All wires, cables, tubes, and hoses shall be supported and protected to minimize chafing and abrasion, and shall be located so as to provide adequate clearance from moving parts and high operational temperatures. Grommets shall be provided wherever wires, cables, tubes, or hoses pass through bulkheads, partitions, or structural members.

2.2.4.3 Foreign object damage (FOD). All loose metal parts, such as pins or connector covers, shall be securely attached to the mobilizer with wire ropes or chains. "Dog tag" style, beaded chains shall not be provided. Removable panels, if provided, shall be attached with captive fasteners. Tire valve-stem caps shall be made of plastic.

2.2.5 Human systems integration. The mobilizer shall be designed in accordance with MIL-STD-1472 for ease of operation, inspection, and maintenance, including the use of arctic mittens and with chemical-warfare gear in the mission-oriented protective posture (MOPP), level

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:32Z
Check the source to verify that this is the current version before use.

4. Chemical-warfare gear is not required for preventive maintenance or major corrective maintenance.

2.2.6 Fastening devices. All screws, bolts, nuts, pins, and other fastening devices shall be properly designed, manufactured, and installed with adequate means of preventing loss of torque or adjustment. Cotter pins, lock washers, or nylon patches shall not be used for this purpose, except for the attachment of trim items or as provided in commercial components (see 6.4.1). Tapped threads shall have a minimum thread engagement in accordance with table I.

TABLE I. Minimum thread engagement.

Material	Minimum Thread Engagement
Steel	1.0 times the nominal fastener diameter
Cast iron, brass, or bronze	1.5 times the nominal fastener diameter
Aluminum, zinc, or plastic	2.0 times the nominal fastener diameter

2.2.7 Welders and welding. All welders shall be certified to weld in accordance with American Welding Society (AWS) D1.1 and AWS D1.2, as applicable. The contractor shall make available to the Government certifications for all welders being utilized on the mobilizer. Welding procedures and all welding on the mobilizer shall be in accordance with AWS D1.1 and AWS D1.2, as applicable. The surface parts to be welded shall be free from rust, scale, paint, grease, and other foreign matter. Welds shall be of sufficient size and shape to develop the full strength of the welded parts. Welds shall transmit stress without cracking or permanent distortion when the parts connected by the welds are subjected to test, proof, and service loadings.

2.3 Environmental conditions.

2.3.1 Operating temperature range. The mobilizer shall be capable of operating in ambient temperatures ranging from -40 to 120 °F without the use of supplemental equipment.

2.3.2 Storage temperature range. The mobilizer shall be capable of being stored in ambient temperatures ranging from -60 to 140 °F.

2.4 Weight and dimensions. Overall weight and dimensions in air-transport configuration (see 2.5.2) shall not exceed:

Weight (unloaded, empty mobilizer in tandem)	6,200 lbs
Length (loaded, mobilizer/container combination, including wagon tongue)	438 in
Width	96 in
Height (loaded, with payload)	110 in

2.5 Transportability.

2.5.1 Surface transportability. The mobilizer shall be transportable via all modes of surface shipment (highway, rail, and water) in accordance with MIL-STD-1366, and shall be capable of withstanding the mechanical shock and vibration characteristics of highway, rail, and water transport, except that design for rail-impact testing (see MIL-STD-1366, 5.2.5) is not required.

2.5.2 Air transportability. The mobilizer, with or without payload, shall be transportable on C-130, C-17, and C-5 aircraft in accordance with MIL-STD-1791. The mobilizer shall be pulled

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:32Z
Check the source to verify that this is the current version before use.

backward into the aircraft using a winch attached to the rear-dolly pintle assembly. When the mobilizer is loaded with a shelter, the lift cylinders on the mobilizer shall be lowered to ensure that the shelter does not exceed height requirements and no contact is made. Once inside the aircraft, the shelter shall be lowered to the floor and secured in tie down position. In all air-transport configurations, the mobilizer shall be capable of being restrained and withstanding 2.0 G up and 4.5 G down accelerations without loss of serviceability, and shall be capable of being restrained and withstanding 3.0 G forward, 1.5 G aft, and 1.5 G lateral accelerations without loss of structural integrity. The mobilizer shall be equipped with pressure-relief devices or configured for air transport to prevent any part from becoming a projectile in the event of catastrophic loss of aircraft cabin pressure. The mobilizer shall roll on and off the aircraft, negotiating the required maximum ramp angles without shoring.

2.5.2.1 Shoring. The mobilizer shall be air transportable without shoring.

2.5.2.2 Axle weight. Axle weight shall not exceed 13,100 lbs.

2.5.2.3 Tire pressure. Tire pressure shall not exceed 120 pounds per square inch (psi) and shall not be reduced for air transport.

2.5.2.4 Winch points. Winch points shall be provided at the front and rear of the mobilizer for aircraft loading using the aircraft's winch.

2.5.2.5 Equipment removal and reconfiguration. Preparation for air transport shall take no more than 20 minutes with ideal conditions for six persons using common hand tools (see 6.4.2). Loading shall begin when the fully-loaded mobilizer is backed to within 1 ft of the aircraft cargo ramp. Loading shall end when the shelter is in tie down position inside the aircraft. Preparation for air transport shall not require the use of special tools (see 6.4.6). All equipment removed shall be stored on the mobilizer; caps and plugs shall permit moving and storage in transport configuration. The maximum dimensions of the loaded mobilizer during aircraft boarding shall be 96 inches in width and 102 inches in height.

2.5.3 Tie downs. The mobilizer shall be symmetrically restrained during air and ground transport. Tie down points shall be rated at a minimum of 26,200 lbs, marked for capacity, with a clear opening compatible with MIL-DTL-25959 and MIL-PRF-27260 tie down devices. Each end of each tie down device shall terminate at a tie down point and not pass through any other tie down point. There shall be no interference between tie down devices and the mobilizer. The tie down provisions shall be in accordance with MIL-STD-209, 4.1 through 4.12.

2.6 Maintainability. The mobilizer shall be designed for maintainability in accordance with MIL-STD-1472, 5.9.1 through 5.9.18; forces shall not exceed those specified for both males and females.

2.6.1 Inspection and servicing provisions.

a. Pre-use inspections and servicing tasks shall not require tools.

b. Routine service and preventive maintenance shall not require special tools.

c. Drain plugs and filters shall be directly accessible from the ground and oriented to have unimpeded drainage to a catch pan.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:32Z
Check the source to verify that this is the current version before use.

d. The mobilizer shall be designed with maximum usage of sealed, lifetime-lubrication bearings.

2.6.2 Special tools. The design of the mobilizer shall minimize the requirement for special tools. All special tools shall be provided with, and stored on, the mobilizer.

2.6.3 Diagnostic software. A copy of any diagnostic software required or recommended for maintaining the mobilizer shall be provided with each mobilizer on CD-ROM or DVD-ROM by the manufacturer.

2.7 Payload. The mobilizer shall be capable of transporting an 8-ft high by 8-ft wide by 20-ft long shelter or container (the payload) configured with ANSI/ISO corners. The standard payload shall not exceed 15,000-lbs gross weight. The CG of the load can be described by a rhombus that varies not more than +/- 5 ft of either side of the longitudinal axis of the shelter and +/- 2 ft of either side of the lateral axis. The vertical CG shall not exceed 4 ft from the floor of the shelter. The design of the dolly shall be such to accommodate this variation in loading. This CG variation applies only to end lifting and transport. For side loading, the CG location should be limited to +/- 2 ft of the longitudinal axis and lateral axis of the shelter.

2.7.1 Overload operation. The mobilizer shall be capable of transporting a payload of up to 20,000 lbs over highways and generally level or improved cross-country terrain, such as found within the perimeter of an airbase or airfield. The performance of the mobilizer shall be at levels at least 90 percent of normal operations, i.e., maximum highway speed of 50 miles per hour (mph) vs. 55 mph under normal conditions.

2.8 Mobility. The mobilizer loaded to its gross vehicle weight rating (GVWR) shall be capable of the following:

2.8.1 Terrain. The mobilizer shall be towable over the following terrain during end-lift transport unless stated otherwise.

2.8.1.1 Paved surfaces. The mobilizer, with maximum payload of 15,000 lbs, shall be towable at speeds up to 55 mph over paved surfaces.

2.8.1.2 Graded gravel. The mobilizer, with maximum payload of 15,000 lbs, shall be towable at speeds up to 20 mph over graded gravel.

2.8.1.3 Cross-country terrain. The mobilizer, with maximum payload of 15,000 lbs, shall be towable at speeds up to 25 mph on level and hilly cross-country terrain.

2.8.2 Side lift transport. The mobilizer, with maximum payload, shall be towable at speeds up to 5 mph at a minimum of 100 ft during side lift configuration (See 2.9.6).

2.8.3 Tandem operation. The tow vehicle shall be able to tow, at speeds under 25 mph, two empty dolly sets in tandem in limited environments, such as airfields, with no special preparation and without unusual wear on the mobilizers or tow vehicle. Interconnection of the dolly sets shall be provided to the extent necessary to meet specified stopping distances and lighting requirements.

2.8.4 Fording. During end-lift transport, with rated payload, the mobilizer shall ford hard bottom salt or fresh water crossings to depths covering the wheels. The mobilizer shall withstand submergence for at least 15 minutes without being damaged, and without special preparation or

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:32Z
Check the source to verify that this is the current version before use.

servicing before or after fording operations. No evidence of water leakage or moisture penetration into sealed wheel bearings shall be permitted.

2.8.5 Clearances. The minimum ground clearance of a fully-loaded mobilizer shall be 14 inches. Ground clearance, ramp breakover angle, and angles of approach and departure shall be in accordance with SAE AS8090, 3.3.9.

2.8.6 Suspension. The mobilizer shall have a suspension system in accordance with SAE AS8090, 3.4.1.2. The suspension shall be able to provide approximately the same ride performance between half of the maximum load and the maximum load (7,500 lbs – 15,000 lbs). Any requirement for the use of air pressure in the suspension system or elsewhere shall not exceed 120 psi (maximum pressure available from tow vehicle). When operating on the maximum side slope, the suspension roll stiffness shall be sufficient to prevent a significant change in the CG location of the load that would in itself cause an unstable geometry, i.e., overturning.

2.8.7 Towing vehicle prime mover capability. The mobilizer shall be compatible with all military, tactical-wheeled vehicles of a 5-ton rating or greater with rear pintle hook.

2.8.8 Steering. The mobilizer shall have a steering system in accordance with SAE AS8090, 3.5.1.1.

2.8.8.1 Tracking ability. The fully-loaded mobilizer shall conform to the tracking requirements of Federal Motor Carrier Safety Administration (FMCSA), 49 CFR, 393.70.

2.8.8.2 Safety chains. The mobilizer shall be equipped with safety chains for coupling to the tow vehicle in accordance with 49 CFR, 393.70.

2.8.8.3 Maneuvering. The fully-loaded mobilizer shall be capable of maneuvering a 38-degree steering angle in both directions to the coupled towing vehicle without interference or damage to the mobilizer or tow vehicle.

2.8.9 Longitudinal inclines. The mobilizer shall follow the tow vehicle, without weaving to an extent which adversely affects the controllability of the vehicle combination when ascending or descending longitudinal inclines having a 30-percent grade (end-lift operations only).

2.8.10 Side slope. The mobilizer shall follow the tow vehicle without slippage or upsetting either left or right when operating on side slopes having a 20-percent grade given the CG of the loaded shelters are within the limits specified (see 2.7) (end-lift operations only).

2.8.11 Brakes.

2.8.11.1 Parking brakes. The mobilizer shall have parking brakes in accordance with SAE AS8090, 3.6.1. The parking brake shall be easily and quickly applied by means of a single manual control, a hand lever not exceeding 18 inches in length, and shall operate all brakes on that portion of the mobilizer to lock the wheel against rotation. Brake actuation force shall not exceed 200 in-lbs.

2.8.11.2 Service brakes. The mobilizer shall have service brakes in accordance with SAE AS8090, 3.6.2. The brake system shall conform to all Federal Motor Vehicle Safety Standards (FMVSS) and 49 CFR, 393.70. Non-asbestos brake materials shall be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:32Z
Check the source to verify that this is the current version before use.

2.8.11.2.1 Emergency brakes. The system shall include emergency breakaway features and relay emergency valves that comply with the requirements of 49 CFR, 393.43. Upon breakaway from the tow vehicle, emergency brakes shall hold the brakes stationary on grades up to 30 percent for a period of 15 minutes.

2.8.11.3 Air line couplings and markings. On the front unit of the mobilizer set, permanently-attached air lines and hoses (attached with thread fittings) shall be provided to supply air for braking requirements. The air lines shall be routed along the trailer tongue, and shall be sufficiently long to couple with the glad hands at the rear of the tow vehicle. No pulling or kinking of lines shall occur throughout the entire articulation range between the towed and towing vehicle. The mobilizer shall have couplers in accordance with SAE AS8090, 3.5. Dummy couplers shall be provided for storing air lines when they are not in use.

2.8.11.4 Brake system hoses and fittings. Air-hose fittings and locations shall comply with SAE J702.

2.8.11.4.1 Connecting hoses, brake intravehicular. A line of sufficient length shall provide a connection between the front and rear dolly sections when loaded with a 20-ft shelter by routing the line over the shelter. Stowage location shall be provided for excess line when the mobilizer is towed in the empty configuration, and to hold the brake lines to the top of the shelter when loaded.

2.8.11.4.2 Tandem interconnector. A quick-disconnect, air line connector shall be provided on the rear section of the mobilizer to permit the towing of tandem, unloaded mobilizers.

2.8.11.4.3 Connecting hoses, brake intervehicular. Lines of sufficient length to reach the towing vehicle without interference during operation and capable of connecting to the towing vehicle connector shall be provided.

2.8.12 Towing force. The towing force shall be in accordance with SAE AS8090, 3.3.4.

2.8.13 Pintle hook. The mobilizer shall be fitted with one pintle hook capable of towing an unloaded dolly set in tandem, mounted in accordance with SAE AS8090, 3.13.

2.8.14 Towbar. The mobilizer shall be equipped with a towbar in accordance with SAE AS8090, 3.17.1. It shall have a lunette eye in accordance with A-A-52464, and accommodate any pintle hook height from 22 through 30 inches. When in operation or storage (not being towed), the towbar shall be stowed upright, secured, and not hinder visibility, operation, or maintenance.

2.8.15 Tires and wheels. The mobilizer shall be equipped with four, single steel-belted radial tires with on-/off-road type tread mounted on steel disc wheel assemblies. Tire and wheel assemblies shall be identical at all wheel positions. Tires and wheels shall be in accordance with the *Tire and Rim Association Year Book* requirements for this application.

2.8.15.1 Tire changing. The tires and wheels on the mobilizer shall be able to be changed with or without the payload. The mobilizer shall be compatible with standard 5-ton truck jacks.

2.9 Mobilizer and shelter interaction.

2.9.1 Payload interfaces and lifting. The mobilizer shall be so designed that no mechanism shall require external power or externally renewed power (except for the diesel engine) other than that provided by the four-man crew to position, attach, lift, and prepare for movement of the shelter or container.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:32Z
Check the source to verify that this is the current version before use.

2.9.2 Operational cycle. The mobilizer operational cycle includes uncoupling an empty mobilizer, attaching it to the shelter in the end-lift mode, and lifting the shelter for transport. This shall be accomplished without special tools or auxiliary equipment, both on- and off-road, by four personnel in 30 minutes or less. The reverse procedure shall also not exceed 30 minutes.

2.9.3 Attaching devices. The mobilizer shall be capable of being attached to the container or shelter utilizing any combination of the ANSI/ISO twist-lock couplers, which shall meet the requirements stated herein. Four couplers are required on each unit of the mobilizer (front and rear), arrayed to match with the fittings at the ends of an ISO shelter or container in accordance with ISO 1161 and ISO 668. For side lift operations, the mobilizer shall be attached by chains to the lower fittings on the sides of the container or shelter.

2.9.3.1 Steps and handles. The mobilizer shall be equipped with, or a combination of, fixed steps, handles, handrails, or a detachable ladder which allow personnel to completely attach the mobilizer and container combination.

2.9.4 Side loading and unloading kit. The mobilizer shall include a design capability for side loading and unloading of containers. When specified (see 6.2), a kit shall be provided to allow the side loading and unloading capability of specified containers and specified payloads from and onto trucks or trains, on level grade. The side loading kit shall also permit cross loading between modes of transport and positioning of containers over short distances (100 ft) when lifted from the sides. The kit shall provide the capability of side lifting the container up to 60 inches above ground level. Use of the side lift capability shall not require any special tools or equipment. The kit shall consist of all necessary hardware, equipment, and instructions necessary to safely attach the mobilizer to the container sides, raise it to the maximum height, lower it to grade, and detach from the container. When the kit is installed on the mobilizer, all kit hardware and equipment is to be stowable on the mobilizer when not in use.

2.9.4.1 Side loading configuration. The operational cycle for side loading consists of uncoupling an empty mobilizer, attaching to the side of the shelter, and raising the shelter to the maximum height (on smooth, level grade). The cycle shall be completed in 30 minutes by four personnel under normal conditions. The reverse procedure, including stowage of the side lift components, shall not exceed 30 minutes.

2.9.5 Coupling and uncoupling performance. A single mobilizer half shall be designed to be easily maneuverable by the crew over all types of terrain likely to be encountered in deployment in preparation for coupling to a shelter. The manual effort in aligning the mobilizer unit with the shelter prior to coupling shall be minimized. A flexible element is required to achieve, by mechanical assist, the final coupling alignment after the mobilizer unit couplers are within a few inches of the ISO container fittings. Alternately, the mobilizer's diesel engine can be used to power the unit into alignment with the shelter. If a hydraulic system is used on the mobilizer, the reservoir shall include a dipstick or sight glass for fluid measurement. The system shall function effectively with the container on the ground or raised up to a height of 1 ft on uneven terrain.

2.9.6 Lifting system. A lifting system, hydraulically driven by a diesel engine (see 2.10), shall be required to lift the shelter into travel mode, i.e. up to required ground clearance with the suspension active. The capacity of the system shall be sufficient to lift shelter weights of up to 20,000 lbs with maximum CG shifts as prescribed in 2.7. The lifting system shall also allow sufficient adjustment for aircraft boarding. The system shall also be able to relieve the payload from the wheels while

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:32Z
Check the source to verify that this is the current version before use.

the dolly set is attached to the deployed shelter. The lifting system shall have a positive mechanical lock to secure to a shelter in the travel mode. The dolly set shall be able to position the shelter to a level position when one wheel is 12 inches lower than the opposite wheel on the same axle relative to the floor of the shelter, or an 18-inch variation from one end of the shelter to the other. This could result when one corner of the shelter is on the ground and the diagonal corner would be 30 inches above the ground. It is desirable that the shelter access door be accessible in either position, but not unreasonable to require the door face downhill in these extreme conditions.

2.10 Engine. The mobilizer shall be equipped with a one-cylinder, four-cycle, diesel engine on each dolly half that powers the hydraulic loading and lifting system to support the 15,000-lb maximum load. The engine shall ensure the rotational force from the crankshaft drives the hydraulic pump. The engine shall be able to start with a 12-volt DC electric starter, with a minimum output of 6.0 horsepower (hp), and have a minimum speed of 3600 revolutions per minute. The engine shall comply with Environmental Protection Agency (EPA), Tier 4, emissions regulations.

2.10.1 Engine fuels and fuel system. The onboard power unit (engine) for the mobilizer shall be capable of using the following fuels:

a. JP-8, in accordance with MIL-DTL-83133, -40 to 125 °F ambient air temperature.

b. 1-D S15, 1-D S500, 1-D S5000, in accordance with ASTM D975, below 60 °F ambient air temperature.

c. 2-D S15, 2-D S500, 2-D S5000, in accordance with ASTM D975, above 32 °F ambient air temperature.

2.10.2 Fuel tank. The fuel tank shall be designed to be compatible with the engine system of the mobilizer. The tank shall have a visual gauge to indicate the level of fuel in the tank. The fuel tank shall be in accordance with SAE ARP1247, 3.13.1.5.5 through 3.13.1.5.9. The tank shall be designed so that the mobilizer can be operated on a 20-degree longitudinal slope facing up and down, and on an 11.5-degree side slope in each direction (right and left side facing up the slope). The tank shall be provided with corrosion protection and baffles. A 0.25- to 0.375-inch nominal drain valve shall be provided for emptying fuel and sediment into a container underneath the mobilizer without removal of the tank or any other major component. The fuel tank shall have a fuel-fill opening of not less than 3-inch inside diameter, and shall be designed to drain fuel spillage overboard for collection outside the mobilizer. The fuel cap shall be equipped with a retention device to prevent loss and FOD. The fuel-fill opening, fuel cap, and fuel-cap retention device shall be fabricated from non-sparking material.

2.11 Electrical system. The electrical lighting system shall be commercial standard, 12-volt DC with 24-volt DC military adaptations incorporated as defined below. Lighting shall be configured to meet all specified requirements when mobilizer is transported, loaded, or unloaded. The electrical lighting system shall conform to all FMCSA and FMVSS guidance.

2.11.1 Lighting. The electrical lighting system shall be 12-volt DC potential with adaptations of 24-volt DC service incorporated as defined herein. The lighting system shall confirm to MIL-STD-1179. All lights and reflectors shall be protected from operational hazards by mounting in guarded locations. Waterproof (Packard type) connectors shall be employed throughout. Additionally, the

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:32Z
Check the source to verify that this is the current version before use.

rear dolly shall be equipped with stoplights and taillights in accordance with FMCSA and FMVSS guidance.

2.11.2 Solid-state reducer. The mobilizer shall be equipped with a solid-state, voltage reducer box.

2.11.3 LED blackout light. LED blackout lights shall be installed on the rear of dolly frame near the taillight. The taillights and stoplights shall be installed such that they shall not function during the use of the LED blackout lights. The rear dolly shall be equipped with stoplights and taillights in accordance with FMCSA and FMVSS guidance.

2.11.4 Connecting cable intravehicular. A cable of sufficient length shall provide an electrical connection between front and rear dolly sections, when loaded with a 20-ft shelter, by routing the cable over the shelter. A stowage location shall be provided for excess cable when the dolly is towed in the empty configuration.

2.11.5 Tandem interconnector. One 7-pin electrical connector, in accordance with SAE J560, shall be provided, if necessary, on the rear section of the dolly to permit towing of an unloaded mobilizer in tandem. A stowage location shall be provided for cable when not in use.

2.11.6 Connecting cable, electrical intravehicular. Cables of sufficient length shall be provided to reach the towing vehicle without interference during operation and capable of connecting to a 7-pin connector and a 12-pin connector.

2.11.7 Reflectors. Reflectors shall be mounted in accordance with 49 CFR, 393.11.

2.12 Redundant power kit. The mobilizer shall include a design capability to share power between mobilizers in the field. A kit shall be provided, when required, which shall allow operation of one mobilizer unit from the other (front-to-rear or rear-to-front) in the event of an engine or pump failure on one unit. This shall be accomplished with extension hoses from one end to the other. The kit shall allow the use of each mobilizer unit to connect to and raise a container for transport, and shall not require the use of special tools. The kit shall be used for end lifting only, not in the side lift mode. The kit shall include all hardware and instructions necessary to safely install and operate the mobilizer. All hardware shall be stowable on the dolly set when not in use, and all hoses shall utilize quick-disconnect connections.

2.13 Winterization system. A winterization system shall be provided for starting in temperatures below -25 to -50 °F as a special purpose kit. The winterization system shall be comprised of an electrical system with associated hardware and connectors. The winterization system shall be designed to operate from an external 12- or 24-volt DC power source. The winterization system shall incorporate high-temperature shutoff switches to prevent overheating of any fluid or component.

2.14 Hydraulic system. The hydraulic system shall be in accordance with SAE ARP1247, 3.13.1.3, except as otherwise specified herein. O-ring face seal hydraulic fittings may be used in lieu of flared fittings (see SAE ARP1247, 3.13.1.3.12). Hydraulic fluid shall be in accordance with MIL-PRF-83282. All hydraulic system components, including the hydraulic tank, shall comply with all corrosion-resistance requirements specified herein.

2.14.1 Hydraulic reservoir. The storage tank shall have a capacity of not less than 110 percent of the fluid required to operate the hydraulic system. The tank shall be equipped with a fluid-level indicator, a drain plug, and an air vent. The hydraulic system and tank shall be fitted with hydraulic

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:32Z
Check the source to verify that this is the current version before use.

fluid in accordance with MIL-PRF-83282. A strainer shall be installed in the hydraulic suction line. A filter system shall be installed in the pump pressure line. The filter shall be so located as to provide access for element replacement. The degree of filtration shall be from 10 - 40 microns.

2.14.2 Hydraulic cylinders. With the possible exception of the main lift cylinder, standard commercial hydraulic cylinders shall be provided. Seals shall be installed to prevent the entrance of moisture into the cylinders, and all cylinders shall be protected with loaded lip seals or O-rings with backup rings.

2.15 Servicing and adjusting. Prior to acceptance of the mobilizer by the Government, the contractor shall service and adjust the mobilizer for immediate operational use. The servicing and adjusting shall include at least the following: inflation of all tires, adjustment of brakes, proper functioning of all lighting, and complete lubrication with grades of lubricants recommended for ambient temperature at the delivery point. The mobilizer shall be conspicuously tagged to identify the lubricants and their temperature range.

2.16 Workmanship. The mobilizer, including all parts and accessories, shall be constructed and finished in a thoroughly workmanlike manner. Workmanship objectives shall include freedom from blemishes, defects, burrs, and sharp corners and edges; accuracy of dimensions, surface finish, and radii of fillets; thoroughness of welding, painting, and riveting; marking of parts and assemblies; and proper alignment of parts and tightness of assembly fasteners.

2.16.1 Bolted connections. Bolt holes shall be accurately punched or drilled, and they shall be deburred. Threaded fasteners shall be tight and shall not work loose during testing or service use.

2.16.2 Riveted connections. Rivet holes shall be accurately punched or drilled, and they shall be deburred. Rivets shall be driven with pressure tools and shall completely fill the holes. Rivet heads shall be full, neatly made, concentric with the rivet holes, and in full contact with the surface of the component.

2.16.3 Gear and lever assemblies. Gear and lever assemblies shall be properly aligned and meshed, and shall be operable without interference, tight spots, loose spots, or other irregularities. Where required for accurate adjustment, gear assemblies shall be free of excessive backlash.

2.16.4 Cleaning. The mobilizer shall be thoroughly cleaned. Loose, spattered, or excess solder; welding slag; stray bolts, nuts, and washers; rust; metal particles; pipe compound; and other foreign matter shall be removed during and after final assembly.

3. REGULATORY REQUIREMENTS.

3.1 Recycled, recovered, environmentally preferable, or biobased materials. Recycled, recovered, environmentally preferable, or biobased materials should be used to the maximum extent possible, provided that the material meets or exceeds the operational and maintenance requirements, and promotes economically advantageous life-cycle costs. The offeror/contractor is encouraged to use recovered materials or biobased products to the maximum extent practicable, in accordance with Federal Acquisition Regulation (FAR), part 23.403. However, used, rebuilt, or refurbished items shall not be provided.

3.2 Green Procurement Program. Green Procurement Program (GPP) is a mandatory federal acquisition program that focuses on the purchase and use of environmentally preferable products and services. GPP requirements apply to all acquisitions using appropriated funds, including

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:32Z
Check the source to verify that this is the current version before use.

services and new requirements. FAR 23.404(b) applies and states the GPP requires 100 percent of EPA-designated product purchase that are included in the Comprehensive Procurement Guidelines list that contains recovered materials, unless the item cannot be acquired: a) competitively within a reasonable timeframe; b) meeting reasonable performance standards; or c) at a reasonable price. The prime contractor is responsible for ensuring that all subcontractors comply with this requirement.

4. PRODUCT CONFORMANCE. The products provided shall meet the salient characteristics of this CID; conform to the producer's own drawings, specifications, standards, and quality assurance practices; and be the same product offered for sale in the commercial marketplace, modified as necessary to comply with the requirements herein. The Government reserves the right to require proof of such conformance.

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First production inspection (see 4.2).

b. Conformance inspection (see 4.3).

4.2 First production inspection. The first production mobilizers shall be subjected to the analyses, demonstrations, examinations, and tests described in 4.5. Except as otherwise specified, all testing in which the engine is operated shall be performed using JP-8 turbine fuel.

4.3 Conformance inspection. Each production mobilizer shall be subjected to the examination described in 4.5.1.

4.4 Inspection requirements.

4.4.1 General inspection requirements. Apparatus used in conjunction with the inspections specified herein shall be laboratory precision-type, calibrated at proper intervals to ensure laboratory accuracy.

4.4.2 Data. During all testing specified herein, at least the following data, unless not applicable, shall be recorded at intervals not to exceed 30 minutes. Additional data or shorter intervals shall be provided as appropriate for any specific test.

a. Date.

b. Time started.

c. Time finished.

d. Ambient temperature.

e. Ambient humidity.

4.4.3 Test rejection criteria. Throughout all tests specified herein, the mobilizer shall be closely observed for the following conditions, which shall be cause for rejection:

a. Failure to conform to design or performance requirements specified herein.

b. Any spillage or leakage of any liquid, including fuel, coolant, lubricant, or hydraulic fluid under any condition, except as allowed herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:32Z
Check the source to verify that this is the current version before use.

c. Structural failure of any component, including permanent deformation or evidence of impending failure.

d. Evidence of excessive wear. If excessive wear is suspected, the original equipment manufacturer specifications or tolerances shall be used for making a determination.

e. Evidence of corrosion or deterioration.

f. Misalignment of components.

g. Conditions that present a safety hazard to personnel during operation, servicing, or maintenance.

h. Interference between the mobilizer components or between the mobilizer, the ground, and all required obstacles, with the exception of normal contact by the tires.

i. Evidence of undesirable mobility characteristics, including instability in handling during cornering, braking, and while traversing all required terrain.

4.5 Test methods.

4.5.1 Examination of product. Each mobilizer shall be examined to verify compliance with the requirements herein prior to accomplishing any other demonstrations or tests listed in 4.5. A contractor-generated, Government-approved checklist (part of the test procedure) shall be used to identify each requirement not verified by an analysis, certification, demonstration, or test, and shall be used to document the examination results. Particular attention shall be given to materials, workmanship, dimensions, surface finishes, protective coatings and sealants and their application, welding, fastening, and markings. Proper operation of each mobilizer function shall be verified. Certifications and analyses shall be provided in accordance with table II. Each production mobilizer shall be inspected to a Government-approved, reduced version of the checklist.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:32Z
Check the source to verify that this is the current version before use.

TABLE II. Certifications and analyses.

Paragraph	Required Certifications and Analyses
2.5.1 Surface transportability.	Contractor surface-transportability analysis (see 4.5.4.1) and certification that the mobilizer is transportable via all modes of surface shipment (highway, rail, and water) in accordance with MIL-STD-1366, and shall be capable of withstanding the mechanical shock and vibration characteristics of highway, rail, and water transport.
2.5.2 Air transportability. 2.5.2.1 Shoring. 2.5.2.4 Winch points.	Contractor air-transportability analysis (see 4.5.4.2).
2.5.3 Tie downs.	Contractor tie down provision analysis (see 4.5.4.4).
2.10 Engine. 2.10.1 Engine primary fuels.	Engine manufacturer certification that the engine is in accordance with all applicable requirements, including exhaust emissions standards and fuels. Engine manufacturer application approval for the engine and its installation.

4.5.2 Environmental testing.

4.5.2.1 High-temperature storage and operation test. A first production mobilizer shall be tested in accordance with MIL-STD-810, Method 501.6, Procedures I and II, to demonstrate compliance with the high-temperature storage and operating requirements of 2.3.1 and 2.3.2. Test duration shall be one 24-hour cycle for each procedure beginning no less than two hours after test item temperature stabilization.

4.5.2.2 Low-temperature storage and operation test. A first production mobilizer shall be tested in accordance with MIL-STD-810, Method 502.6, Procedures I and II, to demonstrate compliance with the low-temperature storage and operating requirements of 2.3.1 and 2.3.2. Test duration shall be one 24-hour cycle for each procedure beginning no less than two hours after test item temperature stabilization.

4.5.3 Weight and dimension tests.

4.5.3.1 Weight and center of gravity test. The weight, center of gravity, and axle weights of a first production mobilizer shall be measured to demonstrate compliance with the weight requirement of 2.4 and the axle-weight requirement of 2.5.2.2.

4.5.3.2 Dimension measurement. A first production mobilizer shall be measured to demonstrate compliance with the dimensional requirements of 2.4.

4.5.4 Transportability verification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:32Z
Check the source to verify that this is the current version before use.

4.5.4.1 Surface-transportability verification. An engineering analysis shall be performed to demonstrate compliance with 2.5.1. The engineering analysis shall utilize the data for road transportation in accordance with MIL-STD-810, Method 514.7, table 514.7C-II.

4.5.4.2 Air-transportability verification. An engineering analysis shall be performed to demonstrate compliance with the air-transportability requirements of 2.5.2. The analysis shall include the tie downs and all major components, and their ability to withstand the accelerations specified in 2.5.2. The analysis shall demonstrate the accessibility and structural adequacy of the winch points specified in 2.5.2.4. The evaluation shall also include a dimensional analysis for the mobilizer while traversing the ramp and while loaded aboard C-130, C-17, and C-5 aircraft.

4.5.4.3 Equipment removal and reconfiguration demonstration. A first production mobilizer shall be configured for transport on C-130, C-17, and C-5 aircraft, then reconfigured for operation to demonstrate compliance with 2.5.2.5. It shall be demonstrated that the forces required do not exceed those allowed in MIL-STD-1472.

4.5.4.4 Tie down provision verification.

4.5.4.4.1 Tie down provision analysis. An engineering analysis shall be performed to demonstrate compliance with the tie down provision requirements of 2.5.3.

4.5.4.4.2 Tie down provision test. A first production mobilizer shall be tested to demonstrate compliance with the tie down provision requirements of 2.5.3.

4.5.5 Mobility tests. A first production mobilizer shall be tested in accordance with SAE AS8090, table VIII, to demonstrate compliance with the payload requirements of 2.7 and 2.7.1, and mobility requirements of 2.8. Note that the maximum towing force is 75 lbs per ton of gross weight, in accordance with SAE AS8090, 3.3.4, rather than 50 lbs per ton of gross weight as stated in SAE AS8090, table VIII.

4.5.5.1 Paved surfaces. A first production mobilizer shall be towed for 10 miles at its maximum speed of 55 mph on a dry, level, paved surface to demonstrate compliance with 2.7, 2.7.1, and 2.8.1.1 in two configurations: (1) a mobilizer with a container at maximum capacity (15,000 lbs) and (2) a mobilizer with a container at overloaded capacity (20,000 lbs) at a minimum of 90-pecent performance levels.

4.5.5.2 Graded gravel. A first production mobilizer shall be towed for 10 miles at its maximum speed of 20 mph on graded gravel to demonstrate compliance with 2.7, 2.7.1, and 2.8.1.2 in two configurations: (1) a mobilizer with a container at maximum capacity (15,000 lbs) and (2) a mobilizer with a container at overloaded capacity (20,000 lbs) at a minimum of 90-percent performance levels.

4.5.5.3 Cross-country terrain. A first production mobilizer shall be towed for 10 miles at its maximum speed of 25 mph on cross-country terrain to demonstrate compliance with 2.7, 2.7.1, and 2.8.1.3 in two configurations: (1) a mobilizer with a container at maximum capacity (15,000 lbs) and (2) a mobilizer with a container at overloaded capacity (20,000 lbs) at a minimum of 90-pecent performance levels.

4.5.5.4 Side lift transport. A first production mobilizer with a container at maximum capacity (15,000 lbs) shall be towed using the side loading and unloading kit for 100 ft at its maximum speed of 5 mph on paved, level surface. The mobilizer shall be able to side lift the container to a

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:32Z
Check the source to verify that this is the current version before use.

minimum of 60 inches above ground level. The mobilizer shall demonstrate compliance with 2.7, 2.7.1, 2.8.2, and 2.9.4.

4.5.5.5 Tandem operation. A first production mobilizer in tandem (without payload) shall be towed for 5 miles at its maximum speed of 25 mph on a combination of surfaces found in an airfield to demonstrate compliance with 2.7, 2.7.1, and 2.8.3.

4.5.5.6 Fording. A first production mobilizer, with a container at maximum capacity, shall ford hard bottom salt or fresh water crossings to depths covering the wheels, and be able to withstand submergence for at least 15 minutes without damage to demonstrate compliance with 2.8.4.

4.5.5.7 Clearances. A first production mobilizer, loaded to its GVWR, shall be parked on a flat, level surface and its ground clearance, angle of approach, angle of departure, and ramp breakover angle shall be measured to demonstrate compliance with 2.8.5.

4.5.5.8 Towing vehicle compatibility. The mobilizer, with a container at maximum capacity, shall be able to demonstrate compliance with a wheeled vehicle of a 5-ton rating or greater, and with a rear pintle-hook assembly. The mobilizer with a container at overload capacity (20,000 lbs) shall be able to demonstrate compliance with a military, tactical-wheeled vehicle with a rear pintle hook and a payload capacity greater than the GVWR. The mobilizer, with a container at maximum capacity, shall be able to maneuver a 38-degree steering angle in both directions to the coupled towing vehicle. The mobilizer, in both configurations, shall demonstrate compliance with 2.8.7, 2.8.8, and 2.8.10 through 2.8.13.

4.5.5.9 Longitudinal inclines. The fully-loaded mobilizer and tow vehicle shall be able to ascend and descend a 30-percent grade ramp in compliance with 2.8.9.

4.5.5.10 Side slope. The fully-loaded mobilizer and tow vehicle shall be able to negotiate a 20-percent grade side slope in each direction (right and left side facing up the slope) in compliance with 2.8.10 and CG requirements of 2.7.

4.5.5.11 Parking brake test. The mobilizer shall be tested in accordance with SAE AS8090, 4.5.7.1, to demonstrate compliance with 2.8.11.1.

4.5.5.12 Service brake test. The mobilizer shall be tested in accordance with SAE AS8090, 4.5.7.2 and 4.5.8, to demonstrate compliance with 2.8.11.2.

4.5.5.13 Towing force test. The towing force of the mobilizer shall be tested in accordance with SAE AS8090, 3.3.4, to demonstrate compliance with 2.8.12.

4.5.5.14 Lifting system. The first production mobilizer shall be able to lift a container at overload capacity during end-lift transport to demonstrate compliance with 2.9.6. The mobilizer shall lift the required payload while one wheel is 14 inches lower than the opposite wheel on the same axle, relative to the plane of the bottom of the container. The mobilizer shall also lift the required payload with an 18-in variation from one end to the other.

5. PACKAGING. Preservation, packing, and marking shall be as specified in the contract or order.

6. NOTES.

6.1 Source of documents.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:32Z
Check the source to verify that this is the current version before use.

6.1.1 Air Force Instructions (AFI). Copies of AFIs are available online at http://www.e-publishing.af.mil/.

6.1.2 American Society for Testing and Materials (ASTM) documents. Copies of these documents may be obtained from ASTM, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959, or online at http://www.astm.org.

6.1.3 American Welding Society (AWS) documents. Copies of AWS documents may be obtained from AWS, 8669 NW 36 Street, # 130, Miami, FL 33166-6672, or online at http://www.aws.org.

6.1.4 Code of Federal Regulations (CFR). CFRs may be obtained from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402, or online at http://www.ecfr.gov/cgi-bin/ECFR?page=browse.

6.1.5 Federal Acquisition Regulations (FAR). FARs may be obtained from the Superintendent of Documents, Government Printing Office, Washington, DC 20402, or online at https://www.acquisition.gov/?q=browsefar.

6.1.6 Government documents. Copies of specifications, standards, and handbooks are available from DLA Document Services, 700 Robbins Avenue, Building 4/D, Philadelphia, PA 19111-5094, or online at https://assist.dla.mil.

6.1.7 Gosudarstvennye Standarty State standard (GOST). Copies of GOST 10227-86 are available from GOST Interstandard, 117049 Moscow, B-29 Russia, Attn: Mr. Nickolay Usov, nusov@gost.ru, or in English from www.ihs.com or from the Procuring Contracting Officer (PCO).

6.1.8 National Electrical Manufacturers Association (NEMA) documents. Copies of documents may be obtained from NEMA, 1300 North 17th Street, Suite 900, Arlington, VA 22209, or online at www.nema.org.

6.1.9 Society of Automotive Engineers (SAE) standards. Copies of SAE standards may be obtained from the SAE, 400 Commonwealth Drive, Warrendale, PA 15096, or online at http://www.sae.org/.

6.1.10 Technology and Maintenance Council (TMC) documents. Copies may be obtained from Technology and Maintenance Council, American Trucking Associations, 950 Glebe Rd., Arlington, VA 22203-4181, or online at http://www.trucking.org/Technology_Council.aspx.

6.1.11 Tire and Rim Association (TRA) standards. Copies of TRA standards may be obtained from TRA, Inc., 175 Montrose West Avenue, Suite 150, Copley, OH 44321, or online at http://www.us-tra.org/publications.html.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this CID.

b. Packaging requirements (see 5).

c. When a side loading and unloading kit is required (see 2.9.4).

d. When a winterization system is required (see 2.13).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:32Z
Check the source to verify that this is the current version before use.

6.3 National Stock Number (NSN). The following is a list of NSN's assigned that correspond to this CID. The list may not be indicative of all possible NSN's associated with this CID.

NSN	2330-01-378-9997

6.4 Definitions.

6.4.1 Commercial item.

(1) Any item, other than real property, that is of a type customarily used by the general public or by non-Governmental entities for purposes other than Governmental purposes, and—

(i) Has been sold, leased, or licensed to the general public; or

(ii) Has been offered for sale, lease, or license to the general public;

(2) Any item that evolved from an item described in paragraph (1) of this definition through advances in technology or performance, and that is not yet available in the commercial marketplace, but will be available in the commercial marketplace in time to satisfy the delivery requirements under a Government solicitation;

(3) Any item that would satisfy a criterion expressed in paragraphs (1) or (2) of this definition, but for—

(i) Modifications of a type customarily available in the commercial marketplace; or

(ii) Minor modifications of a type not customarily available in the commercial marketplace made to meet Federal Government requirements. Minor modifications means modifications that do not significantly alter the non-Governmental function or essential physical characteristics of an item or component, or change the purpose of a process. Factors to be considered in determining whether a modification is minor include the value and size of the modification, and the comparative value and size of the final product. Dollar values and percentages may be used as guideposts, but are not conclusive evidence that a modification is minor;

(4) Any combination of items meeting the requirements of paragraphs (1), (2), (3), or (5) of this definition that are of a type customarily combined and sold in combination to the general public;

(5) Installation services, maintenance services, repair services, training services, and other services if—

(i) Such services are procured for support of an item referred to in paragraph (1), (2), (3), or (4) of this definition, regardless of whether such services are provided by the same source or at the same time as the item; and

(ii) The source of such services provides similar services contemporaneously to the general public under terms and conditions similar to those offered to the Federal Government;

(6) Services of a type offered and sold competitively in substantial quantities in the commercial marketplace based on established catalog or market prices for specific tasks performed or specific outcomes to be achieved and under standard commercial terms and conditions. For purposes of these services—

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:32Z
Check the source to verify that this is the current version before use.

(i) “Catalog price” means a price included in a catalog, price list, schedule, or other form that is regularly maintained by the manufacturer or vendor, is either published or otherwise available for inspection by customers, and states prices at which sales are currently, or were last, made to a significant number of buyers constituting the general public; and

(ii) “Market prices” means current prices that are established in the course of ordinary trade between buyers and sellers free to bargain, and that can be substantiated through competition or from sources independent of the offerors;

(7) Any item, combination of items, or service referred to in paragraphs (1) through (6) of this definition, notwithstanding the fact that the item, combination of items, or service is transferred between or among separate divisions, subsidiaries, or affiliates of a contractor; or

(8) A nondevelopmental item, if the procuring agency determines the item was developed exclusively at private expense and sold in substantial quantities, on a competitive basis, to multiple State and local Government. (Reference FAR 2.101)

6.4.2 Common hand tool. A non-powered tool that is likely to be found in a typical mechanic’s toolbox. Common hand tools include open-end, box-end, combination, socket (both 6- and 12-point in both standard and deep-well), and hex-key wrenches, in SAE sizes up to and including 1-inch, and metric sizes up to and including 25-mm; ratchet handles, extensions, and swivels; slotted and Phillips-head screwdrivers; regular and snap-ring pliers; and a ball-peen hammer.

6.4.3 Cross-country terrain. Cross-country terrain consists of unimproved open fields, broken ground, loose sand, and gravel road encountered by tactical vehicles supporting an army in the field.

6.4.4 Gravel road. A gravel road is a level or rolling gravel trail.

6.4.5 Primary fuel. The fuel or fuels used during tests to demonstrate system performance (contract compliance). Substitutions are presented as Alternate and Emergency fuels.

6.4.6 Special tool. A tool that is not commercially and readily available from a source other than the mobilizer contractor.

6.5 Key words.

Container
Shelter
Lift
Transporter
Hydraulic lift

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:32Z
Check the source to verify that this is the current version before use.

MILITARY INTEREST

Custodian:
Air Force – 184

Preparing Activity:
Air Force – 184

Agent:
Air Force – 99

(Project 2330-2017-003)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:32Z
Check the source to verify that this is the current version before use.