
MILITARY SPECIFICATION SHEET

CONNECTORS, ELECTRICAL, (CIRCULAR, ENVIRONMENT RESISTING), PLUG, (THREADED COUPLING, CRIMP SOCKET CONTACTS), (SERIES II, CLASSES A, G, K, AND R)

This specification sheet is approved for use by the Engineering and Technical Support Division (AFLC), Department of the Air Force, and is available for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the connector described herein shall consist of this document and the latest issue of Specification MIL-C-83723

© INACTIVE USE MS3456 OF MIL-C-5015



NOTES:
1. ALL DIMENSIONS ARE IN INCHES
2. ALL DIMENSIONS ARE AFTER PLATING
© 3. FOR DETAILS OF CONNECTOR FRONT END CONFIGURATION SEE PROCUREMENT SPECIFICATION

© Denotes revision

FSC 5935

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:19Z
Check the source to verify that this is the current version before use.

© TABLE I. CONNECTOR DIMENSIONS

SHELL SIZE - PART NO DESIGNATION	MIL-C-5015 SIZE SHELL	B THREAD	1/ E MAX	F	L MAX	Q MAX	K
08	8S	.4375-28 UNEF-2A	.400	.468 .418	1.135	.760	
10	10S	.500-28	.400			.880	
11	10 SL	.5625-24	.400			.880	
13	12S	.625-24	.400	.468 .418	1.135	1.010	.375
12	12	.625-24	.317	.637 .587	1.495	1.010	
15	14S	.750-20	.400	.468 .418	1.135	1.130	
14	14	.750-20	.317	.637 .587	1.495	1.130	
17	16S	.875-20	.400	.468 .418	1.135	1.250	.375
16	16	.875-20	.317	.637 .587	1.495	1.250	.531
18	18	1.000-20	.380	.637 .587		1.340	
20	20	1.125-18	.380	.621 .571		1.469	
22	22	1.250-18	.380	.621 .571	1.495	1.590	
24	24	1.375-18	.315	.637 .587	1.556	1.719	
28	28	1.625-18 UNEF-2A	.315	.637 .587	1.556	1.969	
32	32	1.875-16 UN-2A	.260	.664 .614	1.620	2.219	
36	36	2.125-16 UN-2A	.260	.664 .614	1.620	2.469	.531
40	40	2.375-16 UN-2A	.260	.669 .619	1.620	2.728	.600

1/ When insulator arrangement sizes 18 thru 40 contain one or more size No. 0 contacts, E dimension will increase .150 max.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:19Z
Check the source to verify that this is the current version before use.

TABLE II. DETAIL B DIMENSIONS

SHELL SIZE	A	B	C	D	E	F	G	R
8S	.280 .271	.250 .237	.245 .232	.180 .167	.427 .401	.342 .326	.286 .276	
10S	.340 .332	.312 .299	.298 .285	.242 .229	.420 .397	.335 .322	.272 .262	
10SL	.409 .401	.380 .367	.378 .365	.310 .297	.430 .407	.335 .322	.237 .227	
12 & 12S	.460 .452	.432 .419	.403 .390	.355 .342	.419 .396	.340 .326	.270 .260	
14 & 14S	.563 .550	.518 .505	.485 .472	.448 .435	.414 .391	.339 .326	.261 .251	.040 .020
16 & 16S	.689 .676	.644 .631	.605 .592	.574 .561	.424 .401	.339 .326	.266 .256	.040 .020
18	.806 .793	.760 .747	.725 .712	.690 .677	.574 .551	.449 .436	.371 .361	.060 .040
20	.941 .928	.894 .881	.863 .850	.814 .801	.573 .550	.458 .445	.385 .375	
22	1.059 1.046	.982 .969	.973 .960	.902 .889	.551 .528	.456 .443	.389 .379	
24	1.170 1.157	1.106 1.093	1.085 1.072	1.026 1.013	.547 .524	.457 .444	.385 .375	
28	1.401 1.388	1.330 1.317	1.245 1.232	1.185 1.172	.573 .550	.458 .445	.329 .319	
32	1.652 1.639	1.608 1.595	1.515 1.502	1.440 1.427	.544 .521	.459 .446	.316 .306	
36	1.860 1.847	1.796 1.783	1.751 1.738	1.653 1.640	.573 .550	.463 .450	.355 .345	.060 .040
40	2.105 2.092	2.000 1.989		1.905 1.892	.823 .800		.379 .279	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:19Z
Check the source to verify that this is the current version before use.

REQUIREMENTS

Dimensions and configuration See figure


This plug mates with MIL-C-83723/18, /20, /22, /25 and /26(USAF)

(C) For insert arrangements see MIL-STD-1651

Rear hardware per MIL-C-83723/27, /35, or /50 must be used for correct wire sealing

(C) Insert positions and alternate rotations The letter N indicates normal (or standard) insert position. Alternate positions are identified in MIL-STD-1651

Part number example



Custodian
Air Force - 85

Review activities.
Air Force - 11, 15, 17, 99

Preparing activity
Air Force - 85

(Project 5935-F024-7)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:19Z
Check the source to verify that this is the current version before use.

FOLD

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

POSTAGE AND FEES PAID
DEPARTMENT OF THE AIR FORCE
D-D-318

U.S. MAIL

AFLC/LOIE/Standardization
Wright-Patterson AFB OH 45433

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:19Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval No 22 R25'

INSTRUCTIONS The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government Fold on lines on reverse side, staple in corner, and send to preparing activity Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements Attach any pertinent data which may be of use in improving this document If there are additional papers, attach to form and place both in an envelope addressed to preparing activity

DOCUMENT IDENTIFIER AND TITLE
MIL-C-83723/23C (USAF) Connectors, Electrical (Circular, Envi=

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER ronment Resisting
FSC 5935

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A GIVE PARAGRAPH NUMBER AND WORDING

B RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2 COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED

C16061

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:19Z
Check the source to verify that this is the current version before use.