INCH-POUND
MIL-DTL-83725/7D
25 June 2024
SUPERSEDING
MIL-DTL-83725/7C
13 August 2018

DETAIL SPECIFICATION SHEET

RELAYS, VACUUM, SPST, N/C, 12 AMPERES DC OR 60 Hz RMS, 3.6 KILOVOLTS PEAK

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the relays described herein shall consist of this specification and the latest issue of MIL-DTL-83725.

Inactive for new design after 13 August 2018.





FIGURE 1. Relay, dimensions and configurations.

AMSC N/A FSC 5945

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:25Z
Check the source to verify that this is the current version before use.



CIRCUIT DIAGRAM

Inches	mm	Inches	mm	Inches	mm
.015	0.38	.17	4.32	0.52	13.2
.030	0.76	.24	6.10	0.65	16.5
.04	1.02	.31	7.87	0.875	22.2
.062	1.57	.32	8.13	1.00	25.4
.13	3.30	.34	8.64	1.03	26.2
.141	3.58	.40	10.2	1.13	28.7
				1.70	43.2

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerances are ±.010 (0.25 mm) for three-place decimals and ±.03 (0.8 mm) for two-place decimals.
4. Shape of coil lug (solder) terminals optional; however, they must accommodate two no. 22 AWG wires.
5. Glazed finish on ceramic insulators is optional.

FIGURE 1. Relay, dimensions and configurations - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:25Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Contact data:

Configuration: SPST, N/C, ground isolated.

Arrangement: 1 form B.

Load ratings:

Resistive (carry only):
12 amperes dc or 60 Hz rms.
10 amperes rms, 2.5 MHz.
6 amperes rms, 16 MHz (-001, and -002).
8 amperes rms, 16 MHz (-003).

Rated operating voltage:
3.6 kilovolts peak, 60 Hz or dc.
3.6 kilovolts peak, 2.5 MHz (-001, and -002).
3.2 kilovolts peak, 16 MHz.
4.0 kilovolts peak, 2.5 MHz (-003).

Contact resistance:

Rated Life:

Before: .020 ohm, maximum.

During: .100 ohm, maximum.

After: .100 ohm, maximum.

Capacitance:
1.6 picofarads, maximum across open contacts.
1.6 picofarads, maximum between open contacts and ground.

Coil data:

Duty rating: Continuous.

Maximum voltage: 32 V dc.

Nominal voltage: 26.5 V dc.

Pickup voltage: 22 V dc, maximum over temperature range.

Dropout voltage: 1 V dc, minimum over temperature range.

Coil resistance: 290 ohms ±10 percent.

Operate time: 10 milliseconds, maximum over temperature range (includes contact bounce time).

Release time: 10 milliseconds, maximum over temperature range.

Electrical data:

Insulation resistance: 1,000 megohms, minimum, except the resistance between coil and housing at high temperature shall be 500 megohms or greater.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:25Z
Check the source to verify that this is the current version before use.

Dielectric withstanding voltage:

At atmospheric pressure: 60 Hz.

Between all mated contacts in the open position: 4 kV peak.

Between high voltage terminals and housing: 4 kV peak.

Between coil and housing: 500 V rms, 60 Hz.

Ground isolated: Ground isolated relays have operating elements insulated from the ground plane to provide absolute voltage isolation between the frame and the high voltage contacts.

Environmental data:

Temperature range: -55°C to +125°C.

Vibration: MIL-STD-202-204, test condition C (10-55 Hz, .06 inch DA/55-2000 Hz, 10 g).

Shock: MIL-STD-202-213, test condition J, 30 g, 11 milliseconds, half sine.

Physical:

Terminal strength: 5 pounds pull.

Dimensions and configuration: See figure 1.

Termination: Solder terminal.

Weight: 1 ounce, maximum.

Life test requirements:

Mechanical cycling: 1,000,000 cycles. Two samples units (cycling rate, 36,000 per hour maximum; contact current shall not exceed 10 milliamperes).

Quality assurance:

Dielectric withstanding voltage:

Tests to be conducted at atmospheric pressure rating only.

Duration of application: 5-10 seconds at a 10 percent increase in the dielectric withstanding voltage.

Part number: M83725/7 and dash number from table I.

TABLE I. Part number and characteristics.

Military part number	Mount
M83725/7-001	Sleeve
M83725/7-002	Flange
M83725/7-003	Sleeve

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:25Z
Check the source to verify that this is the current version before use.

Referenced documents. In addition to MIL-DTL-83725, this document references the following:

MIL-STD-202-204 MIL-STD-202-213

Changes from previous issue: The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Custodians:
Army - CR
Navy – AS
Air Force – 85
DLA - CC

Review activity:
Navy - OS

Preparing activity:
DLA - CC

(Project 5945-2024-037)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:25Z
Check the source to verify that this is the current version before use.