The documentation and process conversion measures necessary to comply with this document shall be completed by 10 January 2024.

INCH-POUND

MIL-PRF-19500/436B
W/AMENDMENT 1
10 October 2023
SUPERSEDING
MIL-PRF-19500/436B
11 May 2018

PERFORMANCE SPECIFICATION SHEET

SEMICONDUCTOR DEVICE, DIODE, SILICON, VOLTAGE-VARIABLE CAPACITOR
TYPES 1N5461B THROUGH 1N5476B, AND 1N5461C THROUGH 1N5476C
JAN, JANTX, AND JANTXV

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-19500.

1. SCOPE

1.1 Scope. This specification covers the performance requirements for a silicon, voltage-variable-capacitor diode. Three levels of product assurance (JAN, JANTX, and JANTXV) are provided for each device type.

1.2 Package outlines. The device package outlines are as follows: similar to DO-7 in accordance with figure 1 for all encapsulated device types.

1.3 Ratings and characteristics.

	P_T 1/	$V_{RM(wkg)}$	BV I_R = 10 µA dc	C V_R = 4 V dc f = 1 MHz	Capacitance ratio	Q V_R = 4 V dc f = 50 MHz
	mW	V(pk)	V dc	pF		
Min	---	---	30	(See table II)	(See table II)	(See table II)
Max	400	30	---	(See table II)	---	---

1/ Derate linearly 2.67 mW/°C above 25°C.

OPERATING AMBIENT TEMPERATURE: -65°C TO +175°C
STORAGE TEMPERATURE: -65°C TO +200°C

* Comments, suggestions, or questions on this document should be addressed to DLA Land and Maritime, ATTN: VAC, P.O. Box 3990, Columbus, OH 43218-3990, or emailed to Semiconductor@dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil/.

AMSC N/A

FSC 5961

* DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T01:51Z
Check the source to verify that this is the current version before use.

1.4 Part or Identifying Number (PIN). The PIN is in accordance with MIL-PRF-19500, and as specified herein. See 6.4 for PIN construction example and 6.5 for a list of available PINs.

1.4.1 JAN certification mark and quality level for encapsulated devices. The quality level designators for encapsulated devices that are applicable for this specification sheet from the lowest to the highest level are as follows: “JAN”, “JANTX” and “JANTXV”.

1.4.2 Device type. The designation system for the device types of voltage-variable-capacitor diodes covered by this specification sheet are as follows.


1.4.2.1 First number and first letter symbols. The diodes of this specification sheet use the first number and letter symbols "1N".

1.4.2.2 Second number symbols. The second number symbols for the diodes covered by this specification sheet are as follows: "5461", "5462", "5463", "5464", "5465", "5466", "5467", "5468", "5469", "5470", "5471", "5472", "5473", "5474", "5475", and "5476".

1.4.2.3 Suffix letters. The suffix letter "B" indicates that the voltage-variable-capacitor diode has electrical characteristics as specified in table II. The suffix letter “C” indicates devices with a smaller range of capacitance than the “B” suffix versions as specified in table II.

1.4.3 Lead finish. The lead finishes applicable to this specification sheet are listed on QPDSIS-19500.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T01:51Z
Check the source to verify that this is the current version before use.



Ltr	Dimensions				Notes
	in	in	mm	mm	
	Min	Max	Min	Max	
LD	.018	.022	0.46	0.56	
BD	.078	.107	1.98	2.72	3
BL	.195	.300	4.95	7.62	3
LL	1.00	1.50	25.40	38.10	
LL1	---	.050	---	1.27	4

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Package contour optional within BD and length BL. Heat slugs, if any, shall be included within this cylinder but shall not be subject to minimum limit of BD.
4. Within this zone lead, diameter may vary to allow for lead finishes and irregularities other than heat slugs.

FIGURE 1. Physical dimensions

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T01:51Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-PRF-19500 - Semiconductor Devices, General Specification for.

DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-750 - Test Methods for Semiconductor Devices.

* (Copies of these documents are available online at https://quicksearch.dla.mil).

2.3 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 General. The individual item requirements shall be as specified in MIL-PRF-19500 and as modified herein.

3.2 Qualification. Devices furnished under this specification shall be products that are manufactured by a manufacturer authorized by the qualifying activity for listing on the applicable qualified manufacturer's list (QML-19500) before contract award (see 4.2 and 6.4).

3.3 Abbreviations, symbols, and definitions. Abbreviations, symbols, and definitions used herein shall be as specified in MIL-PRF-19500.

Q.....Quality factor (ratio of reactance to effective resistance)
TCC .....Temperature coefficient of capacitance.

3.4 Interface and physical dimensions. Interface and physical dimensions shall be as specified in MIL-PRF-19500, and on figure 1 (similar to DO-7) herein.

3.4.1 Lead finish. Lead finish shall be solderable in accordance with MIL-STD-750 and MIL-PRF-19500, and herein. Lead finish may be specified in the contract (see 6.2), without affecting the qualified product status of the device or applicable JAN marking.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T01:51Z
Check the source to verify that this is the current version before use.

3.5 Polarity. The polarity shall be indicated with a contrasting color band to denote the cathode end.

3.6 Electrical performance characteristics. Unless otherwise specified herein, the electrical performance characteristics are as specified in 1.3 and table I.

3.7 Electrical test requirements. The electrical test requirements shall be the subgroups specified in table I herein.

3.8 Qualification. Devices furnished under this specification shall be products that are authorized by the qualifying activity for listing on the applicable qualified products list before contract award (see 4.2 and 6.4).

4. VERIFICATION

4.1 Classification of Inspections. The inspection requirements specified herein are classified as follows:

a. Qualification inspection (see 4.2).

b. Screening (see 4.3)

c. Conformance inspection (see 4.4).

4.2 Qualification inspection. Qualification inspection shall be in accordance with MIL-PRF-19500.

4.2.1 Inspection lot. Inspection lot shall be defined in MIL-PRF-19500, except that the lot accumulation period requirements shall be 6 months in lieu of 6 weeks.

* 4.3 Screening (JANTX and JANTXV levels only). Screening shall be in accordance with MIL-PRF-19500 (table E-IV), and as specified herein. The following measurements shall be made in accordance with table I herein. Devices that exceed the limits of table I herein shall not be acceptable.

Screen	Measurements for JANTX, JANTXV levels
2	T_A = +200°C, 48 hours
10	Not applicable
11	$I_{R;}$
12	See 4.3.1
13	Subgroup 2 of table I herein; ΔI_R = 100 percent of initial value or 10 nA dc whichever is greater.

4.3.1 High temperature reverse bias (HTRB). HTRB conditions are as follows: T_A = 150°C, V_R = 25 V dc, t = 96 hours.

4.4 Conformance inspection. Conformance inspection shall be in accordance with MIL-PRF-19500, and as specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T01:51Z
Check the source to verify that this is the current version before use.

4.4.2 Group B inspection. Group B inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-VIB (JAN, JANTX, and JANTXV) of MIL-PRF-19500, and as follows.

Subgroup	Method	Condition
B2	1051	t_{high} = 175°C; 10 cycles
B3	1027	V_R = 25 V dc, T_A = 150°C, t = 500 hrs.
B6	1032	t = 1000 hrs.
B7	----	T_A = -65°C to +85°C, V_R = 4 V dc, n = 22, c = 0; (see 4.4.4).

4.4.3 Group C inspection. Group C inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-VII of MIL-PRF-19500, and as follows.

Subgroup	Method	Condition
C2	2036	Terminal strength: test condition A; 4 lbs, t = 15 sec. Lead fatigue, test cond. E.
C6	1027	V_R = 25 V dc, T_A = 150°C, t = 500 hrs, T_A = 200°".

4.4.4 Temperature coefficient of capacitance. Throughout the temperature range specified the capacitance shall not change by more than .04 %/°C relative to the capacitance value measured at T_A = 25°C. The temperature coefficient of capacitance may be computed by the following formula:

$$TC_C = \frac{C_T\ (+85°C) - C_T\ (-65°C)}{85 + 65} \times \frac{10^2}{C_T\ (25°C)}$$

(Accuracy is limited by the C_T measurement to ± 0.1 pF.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T01:51Z
Check the source to verify that this is the current version before use.

* TABLE I. Group A inspection.

Inspection 1/	MIL-STD-750		Symbol	Limits	Limits	Unit
	Method	Conditions		Min	Max	
Subgroup 1						
Visual and mechanical inspection	2071					
Subgroup 2						
Breakdown voltage	4021	I_R = 10 μA dc	BV_R	30	---	V dc
* Reverse current	4016	Condition A or B; DC method; V_R = 25 V dc	I_{R1}	---	20	nA dc
Subgroup 3						
* Reverse current	4016	Condition A or B; DC method; V_R = 25 V dc T_A = 150°C	I_{R2}	---	20	μA dc
Subgroup 4						
Capacitance	4001	V_R = 4 V dc; f = 1 MHz	C	Col. 3 table II	Col 4 table II	pF
Capacitance ratio	4001	V_R = 2 V dc to V_R = 30 V dc; f = 1 MHz	---	Col 5 table II	Col 6 table II	---
Quality factor	4036	V_R = 4 V dc; f = 50 MHz	Q	Col 7 table II	---	---

1/ For sampling plan, see MIL-PRF-19500.

*

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T01:51Z
Check the source to verify that this is the current version before use.

TABLE II.

Col. 1	Col. 2	Col. 3	Col. 4	Col. 5	Col. 6	Col. 7
Type	Capacitance V_R = 4 V dc	Capacitance V_R = 4 V dc	Capacitance V_R = 4 V dc	Capacitance ratio from V_R = 2 V dc to V_R = 30 V dc	Capacitance ratio from V_R = 2 V dc to V_R = 30 V dc	Q V_R = 4 V dc f = 50 MHz
	Nom.	Min	Max	Min	Max	Min
	pF	pF	pF			
1N5461B	6.8	6.46	7.14	2.7	3.1	600
1N5462B	8.2	7.79	8.61	2.8	3.1	600
1N5463B	10.0	9.5	10.5	2.8	3.1	550
1N5464B	12.0	11.4	12.6	2.8	3.1	550
1N5465B	15.0	14.25	15.75	2.8	3.1	550
1N5466B	18.0	17.1	18.9	2.9	3.1	500
1N5467B	20.0	19.0	21.0	2.9	3.1	500
1N5468B	22.0	20.9	23.1	2.9	3.2	500
1N5469B	27.0	25.65	28.35	2.9	3.2	500
1N5470B	33.0	31.35	34.65	2.9	3.2	500
1N5471B	39.0	37.05	40.95	2.9	3.2	450
1N5472B	47.0	44.65	49.35	2.9	3.2	400
1N5473B	56.0	53.2	58.8	2.9	3.3	300
1N5474B	68.0	64.6	71.4	2.9	3.3	250
1N5475B	82.0	77.9	86.1	2.9	3.3	225
1N5476B	100.0	95.0	105.0	2.9	3.3	200
1N5461C	6.8	6.66	6.94	2.7	3.1	600
1N5462C	8.2	8.04	8.36	2.8	3.1	600
1N5463C	10.0	9.8	10.2	2.8	3.1	550
1N5464C	12.0	11.76	12.24	2.8	3.1	550
1N5465C	15.0	14.7	15.3	2.8	3.1	550
1N5466C	18.0	17.64	18.36	2.9	3.1	500
1N5467C	20.0	19.60	20.4	2.9	3.1	500
1N5468C	22.0	21.56	22.44	2.9	3.2	500
1N5469C	27.0	26.46	27.54	2.9	3.2	500
1N5470C	33.0	32.34	33.66	2.9	3.2	500
1N5471C	39.0	38.22	39.78	2.9	3.2	450
1N5472C	47.0	46.06	47.94	2.9	3.2	400
1N5473C	56.0	54.88	57.12	2.9	3.3	300
1N5474C	68.0	66.64	69.36	2.9	3.3	250
1N5475C	82.0	80.36	83.64	2.9	3.3	225
1N5476C	100.0	98.0	102.00	2.9	3.3	200

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T01:51Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the Military Service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory. The notes specified in MIL-PRF-19500 are applicable to this specification.)

6.1 Intended use. Semiconductors conforming to this specification are intended for original equipment design applications and logistic support of existing equipment.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. Packaging requirements (see 5.1).


c. Lead finish (see 3.4.1).

d. The complete PIN, see 1.4 and 6.5.

6.3 Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time of award of contract, qualified for inclusion in Qualified Manufacturers List (QPDSIS-19500) whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. Information pertaining to qualification of products may be obtained from DLA Land and Maritime, ATTN: VQE, P.O. Box 3990, Columbus, OH 43218-3990 or e-mail vqe.chief@dla.mil. An online listing of products qualified to this specification may be found in the Qualified Products Database (QPD) at https://assist.dla.mil/.

6.4 PIN construction example.

6.4.1 Encapsulated devices The PINs for encapsulated devices are constructed using the following form.



Source: https://assist.dla.mil -- Downloaded: 2026-10-19T01:51Z
Check the source to verify that this is the current version before use.

6.5 List of PINs.

6.5.1 List of PINs for encapsulated devices. The following is a list of possible PINs for encapsulated devices available on this specification sheet for the “B” suffix. Replace “B” with “C” for “C” suffix part numbers.

PINs for devices of the base quality level	PINs for devices of the "TX" quality level	PINs for devices of the "TXV" quality level
JAN1N5461B	JANTX1N5461B	JANTXV1N5461B
JAN1N5462B	JANTX1N5462B	JANTXV1N5462B
JAN1N5463B	JANTX1N5463B	JANTXV1N5463B
JAN1N5464B	JANTX1N5464B	JANTXV1N5464B
JAN1N5465B	JANTX1N5465B	JANTXV1N5465B
JAN1N5466B	JANTX1N5466B	JANTXV1N5466B
JAN1N5467B	JANTX1N5467B	JANTXV1N5467B
JAN1N5468B	JANTX1N5468B	JANTXV1N5468B
JAN1N5469B	JANTX1N5469B	JANTXV1N5469B
JAN1N5470B	JANTX1N5470B	JANTXV1N5470B
JAN1N5471B	JANTX1N5471B	JANTXV1N5471B
JAN1N5472B	JANTX1N5472B	JANTXV1N5472B
JAN1N5473B	JANTX1N5473B	JANTXV1N5473B
JAN1N5474B	JANTX1N5474B	JANTXV1N5474B
JAN1N5475B	JANTX1N5475B	JANTXV1N5475B
JAN1N5476B	JANTX1N5476B	JANTXV1N5476B

* 6.6 Amendment notations. The margins of this specification are marked with asterisks to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Air Force - 85
DLA - CC

Review activity:
Air Force - 19

Preparing activity:
DLA - CC

(Project 5961-2023-076)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T01:51Z
Check the source to verify that this is the current version before use.