The documentation and process conversion measures necessary to comply with this revision shall be completed by 11 January 2013.

INCH-POUND

MIL–PRF–19500/472F
10 October 2012
SUPERSEDING
MIL–PRF–19500/472E
9 October 2007

PERFORMANCE SPECIFICATION SHEET

SEMICONDUCTOR DEVICE, TRANSISTOR, NPN, SILICON, POWER DARLINGTON, TYPES 2N6350, 2N6351, 2N6352, AND 2N6353, JAN, JANTX, JANTXV, AND JANHC

Inactive for new design after 7 June 1999

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL–PRF–19500.

1. SCOPE

1.1 Scope. This specification covers the performance requirements for NPN silicon power Darlington transistors. Three levels of product assurance are provided for each encapsulated device type as specified in MIL–PRF–19500. One level of product assurance is provided for each unencapsulated device type as specified in MIL–PRF–19500.

1.2 Physical dimensions. The device package styles are as follows: 4-pin TO–33 in accordance with figure 1 for device types 2N6350 and 2N6351, 3-pin TO–66 in accordance with figure 2 for device types 2N6352 and 2N6353, and unencapsulated die in accordance with figure 3 for device type JANHC.

1.3 Maximum ratings. Unless otherwise specified, T_A = +25°C.

Types	P_T		$R_{\theta JC}$ Max	V_{EB1}	V_{EB2}	V_{CBO1} and V_{CER}	I_C	I_C (1)	I_{B1}	T_J and T_{STG}
	T_A = +25°C	T_C = +100°C								
	W	W	°C/W	V dc	V dc	V dc	A dc	A dc	A dc	°C
2N6350	1.0 (2)	5 (3)	20	12	6	80	5	10	0.5	–65 to +200
2N6351	1.0 (2)	5 (3)	20	12	6	150	5	10	0.5	–65 to +200
2N6352	2.0 (4)	25 (5)	4.0	12	6	80	5	10	0.5	–65 to +200
2N6353	2.0 (4)	25 (5)	4.0	12	6	150	5	10	0.5	–65 to +200

(1) Applies for $t_p \leq 10$ ms, duty cycle ≤ 50 percent.
(2) Derate linearly 5.72 mW/°C for T_A > +25°C.
(3) Derate linearly 50 mW/°C for T_C > +100°C.
(4) Derate linearly 11.4 mW/°C for T_A > +25°C.
(5) Derate linearly 250 mW/°C for T_C > +100°C.

Comments, suggestions, or questions on this document should be addressed to DLA Land and Maritime ATTN: VAC, P.O. Box 3990, Columbus, OH 43218–3990, or emailed to semiconductor@dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:17Z
Check the source to verify that this is the current version before use.

1.4 Primary electrical characteristics. Unless otherwise specified, T_A = +25°C.

Limits	h_{FE} (1) V_{CE} = 5 V dc, I_C = 5 A dc		$\|h_{fe}\|$ (1) V_{CE} = 10 V dc, I_C = 1 A dc, f = 10 MHz	$V_{BE(ON)1}$ V_{CE} = 5 V dc, I_C = 5 A dc	C_{OBO} V_{CB1} = 10 V dc, 100 kHz ≤ f ≤ 1 MHz, base 2 open
	2N6350, 2N6352	2N6351, 2N6353			
				V dc	pF
Min	2,000	1,000	5		
Max	10,000	10,000	25	2.5	120

Limits	$V_{CE(SAT)}$		Pulse response (2)	
	R_{B2E} = 100 Ω, I_C = 5 A dc, I_{B1} = 5 mA dc	R_{B2E} = 100 Ω, I_C = 5 A dc, I_{B1} = 10 mA dc	V_{CC} = 30 V dc, I_C = 5 A dc	
	2N6350, 2N6352	2N6351, 2N6353	t_{on}	t_{off}
	V dc	V dc	µs	µs
Min				
Max	1.5	2.5	0.5	1.2

(1) Pulsed (see 4.5.1).
(2) See figures 4 and 5 for pulse response circuits.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3, 4, or 5 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3, 4, or 5 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL–PRF–19500 – Semiconductor Devices, General Specification for.


DEPARTMENT OF DEFENSE STANDARDS


MIL–STD–750 – Test Methods for Semiconductor Devices.

(Copies of these documents are available online at https://assist.dla.mil/quicksearch or https://assist.dla.mil or from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111–5094.)

2.3 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:17Z
Check the source to verify that this is the current version before use.





SCHEMATIC CIRCUIT

FIGURE 1. Physical dimensions (TO–33) and schematic circuit for 2N6350 and 2N6351.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:17Z
Check the source to verify that this is the current version before use.

Symbol	Dimensions				Notes
	Inches		Millimeters		
	Min	Max	Min	Max	
CD	.305	.335	7.75	8.51	3
CH	.184	.260	4.67	6.60	
HD	.335	.370	8.51	9.40	
LC	0.200 TP		5.080 TP		4
LD	.016	.021	0.407	0.533	5, 6
LL	1.500	1.750	38.10	44.45	5, 6
L_1		.050		1.27	5, 6
L_2	.250		6.35		5, 6
LU	.016	.019	0.407	0.482	5, 6
TL	.029	.045	0.74	1.14	7
TW	.028	.034	0.712	0.863	8
P	.100		2.54		3
Q		.050		1.27	9
r		.010		0.254	10
α	45° TP		45° TP		4

NOTES:

1. Dimensions are in inches. Millimeters are given for general information only.
2. Internal resistance (typically 750 ohms). This resistor is optional.
3. Dimension CD shall not vary more than .010 inch (0.25 mm) in zone P. This zone is controlled for automatic handling.
4. Leads at gauge plane .054 +.001 –.000 inch (1.37 +0.03 –0.00 mm) below seating plane shall be within .007 inch (0.18 mm) radius of true position (TP) at maximum material condition (MMC) relative to tab at MMC. The device may be measured by direct methods.
5. Dimension LU applies between dimension L_1 and dimension L_2. Dimension LD applies between L_2 and LL minimum. Diameter is uncontrolled in dimension L_1 and beyond dimension LL minimum.
6. All terminals.
7. Dimension TL measured from maximum HD.
8. Beyond r (radius) maximum, dimension TW shall be held for a minimum length of .011 inch (0.28 mm).
9. Outline in this zone is not controlled.
10. The radius (dimension r) applies to both inside corners of the tab.
11. Terminal designation is as follows: 1 – emitter, 2 – base (B2), 3 – base (B1), 4 – collector. The collector shall be connected to the case.
12. In accordance with ASME Y14.5M, diameters are equivalent to ϕx symbology.

FIGURE 1. Physical dimensions (TO–33) and schematic circuit for 2N6350 and 2N6351 – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:17Z
Check the source to verify that this is the current version before use.




FIGURE 2. Physical dimensions (3-pin TO–66) and schematic circuit for 2N6352 and 2N6353.


Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:17Z
Check the source to verify that this is the current version before use.

Symbol	Dimensions				Notes
	Inches		Millimeters		
	Min	Max	Min	Max	
CD		.620		15.75	
CH	.250	.340	6.35	8.64	
HT	.050	.075	1.27	1.91	3
HR		.350		8.89	
HR_1	.115	.145	2.92	3.68	
LD	.028	.034	0.711	0.863	4
LL	.360	.500	9.14	12.70	4
L_1		.050		1.27	4
MHD	.142	.152	3.61	3.86	
MHS	.958	.962	24.33	24.43	
PS	.190	.210	4.83	5.33	
PS_1	.093	.105	2.36	2.67	
S	.570	.590	14.48	14.99	
T	.190	.210	4.83	5.33	

NOTES:
1. Dimensions are in inches. Millimeters are given for general information only.
2. Internal resistance (typically 750 ohms). This resistor is optional.
3. The outline contour is optional.
4. Dimension does not include sealing flanges.
5. All leads.
6. Terminal designation is as follows: 1 – emitter, 2 – base (B_1), 3 – base (B_2). The collector shall be connected to the case.
7. Shape of capweld flange is optional and cannot extend beyond dimension HR.
8. In accordance with ASME Y14.5M, diameters are equivalent to ϕx symbology.

FIGURE 2. Physical dimensions (3-pin TO–66) and schematic circuit for 2N6352 and 2N6353 – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:17Z
Check the source to verify that this is the current version before use.



NOTES:

1. Chip size: .087 x .100 inch ±.002 inch (2.2098 x 2.54 ±0.0508 mm).
2. Chip thickness: .010 ±.0015 inch (0.254 ±0.0381 mm) nominal.
3. Top metal: Aluminum 30,000Å minimum, 33,000Å nominal.
4. Back metal: A. Al / Ti / Ni / Ag: 12kÅ / 3kÅ / 7kÅ / 7kÅ minimum, 15kÅ / 5kÅ / 10kÅ / 10kÅ nominal.
   B. Gold: 2,500Å minimum, 3,000Å nominal.
5. Backside: Collector.
6. Bonding pad: B_1 = .016 x .014 inch (0.4064 x 0.3556 mm),
   B_2 = .016 x .018 inch (0.4064 x 0.4572 mm),
   and E = .040 x .008 inch (1.016 x 0.2032 mm).

FIGURE 3. Physical dimensions for die JANHC (A-version).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:17Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 General. The individual item requirements shall be as specified in MIL–PRF–19500 and as modified herein.

3.2 Qualification. Devices furnished under this specification shall be products that are manufactured by a manufacturer authorized by the qualifying activity for listing on the applicable qualified manufacturer's list (QML) before contract award (see 4.2 and 6.3).

3.3 Abbreviations, symbols, and definitions. The abbreviations, symbols, and definitions used herein shall be as specified in MIL–PRF–19500.

I_M = The measurement current applied to forward bias the junction for measurement of V_{BE}.
I_H = The collector current applied to the device under test during the heating period.
t_H = The duration of the applied heating power pulse.
t_{SW} = Sample window time during which final V_{BE} measurement is made.

3.4 Interface requirements and physical dimensions. The interface requirements and physical dimensions shall be as specified in MIL–PRF–19500 and figure 1 (TO–33) for device types 2N6350 and 2N6351, figure 2 (3-pin TO–66) for device types 2N6352 and 2N6353, and figure 3 for unencapsulated die JANHC herein.

3.4.1 Lead finish. Unless otherwise specified, lead finish shall be solderable in accordance with MIL–STD–750, MIL–PRF–19500, and herein. Where a choice of lead finish or formation is desired, it shall be specified in the acquisition document (see 6.2).

3.4.2 Polarity. The polarity of the device types shall be as shown on figures 1, 2, and 3. For device types 2N6350 and 2N6351 (TO–33), terminal 1 is the emitter, terminal 2 is base (B_2), terminal 3 is base (B_1), and terminal 4 is the collector. The collector shall be also electrically connected to the case. For device types 2N6352 and 2N6353 (3 pin TO–66), terminal 1 is the emitter, terminal 2 is base (B_1), terminal 3 is base (B_2), and the collector shall be electrically connected to the case. The connections for unencapsulated die shall be as depicted on figure 3.

3.5 Marking. Marking shall be in accordance with MIL–PRF–19500.

3.6 Electrical performance characteristics. Unless otherwise specified herein, the electrical performance characteristics are as specified in 1.3, 1.4, and table I herein.

3.7 Electrical test requirements. The electrical test requirements shall be as specified in table I.

3.8 Workmanship. Semiconductor devices shall be processed in such a manner as to be uniform in quality and shall be free from other defects that will affect life, serviceability, or appearance.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. Qualification inspection (see 4.2).

b. Screening (see 4.3).

c. Conformance inspection (see 4.4 and tables I and II).

4.2 Qualification inspection. Qualification inspection shall be in accordance with MIL–PRF–19500, and as specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:17Z
Check the source to verify that this is the current version before use.

4.2.1 Qualification of unencapsulated die. Qualification inspection for unencapsulated die shall be in accordance with appendix G of MIL–PRF–19500.

4.2.2 Group E qualification. Group E inspection shall be performed for qualification or re-qualification only. In case qualification was awarded to a prior revision of the specification sheet that did not request the performance of table II tests, the tests specified in table II herein that were not performed in the prior revision shall be performed on the first inspection lot of this revision to maintain qualification.

4.3 Screening.

4.3.1 Screening of packaged devices (JANTX and JANTXV levels only). Screening of packaged devices shall be in accordance with table E–IV of MIL–PRF–19500, and as specified herein. The following measurements shall be made in accordance with table I herein. Devices that exceed the limits of table I herein shall not be acceptable.

Screen (see table E–IV of MIL–PRF–19500)	Measurement
	JANTX and JANTXV levels only
3c (1)	Thermal impedance, see 4.3.1.1
11	I_{CEX1} and h_{FE1}
12	See 4.3.1.2
13	See table I, subgroup 2 herein ΔI_{CEX1} = ±100 percent of initial value or 20 nA dc, whichever is greater Δh_{FE1} = ±25 percent of initial value

(1) This test shall be performed anytime after temperature cycling, screen 3a, and does not need to be repeated in screening requirements.

4.3.1.1 Thermal impedance. The thermal impedance measurements shall be performed in accordance with test method 3131 of MIL–STD–750 using the guidelines in that test method for determining I_M, I_H, t_H, t_{SW}, (and V_H where appropriate). Measurement delay time (t_{MD}) = 70 μs maximum. The thermal impedance limit used in screen 3c and table I, subgroup 2 herein shall be set statistically by the supplier. See table II, subgroup 4 herein.

4.3.1.2 Power burn-in conditions. Power burn-in conditions shall be as follows: T_A = +25°C; power shall be applied to achieve T_J = +135°C minimum and power dissipation of P_D ≥ 75 percent of maximum rated P_T as defined in 1.3. The following details shall apply:

a. V_{CE} = 60 V dc for device types 2N6350 and 2N6352.

b. V_{CE} = 100 V dc for device types 2N6351 and 2N6353.

4.3.2 Screening of unencapsulated die (JANHC). Screening of JANHC unencapsulated die shall be in accordance with appendix G of MIL–PRF–19500. The burn-in duration for JANHC level shall follow the JANTX requirements of table E–IV of MIL–PRF–19500.

4.4 Conformance inspection. Conformance inspection shall be in accordance with MIL–PRF–19500, and as specified herein.

4.4.1 Group A inspection. Group A inspection shall be conducted in accordance with table E–V of MIL–PRF–19500 and table I herein. Electrical measurements (end-points) shall be in accordance with table I, subgroup 2 herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:17Z
Check the source to verify that this is the current version before use.

4.4.2 Group B inspection. Group B inspection shall be conducted in accordance with the tests and conditions specified for subgroup testing in table E–VIB (JAN, JANTX, and JANTXV) of MIL–PRF–19500 and as follows herein. Electrical measurements (end-points) shall be in accordance with table I, subgroup 2 herein. Delta requirements shall be in accordance with the applicable step of 4.6 herein.

Subgroup	Method	Conditions
B3	1027	For 2N6350 and 2N6352; V_{CE} = +40 V dc. For 2N6351 and 2N6353; V_{CE} = +100 V dc. Power shall be applied to achieve T_J = +150°C minimum and power dissipation of $P_D \geq 75$ percent of maximum rated P_T as defined in 1.3.

4.4.3 Group C inspection. Group C inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E–VII of MIL–PRF–19500 and as follows herein. Electrical measurements (end-points) shall be in accordance with table I, subgroup 2 herein.

Subgroup	Method	Conditions
C2	2036	Test condition E for 2N6350 and 2N6351. Test condition A for 2N6352 and 2N6353, weight = 3 lbs (1.36 Kg), t = 15s.
C5	3131	Base 1 shorted to base 2 (see 1.3).
C6	1026	For 2N6350 and 2N6352; V_{CE} = +40 V dc. For 2N6351 and 2N6353; V_{CE} = +100 V dc. Power shall be applied to achieve T_J = +150°C minimum and power dissipation of $P_D \geq 75$ percent of maximum rated P_T as defined in 1.3.

4.4.4 Group E inspection. Group E inspection shall be conducted in accordance with the conditions specified for subgroup testing in appendix E, table E–IX of MIL–PRF–19500 and as specified in table II herein. Electrical measurements (end-points) shall be in accordance with table I, subgroup 2 herein. Delta requirements shall be in accordance with the applicable step of 4.6 herein.

4.5 Method of inspection. Methods of inspection shall be as specified in the appropriate tables and as follows.

4.5.1 Pulse response measurements. Conditions for pulse response measurement shall be as specified in section 4 of MIL–STD–750.

4.6 Delta requirements. The delta requirements for group B inspection shall be as specified below. (1) (2)

Step	Inspection	MIL–STD–750		Symbol	Limit
		Method	Conditions		
1	Forward-current transfer ratio	3076	V_{CE} = 5 V dc; I_C = 5.0 A dc; pulsed see 4.5.1, R_{B2E} = 100 ohm	Δh_{FE2}	±25 percent change from initial reading.

(1) The delta measurements for group B, product assurance levels JAN, JANTX, and JANTXV shall be as follows: In addition to the measurements specified for subgroup 3 of table E–VIB of MIL–PRF–19500, the measurements of step 1 herein shall also be taken.
(2) The delta measurements for group E shall be as follows: In addition to the measurements specified for subgroups 1 and 2 of table E–IX of MIL–PRF–19500, the measurements of step 1 herein shall also be taken.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:17Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection.

Inspection 1/	MIL–STD–750		Symbol	Limit		Unit
	Method	Conditions		Min	Max	
Subgroup 1						
Visual and mechanical examination	2071					
Subgroup 2						
Thermal impedance 2/	3131	See 4.3.1	$Z_{\theta JX}$			°C/W
Collector to emitter breakdown voltage	3011	Bias condition B, I_C = 25 mA dc; pulsed (see 4.5.1); R_{B1E} = 2.2 k ohm; R_{B2E} = 100 ohms	$V_{(BR)CER}$			
2N6350, 2N6352				80		V dc
2N6351, 2N6353				150		V dc
Emitter to base 1, breakdown voltage	3026	Bias condition D, I_E = 12 mA dc; base 2 open	$V_{(BR)EBO1}$	12		V dc
Emitter to base 2, breakdown voltage	3026	Bias condition D, I_E = 12 mA dc; base 1 open	$V_{(BR)EBO2}$	6		V dc
Collector to emitter cutoff current	3041	Bias condition A, V_{EB1} = 2 V dc; R_{B2E} = 100 ohms	I_{CEX1}			
2N6350, 2N6352		V_{CE} = 80 V dc			1.0	µA dc
2N6351, 2N6353		V_{CE} = 150 V dc			1.0	µA dc
Saturation voltage and resistance	3071	I_C = 5.0 A dc; R_{B2E} = 100 ohms	$V_{CE(sat)1}$			
2N6350, 2N6352		I_B = 5 mA dc; pulsed (see 4.5.1)			1.5	V dc
2N6351, 2N6353		I_B = 10 mA dc; pulsed (see 4.5.1)			2.5	V dc
Base emitter voltage (nonsaturated)	3066	V_{CE} = 5 V dc; I_C = 5.0 A dc; pulsed (see 4.5.1); R_{B2E} = 100 ohms	$V_{BE(on)1}$		2.5	V dc
Forward-current transfer ratio	3076	V_{CE} = 5 V dc; I_C = 1.0 A dc; pulsed (see 4.5.1); R_{B2E} = 1 k ohms	h_{FE1}			
2N6350, 2N6352				2,000		
2N6351, 2N6353				1,000		

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:17Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection – Continued.

Inspection 1/	MIL–STD–750		Symbol	Limit		Unit
	Method	Conditions		Min	Max	
Subgroup 2 – Continued.						
Forward-current transfer rato	3076	V_{CE} = 5 V dc; I_C = 5.0 A dc; pulsed (see 4.5.1); R_{B2E} = 100 ohms	h_{FE2}			
2N6350, 2N6352				2,000	10,000	
2N6351, 2N6353				1,000	10,000	
Forward-current transfer ratio	3076	V_{CE} = 5 V dc; I_C = 10 A dc; pulsed (see 4.5.1); R_{B2E} = 100 ohms	h_{FE3}			
2N6350, 2N6352				400		
2N6351, 2N6353				200		
Subgroup 3						
High temperature operation:		T_A = +150°C				
Collector to emitter cutoff current	3041	Bias condition A, V_{EB1} = 2 V dc; R_{B2E} = 100 ohms	I_{CEX2}			
2N6350, 2N6352		V_{CE} = 80 V dc			1.0	mA dc
2N6351, 2N6353		V_{CE} = 150 V dc			1.0	mA dc
Low temperature operation:		T_A = –65°C				
Forward-current transfer ratio	3076	V_{CE} = 5 V dc; I_C = 5.0 A dc; pulsed (see 4.5.1); R_{B2E} = 100 ohms	h_{FE4}			
2N6350, 2N6352				400		
2N6351, 2N6353				200		
Subgroup 4						
Small-signal, short-circuit forward-current transfer ratio	3306	V_{CE} = 10 V dc; I_C = 1.0 A dc; f = 10 MHz; R_{B2E} = 100 ohms	$\|h_{fe}\|$	5	25	
Open-circuit output capacitance	3236	V_{CB1} = 10 V dc; 100 kHz ≤ f ≤ 1 MHz; base 2 open	C_{obo}		120	pF

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:17Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection – Continued.

Inspection 1/	MIL–STD–750		Symbol	Limit		Unit
	Method	Conditions		Min	Max	
Subgroup 4 – Continued.						
Pulse response						
Turn-on time	3251	Test condition A, V_{CC} = 30 V dc; I_C = 5.0 A dc	t_{on}			
2N6350, 2N6352		See figure 4			0.5	µs
2N6351, 2N6353		See figure 5			0.5	µs
Turn-off time	3251	Test condition A, V_{CC} = 30 V dc; I_C = 5.0 A dc	t_{off}			
2N6350, 2N6352		See figure 4			1.2	µs
2N6351, 2N6353		See figure 5			1.2	µs
Subgroup 5						
Safe operating area (continuous dc) (for types 2N6350 and 2N6351 only)	3051	T_C = +100°C; t ≥ 1.0 s, 1 cycle; $t_r + t_f$ = 10 µs (see figure 6); R_{B2E} = 100 ohms				
Test 1						
(2N6350, 2N6351)		V_{CE} = 1.5 V dc; I_C = 3.3 A dc				
Test 2						
(2N6350, 2N6351)		V_{CE} = 30 V dc; I_C = 167 mA dc				
Test 3						
(2N6350)		V_{CE} = 80 V dc; I_C = 35 mA dc				
Test 4						
(2N6351)		V_{CE} = 150 V dc; I_C = 13 mA dc				

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:17Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection – Continued.

Inspection 1/	MIL–STD–750		Symbol	Limit		Unit
	Method	Conditions		Min	Max	
Subgroup 5 – Continued.						
Safe operating area (continuous dc) (for types 2N6352 and 2N6353 only)	3051	T_C = +100°C; t ≥ 1.0 s, 1 cycle; $t_r + t_f$ = 10 μs (see figure 7); R_{B2E} = 100 ohms				
Test 1 (2N6352, 2N6353)		V_{CE} = 5.0 V dc; I_C = 5 A dc				
Test 2 (2N6352, 2N6353)		V_{CE} = 10 V dc; I_C = 2.5 A dc				
Test 3 (2N6352)		V_{CE} = 80 V dc; I_C = 95 mA dc				
Test 4 (2N6353)		V_{CE} = 150 V dc; I_C = 35 mA dc				
Electrical measurements		See subgroup 2 of table I				
Safe operating area (switching)	3053	Load condition B (clamped inductive load) see figure 8; T_A = + 100°C; $t_r + t_f$ ≤ 1.0 μs; duty cycle ≤ 2 percent; t_p = 8 ms (vary to obtain I_C); R_s = 0.1 Ω; R_{BB1} = 200 Ω; V_{BB1} = 10 V dc; R_{BB2} = 2.2 kΩ; V_{BB2} = –4 V dc; I_C = 5 A dc; V_{CC} = 25 V dc; R_L ≤ 2.5 Ω; L = 40 mH (Triad c-48U, or equivalent); R_{B2E} = 100 Ω				
2N6350, 2N6352 2N6351, 2N6353		Clamp voltage = 50 +0, –5 V dc Clamp voltage = 90 +0, –5 V dc				
Electrical measurements		See subgroup 2 of table I				


1/ For sampling plan, see MIL–PRF–19500.
2/ This test required for the following end-point measurements only:
Group B, subgroups 2 and 3 (JAN, JANTX, and JANTXV).
Group C, subgroup 2 and 6.
Group E, subgroup 1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:17Z
Check the source to verify that this is the current version before use.

TABLE II. Group E inspection (all quality levels) – for qualification and requalification only.

Inspection	MIL–STD–750		Sample plan
	Method	Conditions	
Subgroup 1			45 devices c = 0
Temperature cycling (air to air)	1051	Test condition C, 500 cycles.	
Hermetic seal Fine leak Gross leak	1071		
End-point electrical measurements		See table I, subgroup 2 and 4.6 herein.	
Subgroup 2			45 devices c = 0
Intermittent operation life	1037	V_{CB} = 10 V dc, 6,000 cycles.	
End-point electrical measurements		See table I, subgroup 2 and 4.6 herein.	
Subgroup 4			Sample size N/A
Thermal impedance curves		See MIL–PRF–19500.	
Subgroup 6			11 devices
Electrostatic discharge sensitivity	1020	Testing not required for devices listed as class 3. Testing required for non-sensitive listing to prove capability.	
Subgroup 8			45 devices c = 0
Reverse voltage leakage stability	1033	Condition B.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:17Z
Check the source to verify that this is the current version before use.




NOTES:

1. The input waveform is supplied by a pulse generator with the following characteristics: $t_r \leq 15$ ns, $t_f \leq 15$ ns, $Z_{OUT} = 50$ ohms, PW = 10 μs, duty cycle ≤ 2 percent.
2. Output waveforms are monitored on an oscilloscope with the following characteristics: $t_r \leq 15$ ns, $Z_{IN} \geq 10$ MΩ, $C_{IN} \leq 11.5$ pf.
3. Resistors shall be non-inductive types.
4. The dc power supplies may require additional by-passing in order to minimize ringing.

FIGURE 4. Pulse response test circuit for device types 2N6350 and 2N6352.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:17Z
Check the source to verify that this is the current version before use.



NOTES:

1. The input waveform is supplied by a pulse generator with the following characteristics: $t_f \leq 15$ ns, $Z_{OUT} = 50\ \Omega$, PW = 10 μs, duty cycle ≤ 2 percent.
2. Output waveforms are monitored on an oscilloscope with the following characteristics: $t_r \leq 15$ ns, $Z_{IN} \geq 10\ M\Omega$, $C_{in} \leq 11.5$ pf.
3. Resistors shall be non-inductive types.
4. The dc power supplies may require additional by-passing in order to minimize ringing.

FIGURE 5. Pulse response test circuit for device types 2N6351 and 2N6353.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:17Z
Check the source to verify that this is the current version before use.




FIGURE 6. Maximum safe operating area graph for device types 2N6350 and 2N6351.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:17Z
Check the source to verify that this is the current version before use.




FIGURE 7. Maximum safe operating area graph for device types 2N6352 and 2N6353.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:17Z
Check the source to verify that this is the current version before use.




FIGURE 8. Safe operating area for switching between saturation and cutoff – (clamped inductive load).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:17Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the Military Service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory. The notes specified in MIL–PRF–19500 are applicable to this specification.)

6.1 Intended use. Semiconductors conforming to this specification are intended for original equipment design applications and logistic support of existing equipment.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. Packaging requirements (see 5.1).

c. Lead finish (see 3.4.1).

d. Quality level and type designator.

6.3 Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time of award of contract, qualified for inclusion in Qualified Manufacturers List (QML 19500) whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. Information pertaining to qualification of products may be obtained from DLA Land and Maritime, ATTN: VQE, P.O. Box 3990, Columbus, OH 43218–3990 or e-mail vqe.chief@dla.mil. An online listing of products qualified to this specification may be found in the Qualified Products Database (QPD) at https://assist.dla.mil.

6.4 Suppliers of JANHC die. The qualified die suppliers with the applicable letter version (example, JANHCA2N6350) will be identified on the QML.

JANC ordering information	
Device type	Manufacturer
	43611
2N6350	JANHCA2N6350

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:17Z
Check the source to verify that this is the current version before use.

6.5 Changes from previous issue. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army – CR
Navy – EC
Air Force – 99
NASA – NA
DLA – CC

Review activities:
Army – AV

Preparing activity:
DLA – CC

(Project 5961–2012–037)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:17Z
Check the source to verify that this is the current version before use.