The documentation and process conversion measures necessary to comply with this amendment shall be completed by 9 March 2017.

INCH–POUND

MIL-PRF-19500/502H
w/AMENDMENT 1
9 December 2016
SUPERSEDING
MIL-PRF-19500/502H
22 March 2016

PERFORMANCE SPECIFICATION SHEET

TRANSISTOR, DARLINGTON, NPN, SILICON, POWER,
ENCAPSULATED (THROUGH-HOLE MOUNT PACKAGE)
TYPES 2N6058 AND 2N6059, QUALITY LEVELS JAN, JANTX, AND JANTXV

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-19500.

1. SCOPE

1.1 Scope. This specification covers the performance requirements for NPN silicon power Darlington transistors. Three levels of product assurance are (JAN, JANTX, and JANTXV) provided for each encapsulated device.

1.2 Package outlines. The device package outlines are as follows: TO-204AA (similar to TO-3) in accordance with figure 1 for all encapsulated device types.

1.3 Maximum ratings. Unless otherwise specified, T_C = +25°C.

Types	P_T		V_{CBO}	V_{CEO}	V_{EBO}	I_C	I_B	T_J and T_{STG}
	T_C = +25°C (1)	T_C = +100°C						
	W	W	V dc	V dc	V dc	A dc	A dc	°C
2N6058	150	75	80	80	5	12	0.2	-55 to +175
2N6059	150	75	100	100	5	12	0.2	-55 to +175

(1) Derate linearly at 1.00 W/°C above T_C > +25°C.

Comments, suggestions, or questions on this document should be addressed to DLA Land and Maritime ATTN: VAC, P.O. Box 3990, Columbus, OH 43218-3990, or emailed to semiconductor@dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil/.

AMSC N/A

FSC 5961

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:30Z
Check the source to verify that this is the current version before use.

1.4 Primary electrical characteristics. Unless otherwise specified, T_C = +25°C.

Limit	h_{FE2} (1) V_{CE} = 3 V dc I_C = 6 A dc	h_{FE3} (1) V_{CE} = 3 V dc I_C = 12 A dc	h_{fe} V_{CE} = 3 V dc I_C = 5 A dc f = 1 kHz	$\|h_{fe}\|$ V_{CE} = 3 V dc I_C = 5 A dc f = 1 MHz	C_{obo} 100 kHz ≤ f ≤ 1 MHz V_{CB} = 10 V dc I_E = 0	$R_{\theta JC}$
					pF	°C/W
Minimum	1,000	150	1,000	10		
Maximum	18,000			250	300	1.0

Limit	$V_{BE(sat)}$ (1) I_C = 12 A dc I_B = 120 mA dc	$V_{CE(sat)1}$ (1) I_C = 12 A dc I_B = 120 mA dc	$V_{CE(sat)2}$ (1) I_C = 6 A dc I_B = 24 mA dc	Pulse response (2)	
				t_{on}	t_{off}
	V dc	V dc	V dc	µs	µs
Minimum					
Maximum	4.0	3.0	2.0	2	10

(1) Pulsed (see 4.5.1).
(2) See figure 2 for pulse response circuits.

1.5 Part or Identifying Number (PIN). The PIN is in accordance with MIL-PRF-19500, and as specified herein. See 6.4 for PIN construction example and 6.5 for a list of available PINs.

1.5.1 JAN certification mark and quality level for encapsulated devices. The quality level designators for encapsulated devices that are applicable for this specification sheet from the lowest to the highest level are as follows: “JAN”, “JANTX”, and "JANTXV".

1.5.2 Device type. The designation system for the device types of transistors covered by this specification sheet are as follows.

1.5.2.1 First number and first letter symbols. The transistors of this specification sheet use the first number and letter symbols "2N".

1.5.2.2 Second number symbols. The second number symbols for the transistors covered by this specification sheet are as follows: "6058" and "6059".

1.5.3 Lead finish. The lead finishes applicable to this specification sheet are listed on QPDSIS-19500.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:30Z
Check the source to verify that this is the current version before use.




FIGURE 1. Physical dimensions and schematic circuit (TO-204AA, similar to TO-3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:30Z
Check the source to verify that this is the current version before use.

Symbol	Dimensions				Notes
	Inches		Millimeters		
	Min	Max	Min	Max	
CD		.875		22.23	
CH	.250	.328	6.35	8.33	
HR	.495	.525	12.57	13.34	
HR_1	.131	.188	3.33	4.78	3
HT	.060	.135	1.52	3.43	
LD	.038	.043	0.97	1.09	4 , 5
LL	.312	.500	7.92	12.7	4
L_1		.050		1.27	4 , 5
MHD	.151	.161	3.84	4.09	6
MHS	1.177	1.197	29.90	30.40	
PS	.420	.440	10.67	11.18	7, 8
PS_1	.205	.225	5.21	5.72	7, 4, 8
S_1	.655	.675	16.64	17.15	7

NOTES:

1. Dimensions are in inches. Millimeters are given for general information only.
2. Body contour is optional within zone defined by dimension CD.
3. At both ends.
4. Both terminals.
5. Dimension LD applies between dimension L_1 and LL. Lead diameter shall not exceed twice dimension LD within dimension L_1. Diameter is uncontrolled in dimension L_1.
6. Two holes.
7. These dimensions shall be measured at points .050 inch (1.27 mm) to .055 inch (1.40 mm) below the seating plane. When gauge is not used, measurement shall be made at seating plane.
8. The seating plane of the header shall be flat within .001 inch (0.03 mm) concave to .004 inch (0.10 mm) convex inside a .930 inch (23.62 mm) diameter circle on the center of the header and flat within .001 inch (0.03 mm) concave to .006 inch (0.15 mm) convex overall.
9. The collector shall be electrically connected to the case.
10. In accordance with ASME Y14.5M, diameters are equivalent to ϕ symbology.

FIGURE 1. Physical dimensions and schematic circuit (TO-204AA, similar to TO-3) - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:30Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-PRF-19500 - Semiconductor Devices, General Specification for.

DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-750 - Test Methods for Semiconductor Devices.

(Copies of these documents are available online at http://quicksearch.dla.mil/).

2.3 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 General. The individual item requirements shall be as specified in MIL-PRF-19500 and as modified herein.

3.2 Qualification. Devices furnished under this specification shall be products that are manufactured by a manufacturer authorized by the qualifying activity for listing on the applicable qualified manufacturer's list (QML) before contract award (see 4.2 and 6.3).

3.3 Abbreviations, symbols, and definitions. The abbreviations, symbols, and definitions used herein shall be as specified in MIL-PRF-19500 and as follows:

I_M - The measurement current applied to forward bias the junction for measurement of V_{BE}.
I_H - The collector current applied to the device under test during the heating period.
t_H - The duration of the applied heating power pulse.
t_{SW} - Sample window time during which final V_{BE} measurement is made.

3.4 Interface requirements and physical dimensions. The interface requirements and physical dimensions shall be as specified in MIL-PRF-19500 and on figure 1 (TO-204AA, similar to TO-3) herein.

3.4.1 Lead finish. The lead finish shall be solderable in accordance with MIL-STD-750, MIL-PRF-19500, and herein. Where a choice of lead finish is desired, it shall be specified in the acquisition document (see 6.2).

3.4.2 Polarity. The polarity of the device types shall be as shown on figure 1. The collector shall be electrically connected to the case.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:30Z
Check the source to verify that this is the current version before use.

3.5 Marking. Marking shall be in accordance with MIL-PRF-19500.

3.6 Electrical performance characteristics. Unless otherwise specified herein, the electrical performance characteristics are as specified in 1.3, 1.4, and table I herein.

3.7 Electrical test requirements. The electrical test requirements shall be as specified in table I.

3.8 Workmanship. Semiconductor devices shall be processed in such a manner as to be uniform in quality and shall be free from other defects that will affect life, serviceability, or appearance.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. Qualification inspection (see 4.2).

b. Screening (see 4.3).

c. Conformance inspection (see 4.4 and tables I and II).

4.2 Qualification inspection. Qualification inspection shall be in accordance with MIL-PRF-19500, and as specified herein.

4.2.1 Group E qualification. Group E inspection shall be performed for qualification or re-qualification only. In case qualification was awarded to a prior revision of the specification sheet that did not request the performance of table II tests, the tests specified in table II herein that were not performed in the prior revision shall be performed on the first inspection lot of this revision to maintain qualification.

4.3 Screening (JANTX and JANTXV levels only). Screening shall be in accordance with table E-IV of MIL-PRF-19500, and as specified herein. The following measurements shall be made in accordance with table I herein. Devices that exceed the limits of table I herein shall not be acceptable.

Screen (see table E-IV of MIL-PRF-19500)	Measurement
	JANTX and JANTXV levels only
3c (1)	Thermal impedance, see 4.3.1
9	I_{CEX1}.
11	I_{CEX1}, h_{FE2}; ΔI_{CEX1} = 100 percent of initial value or 2 μA dc, whichever is greater.
12	See 4.3.2.
13	See table I, subgroup 2 herein. ΔI_{CEX1} = 100 percent of initial value or 2 μA dc, whichever is greater. Δh_{FE2} = ±40 percent of initial value.

(1) This test shall be performed anytime after temperature cycling, screen 3a, and does not need to be repeated in screening requirements.

4.3.1 Thermal impedance. The thermal impedance measurements shall be performed in accordance with test method 3131 of MIL-STD-750 using the guidelines in that test method for determining I_M, I_H, t_H, t_{SW}, (and V_H where appropriate). The thermal impedance limit used in screen 3c and table I, subgroup 2 herein shall be set statistically by the supplier. See table II, subgroup 4 herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:30Z
Check the source to verify that this is the current version before use.

4.3.2 Power burn-in conditions. The power burn-in conditions shall be as follows: T_J = +162.5°C ± 12.5°C; V_{CE} ≥ 10 V dc, T_A ≤ +100°C. NOTE: No heat sink or forced air cooling on the devices shall be permitted.

4.4 Conformance inspection. Conformance inspection shall be in accordance with MIL-PRF-19500, and as specified herein.

4.4.1 Group A inspection. Group A inspection shall be conducted in accordance with table E-V of MIL-PRF-19500 and table I herein.

4.4.2 Group B inspection. Group B inspection shall be conducted in accordance with the tests and conditions specified for subgroup testing in table E-VIB (JAN, JANTX, and JANTXV) of MIL-PRF-19500 and as follows. Delta requirements shall be in accordance with the applicable step of 4.6 herein.

4.4.2.1 Quality levels JAN, JANTX and JANTXV, table E-VIB of MIL-PRF-19500.

Subgroup	Method	Conditions
B3	1037	V_{CB} ≥ 10 V dc; ΔT_J = between cycles ≥ +100°C. $t_{on} = t_{off}$ = 3 minutes. No heat sink or forced-air cooling on the devices shall be permitted.
B5	3131	See 4.3.1, $R_{\theta JC}$ = 1°C/W (maximum).

4.4.3 Group C inspection. Group C inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-VII of MIL-PRF-19500 and as follows. Delta requirements shall be in accordance with the applicable step of 4.6 herein.

Subgroup	Method	Conditions
C2	2036	Test condition A, weight = 10 lbs (4.54 Kg), t = 15s.
C6	1037	V_{CB} ≥ 10 V dc; ΔT_J between cycles ≥ +100 °C; $t_{on} = t_{off}$ = 3 minutes. No heat sink or forced-air cooling on device shall be permitted.

4.4.4 Group E inspection. Group E inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-IX of MIL-PRF-19500 and as specified in table II herein. Delta requirements shall be in accordance with the applicable step of 4.6 herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:30Z
Check the source to verify that this is the current version before use.

4.5 Method of inspection. Methods of inspection shall be as specified in the appropriate tables and as follows.

4.5.1 Pulse response measurements. The conditions for pulse response measurement shall be as specified in section 4 of MIL-STD-750.

4.6 Delta measurements. The requirements for delta measurements for groups B, C, and E inspection shall be as specified below. (1) (2) (3)

Step	Inspection	MIL-STD-750		Symbol	Limit
		Method	Conditions		
1	Forward-current transfer ratio	3076	V_{CE} = 3 V dc; I_C = 6.0 A dc; pulsed (see 4.5.1).	Δh_{FE2}	±40 percent change from initial reading.

(1) The delta measurement for group B, quality levels (JAN, JANTX and JANTXV) shall be as follows: In addition to the measurements specified for subgroups 3 and 6 of table E-VIB of MIL-PRF-19500, the measurements of step 1 shall also be taken.
(2) The delta measurement for group C shall be as follows: In addition to the measurements specified for subgroup 6 of table E-VII of MIL-PRF-19500, the measurements of step 1 shall also be taken.
(3) The delta measurement for group E shall be as follows: In addition to the measurements specified for subgroups 1 and 2 of table E-IX of MIL-PRF-19500, the measurements of step 1 shall also be taken.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:30Z
Check the source to verify that this is the current version before use.

* TABLE I. Group A inspection.

Inspection 1/	MIL-STD-750		Symbol	Limit		Unit
	Method	Conditions		Min	Max	
Subgroup 1						
Visual and mechanical examination	2071					
Subgroup 2						
Thermal impedance 2/	3131	See 4.3.1	$Z_{\theta JC}$			°C/W
Collector to emitter breakdown voltage	3011	Bias condition D, I_C = 100 mA dc; pulsed (see 4.5.1)	$V_{(BR)CEO}$			
2N6058				80		V dc
2N6059				100		V dc
Collector to emitter cutoff current	3041	Bias condition A, V_{BE} = 1.5 V dc	I_{CEX1}			
2N6058		V_{CE} = 80 V dc			10	µA dc
2N6059		V_{CE} = 100 V dc			10	µA dc
Collector to emitter cutoff current	3041	Bias condition D	I_{CEO}			
2N6058		V_{CE} = 40 V dc			1.0	mA dc
2N6059		V_{CE} = 50 V dc			1.0	mA dc
Emitter to base cutoff current	3061	Bias condition D, V_{EB} = 5 V dc	I_{EBO}		2.0	mA dc
Base to emitter voltage (nonsaturated)	3066	Test condition B, V_{CE} = 3 V dc; I_C = 6 A dc	V_{BE}		2.8	V dc
Base to emitter voltage (saturated)	3066	Test condition A, I_C = 12 A dc; I_B = 120 mA dc; pulsed (see 4.5.1)	$V_{BE(sat)}$		4.0	V dc
Collector to emitter voltage (saturation voltage)	3071	I_C = 12 A dc; I_B = 120 mA dc; pulsed (see 4.5.1)	$V_{CE(sat)1}$		3.0	V dc
Collector to emitter voltage (saturation voltage)	3071	I_C = 6 A dc; I_B = 24 mA dc; pulsed (see 4.5.1)	$V_{CE(sat)2}$		2.0	V dc
Forward-current transfer ratio	3076	V_{CE} = 3 V dc; I_C = 1 A dc; pulsed (see 4.5.1)	h_{FE1}	1,000		
Forward-current transfer ratio	3076	V_{CE} = 3 V dc; I_C = 6 A dc; pulsed (see 4.5.1)	h_{FE2}	1,000	18,000	
Forward-current transfer ratio	3076	V_{CE} = 3 V dc; I_C = 12 A dc; pulsed (see 4.5.1)	h_{FE3}	150		

See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:30Z
Check the source to verify that this is the current version before use.

* TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limit		Unit
	Method	Conditions		Min	Max	
Subgroup 3						
High temperature operation:		T_A = +150°C				
Collector to emitter cutoff current	3041	Bias condition A, V_{BE} = 1.5 V dc	I_{CEX2}			
2N6058		V_{CE} = 80 V dc			5.0	mA dc
2N6059		V_{CE} = 100 V dc			5.0	mA dc
Collector to emitter voltage (saturation voltage)	3071	I_C = 6 A dc; I_B = 24 mA dc; pulsed (see 4.5.1)	$V_{CE(sat)3}$		2.0	V dc
Low temperature operation:		T_A = -55°C				
Forward-current transfer ratio	3076	V_{CE} = 3 V dc; I_C = 6 A dc; pulsed (see 4.5.1)	h_{FE4}	300		
Subgroup 4						
Small-signal, short-circuit forward-current transfer ratio	3206	V_{CE} = 3 V dc; I_C = 5 A dc; f = 1 kHz	h_{fe}	1,000		
Magnitude of common-emitter small-signal short-circuit forward-current transfer ratio	3306	V_{CE} = 3 V dc; I_C = 5 A dc; f = 1.0 MHz	$\|h_{fe}\|$	10	250	
Open-circuit output capacitance	3236	V_{CB} = 10 V dc; I_E = 0; 100 kHz ≤ f ≤ 1 MHz	C_{obo}		300	pF
Pulse response						
Turn-on time		(See figure 2), V_{CC} = 30 V dc; I_C = 5 A dc; I_B = 20 mA dc	t_{on}		2.0	µs
Turn-off time		(See figure 2); V_{CC} = 30 V dc; I_C = 5 A dc; I_{B1} = I_{B2} = 20 mA dc	t_{off}		10	µs

See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:30Z
Check the source to verify that this is the current version before use.

* TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limit		Unit
	Method	Conditions		Min	Max	
Subgroup 5						
Safe operating area (continuous dc)	3051	T_C = +25°C +10°C, -0°; t ≥ 1 s; 1 cycle; (see figure 3)				
Test 1 (Both device types)		V_{CE} = 12.5 V dc; I_C = 12 A dc				
Test 2 (Both device types)		V_{CE} = 30 V dc; I_C = 5 A dc				
Test 3						
(2N6058)		V_{CE} = 70 V dc; I_C = 200 mA dc				
(2N6059)		V_{CE} = 90 V dc; I_C = 155 mA dc				
* Safe operating area (switching)	3053	Load condition B; (clamped inductive load); T_A = +25°C; $t_r + t_f \leq 1.0$ µs; duty cycle ≤ 2 percent; t_p = 1 ms; (vary to obtain I_C); R_s = 0.10 Ω; R_{BB1} = 80 Ω; V_{BB1} = 16 V dc; R_{BB2} = 100 Ω; V_{BB2} = 1.5 V dc; I_C = 12 A dc; V_{CC} = 20 V dc; $R_L \leq 2$ Ω; L = 10 mH (Stancor C-2688 or equivalent); (see figure 4 for reference only).				
2N6058		Clamp voltage = 80 +0, -5 V dc				
2N6059		Clamp voltage = 100 +0, -5 V dc				
		Device fails if clamp voltage not reached.				
End-point electrical measurements		See subgroup 2 of table I herein.				
Subgroups 6 and 7						
Not applicable						


1/ For sampling plan, see MIL-PRF-19500.
2/ This test required for the following end-point measurements only:
Group B, subgroups 2 and 3 (JAN, JANTX, and JANTXV).
Group C, subgroup 2 and 6.
Group E, subgroup 1.


Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:30Z
Check the source to verify that this is the current version before use.

TABLE II. Group E inspection (all quality levels) - for qualification and requalification only.

Inspection	MIL-STD-750		Sample plan
	Method	Conditions	
Subgroup 1			45 devices c = 0
Temperature cycling (air to air)	1051	Test condition C, 500 cycles.	
Hermetic seal Fine leak Gross leak	1071		
End-point electrical measurements		See table I, subgroup 2 and 4.6 herein.	
Subgroup 2			45 devices c = 0
Intermittent operation life	1037	V_{CB} ≥ 10 V dc, 6,000 cycles.	
End-point electrical measurements		See table I, subgroup 2 and 4.6 herein.	
Subgroup 4			Sample size N/A
Thermal impedance curves		See MIL-PRF-19500.	
Subgroup 8			45 devices c = 0
Reverse voltage leakage stability	1033	Condition B.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:30Z
Check the source to verify that this is the current version before use.





NOTES:

1. The input waveform is supplied by a pulse generator with the following characteristics: $t_r \leq 20$ ns, $t_f \leq 20$ ns, $Z_{OUT} = 50$ ohms, PW = 25 µs, duty cycle ≤ 2 percent.
2. Output waveforms are monitored on an oscilloscope with the following characteristics: $t_r \leq 2.0$ ns, $Z_{in} \geq 20$ kΩ, $C_{in} \leq 11.5$ pf.
3. Resistors shall be non-inductive types.
4. The dc power supplies may require additional by-passing in order to minimize ringing.

FIGURE 2. Pulse response test circuit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:30Z
Check the source to verify that this is the current version before use.




FIGURE 3. Maximum safe operating area graph (continuous dc).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:30Z
Check the source to verify that this is the current version before use.




FIGURE 4. Safe operating area for switching between saturation and cutoff (unclamped inductive load).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:30Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the Military Service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.) The notes specified in MIL-PRF-19500 are applicable to this specification.)

6.1 Intended use. Semiconductors conforming to this specification are intended for original equipment design applications and logistic support of existing equipment.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. Packaging requirements (see 5.1).


c. Lead finish (see 3.4.1).

d. The complete PIN, see 1.5 and 6.5.

6.3 Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time of award of contract, qualified for inclusion in Qualified Manufacturers List (QML 19500) whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. Information pertaining to qualification of products may be obtained from DLA Land and Maritime, ATTN: VQE, P.O. Box 3990, Columbus, OH 43218-3990 or e-mail vqe.chief@dla.mil. An online listing of products qualified to this specification may be found in the Qualified Products Database (QPD) at https://assist.dla.mil.

6.4 PIN construction example.

6.4.1 Encapsulated devices The PINs for encapsulated devices are constructed using the following form.



Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:30Z
Check the source to verify that this is the current version before use.

6.5 List of PINs.

6.5.1 List of PINs for encapsulated devices. The following is a list of possible PINs for encapsulated devices available on this specification sheet.

PINs for devices of the base quality level	PINs for devices of the "TX" quality level	PINs for devices of the "TXV" quality level
JAN2N6058	JANTX2N6058	JANTXV2N6058
JAN2N6059	JANTX2N6059	JANTXV2N6059

6.6 Request for new types and configurations. Requests for new device types or configurations for inclusions in this specification sheet should be submitted to: DLA Land and Maritime, ATTN: VAC, Post Office Box 3990, Columbus, OH 43218-3990 or by electronic mail at Semiconductor@dla.mil or by facsimile (614) 693-1642 or DSN 850-6939.

* 6.7 Amendment notations. The margins of this specification are marked with asterisks to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Custodians:
Army - CR
Navy - EC
Air Force - 85
NASA - NA
DLA - CC

Review activities:
Air Force - 19, 99

Preparing activity:
DLA - CC

(Project 5961-2017-004)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:30Z
Check the source to verify that this is the current version before use.