The documentation and process conversion measures necessary to comply with this revision shall be completed by 21 February 2007.

INCH-POUND

MIL-PRF-19500/525D
21 November 2006
SUPERSEDING
MIL-PRF-19500/525C
10 March 2003

* PERFORMANCE SPECIFICATION SHEET

SEMICONDUCTOR DEVICE, TRANSISTOR, NPN, SILICON, POWER TYPES 2N6546, 2N6546T1, 2N6546T3, 2N6547, 2N6547T1, AND 2N6547T3 JAN, JANTX, AND JANTXV

This specification is approved for use by all Departments and Agencies of the Department of Defense.

* The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-19500.

1. SCOPE

1.1 Scope. This specification covers the performance requirements for NPN, silicon, power transistors. Three levels of product assurance are provided for each device type as specified in MIL-PRF-19500.

1.2 Physical dimensions. See figure 1 (TO-3), figure 2 (TO-254), and figure 3 (TO-257).

* 1.3 Maximum ratings. Unless otherwise specified, T_A = +25°C.

Limits	P_T (1)		V_{CEX}	V_{CEO}	V_{EBO}	I_B	I_C	T_J and T_{STG}	$R_{\theta JC}$ (2)
	T_C = +25°C	T_C = +100°C							
	W	W	V dc	V dc	V dc	A dc	A dc	°C	°C/W
2N6546	175	100	600	300	8	10	15	-65 to +200	1.0
2N6546T1	175	100	600	300	8	10	15	-65 to +200	1.0
2N6546T3	125	100	600	300	8	10	15	-65 to +200	1.4
2N6547	175	100	850	400	8	10	15	-65 to +200	1.0
2N6547T1	175	100	850	400	8	10	15	-65 to +200	1.0
2N6547T3	125	100	850	400	8	10	15	-65 to +200	1.4

(1) See figure 4 for derating curves.
(2) See figures 5, 6, and 7 for thermal impedance graphs.

* Comments, suggestions, or questions on this document should be addressed to Defense Supply Center, Columbus, ATTN: DSCC-VAC, P.O. Box 3990, Columbus, OH 43218-3990, or emailed to Semiconductor@dscc.dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at http://assist.daps.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:47Z
Check the source to verify that this is the current version before use.

* 1.4 Primary electrical characteristics.

Limits	h_{FE2} (1)	h_{FE3} (1)	C_{obo}	$\lvert h_{fe} \rvert$	Switching times (2)	
	V_{CE} = 2 V dc I_C = 5 A dc	V_{CE} = 2 V dc I_C = 10 A dc	V_{CB} = 10 V dc I_E = 0 0.1 MHz ≤ f ≤ 1 MHz	V_{CE} = 10 V dc I_C = 0.5 A dc f = 1 MHz	V_{CC} = 250 V dc I_C = 10 A dc	
					t_{on}	t_{off}
			pF			
Min	12	6		6		
Max	60		500	30	1.0	4.7

(1) Pulsed (see 4.5.1).
(2) See figure 8 for pulse response circuits.

2. APPLICABLE DOCUMENTS

* 2.1 General. The documents listed in this section are specified in sections 3, 4, or 5 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3, 4, or 5 of this specification, whether or not they are listed.

2.2 Government documents.

* 2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

* DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-PRF-19500 - Semiconductor Devices, General Specification for.


* DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-750 - Test Methods for Semiconductor Devices.

* (Copies of these documents are available online at http://assist.daps.dla.mil/quicksearch/ or http://assist.daps.dla.mil/ or from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:47Z
Check the source to verify that this is the current version before use.



* FIGURE 1. Dimensions and configuration (TO-3).


Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:47Z
Check the source to verify that this is the current version before use.

Symbol	Dimensions				Notes
	Inches		Millimeters		
	Min	Max	Min	Max	
CD		.875		22.23	3
CH	.250	.450	6.35	11.43	
HR	.495	.525	12.57	13.34	
HR_1	.131	.188	3.33	4.78	6
HT	.050	.135	1.27	3.43	
LD	.038	.043	0.97	1.09	4,5,9
LL	.312		7.92		4,5,9
L_1		.050		1.27	
MHD	.151	.161	3.84	4.09	7
MHS	1.177	1.197	29.90	30.40	
PS	.420	.440	10.67	11.18	5
PS_1	.205	.225	5.21	5.72	5
S1	.655	.675	16.64	17.15	

NOTES:
1. Dimensions are in inches.
2. Millimeters are given for general information only.
3. Body contour is optional within zone defined by CD.
4. These dimensions shall be measured at points .050 inch (1.27 mm) to .055 inch (1.40 mm) below seating plane. When gauge is not used, measurement shall be made at seating plane.
5. Both terminals.
6. At both ends.
7. Two holes.
8. The collector shall be electrically connected to the case.
9. LD applies between L1 and LL. Lead diameter shall not exceed twice LD within L1.
10. In accordance with ASME Y14.5M, diameters are equivalent to ϕx symbology.
11. The seating plane of the header shall be flat within .001 inch (0.03 mm) concave to .004 inch (0.10 mm) convex inside a .930 inch (23.62 mm) diameter circle on the center of the header and flat within .001 inch (0.03 mm) concave to 0.006 inch (0.15 mm) convex overall.
12. Mounting holes shall be deburred on the seating plane side.

* FIGURE 1. Dimensions and configuration (TO-3) - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:47Z
Check the source to verify that this is the current version before use.




Ltr	Dimensions			
	Inches		Millimeters	
	Min	Max	Min	Max
BL	.535	.545	13.59	13.84
CH	.249	.260	6.32	6.60
LD	.035	.045	0.89	1.14
LL	.530	.550	13.46	13.97
LO	.150 BSC		3.81 BSC	
LS	.150 BSC		3.81 BSC	
MHD	.139	.149	3.53	3.78
MHO	.665	.685	16.89	17.40
TL	.790	.800	20.07	20.32
TT	.040	.050	1.02	1.27
TW	.535	.545	13.59	13.84
Term 1	Base			
Term 2	Collector			
Term 3	Emitter			

NOTES:
1. Dimensions are in inches.
* 2. Millimeters are given for general information only.
3. All terminals are isolated from case.
4. In accordance with ASME Y14.5M, diameters are equivalent to ϕx symbology.

* FIGURE 2. Dimensions and configuration for 2N6546T1 and 2N6547T1 (TO-254).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:47Z
Check the source to verify that this is the current version before use.



Ltr	Dimensions			
	Inches		Millimeters	
	Min	Max	Min	Max
BL	.410	.430	10.41	10.92
CH	.190	.200	4.83	5.08
LD	.025	.035	0.64	0.89
LL	.500	.750	12.70	19.05
LO	.120 BSC		3.05 BSC	
LS	.100 BSC		2.54 BSC	
MHD	.140	.150	3.56	3.81
MHO	.527	.537	13.39	13.63
TL	.645	.665	16.38	16.89
TT	.035	.045	0.89	1.14
TW	.410	.420	10.41	10.67
Term 1	Base			
Term 2	Collector			
Term 3	Emitter			

NOTES:
1. Dimensions are in inches.
* 2. Millimeters are given for general information only.
3. Methods used for electrical isolation of the terminals feedthroughs shall employ materials that contain a minimum of 90 percent AL2O3 (ceramic).
4. In accordance with ASME Y14.5M, diameters are equivalent to ϕx symbology.

* FIGURE 3. Dimensions and configuration for 2N6546T3 and 2N6547T3 (TO-257).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:47Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 General. The individual item requirements shall be as specified in MIL-PRF-19500 and as modified herein.

3.2 Qualification. Devices furnished under this specification shall be products that are manufactured by a manufacturer authorized by the qualifying activity for listing on the applicable qualified manufacturer's list (QML) before contract award (see 4.2 and 6.3).

3.3 Abbreviations, symbols, and definitions. Abbreviations, symbols, and definitions used herein shall be as specified in MIL-PRF-19500.

3.4 Interface and physical dimensions. Interface and physical dimensions shall be as specified in MIL-PRF-19500, and on figure 1 (TO-3), figure 2 (TO-254), and figure 3 (TO-257).

3.4.1 Lead finish. Lead finish shall be solderable in accordance with MIL-STD-750, MIL-PRF-19500, and herein. Where a choice of lead finish or formation is desired, it shall be specified in the acquisition requirements (see 6.2).

3.5 Marking. Marking shall be in accordance with MIL-PRF-19500.

3.6 Electrical performance characteristics. Unless otherwise specified, the electrical performance characteristics are as specified in 1.3, 1.4, and table I herein.

* 3.7 Electrical test requirements. The electrical test requirements shall be as specified in table I.

3.8 Workmanship. Semiconductor devices shall be processed in such a manner as to be uniform in quality and shall be free from other defects that will affect life, serviceability, or appearance.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. Qualification inspection (see 4.2).

b. Screening (see 4.3).

* c. Conformance inspection (see 4.4 and table I).

4.2 Qualification inspection. Qualification inspection shall be in accordance with MIL-PRF-19500.

* 4.2.1 Group E qualification. Group E inspection shall be performed for qualification or re-qualification only. In case qualification was awarded to a prior revision of the specification sheet that did not request the performance of table II tests, the tests specified in table II herein that were not performed in the prior revision shall be performed on the first inspection lot of this revision to maintain qualification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:47Z
Check the source to verify that this is the current version before use.

* 4.3 Screening (JANTX and JANTXV levels only). Screening shall be in accordance with table E-IV of MIL-PRF-19500, and as specified herein. The following measurements shall be made in accordance with table I herein. Devices that exceed the limits of table I herein shall not be acceptable.

Screen (see table E-IV of MIL-PRF-19500)	Measurements
	JANTX, JANTXV levels
(1) 3c	Thermal impedance, method 3131 of MIL-STD-750 (see 4.3.2).
10	T_A = +150°C; t = 48 hours min. V_{CB} = 200 V dc for 2N6546, 2N6546T1, 2N6546T3 V_{CB} = 300 V dc for 2N6547, 2N6547T1, 2N6547T3
11	h_{FE2} ; I_{CEX1}
12	See 4.3.1
13	Subgroup 2 of table I herein. ΔI_{CEX1} = 100 percent of initial value or 100 μA dc, whichever is greater; Δh_{FE2} = ±25 percent of initial value.

(1) Shall be performed anytime after temperature cycling, screen 3a; and does not need to be repeated in screening requirements.

4.3.1 Power burn-in conditions. Power burn-in conditions are as follows: T_J = + 175°C minimum, $V_{CB} \geq$ 20 V dc, T_A = +35°C maximum.

* 4.3.2 Thermal impedance. The thermal impedance measurements shall be performed in accordance with method 3131 of MIL-STD-750 using the guidelines in that method for determining I_M, I_H, t_H, t_{SW}, (and V_H where appropriate). Measurement delay time (t_{MD}) = 70 μs max. See table II, group E, subgroup 4 herein.

4.4 Conformance inspection. Conformance inspection shall be in accordance with MIL-PRF-19500.

4.4.1 Group A inspection. Group A inspection shall be conducted in accordance with MIL-PRF-19500 and table I herein.

4.4.2 Group B inspection. Group B inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-VIB of MIL-PRF-19500 and herein. Electrical measurements (end-points) shall be in accordance with table I, subgroup 2, herein.

* 4.4.2.1 Group B inspection, table E-VIB (JAN, JANTX and JANTXV) of MIL-PRF-19500

	Subgroup	Method	Conditions
*	B3	1037	For solder die attach: $V_{CB} \geq$ 20 V dc, for 2,000 cycles, $T_A \leq$ +35°C, adjust power or current to achieve a minimum ΔT_J = +100°C.
*	B3	1027	For eutectic die attach: $V_{CB} \geq$ 20 V dc; adjust P_T to achieve T_J = +175°C minimum, $T_A \leq$ +35°C.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:47Z
Check the source to verify that this is the current version before use.

* 4.4.3 Group C inspection. Group C inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-VII of MIL-PRF-19500. Electrical measurements (end-points) shall be in accordance with table I, subgroup 2, herein.

	Subgroup	Method	Conditions
*	C2	2036	Test condition A; weight = 10 pounds; t = 15 seconds.
*	C5	3131	See 4.3.2, $R_{\theta JC}$ = 1.0°C/W for 2N6546, 2N6546T1, 2N6547 and 2N6547T1; $R_{\theta JC}$ = 1.4°C/W for 2N6546T3 and 2N6547T3.
*	C6	1037	For solder die attach: $V_{CB} \geq 20$ V dc, for 6,000 cycles, $T_A \leq +35°C$, adjust power or current to achieve a minimum $\Delta T_J = +100°C$.
*	C6	1026	For eutectic die attach: $V_{CB} \geq 20$ V dc; adjust P_T to achieve $T_J = +175°C$ minimum, $T_A \leq +35°C$.

4.4.4 Group E inspection. Group E inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-IX of MIL-PRF-19500 and as specified in table II herein. Electrical measurements (end-points) shall be in accordance with table I, subgroup 2 herein.

4.5 Method of inspection. Methods of inspection shall be as specified in the appropriate tables and as follows.

4.5.1 Pulse measurements. Conditions for pulse measurement shall be as specified in section 4 of MIL-STD-750.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:47Z
Check the source to verify that this is the current version before use.

* TABLE I. Group A inspection.

Inspection 1/	MIL-STD-750		Symbol	Limits		Unit
	Method	Conditions		Min	Max	
Subgroup 1						
Visual and mechanical examination	2071					
Subgroup 2						
Thermal impedance 2/	3131	See 4.3.2	$Z_{\theta JX}$			°C/W
Collector to emitter breakdown voltage	3011	Bias condition D; I_C = 100 mA dc; pulsed (see 4.5.1)	$V_{(BR)CEO}$			
2N6546, 2N6546T1, 2N6546T3 2N6547, 2N6547T1, 2N6547T3				300 400		V dc V dc
Emitter to base cutoff current	3061	Bias condition D; V_{EB} = 8 V dc	I_{EBO}		1.0	mA dc
Collector to emitter cutoff current	3041	Bias condition A; V_{BE} = 1.5 V dc;	I_{CEX1}		1.0	mA dc
2N6546, 2N6546T1, 2N6546T3 2N6547, 2N6547T1, 2N6547T3		V_{CE} = 600 V dc V_{CE} = 850 V dc				
Base emitter voltage (saturated)	3066	Test condition A; I_C = 10 A dc; I_B = 2.0 A dc; pulsed (see 4.5.1)	$V_{BE(sat)}$		1.6	V dc
Collector to emitter saturated voltage	3071	I_C = 10 A dc; I_B = 2.0 A dc; pulsed (see 4.5.1)	$V_{CE(sat)1}$		1.5	V dc
Collector to emitter saturated voltage	3071	I_C = 15 A dc; I_B = 3.0 A dc; pulsed (see 4.5.1)	$V_{CE(sat)2}$		5.0	V dc
Forward-current transfer ratio	3076	V_{CE} = 2 V dc; I_C = 1 A dc; pulsed (see 4.5.1)	h_{FE1}	15		
Forward-current transfer ratio	3076	V_{CE} = 2 V dc; I_C = 5 A dc; pulsed (see 4.5.1)	h_{FE2}	12	60	
Forward-current transfer ratio	3076	V_{CE} = 2 V dc; I_C = 10 A dc; pulsed (see 4.5.1)	h_{FE3}	6		

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:47Z
Check the source to verify that this is the current version before use.

* TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limits		Unit
	Method	Conditions		Min	Max	
Subgroup 3						
High temperature operation:		T_A = +150°C				
Collector to emitter cutoff current	3041	Bias condition A; V_{BE} = 1.5 V dc	I_{CEX2}		30	mA dc
2N6546, 2N6546T1, 2N6546T3		V_{CE} = 600 V dc				
2N6547, 2N6547T1, 2N6547T3		V_{CE} = 850 V dc				
Collector to emitter cutoff current	3041	Bias condition A; V_{BE} = 1.5 V dc;	I_{CEX3}		450	µA dc
2N6546, 2N6546T1, 2N6546T3		V_{CE} = 300 V dc				
2N6547, 2N6547T1, 2N6547T3		V_{CE} = 400 V dc				
Low temperature operation:		T_A = -55°C				
Forward-current transfer current	3076	V_{CE} = 2.0 V dc; I_C = 5 A dc; pulsed (see 4.5.1)	h_{FE4}	4		
Subgroup 4						
Pulse response	3251	Test condition A except test circuit and pulse requirements in accordance with figure 8 herein.				
Turn-on time		V_{CC} = 250 V dc; I_C = 10 A dc; I_{B1} = I_{B2} = 2 A dc	t_{on}		1.0	µs
Turn-off time		V_{CC} = 250 V dc; I_C = 10 A dc; I_{B1} = I_{B2} = 2 A dc	t_{off}		4.7	µs
Magnitude of common emitter small-signal short-circuit forward-current transfer ratio	3306	V_{CE} = 10 V dc; I_C = .5 A dc; f = 1 MHz	$\lvert h_{fe} \rvert$	6.0	30	
Output capacitance (open circuit)	3236	V_{CB} = 10 V dc; I_E = 0; 0.1 MHz ≤ f ≤ 1.0 MHz	C_{obo}		500	pF

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:47Z
Check the source to verify that this is the current version before use.

* TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limits		Unit
	Method	Conditions		Min	Max	
Subgroup 5						
Safe operating area (dc operation)	3051	T_C = +25°C; t = 1 s; 1 cycle; (see figure 9)				
Test 1 (All device types)		I_C = 15 A dc, V_{CE} = 11.7 V dc				
Test 2 (All device types)		I_C = 8.75 A dc, V_{CE} = 20 V dc				
Test 3 2N6546, 2N6546T1, 2N6546T3		V_{CE} = 250 V dc; I_C = 45 mA dc				
2N6547, 2N6547T1, 2N6547T3		V_{CE} = 350 V dc; I_C = 30 mA dc				
Safe operating area	3053	Load condition C; (unclamped inductive load); see figure 10; T_C = +25°C; duty cycle ≤ 10 percent R_S = 0.1 Ω; $t_r = t_f \leq 500$ ns				
Test 1		t_p = 5 ms; (vary to obtain I_C); R_{BB1} = 15 Ω; V_{BB1} = 38.5 V dc; R_{BB2} = 50 Ω; V_{BB2} = -4 V dc; V_{CC} = 20 V dc; I_C = 15 A dc; L = 10 µH 3/				
Test 2		t_p = 5 ms; (vary to obtain I_C); R_{BB1} = 15 Ω; V_{BB1} = 38.5 V dc; R_{BB2} = 50 Ω; V_{BB2} = -4 V dc; V_{CC} = 20 V dc; I_C = 100 mA dc; L = 1 mH 4/				
Electrical measurements:						
Collector to emitter cutoff current	3041	Bias condition A, V_{BE} = 1.5 V dc	I_{CEX3}			
2N6546, 2N6546T1, 2N6546T3		V_{CE} = 600 V dc			2.0	mA dc
2N6547, 2N6547T1, 2N6547T3		V_{CE} = 850 V dc			2.0	mA dc

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:47Z
Check the source to verify that this is the current version before use.

* TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limits		Unit
	Method	Conditions		Min	Max	
Subgroup 5- continued.						
Safe operating area (switching)		Clamped inductive load; T_A = +25°C; duty cycle ≤ 5 percent; t_p = 1.5 ms; (vary to obtain I_C); V_{CC} = 20 V dc; I_C = 8 A dc; L = 180 µH (see figure 11)				
2N6546, 2N6546T1, 2N6546T3		Clamp voltage = 350 V dc				
2N6547, 2N6547T1, 2N6547T3		Clamp voltage = 450 V dc				
Electrical measurements		Same as safe operating area (unclamped inductive) above				
Subgroups 6 and 7						
Not applicable						


1/ For sampling plan, see MIL-PRF-19500.
2/ This test required for the following end-point measurements only:
Group B, subgroups 2 and 3 (JAN, JANTX, and JANTXV).
Group C, subgroup 2 and 6.
Group E, subgroup 1.
3/ L = 10 µH (approx. 10 turns, 1 row of #16ASG wire on an air core 2 7/8 inches ID) .0007 ohms, or equivalent.
4/ L = 1 mH (one each Miller type 7827 in parallel with two each series strung Miller type 7825 and this in series with two each series strung Miller type 7827) .45 ohms, or equivalent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:47Z
Check the source to verify that this is the current version before use.

* TABLE II. Group E inspection (all quality levels) - for qualification and re-qualification only.

Inspection	MIL-STD-750		Sample size
	Method	Conditions	
Subgroup 1			45 devices c = 0
Temperature cycling	1051		
Hermetic seal	1071		
Fine leak Gross leak			
Electrical measurements		See table I, subgroup 2 herein.	
Subgroup 2			45 devices c = 0
Blocking life	1048	Test temperature = +125°C; V_{CB} = 80 percent of rated; T = 1,000 hours.	
Electrical measurements		See table I, subgroup 2 herein.	
Subgroup 4			N/A
Thermal impedance curves		See MIL-PRF-19500.	
Subgroup 5			22 devices, c = 0
Barometric pressure	1001	Pressure = 8.0 mm Hg time = 60 seconds; normal mounting, see 1.4.	
Subgroup 6			3 devices
ESD	1020	Testing not required for class 3 listing. Testing is required for nonsensitive listing to prove capability.	
Subgroup 8			45 devices c = 0
Reverse stability	1033	Condition A for devices ≥ 400 V, condition B for devices < 400 V.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:47Z
Check the source to verify that this is the current version before use.




NOTES:

1. All devices are capable of operating at ≤ T_J specified on this curve. Any parallel line to this curve will intersect the appropriate power for the desired maximum T_J allowed.
2. Derate design curve constrained by the maximum junction temperature (T_J ≤ +200°C) and power rating specified. (See 1.3 herein.)
3. Derate design curve chosen at T_J ≤ +150°C where the maximum temperature of electrical test is performed.
4. Derate design curves chosen at T_J ≤ +125°C and +110°C to show power rating where most users want to limit T_J in their application.

* FIGURE 4. Temperature-power derating graph.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:47Z
Check the source to verify that this is the current version before use.




NOTES:

1. All devices are capable of operating at $\leq T_J$ specified on this curve. Any parallel line to this curve will intersect the appropriate power for the desired maximum T_J allowed.
2. Derate design curve constrained by the maximum junction temperature ($T_J \leq +200°C$) and power rating specified. (See 1.3 herein.)
3. Derate design curve chosen at $T_J \leq +150°C$ where the maximum temperature of electrical test is performed.
4. Derate design curves chosen at $T_J \leq +125°C$ and +110°C to show power rating where most users want to limit T_J in their application.

* FIGURE 4. Temperature-power derating graph - Continued.


Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:47Z
Check the source to verify that this is the current version before use.



$R_{\theta JC}$ = 1.0 °C/W max., TO-3.

FIGURE 5. Thermal impedance graph (2N6546 and 2N6547).


Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:47Z
Check the source to verify that this is the current version before use.



$R_{\theta JC}$ = 1.0 °C/W max.

FIGURE 6. Thermal impedance graph (2N6546T1 and 2N6547T1).


Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:47Z
Check the source to verify that this is the current version before use.




$R_{\theta JC}$ = 1.4 °C/W max.

FIGURE 7. Thermal impedance graph (2N6546T3 and 2N6547T3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:47Z
Check the source to verify that this is the current version before use.



TURN-ON (t_{on}) TIME TEST CIRCUIT



TURN-OFF (t_{off}) TIME TEST CIRCUIT

FIGURE 8. Switching time test circuits.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:47Z
Check the source to verify that this is the current version before use.




FIGURE 9. Maximum safe operating area graph (continuous dc).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:47Z
Check the source to verify that this is the current version before use.





FIGURE 10. Safe operating area for switching between saturation and cutoff (unclamped inductive load, all devices).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:47Z
Check the source to verify that this is the current version before use.



NOTES:
1. Either a clamping circuit or clamping diode may be used.
2. The coil used shall provide a minimum inductance of 180 μH at 8 A with a maximum dc resistance of 0.05 ohm. For reference only: 2 each Miller type 7827 in parallel, or equivalent.
3. $R_S \leq .1$ ohm, 12 W, 1 percent tolerance maximum, (noninductive).

Procedure:
1. With switch S1 closed, set the specified test conditions.
2. Open S1. Device fails if clamp voltage not reached and maintained until current reaches zero.
3. Perform specified end-point tests.

FIGURE 11. Clamped inductive sweep test circuit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:47Z
Check the source to verify that this is the current version before use.

5. PACKAGING

* 5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the Military Service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The notes specified in MIL-PRF-19500 are applicable to this specification.

* 6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. Packaging requirements (see 5.1).

c. Lead finish (see 3.4.1).

d. Product assurance level and type designator.

* 6.3 Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time of award of contract, qualified for inclusion in Qualified Manufacturers List (QML 19500) whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. Information pertaining to qualification of products may be obtained from Defense Supply Center, Columbus, ATTN: DSCC/VQE, P.O. Box 3990, Columbus, OH 43218-3990 or e-mail vqe.chief@dla.mil.

6.4 Changes from previous issue. The margins of this specification are marked with asterisks to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - CR
Air Force - 11
NASA - NA
DLA - CC

Preparing activity:
DLA - CC

(Project 5961-2006-017)

Review activities:
Army - AR, MI
Air Force - 19, 99

* NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil/ .

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:47Z
Check the source to verify that this is the current version before use.