The documentation and process conversion measures necessary to comply with this document shall be completed by 23 January 2020.

INCH-POUND

MIL-PRF-19500/547E
23 September 2019
SUPERSEDING
MIL-PRF-19500/547D
29 August 2011

PERFORMANCE SPECIFICATION SHEET

TRANSISTOR, FIELD EFFECT, N-CHANNEL, SILICON, TYPES 2N6660 AND 2N6661, QUALITY LEVELS JAN, JANTX, JANTXV, AND JANS

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-19500.

1. SCOPE

1.1 Scope. This specification covers the performance requirements for a N-channel, enhancement-mode, low-threshold logic level, high frequency, high switching speed MOSFET, power transistor. Four levels of product assurance (JAN, JANTX, JANTXV, and JANS) are provided for each encapsulated device type as specified in MIL-PRF-19500.

1.2 Package outlines. The device package outline is a three terminal metal can package (TO-205AD) in accordance with figure 1.

1.3 Maximum ratings. Unless otherwise specified, T_A = +25°C.

Type	P_T (1) T_C = +25°C	P_T T_A = +25°C	$R_{\theta JC}$	V_{DS}	V_{DGR}	V_{GS}	I_{D1} (3) T_C = +25°C	I_{D2} (3) T_C = +100°C	I_S	I_{DM}	T_J and T_{STG}
	W	mW	°C/W	V dc	V dc	V dc	A dc	A dc	A dc	A (pk)	°C
2N6660	6.25	725	20	60	60	±20	0.99	0.62	-0.99	3	−65 to
2N6661	6.25	725	20	90	90	±20	0.86	0.54	-0.86	3	+150

(1) Derate linearly by 0.05 W/°C for T_C > +25°C.
(2) R_{GS} ≤ 1 M ohm.
(3) The following formula derives the maximum theoretical I_D limit. I_D is limited by package and internal construction.

$$I_D = \sqrt{\frac{T_{JM} - T_C}{(R_{\theta JC}) \times (R_{DS}(on) \text{ at } T_{JM})}}$$

Comments, suggestions, or questions on this document should be addressed to DLA Land and Maritime, ATTN: VAC, P.O. Box 3990, Columbus, OH 43218-3990, or emailed to Semiconductor@dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil.

AMSC N/A

FSC 5961

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:07Z
Check the source to verify that this is the current version before use.

1.4 Primary electrical characteristics. T_C = +25°C unless otherwise noted.

Type	Min $V_{(BR)DSS}$ V_{GS} = 0 V I_D = 10 µA dc	$V_{GS(th)1}$ $V_{DS} \geq V_{GS}$ I_D = 1.0 mA dc	Max I_{DSS1} V_{GS} = 0 V	Max $r_{DS(on)}$ 1/ V_{GS} = 10 V dc	
			V_{DS} = 80 percent of rated V_{DS}	T_J = +25°C at I_{D1}	T_J = +150°C at I_{D2}
	V dc	V dc Min Max	µA dc	Ohm	Ohm
2N6660	60	0.8 2.0	1.0	3.0	6.33
2N6661	90	0.8 2.0	1.0	4.0	8.44

(1) Pulsed (see 4.5.1).

1.5 Part or Identifying Number (PIN). The PIN is in accordance with MIL-PRF-19500, and as specified herein. See 6.4 for PIN construction example and 6.5 for a list of available PINs.

1.5.1 JAN certification mark and quality level. The quality level designators for encapsulated devices that are applicable for this specification sheet from the lowest to the highest level are as follows: "JAN", "JANTX", "JANTXV" and "JANS".

1.5.2 Device type. The designation system for the devices covered by this specification sheet is as follows.

1.5.2.1 First number and first letter symbols. The devices of this specification sheet use the first number and letter symbols "2N".

1.5.2.2 Second number symbols. The second number symbols for the devices covered by this specification sheet are as follows: "6660" and "6661".

1.5.3 Lead finish. The lead finishes applicable to this specification sheet are listed on QPDSIS-19500.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-PRF-19500 Semiconductor Devices, General Specification for.

DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-750 – Test Methods for Semiconductor Devices.

(Copies of these documents are available online at https://quicksearch.dla.mil.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:07Z
Check the source to verify that this is the current version before use.

2.3 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.




FIGURE 1. Physical dimensions (TO-205AD).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:07Z
Check the source to verify that this is the current version before use.

	Dimensions				
LTR	Inches		Millimeters		Notes
	Min	Max	Min	Max	
CD	.305	.335	7.75	8.51	
CH	.240	.260	6.10	6.60	
HD	.335	.370	8.51	9.40	
TW	.028	.034	0.71	0.86	2
TL	.029	.045	0.74	1.14	3
LD	.016	.021	0.41	0.53	7,8
LL	.500	.750	12.70	19.05	7,8
LC	0.200 TP		5.08 TP		6
LU	.016	.019	0.41	0.48	7,8
L_1		.050		1.27	7,8
L_2	.250		6.35		7,8
P	.100		2.54		5
Q		.050		1.27	4
r		.010		0.25	9
α	45° TP		45° TP		6

NOTES:
1. Dimensions are in inches. Millimeters are given for general information only.
2. Beyond radius (r) maximum, dimension TW shall be held for a minimum length of .011 inch (0.28 mm).
3. Dimension TL measured from maximum HD.
4. Outline in this zone is not controlled.
5. Dimension CD shall not vary more than .010 inch (0.25 mm) in zone P. This zone is controlled for automatic handling.
6. Leads at gauge plane .054 +.001, −.000 inch (1.37 +0.03, −0.00 mm) below seating plane shall be within .007 inch (0.18 mm) radius of true position (TP) at maximum material condition (MMC) relative to tab at MMC.
7. Dimension LU applies between L_1 and L_2. Dimension LD applies between dimension L_2 and L minimum. Diameter is uncontrolled in dimension L_1 and beyond dimension LL minimum.
8. All three leads.
9. Radius (r) applies to both inside corners of tab.
10. Drain is electrically connected to the case.

FIGURE 1. Physical dimensions(TO-205AD) - Continued.

3. REQUIREMENTS

3.1 General. The individual item requirements shall be as specified in MIL-PRF-19500 and as modified herein.

3.2 Qualification. Devices furnished under this specification shall be products that are manufactured by a manufacturer authorized by the qualifying activity for listing on the applicable qualified manufacturer's list (QML) before contract award (see 4.2 and 6.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:07Z
Check the source to verify that this is the current version before use.

3.3 Abbreviations, symbols, and definitions. Abbreviations, symbols, and definitions used herein shall be as specified in MIL-PRF-19500.

3.4 Interface and physical dimensions. The interface and physical dimensions shall be as specified in MIL-PRF-19500 and on figure 1 (TO-205AD) herein.

3.4.1 Lead finish. Lead finish shall be solderable in accordance with MIL-PRF-19500, MIL-STD-750, and herein. Where a choice of lead finish is desired, it shall be specified in the acquisition document (see 6.2).

3.4.2 Internal construction. Multiple chip construction shall not be permitted.

3.5 Marking. Marking shall be in accordance with MIL-PRF-19500.

3.6 Electrical performance characteristics. Unless otherwise specified herein, the electrical performance characteristics are as specified in paragraph 1.3, 1.4 and table I.

3.7 Electrical test requirements. The electrical test requirements shall be as specified in table I.

3.8 Electrostatic discharge sensitive (ESDS). The devices covered by this specification sheet have been classified as ESDS. The devices shall be handled in accordance with the ESD program established to comply with the requirements of MIL-PRF-19500 to avoid damage due to the accumulation of static charge. The following handling practices shall be followed:

a. Devices shall be handled on benches with conductive handling devices.

b. Ground test equipment, tools and personnel handling devices.

c. Do not handle devices by the leads.

d. Store devices in conductive foam or carriers.

e. Avoid use of plastic, rubber or silk in MOS areas.

f. Maintain relative humidity above 50 percent if practical.

g. Care should be exercised during test and troubleshooting to apply not more than maximum rated voltage to any lead.

h. Gate must be terminated to source, $R \leq 100\ k\Omega$, whenever bias voltage is applied drain to source.

3.9 Workmanship. Semiconductor devices shall be processed in such a manner as to be uniform in quality and shall be free from other defects that will affect life, serviceability, or appearance.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. Qualification inspection (see 4.2).

b. Screening (see 4.3).

c. Conformance inspection (see 4.4 and table I).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:07Z
Check the source to verify that this is the current version before use.

4.2 Qualification inspection. Qualification inspection shall be in accordance with MIL-PRF-19500 and herein. Alternate flow is allowed for qualification inspection in accordance with MIL-PRF-19500.

4.2.1 Group E qualification. Group E inspection shall be performed for qualification or re-qualification only. In case qualification was awarded to a prior revision of the specification sheet that did not request the performance of table II tests, the tests specified in table II herein that were not performed in the prior revision shall be performed on the first inspection lot of this revision to maintain qualification.

4.3 Screening (quality levels JANS, JANTX and JANTXV only). Screening shall be in accordance with table E-IV of MIL-PRF-19500 and as specified herein. The following measurements shall be made in accordance with table I herein. Devices that exceed the limits of table I herein shall not be acceptable.

Screen (1) (2)	Measurement	
	JANS level	JANTX and JANTXV levels
(3)	Gate stress test (see 4.3.1)	Gate stress test (see 4.3.1)
(3) 3c	Method 3161 of MIL-STD-750, thermal impedance (see 4.3.2)	Method 3161 of MIL-STD-750, thermal impedance (see 4.3.2)
9	Subgroup 2 of table I herein. I_{DSS1}, I_{GSSF1}, I_{GSSR1}	Not applicable
10	Method 1042 of MIL-STD-750, test condition B	Method 1042 of MIL-STD-750, test condition B
11	I_{GSSF1}, I_{GSSR1}, I_{DSS1}, $r_{DS(on)1}$, $V_{GS(TH)1}$. Subgroup 2 of table I herein. ΔI_{GSSF1} = ±20 nA dc or ±100 percent of initial value, whichever is greater. ΔI_{GSSR1} = ±20 nA dc or ±100 percent of initial value, whichever is greater. ΔI_{DSS1} = ±10 µA dc or ±100 percent of initial value, whichever is greater.	I_{GSSF1}, I_{GSSR1}, I_{DSS1}, $r_{DS(on)1}$, $V_{GS(TH)1}$. Subgroup 2 of table I herein.
12	Method 1042 of MIL-STD-750, test condition A.	Method 1042 of MIL-STD-750, test condition A.
13	Subgroups 2 and 3 of table I herein. ΔI_{GSSF1} = ±10 nA dc or ±100 percent of initial value, whichever is greater. ΔI_{GSSR1} = ±10 nA dc or ±100 percent of initial value, whichever is greater. ΔI_{DSS1} = ±1 µA dc or ±100 percent of initial value, whichever is greater. $\Delta r_{DS(on)1}$ = ±20 percent of initial value or ±0.5 ohm, whichever is greater. $\Delta V_{GS(TH)1}$ = ±10 percent of initial value or ±0.3 V dc.	Subgroup 2 of table I herein. ΔI_{GSSF1} = ±10 nA dc or ±100 percent of initial value, whichever is greater. ΔI_{GSSR1} = ±10 nA dc or ±100 percent of initial value, whichever is greater. ΔI_{DSS1} = ±1 µA dc or ±100 percent of initial value, whichever is greater. $\Delta r_{DS(on)1}$ = ±20 percent of initial value or ±0.5 ohm, whichever is greater. $\Delta V_{GS(TH)1}$. = ±10 percent of initial value or ±0.3 V dc.

(1) At the end of the test program, I_{GSSF1}, I_{GSSR1}, and I_{DSS1} are measured.
(2) An out-of-family program to characterize I_{GSSF1}, I_{GSSR1}, I_{DSS1} and $V_{GS(th)1}$ shall be invoked.
(3) Shall be performed anytime after temperature cycling, screen 3a; JANTX and JANTXV levels do not need to be repeated in screening requirements.

4.3.1 Gate stress test. Apply V_{GS} = 30 V minimum for t = 250 µs minimum.

4.3.2 Thermal impedance. The thermal impedance measurements shall be performed in accordance with method 3161 of MIL-STD-750 using the guidelines in that method for determining I_M, I_H, t_H, t_{SW}, t_{MD} (and V_H where appropriate). See group E, table II, subgroup 4 herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:07Z
Check the source to verify that this is the current version before use.

4.4 Conformance inspection. Conformance inspection shall be in accordance with MIL-PRF-19500.

4.4.1 Group A inspection. Group A inspection shall be conducted in accordance with MIL-PRF-19500 and table I herein.

4.4.2 Group B inspection. Group B inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-VIA (JANS) and table E-VIB (JAN, JANTX, and JANTXV) of MIL-PRF-19500, and herein.

4.4.2.1 Quality level JANS.

Subgroup	Method	Conditions
B3	1051	Test condition G.
B4	1042	Test condition D; 2,000 cycles. The heating cycle shall be 1 minute minimum. V_{DS} = 10 V dc, P_T = See 1.4 at T_A = +25°C ±3°C.
B5	1042	Accelerated steady-state operation life; test condition C; T_A = + 25°C, −5°C, +10°C, V_{DS} = 10 V min.; I_D adjusted to meet a junction temperature of 140°C, −0°C, +10°C, t = 240 hours.
B5	2037	Bond strength (Al-Au die interconnects only); test condition D.

4.4.2.2 Quality levels JAN, JANTX, and JANTXV.

Subgroup	Method	Condition
B2	1051	Test condition G, 25 cycles.
B3	1042	Intermittent operation life, condition D, 2,000 cycles. No heat sink or forced air cooling on the device shall be permitted during the on cycle; t_{on} = 30 seconds minimum.

4.4.3 Group C inspection. Group C inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-VII of MIL-PRF-19500 and as follows.

Subgroup	Method	Condition
C2	2036	Test condition E.
C5	3161	Thermal resistance, see 4.5.2, $R_{\theta JC(max)}$ = 20°C/W.
C6	1042	Intermittent operation life, condition D, 6,000 cycles. No heat sink or forced air cooling on the device shall be permitted during the on cycle; t_{on} = 30 seconds minimum.

4.4.4 Group E inspection. Group E inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-IX of MIL-PRF-19500 and as specified in table II herein.

4.5 Methods of inspection. Methods of inspection shall be as specified in the appropriate tables and as follows.

4.5.1 Pulse measurements. Conditions for pulse measurement shall be as specified in section 4 of MIL-STD-750.

4.5.2 Thermal resistance. The thermal resistance measurements shall be performed in accordance with method 3161 of MIL-STD-750 using the guidelines in that method for determining I_M, I_H, t_H, t_{SW}, t_{MD} (and V_H where appropriate). See table E-IX of MIL-PRF-19500, group E, subgroup 4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:07Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection.

Inspection 1/	MIL-STD-750		Symbol	Limits		Unit
	Method	Conditions		Min	Max	
Subgroup 1						
Visual and mechanical examination	2071					
Subgroup 2						
Thermal impedance 2/	3161	See 4.3.1	$Z_{\theta JC}$			°C/W
Breakdown voltage, drain to source 2N6660 2N6661	3407	Bias condition C, V_{GS} = 0 V; I_D = 1.0 µA dc	$V_{(BR)DSS}$	 60 90		
Gate to source voltage (threshold)	3403	$V_{DS} > V_{GS}$; I_D = 1.0 mA dc	$V_{GS(th)1}$	0.8	2.0	V dc
Gate current	3411	Bias condition C; V_{DS} = 0 V; V_{GS} = +20 V dc	I_{GSSF1}		+100	nA dc
Gate current	3411	Bias condition C; V_{DS} = 0 V; V_{GS} = −20 V dc	I_{GSSR1}		−100	nA dc
Drain current	3413	Bias condition C; V_{GS} = 0; V_{DS} = 80 percent of rated V_{DS} (see 1.3)	I_{DSS1}		1.0	µA dc
Static drain to source on-state resistance 2N6660 2N6661	3421	Condition A; V_{GS} = 10 V dc; pulsed (see 4.5.1); I_D = 1.0 A dc	$r_{DS(on)1}$	 	 3.0 4.0	 ohms ohms
Static drain to source on-state resistance 2N6660 2N6661	3421	Condition A; V_{GS} = 5 V dc; pulsed (see 4.5.1); I_D = 0.3 A dc	$r_{DS(on)2}$	 	 5.0 5.3	 ohms ohms
Forward voltage (source drain diode) 2N6660 2N6661	4011	Condition A, pulsed (see 4.5.1); V_{GS} = 0 V I_S = 0.99 A dc I_S = 0.86 A dc	V_{SD}	 0.7 0.7	 1.6 1.4	 V(pk) V(pk)
Forward transconductance 2N6660 2N6661	3475	Pulsed (see 4.5.1), V_{DS} = V_{GS} = 7.5 V dc I_{D1} = 525 m A dc I_{D2} = 475 m A dc	g_{FS}	170		ms

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:07Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limits		Unit
	Method	Conditions		Min	Max	
Subgroup 3						
High temperature operation		T_C = +125°C				
Gate current	3411	Bias condition C, V_{DS} = 0 V; V_{GS} = +20 V dc or −20 V dc	I_{GSS2}		±500	nA dc
Drain current	3413	Bias condition C, V_{GS} = 0 V, V_{DS} = −80 percent of rated V_{DS} (see 1.3)	I_{DSS2}		100	µA dc
Static drain to source on-state resistance 2N6660 2N6661	3421	V_{GS} = 10 V dc; condition A; pulsed (see 4.5.1); I_D = 1.0 A dc	$r_{DS(on)3}$		 5.6 7.5	ohms
Gate to source voltage (threshold)	3403	$V_{DS} \geq V_{GS}$, I_D = 1.0 mA dc	$V_{GS(th)2}$	0.3		V dc
Low temperature operation:		T_C = −55°C				
Gate to source voltage (threshold)	3403	$V_{DS} \geq V_{GS}$; I_D = 1.0 mA	$V_{GS(th)3}$		2.5	V dc
Subgroup 4						
Switching time test	3472	R_{GS} = 23 Ω, R_L = 23 Ω , V_{GEN} = 10 V				
Turn-on delay time		V_{DD} = 25 V dc; $I_D \cong$ 1 A dc,	$t_{d(on)}$		10	ns
Turn-off delay time		V_{DD} = 25 V dc; $I_D \cong$ 1 A dc	$t_{d(off)}$		10	ns
Small signal common source short-circuit input capacitance	3431	V_{DS} = 25 V dc; V_{GS} = 0 V; f = 1 MHz	C_{iss}		50	pF
Small signal common source short-circuit output capacitance		V_{DS} = 25 V dc; V_{GS} = 0 V; f = 1 MHz	C_{oss}		40	pF
Small signal common source short-circuit reverse transfer capacitance	3433	V_{DS} = 25 V dc; V_{GS} = 0 V; f = 1 MHz	C_{rss}		10	pF

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:07Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limits		Unit
	Method	Conditions		Min	Max	
Subgroup 4 – Continued.						
Small signal common source short-circuit input capacitance	3431	V_{DS} = 25 V dc; V_{GS} = 0 V; f = 1 MHz	C_{iss}		50	pF
Small signal common source short-circuit output capacitance		V_{DS} = 25 V dc; V_{GS} = 0V; f = 1 MHz	C_{oss}		40	pF
Small signal common source short-circuit reverse transfer capacitance	3433	V_{DS} = 25 V dc; V_{GS} = 0 V; f = 1 MHz	C_{rss}		10	pF
Subgroup 5						
Safe operating area		See figure 2				
High voltage test		V_{DS} = 80 percent of rated V_{DS} (see 1.3)				
Electrical measurements		See table I, subgroup 2				
Subgroups 6 and 7						
Not applicable						

1/ For sampling plan, see MIL-PRF-19500.
2/ For end-point measurements, this test required for the following subgroups:
Group B, subgroups 3, 4 and 5 (JANS).
Group B, subgroups 2 and 3 (JAN, JANTX, and JANTXV).
Group C, subgroup 2 and 6.
Group E, subgroup 1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:07Z
Check the source to verify that this is the current version before use.

TABLE II. Group E inspection (all quality levels) for qualification or re-qualification only.

Inspection	MIL-STD-750		Sample plan
	Method	Conditions	
Subgroup 1			45 devices, c = 0
Temperature cycling	1051	Test condition G, 500 cycles	
Hermetic seal Fine leak Gross leak	1071		
Electrical measurements		See table I, subgroup 2	
Subgroup 2			45 devices, c = 0
Steady-state reverse bias	1042	Condition A, 1,000 hours	
Electrical measurements		See table I, subgroup 2	
Steady-state gate bias	1042	Condition B, 1,000 hour	
Electrical measurements		See table I, subgroup 2	
Subgroup 4			Sample size, N/A
Thermal impedance curves		See MIL-PRF-19500	
Subgroup 10			22 devices, c = 0
Commutating diode for safe operating area test procedure for measuring dv/dt during reverse recovery of power MOSFET transistors or insulated gate bipolar transistors	3476	Test conditions shall be derived by the manufacturer	

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:07Z
Check the source to verify that this is the current version before use.




FIGURE 2. Maximum safe operating area.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:07Z
Check the source to verify that this is the current version before use.




FIGURE 2. Maximum safe operating area - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:07Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the Military Service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory. The notes specified in MIL-PRF-19500 are applicable to this specification.)

6.1 Intended use. Semiconductors conforming to this specification are intended for original equipment design applications and logistic support of existing equipment.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.


b. Packaging requirements (see 5.1).

c. Lead finish (see 3.4.1).

d. The complete PIN, see 1.5 and 6.4.

6.3 Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time of award of contract, qualified for inclusion in Qualified Manufacturers List (QML 19500) whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. Information pertaining to qualification of products may be obtained from DLA Land and Maritime, ATTN: VQE, P.O. Box 3990, Columbus, OH 43218-3990 or e-mail vqe.chief@dla.mil. An online listing of products qualified to this specification may be found in the Qualified Products Database (QPD) at https://qpldocs.dla.mil.

6.4 PIN construction example. The PINs for encapsulated devices are constructed using the following form.



6.5 List of PINs. The following is a list of all possible PINs for the devices available on this specification sheet.

Quality level "JAN"	Quality level "JANTX"	Quality level "JANTXV"	Quality level "JANS"
JAN2N6660	JANTX2N6660	JANTXV2N6660	JANS2N6660
JAN2N6661	JANTX2N6661	JANTXV2N6661	JANS2N6661

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:07Z
Check the source to verify that this is the current version before use.

6.6 Request for new types and configurations. Requests for new device types or configurations for inclusions in this specification sheet should be submitted to: DLA Land and Maritime, ATTN: VAC, Post Office Box 3990, Columbus, OH 43218-3990 or by electronic mail at Semiconductor@dla.mil or by facsimile (614) 693-1642 or DSN 850-6939.

6.7 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army − CR
Navy − EC
Air Force − 85
DLA − CC

Review activity:
Army − AR

Preparing activity:
DLA − CC

(Project 5961−2019−103)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:07Z
Check the source to verify that this is the current version before use.