The documentation and process conversion measures necessary to comply with this revision shall be completed by 26 November 2011.

INCH-POUND

MIL-PRF-19500/551E
26 August 2011
SUPERSEDING
MIL-PRF-19500/551D
18 October 2010

PERFORMANCE SPECIFICATION SHEET

SEMICONDUCTOR DEVICE, DIODE, SILICON, TRANSIENT VOLTAGE SUPPRESSOR TYPES 1N6461 THROUGH 1N6468, 1N6461US THROUGH 1N6468US, AND 1N6461URS THROUGH 1N6468URS, JAN, JANTX, AND JANTXV

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-19500.

1. SCOPE

1.1 Scope. This specification covers the performance requirements for 500-watt peak pulse, power, silicon, transient voltage suppressor diodes. Three levels of product assurance are provided for each device type as specified in MIL-PRF-19500.

1.2 Physical dimensions. See figures 1, 2, and 3.

1.3 Maximum ratings. Maximum ratings are as shown in columns 4, 6, and 7 of the electrical characteristics table herein and as follows:

a. P_R = 2.5 W (T_A = room ambient as defined in the general requirements of 4.5 of MIL-STD-750). Derate at 16.7 mW/°C for leaded devices and 50 mW/°C for surface mount devices (see figure 4).

b. P_{PR} = 500 W (see figure 5) at t_p = 1 ms.

c. I_{FSM} = 80 A(pk) at t_p = 8.33 ms (T_A = +25°C).

d. -55°C ≤ T_{op} ≤ +175°C; -55°C ≤ T_{STG} ≤ +175°C (ambient).

1.4 Primary electrical characteristics. Primary electrical characteristic columns 2 and 4 of the electrical characteristics herein.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3, 4, or 5 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3, 4, or 5 of this specification, whether or not they are listed.

* Comments, suggestions, or questions on this document should be addressed to DLA Land and Maritime, ATTN: VAC, P.O. Box 3990, Columbus, OH 43218-3990, or emailed to Semiconductor@dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.daps.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:10Z
Check the source to verify that this is the current version before use.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-PRF-19500 - Semiconductor Devices, General Specification for.

DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-750 - Test Methods for Semiconductor Devices.

(Copies of these documents are available online at https://assist.daps.dla.mil/quicksearch/ or https://assist.daps.dla.mil or from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

2.3 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 General. The individual item requirements shall be as specified in MIL-PRF-19500 and as modified herein.

3.2 Qualification. Devices furnished under this specification shall be products that are manufactured by a manufacturer authorized by the qualifying activity for listing on the applicable qualified manufacturers list (QML) before contract award (see 4.2 and 6.3).

3.3 Abbreviations, symbols, and definitions. Abbreviations, symbols, and definitions used herein shall be as specified in MIL-PRF-19500 and as follows:

I_P Maximum peak pulse current at a specified condition.
$I_{(BR)}$ Reverse breakdown current at a specified condition.
T_{EC} End-cap temperature.

3.4 Interface requirements and physical dimensions. The interface requirements and physical dimensions shall be as specified in MIL-PRF-19500 and on figures 1, 2, and 3 herein. The surface mount devices (US and URS) shall be structurally identical to the "non US" version except for lead attachment.

3.4.1 Construction. These devices shall be constructed utilizing metallurgically bonded noncavity double plug construction between both sides of the silicon die and the terminal pins.

3.4.2 Lead finish. Lead finish shall be solderable as defined in MIL-PRF-19500, MIL-STD-750, and herein. Where a choice of lead finish is desired, it shall be specified in the acquisition document (see 6.2).

3.4.3. Metallurgical bond construction. Devices shall be metallurgically bonded, thermally matched, noncavity-double plug construction in accordance with MIL-PRF-19500, and herein.

3.5 Marking. Marking shall be in accordance with MIL-PRF-19500.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:10Z
Check the source to verify that this is the current version before use.


3.5.1 Marking of US and URS versions. For US and URS versions only, all marking may be omitted from the device except for the cathode marking. US and URS devices shall be marked with a cathode band as a minimum, or a minimum of three evenly spaced contrasting color dots around the periphery of the cathode end may be used. At the option of the manufacturer, US and URS devices may include laser marking on an end-cap, to include part number and lot date code for all levels. The prefixes JAN, JANTX, or JANTXV may be abbreviated as J, JX, or JV respectively. (For example: The part number may be reduced to JV6461).

3.6 Electrical performance characteristics. Unless otherwise specified herein, the electrical performance characteristics are as specified in 1.3, 1.4, and table I herein.


3.7 Electrical test requirements. The electrical test requirements shall be the subgroups specified in 1.3 and table I herein.

3.8 Workmanship. Semiconductor devices shall be processed in such a manner as to be uniform in quality and shall be free from other defects that will affect life, serviceability, or appearance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:10Z
Check the source to verify that this is the current version before use.




Ltr	Dimensions				Notes
	Inches		Millimeters		
	Min	Max	Min	Max	
BD	.115	.145	2.92	3.68	3, 4
BL	.150	.300	3.81	7.62	4
LD	.037	.042	0.94	1.07	4
LL	.900	1.300	22.86	33.02	
LL_1		.050		1.27	4


schematic symbol


NOTES:
1. Dimensions are in inches.
2. Millimeters are given for general information only.
3. Dimension BD shall be measured at the largest diameter.
4. Dimension BL includes dimension LL_1 region in which the diameter may vary from BD maximum to LD minimum.
5. In accordance with ASME Y14.5M, diameters are equivalent to Φx symbology.

* FIGURE 1. Physical dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:10Z
Check the source to verify that this is the current version before use.



Ltr	Dimensions			
	Inches		Millimeters	
	Min	Max	Min	Max
BD	.137	.148	3.48	3.76
BL	.200	.225	5.08	5.72
ECT	.019	.028	0.48	0.71
S	.003		0.08	




schematic symbol

NOTES:
1. Dimensions are in inches.
2. Millimeters are given for general information only.
3. Referencing to dimension S, minimum clearance of glass body to mounting surface on all orientations.
4. Dimensions are pre-solder dip.
5. In accordance with ASME Y14.5M, diameters are equivalent to Φx symbology.

* FIGURE 2. Physical dimensions surface mount devices “US”.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:10Z
Check the source to verify that this is the current version before use.



Ltr	Dimensions			
	Inches		Millimeters	
	Min	Max	Min	Max
BD	.137	.148	3.48	3.76
BL	.200	.225	5.08	5.72
ECT	.019	.028	0.48	0.71
S	.003		0.08	

NOTES:
1. Dimensions are in inches.
2. Millimeters are given for general information only.
3. Dimensions are pre-solder dip.
4. One end-cap shall be square and the other end-cap shall be round.
5. In accordance with ASME Y14.5M, diameters are equivalent to Φx symbology.
6. The cathode shall be connected to the round endcap.

* FIGURE 3. Physical dimensions, surface mount devices "URS".

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:10Z
Check the source to verify that this is the current version before use.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. Qualification inspection (see 4.2).

b. Screening (see 4.3).

c. Conformance inspection (see 4.4 and tables I, II, and III).

4.1.1 Sampling and inspection. Sampling and inspection shall be in accordance with MIL-PRF-19500, and as specified herein. Lot accumulation period shall be 3 months in lieu of 6 weeks.

4.2 Qualification inspection. Qualification inspection shall be in accordance with MIL-PRF-19500.

* 4.2.1 Group E qualification. Group E inspection shall be performed for qualification or re-qualification only. In case qualification was awarded to a prior revision of the specification sheet that did not require the performance of table III tests, the tests specified in table III herein that were not performed in the prior revision shall be performed on the first inspection lot of this revision to maintain qualification.

4.3 Screening (JANTX and JANTXV levels only). Screening shall be in accordance with table E-IV of MIL-PRF-19500, and as specified herein. The following measurements shall be made in accordance with table I herein. Devices that exceed the limits of table I herein shall not be acceptable.

Screen (see table E-IV of MIL-PRF-19500)	Measurement
	JANTX and JANTXV levels
9	Not applicable
11	Not applicable
12	See 4.3.1
13	Not applicable

4.3.1 Burn-in (HTRB) and steady-state operation life (HTRB) conditions. This test shall be conducted with the devices subjected to test conditions in the following order of events and conditions:

a. Pulse in accordance with 4.5.2b herein 20 times (screening and group B operation life test) and 100 times (group C) at T_A = room ambient as defined in the general requirements of MIL-STD-750.

b. Read and record I_D and V_{BR} at T_A = room ambient as defined in the general requirements of MIL-STD-750. Remove defective devices, and record the number of failures.

(1) For 96 hours (JANTX and JANTXV) for the screening test.

(2) For 340 hours (JANTX and JANTXV) for group B, steady-state operation life test.

(3) For 1,000 hours for group C, steady-state operation life test.

Read and record I_D and $V_{(BR)}$ at T_A = room ambient as defined in the general requirements of MIL-STD-750. Devices with ΔI_D > 50 percent (100 percent for steady-state operation life) of initial value, or 20 percent of column 5 of table II, whichever is greater, or $\Delta V_{(BR)}$ = ±2 percent (±5 percent for steady-state operation life) of initial value shall be considered defective. Remove defective devices and record the number of failures.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:10Z
Check the source to verify that this is the current version before use.

4.4 Conformance inspection. Conformance inspection shall be in accordance with MIL-PRF-19500 and as herein.

4.4.1 Group A inspection. Group A inspection shall be conducted in accordance with MIL-PRF-19500 and table I herein. End-point electrical measurements shall be in accordance with table I, subgroup 2 herein.

4.4.2 Group B inspection. Group B inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-VIB (JAN, JANTX, and JANTXV) of MIL-PRF-19500 and 4.4.2.1 herein. Electrical measurements (end-points) shall be in accordance with table I, subgroup 2 herein.

4.4.2.1 Group B inspection, table E-VIB of MIL-PRF-19500.

Subgroup	Method	Conditions
B3	1026	T_A = +125°C, (see 4.3.1).
B5	4081	$R_{\Theta JL} \leq 60$°C/W at L = .375 inches (9.53 mm), non-surface mount devices; $R_{\Theta JEC} \leq 20$°C/W at L = 0 inches for surface mount devices.

4.4.3 Group C inspection. Group C inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-VII of MIL-PRF-19500 and as follows. Electrical measurements (end-points) shall be in accordance with table I, subgroup 2 herein.

4.4.3.1 Group C inspection, table E-VII of MIL-PRF-19500.

Subgroup	Method	Conditions
C2	2036	Test condition A; weight = 12 pounds; t = 15 seconds minimum, (not applicable to surface mount devices).
C2	2036	Test condition E (not applicable to surface mount devices).
C5	4081	$R_{\Theta JL} \leq 60$°C/W at L = .375 inches (9.53 mm), non-surface mount devices; $R_{\Theta JEC} \leq 20$°C/W at L = 0 inches for surface mount devices.
C6	1026	T_A = +125°C, (see 4.3.1). Leaded samples from the same lot may be used in lieu of surface mount devices.
C7	4071	$I_{(BR)}$ = column 3 of table II, $\alpha V_{(BR)}$, T_1 = +25°C ±3°C; T_2 = +125°C ±3°C; maximum limits = column 8 of table II. Sample size: 22 devices, c = 0.
C8		See 4.5.2.a, ten pulses, sample size: 22 devices, c = 0.

* 4.4.4 Group E inspection. Group E inspection shall be conducted in accordance with the tests and conditions specified for subgroup testing in table E-IX of MIL-PRF-19500, and table III herein. Electrical measurements (end-points) shall be in accordance with table I, subgroup 2 herein.

4.5 Methods of inspection. Methods of inspection shall be as specified in the appropriate tables and as follows.

4.5.1 Pulse measurements. Conditions for pulse measurement shall be as specified in section 4 of MIL-STD-750.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:10Z
Check the source to verify that this is the current version before use.

4.5.2 Maximum peak pulse current (I_{PP}). The peak currents specified in column 7 of table II shall be applied in the reverse direction while simultaneously maintaining a reverse bias voltage of not less than the applicable voltage specified in column 4 of table II. The peak current shall be applied with a current versus time waveform as follows (one pulse per minute maximum):

a. Pulse current shall reach 100 percent of I_{PP} at $t \leq 8$ μs and decay to 50 percent at $t \geq 20$ μs for $t_p = 20$ μs (see figure 6).

b. Pulse current shall reach 100 percent of I_{PP} at $t \leq 10$ μs and decay to 50 percent at $t \geq 1$ ms for $t_p = 1$ ms (see figure 7).

NOTE: Tolerance on pulse time shall be ±10 percent.

4.5.3 Clamping voltage V_C. The peak pulse clamping voltage shall be measured across the diode in a 1 ms time interval. The response detector shall demonstrate equipment accuracy of ±3 percent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:10Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection.

Inspection 1/	MIL-STD-750		Symbol	Limits 2/		Unit
	Method	Conditions		Min	Max	
Subgroup 1						
Visual and mechanical examination	2071					
Subgroup 2						
Standby current	4016	DC method; $V_R = V_{RWM}$ (column 4 of table II)	I_D		Column 5 of table II	μA dc
Breakdown voltage	4022	$t_p \leq 300$ ms, duty cycle ≤ 2 percent; $I_{(BR)}$ = column 3 of table II	$V_{(BR)1}$	Column 2 of table II		V dc
Forward voltage	4011	$I_F = 1$ A dc	V_F		1.5	V (pk)
Subgroup 3						
Low temperature operation		$T_A = -55°C$				
Breakdown voltage	4022	$t_p \leq 300$ ms, duty cycle ≤ 2 percent; $I_{(BR)}$ = column 3 of table II.	$V_{(BR)2}$	Column 9 of table II		V dc
Subgroup 4						
Clamping voltage (see 4.5.3)		$t_p = 1.0$ ms (see 4.5.2.b) I_{PP} = column 7 of table II	V_C		Column 6 of table II	V (pk)
Subgroup 5						
Not applicable						
Subgroup 6						
Forward surge current	4066	One pulse, half sine wave 8.3 ms; $I_F = 0$, $V_{RWM} = 0$, $T_A = +25°C$	I_{FSM}		80	A (pk)
Electrical measurements		See table I, subgroup 2				
Subgroup 7						
Clamping voltage inverse polarity maximum (see 4.5.3)		$t_p = 1.0$ ms (see 4.5.2.b) except use forward direction current without prior bias voltage	$-V_C$		Column 11 of table II	V (pk)

1/ For sampling plan, see MIL-PRF-19500.
2/ Column references are to table II herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:10Z
Check the source to verify that this is the current version before use.

TABLE II. Electrical characteristics. 1/

Col 1	Col 2	Col 3	Col 4	Col 5	Col 6	Col 7		Col 8	Col 9	Col 10	Col 11
	$V_{(BR)1}$ at $I_{(BR)}$	$I_{(BR)}$	V_{RWM}	I_D at V_{RWM}	V_C at I_{PP} for t_p = 1 ms	I_{PP}		$\alpha V_{(BR)}$	$V_{(BR)2}$ Minimum at I_{BR} T_A = - 55°C	(I_{RM}) Maximum dc current T_A = + 25°C	-V_C at t_p = 1 ms A(pk) = in accordance with column 7 inverse polarity
						t_p = 20 µs t_r = 8 µs	t_p = 1 ms t_r = 10 µs				
	V dc	mA dc	V (pk)	µA dc	V (pk)	A (pk)	A (pk)	%/°C	V dc	mA	V(pk)
1N6461	5.6	25	5	3,000	9.0	315	56	-0.03, +0.045	5.4	367	-3.5
1N6462	6.5	20	6	2,500	11.0	258	46	+0.060	6.2	304	-3.2
1N6463	13.6	5	12	500	22.6	125	22	+0.085	13.0	139	-3.8
1N6464	16.4	5	15	500	26.5	107	19	+0.085	15.6	63	-3.8
1N6465	27.0	2	24	50	41.4	69	12	+0.096	25.1	39	-3.6
1N6466	33.0	1	30.5	3	47.5	63	11	+0.098	30.2	34	-3.6
1N6467	43.7	1	40.3	2	63.5	45	8	+0.101	40.0	46	-3.5
1N6468	54.0	1	51.6	2	78.5	35	6	+0.103	48.5	20	-3.4

1/ These limits apply to the US and URS device types also.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:10Z
Check the source to verify that this is the current version before use.

* TABLE III. Group E inspection (all quality levels) for qualification only.

Inspection	MIL-STD-750		Sampling plan
	Method	Conditions	
Subgroup 1			45 devices, c = 0
Temperature cycling	1051	500 cycles, condition C, -55°C to +175°C	
Electrical measurements		See table I, subgroup 2	
Subgroup 2			22 devices, c = 0
Life test	1048	1,000 hours. See 4.3.1	
Electrical measurements		See table I, subgroup 2	
Subgroups 3, 4 and 5			
Not applicable			
Subgroup 7			3 devices, c = 0
* Soldering heat	2031		
Subgroup 8			
Peak pulse current		See 4.5.2. I_{PP} shall be characterized by the supplier and this data shall be available to the Government. Test shall be performed on each low and high voltage device for each structurally identical grouping. Test to failure.	
Electrical measurements		See table I, subgroup 2	
Subgroup 9			
Resistance to glass cracking.	1057	Condition B	

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:10Z
Check the source to verify that this is the current version before use.




FIGURE 4. Derating curve.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:10Z
Check the source to verify that this is the current version before use.




FIGURE 5. Peak pulse power versus pulse time.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:10Z
Check the source to verify that this is the current version before use.




FIGURE 6. Current impulse waveform.




FIGURE 7. Current impulse waveform.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:10Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the Military Service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory. The notes specified in MIL-PRF-19500 are applicable to this specification.)

6.1 Intended use. Semiconductors conforming to this specification are intended for original equipment design applications and logistic support of existing equipment.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. Lead finish (see 3.4.2).

c. Packaging requirements (see 5.1).

d. Product assurance level and type designator.

e. Destructive physical analysis when requested.

6.3 Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time of award of contract, qualified for inclusion in Qualified Manufacturers List (QML 19500) whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. Information pertaining to qualification of products may be obtained from DLA Land and Maritime, ATTN: VQE, P.O. Box 3990, Columbus, OH 43218-3990 or e-mail vqe.chief@dla.mil . An online listing of products qualified to this specification may be found in the Qualified Products Database (QPD) at https://assist.daps.dla.mil .

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:10Z
Check the source to verify that this is the current version before use.

6.4 Changes from previous issue. The margins of this specification are marked with asterisks to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - CR
Navy - EC
Air Force - 85
NASA - NA
DLA - CC

Preparing activity:
DLA - CC

(Project 5961-2011-048)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.daps.dla.mil .

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:10Z
Check the source to verify that this is the current version before use.