# FEDERAL SPECIFICATION

## BASKETS, WASTEPAPER, PLASTIC

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

## 1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers requirements for rectangular shaped, molded plastic wastepaper baskets.

1.2 Classification.

1.2.1 Size. The wastepaper basket shall be one size (see 3.1).

1.2.2 Color. Color of baskets shall be as specified in the invitations for bid, contract or order (see 3.4 and 6.2).

## 2. APPLICABLE DOCUMENTS

2.1 The following documents of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specification:

PPP-B-636 - Boxes, Shipping, Fiberboard.

Federal Standard:

Fed. Std. No. 123 - Marking for Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration, Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:11Z
Check the source to verify that this is the current version before use.

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Traffic Department, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

3. REQUIREMENTS

3.1 Design. The wastepaper basket described in this specification shall be one size. The basket shall be rectangular in shape and tapered so that the basket is longer and wider at the top than at the bottom. The basket shall meet the dimension requirements of Table I.

TABLE I. Outside dimensions inches (± 0.5000 inches)

| Characteristics | Dimensions |
|---|---|
| Overall Height | 12.00 |
| Width at top | 8.00 |
| Length at top | 11.250 |
| Width at bottom | 6.00 |
| Length at bottom | 9.250 |

3.2 Construction. All wastepaper baskets shall be molded and seamless. All interior and exterior horizontal and vertical edges and corners shall be rounded.

3.3 Material. The wastepaper baskets shall be made from a plastic material that meets the requirements of paragraphs 3.3.1, 3.3.2 and 3.3.3.

3.3.1 Fire hazard. When tested as specified in 4.3.1, the wastepaper basket shall contain the fire, shall not fuel the fire, and shall not spill the contents or parts of the basket on the floor. During the fire test, the sheets of paper underneath the wastepaper basket shall not ignite.

3.3.2 Water tightness. When tested as specified in 4.3.2, the wastepaper baskets shall not leak.

3.3.3 Physical requirements. When tested as specified in 4.3.3, the wastepaper baskets shall not deform, crack, split or buckle.

3.4 Color. The wastepaper baskets interior and exterior surfaces shall be the color specified (see 6.2).

3.5 Marking for identification. The exterior bottom of each basket shall be legibly marked with the contractor's name or trademark, in letters a minimum of 1/8 inch in height, using one of the following methods. Hot stamp, embossing or molded into the basket concurrent to molding the basket.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:11Z
Check the source to verify that this is the current version before use.

3.6 Workmanship. Workmanship shall conform to the quality of product established by this specification. The finished wastepaper baskets shall present a neat finished appearance both inside and outside and shall exhibit no evidence of sharp, jagged or rough molding. The wastepaper baskets shall be free from defects which may affect their durability, serviceability or appearance.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Inspection. Sampling for inspection and testing for acceptance of the end item shall be performed in accordnace with MIL-STD-105, except where otherwise indicated hereinafter.

4.2.1 Inspection of the end item.

4.2.1.1 Examination of the end item. The defects found during examination shall be classified in accordance with 4.2.1.1.1 and 4.2.1.1.2. The inspection levels shall be as indicated in 4.2.1.1.3.

4.2.1.1.1 Visual examination. Visual examination of the end item for defects in appearance, construction, and workmanship shall be in accordance with Table II.

TABLE II.

| Examine | Defect |
|---|---|
| Color of basket | Not required color.<br>Color not uniform. |
| Workmanship | Molded plastic not uniform, evidence of cracks, crazing, deformation, bubbles, flow lines, or wrinkles affecting serviceability or appearance.<br><br>Evidence of sharp edges.<br>Corners and edges not rounded. |

4.2.1.1.2 Dimensional examination. Any dimension not within the limits specified shall be classified as a defect.

4.2.1.1.3 Acceptable quality levels (AQL's) and inspection levels. The AQL's expressed in percent defective and the inspection level shall be: Inspection level II; AQL 6.5.

4.2.2 Testing.

4.2.2.1 Testing of end item. The test sample shall consist of 3 baskets randomly selected from the sample taken for visual examination, which shall be subject to the tests outlined in 4.3.1, 4.3.2, and 4.3.3, using the following procedures. Mark each unit with number 1, 2, or 3, and administer tests in the manner indicated below to the baskets as numbered. Each basket shall satisfactorily pass the tests as prescribed.

| Basket Number | Test Title | Paragraph Number |
|---|---|---|
| 1 | Flammability test | 4.3.1 |
| 2 | Leakage test | 4.3.2 |
| 3 | Physical test | 4.3.3 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:11Z
Check the source to verify that this is the current version before use.

4.3 Tests.

4.3.1 Flammability test. Testing shall be performed in a draft-free area away from any wall or other obstruction. Place two sheets of newspaper flat on a concrete floor, and place sample wastepaper basket in the center of the newspaper. Fill the wastepaper basket to approximately 3 inches below the rim with wadded combustible paper consisting of approximately equal amounts of intermingled carbon paper, writing paper and newspaper, and three empty 1-pint milk cartons of the standard retail variety, having a protective wax or plastic coating. The bulk density of the combustible material, including the cartons, shall be not less than 5.1 ounces per cubic foot of the wastepaper basket. Ignite the paper and permit it to burn naturally. After the fire has completely extinguished itself, examine the basket to insure that the basket meets the requirements of 3.3.1.

4.3.2 Leakage test. Fill the basket with water to within 3 inches of the top, allow to stand for one hour. Examine to determine compliance with 3.3.2.

4.3.3 Weight test. Place the basket bottom up, on a level surface. Place a 300 pound weight on the turned-up bottom of the basket. This weight may be in the form of sandbags, stacked weights, or any other suitable material. The weight shall be evenly distributed on the upturned bottom. Overhang of the edge is permissible, so long as none of the weight touches the floor. Allow the weight to fully rest on the basket for 5 minutes. Remove the weight and examine the basket for compliance with 3.3.3.

4.4 Inspection of preparation for delivery. An inspection shall be made to determine that the packaging, packing and marking comply with the requirements of section 5. Defects shall be scored in accordance with Table III. Sampling shall be in accordance with MIL-STD-105. The lot size shall be the number of shipping containers offered at one time. The sample unit shall be one shipping container fully prepared for delivery. Closure defects shall be examined on shipping containers fully prepared for delivery. The inspection level shall be S-2 with an AQL of 4.0 percent defective.

TABLE III. Inspection for preparation of delivery defects

| Examine | Defects |
|---|---|
| Markings | Omitted; incorrect; illegible; improper size, location, sequence or method of application. |
| Materials | Any component missing or damaged. |
| Contents | Number per container is more or less than required. |
| Workmanship | Inadequate application of components such as incomplete closure of container flaps, loose strapping or distortion of container. |

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B or C, as specified (see 6.2).

5.1.1 Level A or B. Each wastepaper basket shall be wrapped with paper or plastic film to protect the surface.

5.1.2 Level C. The wastepaper baskets shall be packaged to provide protection against physical damage during shipment from the contractor to the first receiving activity. The package shall be the same as that used by the supplier for retail distribution when it fulfills these requirements.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:11Z
Check the source to verify that this is the current version before use.

5.2 Packing. Packing shall be level A, B or C as specified (see 6.2).

5.2.1 Level A. Six packaged wastepaper baskets shall be packed in a close-fitting box conforming to PPP-B-636, class weather-resistant. Forms or collars of sufficient size, strength, and stability to prevent nesting during shipment, handling, and storage shall be placed between each wastepaper basket. The box shall be closed, waterproof sealed, and strapped in accordance with the appendix to PPP-B-636.

5.2.2 Level B. Six packaged wastepaper baskets shall be packed as specified in 5.2.1, except the box shall be class domestic and closure shall be in accordance with the appendix to PPP-B-636.

5.3.2 Level C. The wastepaper baskets shall be packed to insure carrier acceptance and safe delivery to destination. Containers shall comply with the Uniform Freight Classification Rules or National Motor Freight Classification Rules, as applicable.

5.3 Marking.

5.3.1 Civil agencies. The shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.3.2 Military activities. The shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The plastic wastepaper basket covered by this specification is intended to be used as an individual wastepaper receptacle in a personal living area i.e, a military billet.

6.2 Ordering data. Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

a. Title, number and date of this specification.
b. Color (see 3.4).
c. Selection of application levels of packaging and packing (see 5.1 and 5.2).

Preparing Activity

GSA-FSS

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See Section 2 of this specification to obtain extra copies and other documents referenced herein. Price 30 cents each.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:11Z
Check the source to verify that this is the current version before use.