L-S-1805
July 1, 1974

FEDERAL SPECIFICATION

DRY TRANSFER SHEETS

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers dry transfer lettering sheets printed with letters, numerals, and punctuation marks.

1.2 Classification. Dry transfer lettering sheets shall be furnished in the following character type styles, as specified (see 6.2).

Style 1 - Franklin Gothic Extra Condensed.
Style 2 - Futura Demibold
Style 3 - Helvetica Medium.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

L-T-90 - Tape, Pressure-Sensitive, Adhesive.
UU-P-561 - Paper, Tracing.
PPP-B-566 - Boxes, Folding, Paperboard.
PPP-B-636 - Boxes, Shipping, Fiberboard.
PPP-B-665 - Boxes, Paperboard, Metal Edged and Components.
PPP-B-676 - Boxes, Setup.

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

FSC 7510

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:11Z
Check the source to verify that this is the current version before use.

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza., Chicago, IL 60606.)

3. REQUIREMENTS

3.1 Material.

3.1.1 Carrier sheet. The carrier sheet shall be of material that offers dimensional stability to enable transfer of the characters without distortion, and shall have high release properties.

3.1.2 Backing sheet. A backing sheet shall be provided with each carrier sheet. The backing sheet shall be chemically treated to prevent transfer of characters during non-use (storage), and shall act as a burnishing sheet after character transfer.

3.1.3 Ink. Characters shall be printed with a coherent-film-forming transferable-when-dry ink. Unless otherwise specified (see 6.2), the color of ink shall be black.

3.1.4 Adhesive backing. The adhesive backing shall be the dry type, and upon transfer, only the letters and the exact area of adhesive covering the letters shall transfer.

3.2 Design. Characters shall be of the positive type, heat resistant, transfer by pressure, and shall form clean, sharp images upon transfer without distortion.

3.2.1 Type style. The type style (see 1.2) shall be in accordance with the originators oringinal type design (see 6.4).

3.2.2 Type size. Type size shall be 8, 10, 12, 14, 18, 24, 30, 36, 42, 48, and 60 point, as specified (see 6.2). The point size measurement shall be the English-American Point System.

3.2.3 Sheet size. The sheet size shall be not less than 8 inches by 11 inches and not more than 12-1/4 inches by 16-1/4 inches (see 6.3).

3.2.4 Printing. The following characters shall be printed on one carrier sheet, or set: Capital and lower case letters of the alphabet, numerals 1 through 9 and 0, and punctuation marks. Character frequency shall be in accordance with the manufacturer's commercial practice, provided addtional vowels are included and all characters are proportionate. Character spacing shall be uniform and sufficient to prevent transfer of more than one character at a time when transferring.

3.3 Performance.

3.3.1 Heat resistance. Characters shall withstand the heat test described in 4.4.1 without distortion.

3.3.2 Correctability. Before burnishing, characters shall be completely removable by erasing or lifting with pressure-sensitive adhesive tape (see 4.4.2).

3.3.3 Permanence. After burnishing, characters shall be fixed, and penciled guide lines shall be erasable without distorting or damaging the characters on finished art (see 4.4.3).

3.4 Identification marking. Each dry transfer sheet shall be marked with the manufacturer's name or trademark.

3.5 Workmanship. The dry transfer sheet shall lay flat and shall be squarely cut. The sheets and characters shall be free from foreign matter, scratches, scuffs, cracks, blisters, pits, tears, cuts, dents, holes, or other defects which may affect serviceability.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:11:17
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling.

4.2.1 Lot. A lot shall consist of all dry transfer sheets, or sets offered for delivery at one time as defined in MIL-STD-105.

4.2.2 Sampling for visual and dimensional examination. A random sample of sheets, or sets shall be taken from each lot in accordance with MIL-STD-105, inspection level I, acceptable quality level (AQL) of 4.0 percent defective. The sample unit shall be one sheet, or set.

4.2.3 Sampling preparation of delivery requirements. Sampling shall be in accordance with MIL-STD-105. For examination of interior packages the sample unit shall be one shipping container fully prepared for delivery selected just prior to the closing operations. Defects of closure listed shall be examined on shipping containers in the end item inspection lot. The inspection level shall be II and the acceptable quality level (AQL) shall be 4.0 defects per hundred units.

4.2.4 Sampling for tests. A random sample of sheets, or sets shall be taken from each lot in accordance with MIL-STD-105, inspection level S-1, acceptable quality level (AQL) of 4.0 percent defective. The sample unit shall be one sheet, or set.

4.3 Examination.

4.3.1 Visual examination. Samples, taken in accordance with 4.2.2 shall be examined for defects listed in table I.

TABLE I. Classification of defects

Examine	Defects
Design	Not positive type (see 3.2). Not designed for transfer by pressure (see 3.2).
Sheet size	Not as specified in 3.2.3.
Printing	Required characters not on one sheet, or set (see 3.2.4). Additional vowels not furnished (see 3.2.4). Insufficient spacing between characters (see 3.2.4). Characters not proportionate (see 3.2.4).
Identification marking	Missing (see 3.4).
Workmanship	Not as required in 3.5.

4.3.2 Examination of preparation for delivery. Samples taken in accordance with 4.2.3 shall be examined to determine that packaging, packing, and marking requirements are in compliance with section 5 of the specification. Defects shall be scored in accordance with table II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:11Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of preparation for delivery defects

Examine	Defects
Marking	Omitted, incorrect; illegible; improper size, location; sequence or method of application.
Materials	Any component missing, damaged or not conforming to the applicable specification or requirements stated herein.
Contents	Quantity per container is more or less than required.
	Gross weight exceeds the requirements of the box specification.
Workmanship	Inadequate application of components such as incomplete closure of container flaps; loose strapping; or distortion of containers.

4.4 Tests. Samples taken in accordance with 4.2.4 shall be subjected to the following tests.

4.4.1 Heat resistance. Transfer and burnish 10 characters in close proximity (one or two lines, depending on point size), on tracing paper conforming to UU-P-561, Type III. Place a lighted 500 watt reflector flood lamp, 90 degree beam (photographic bulb), one foot above the specimen. Place a thermometer close to the specimen, and withdraw specimen when temperature reaches 225°F. Examine characters for distortion (see 3.3.1).

4.4.2 Correctability. Six characters shall be transferred onto tracing paper conforming to UU-P-561, type III. Do not burnish. Characters shall be removed either by lifting with pressure-sensitive tape conforming to type II, class A of L-T-90, or erasing with an art gum eraser. Examine for complete removal. (See 3.3.2).

4.4.3 Permanence. Using a No. 2 pencil, rule a light line 8 inches long on tracing paper conforming to UU-P-561, type III. Using this line as a guide, transfer and burnish characters 1/4 inch apart just above the line. Using an art-gum eraser remove the pencil line. The line shall be completely removed with no distortion or damage to the characters. (See 3.3.3).

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A or C as specified (see 6.2).

5.1.1 Level A. Each dry transfer sheet with backing sheet shall be enclosed in a polyethylene bag, manila envelope, or otherwise packaged for physical protection. Sheets in quantities specified (see 6.2), shall be packaged in a close-fitting box conforming to PPP-B-566, PPP-B-665, or PPP-B-676. The box shall be closed in accordance with the applicable box specification or appendix thereto.

5.1.2 Level C. The dry trnasfer sheets shall be packed in containers to assure carrier acceptance and safe delivery at destination in compliance with the Uniform Freight Classification Rules or National Motor Freight Classification Rules.

5.2 Packing. Packing shall be level A, B or C as specified (see 6.2).

5.2.1 Level A. Dry transfer sheets packaged as specified in 5.1 shall be packed in quantities specified (see 6.2), in a close-fitting box conforming to PPP-B-636, class wheather resistant. Close, waterproof seal and strap the box in accordance with the appendix to PPP-B-636.

5.2.2 Level B. Dry transfer sheets packaged as specified in 5.1 shall be packed in quantities specified (see 6.2), in a close-fitting box conforming to PPP-B-636, class domestic. Closure of the box shall be in accordance with method II of the appendix to PPP-B-636.

5.2.3 Level C. The dry transfer sheets shall be packed to insure carrier acceptance and safe delivery at destination in compliance with the Uniform Freight Classification Rules or National Motor Freight Classification Rules.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:11Z
Check the source to verify that this is the current version before use.

5.3 Marking. In addition to any special marking required by the contract or order, all marking shall be in accordance with 5.3.1 or 5.3.2, as specified (see 6.2).

5.3.1 Civil agencies. Marking shall be in accordance with Fed. Std. No. 123.

5.3.2 Military agencies. Marking shall be in accordance with MIL-STD-129.

5.3.3 Special marking. In addition to the markings required by 5.3.1 and 5.3.2, each intermediate package and shipping container shall be marked with the date of manufacture (month and year) expressed numerically, followed by the letter "P"; e.g., 12-74-P.

6. NOTES

6.1 Intended use. Dry transfer sheets covered by this specification are intended for use by designers, architects, map and chart makers, draftsmen, and art professional and students as a graphic aid. Can be used in the production of advertising layouts, maps and charts, graphs, titles, presentations and posters, and visual aids.

6.2 Ordering data. Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Style required (see 1.2).
(c) Color of ink if other than black is required (see 3.1.3).
(d) Type size required (see 3.2.2).
(e) Selection of applicable levels of packaging and packing, and marking requirements (see 5.1, 5.2 and 5.3).
(f) Number of sheets per package for level A packaging (see 5.1.1).
(g) Number of packages per shipping container for level A and level B packing (see 5.2.1 and 5.2.2).

6.3 Sheet size and number of characters per sheet vary from manufacturer to manufacturer. For competitive procurement of individual items (e.g. a particular point size and character style), it is recommended that the purchaser use the following bid formula in the invitation for bid:

Special Item No.	Style & point size	Total number of characters per sheet (or set)	Bid price per sheet (or set)	Cost per character

The invitation for bid or request for quotation should state that awards will be determined on a "cost per character" basis. Further, the invitation for bid should state:

(1) When more than one character is stacked in a line space, the bottom character will be the only character counted;

(2) Marks or symbols that are normally used in pairs (such as quotation marks, brackets, parentheses, etc.) will be counted as one entry;

(3) Accent marks will not be counted; and

(4) Straight, vertical line type characters such as "i" or "l", shall not be used to inflate the number of character count.

In addition, it is recommended that a "Bid Sample" requirement be included in the invitation for bid, and the invitation for bid should stipulate that bid samples shall be examined and tested as follows:

Visual examination	(see 4.3.1)
Heat resistance	(see 4.4.1)
Correctability	(see 4.4.2)
Permanence	(see 4.4.3)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:11Z
Check the source to verify that this is the current version before use.

6.4 The originators of the type styles are:

Style 1 - Franklin Gothic Extra Condensed -
American Type Founders Company
200 Elmora Avenue
Elizabeth, New Jersey 07202

Style 2 - Futura Demibold -
Bauer Type Founders
Frankfurt, Germany

Style 3 - Helvetica Medium -
Haas Type Foundary, Ltd.
Basel, Switzerland

DOD WAIVED COORDINATION

User Interest:

Army - CL

Preparing activity:

GSA-FSS

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See Section 2 of this specification to obtain extra copies and other documents referenced herein. Price 25 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:11Z
Check the source to verify that this is the current version before use.