L-W-001653(GSA-FSS)
AMENDMENT-1
December 27, 1976

AMENDMENT

TO

INTERIM FEDERAL SPECIFICATION

WASTE RECEPTACLE, MOBILE, PLASTIC

This amendment was developed by the General Services Administration, Federal Supply Service, Washington, DC 20406, based upon currently, available technical information. The General Services Administration has authorized this amendment as part of Interim Federal Specification L-W-001653(GSA-FSS), dated May 21, 1971.

PAGE 1

Paragraph 2.1, under "Federal Standard", delete "Domestic".

PAGE 2

Paragraph 2.2. Delete in its entirety and substitute:

"2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., Traffic Department, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)"

Paragraph 3.1.1 Delete and substitute:

"Plastic. The plastic for the receptacle shall be polyethylene. Plastic of sufficient density and thickness is acceptable for the component platform when the alternate method of securing the undercarriage to the receptacle is used (see 3.5).

Paragraph 3.1.2. Delete heading and first sentence and substitute:

"Metal. The metal for the plate and spacer, when the casters are extended through the receptacle body as outlined in 3.5, shall be AISI 1010 or 1020 hot rolled carbon steel sheet".

Paragraph 3.3. First line, delete "injection", sixth line, add "or two moveable handles located not lower than eight inches from the top edge".

Paragraph 3.4, third line, delete "by lugs".

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:11Z
Check the source to verify that this is the current version before use.

Paragraph 3.5. Delete in its entirety and substitute:

"3.5 Undercarriage. The undercarriage shall be attached to the receptacle by extending the threaded stems of the casters upward through the plate, spacer, and the receptacle bottom. Alternatively, the undercarriage may be fastened to the receptacle bottom by means of a minimum of four equally spaced bolts or studs threaded into nuts molded in the receptacle bottom. Casters shall extend through the platform and be secured.

3.5.1 Casters. Casters shall be type II, class A, style C, mounting T, in accordance with FF-C-77. Caster wheels shall be 3 inches in diameter of solid hard rubber composition. Casters shall be secured by a combination nut and lock washer with a minimum torque of 90 inch-pounds."

Paragraph 4.2.1, delete in its entirety and substitute:

"4.2.1 Inspection and acceptance. Sampling for inspection and acceptance shall be in accordance with MIL-STD-105, except where otherwise indicated hereinafter."

Paragraph 6.2, delete subparagraph (c).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:11Z
Check the source to verify that this is the current version before use.