INTERIM FEDERAL SPECIFICATION

WASTE RECEPTACLE, MOBILE, PLASTIC

This Interim Federal Specification was developed by the General Services Administration, Federal Supply Service, Washington, DC 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers mobile polyethylene (PE) plastic waste receptacles with or without covers.

1.2 Classification. The mobile plastic waste receptacles shall be of one type with the following sizes and classes, as specified (see 6.2):

Size 1 - 32 gallons capacity.
Size 2 - 44 gallons capacity.

Class A - With cover.
Class B - Without cover.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

FF-C-77 - Casters, Institutional Duty.
PPP-B-636 - Box, Fiberboard.

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtain from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:11Z
Check the source to verify that this is the current version before use.

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the National Motor Freight Traffic Association, Inc., Agent, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Tariff Publishing Officer, Room 202, Union Station, 516 West Jackson Blvd., Chicago, IL 60606.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Material.

3.1.1 Plastic. Polyethylene shall be virgin material or virgin material blended with clear rework material, generated from the manufacturer's own production. When reworked material is used it shall be blended back into the same type and kind of virgin compound to produce a receptacle equal in quality to the one molded from virgin material.

3.1.2 Plate and spacer. Plate and spacer shall be AISI 1010 or 1020 hot rolled carbon steel sheet. The carbon steel sheet shall be zinc plated with a minimum plating thickness of 0.0002 inch.

3.2 Dimensions. The receptacles shall conform to the dimensions of table I.

TABLE I. Dimensions

Size	Capacity 1/	Height 1/	Outside top diameter 1/	Outside bottom dia. 1/	Minimum wall and bottom thickness, average 2/
	Gallons	Inches	Inches	Inches	Inch
1	32	28	22	18	0.085
2	44	32	24	20	0.100

1/ Tolerance ± 5 percent.

2/ When inspected in accordance with 4.4.4.

3.3 Receptacle. The receptacle shall be injection molded of one piece and shall be watertight. The interior and exterior surfaces shall be smooth to allow for ease in cleaning. The walls of the receptacles shall be molded with a shoulder approximately 1/2 inch dimension completely around the circumference at approximately one fourth of the distance from the top edge to give strength and rigidity. The receptacle shall have two integrally molded handles 180 degrees apart near the top edge.

3.3.1 Leakage. There shall be no evidence of leakage when tested in accordance with 4.4.1.

3.3.2 Crush. There shall be no evidence of cracking, splitting, or failure after completion of test in 4.4.2.

3.3.3 Side handles. There shall be no evidence of failure, permanent deformation, cracking, or splitting of the handles or adjacent receptacle wall when tested in accordance with 4.4.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:11Z
Check the source to verify that this is the current version before use.

3.4 Cover. The cover shall be molded in one piece and shall be of the same thickness as the applicable receptacle wall thickness specified in table I. The cover shall be designed to lock securely to the receptacle by lugs.

3.5 Undercarriage. The receptacle shall have attached four swivel casters with threaded stems extending upward through a plate, spacer, and the receptacle body. Casters shall be secured by a combination nut and lock washer with a minimum torque of 90 inch-pounds. Casters shall be type II, class A, style C, mounting T in accordance with FF-C-77. Caster wheels shall be 3 inches in diameter of solid hard rubber composition. The plate and spacer shall be carbon steel specified in 3.1.2. The plate shall be 0.093 inch (13 gauge) minimum thickness and 16 inches ± 0.060 inch square. The spacer shall be 0.080 inch minimum thickness, 0.590 ± 0.010 inch in height, and a minimum diameter of 1.000 inch.

3.6 Color. Color of receptacle and cover shall be gray.

3.7 Identification marking. The receptacles shall bear the manufacturer's name, trade name, or trademark of such known character as to be easily identifiable with the manufacturer.

3.8 Workmanship. The receptacles and covers shall be smooth and free of seams, fins, sharp edges, cracks, chipped edges, welds and defects that may affect their durability and serviceability. The polyethylene shall be free from contamination (dirt and foreign matter).

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling.

4.2.1 Lot. Unless otherwise specified (see 6.2), a lot shall consist of all receptacles and covers of the same size, submitted for inspection at the same time.

4.2.2 Visual examination of end item. Sampling for this examination shall be according to level S-2 in MIL-STD-105. The Acceptable Quality Levels (AQL's) for defects listed in table II shall be 2.5 percent defective for major defects and 6.5 percent defective for total defects.

4.2.3 Sampling for tests. Sampling for tests shall be in accordance with level S-2 in MIL-STD-105. AQL for tests shall be 4.0 on the basis of percent defective.

4.3 Examination.

4.3.1 End item. Receptacles and covers selected in accordance with 4.2.2 shall be examined for defects listed in table II.

TABLE II. Classification of defects, end item

Defects	Major	Minor
Size not as specified.	X	
Dimensions not as specified.	X	
Color not as specified.		X
Scratches in receptacle or cover.		X
Dirt, grit, or foreign matter imbedded in finish.		X
Component not of specified design.	X	
Handle missing.	X	
Component malformed or damaged.	X	
Sharp or burred edge which might cause injury.		X
Label missing or in wrong location, incorrect size, or not applied as required.	X	
Damage or defect not affecting function or serviceability.		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:11Z
Check the source to verify that this is the current version before use.

4.3.2 Inspection of preparation for delivery. An inspection shall be made to determine that the packaging, packing and marking comply with the requirements in section 5 of this specification. Defects shall be scored in accordance with table III. For examination of interior packaging the sample unit shall be one shipping container fully prepared for delivery, selected at random just prior to the closing operations. Sampling shall be in accordance with MIL-STD-105. Defects of closure listed in table III shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 with an acceptable quality level (AQL) of 4.0 defects per hundred units.

TABLE III. Classification of preparation for delivery defects

Examine	Defects
Markings (exterior and interior).	Omitted, incorrect, illegible, improper size, location, sequence, or method of application.
Materials.	Any component missing or damaged.
Workmanship.	Inadequate application of components such as incomplete closure of container flaps, loose strapping, inadequate stapling. Distortion of container.

4.4 Tests.

4.4.1 Leakage test. Receptacles shall be filled to capacity with water at room temperature and allowed to stand for 24 hours. Examination shall be made to determine compliance with 3.3.1.

4.4.2 Crush test. Receptacles shall be placed in an environmental chamber at 0° ± 5°F. for a minimum period of 12 hours. Within 15 seconds after removal from the chamber, receptacles shall be placed on one side on a concrete slab or floor. Sufficient weight shall then be applied from above to an area 4 to 6 inches below the top rim to cause sidewalls to touch. Receptacles will be inspected for conformance with 3.3.2.

4.4.3 Side handle test. The receptacles filled with evenly distributed weights of 125 lbs and 175 lbs for the sizes 1 and 2, respectively, shall be supported by the side handles for one hour. The weight on the handles shall be equally distributed. The receptacle shall then be lowered and raised to carrying position a minimum of four times. Any failure or defect affecting serviceability shall constitute failure of the test (see 3.3.3).

4.4.4 Wall and bottom thickness. Measure the wall and bottom thickness of the receptacles a minimum of 4 places for each measurement. The wall thickness shall be measured at 90 degree intervals around the periphery, not less than 1 inch from the top edge. The average of each of the 4 measurements shall not be less than the thickness requirements indicated in table I.

5. PREPARATION FOR DELIVERY

5.1 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.1.1 Level A. Six 32 gallon or four 44 gallon receptacles, nested together with covers, when applicable, shall be packed in a close fitting box conforming to PPP-B-636, class weather-resistant. The box shall be closed and strapped in accordance with the appendix to PPP-B-636.

5.1.2 Level B. Receptacles shall be packed as specified in 5.1.1 except the box shall be class domestic and strapping is not required.

5.1.3 Level C. Receptacles, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers and packing shall comply with Uniform Freight Classification or National Motor Freight Classification.

5.2 Marking.

5.2.1 Civil agencies. In addition to markings required by the contract or order, the shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.2.2 Military agencies. In addition to markings required by the contract or order, the shipping containers shall be marked in accordance with MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:11Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. Plastic waste receptacles covered by this specification are intended for refuse, waste, or garbage prior to bulk disposal. The receptacles are not intended to be used for hot ashes or near an open flame.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Size and class (see 1.2).
(c) Size of lot, if different from 4.2.1.
(d) Selection of applicable levels of packing required (see 5.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:11Z
Check the source to verify that this is the current version before use.

GENERAL SERVICES ADMINISTRATION - FEDERAL SUPPLY SERVICE

SPECIFICATION COMMENT SHEET

BUDGET BUREAU NO. 29-R0178

INSTRUCTIONS

This form provides a way for users of this specification to inform the originator of problems encountered in its use. It is not to be used to request changes to accommodate proprietary features. All comments will be considered and appreciated, but please do not expect a reply. To comment: detach, complete, and mail to Gen. Services Adm., FSS (FMSH), Washington, DC 20406

NOTE: Comments on this form do not constitute or imply authorization to waive any part of the document or serve to amend contractual requirements.

1. SPECIFICATION

L-W-001653(GSA-FSS) WASTE RECEPTACLE, MOBILE, PLASTIC

2. CONTRACT NO. *(If any)*	3. QUANTITY ON CONTRACT *(Optional)*	4. DOLLAR VALUE *(Optional)*

5. GENERAL NATURE OF PROBLEM *(e.g., inspection difficulties, manufacturers unable to meet tolerances, containers collapse under normal warehousing conditions, etc.)*

6. SPECIFIC REQUIREMENTS AFFECTED *(Include paragraph number and lines of wording)*

7. SPECIFIC PROBLEMS *(e.g. tests in 4.2.2 will not assure that the battery will last required time; temperature ranges in table 2 do not conform to commercially available items.)*

8. RECOMMENDATIONS

9. NAME OF MANUFACTURER, ASSOCIATION, GOVT., AGENCY, ETC.	10. ADDRESS *(Number, Street, City, State and Zip Code)*

11. NAME AND TITLE OF SUBMITTER	12. DATE

FORM GSA FEB 69 2200

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:11Z
Check the source to verify that this is the current version before use.