N-N-002182A(Army-GL)
April 30, 1986
SUPERSEDING
N-N-002182(Army-GL)
June 23, 1983

INTERIM FEDERAL SPECIFICATION

NOODLES, BUTTERED, THERMOSTABILIZED, TRAY PACK

This interim Federal specification was developed by the U.S. Army Natick Research, Development and Engineering Center, Natick, MA 01760-5014, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

1. SCOPE

1.1 Scope. This specification covers buttered noodles thermostabilized in tray pack cans for use by the Department of Defense as a component of operational rations.

2. APPLICABLE DOCUMENTS

2.1 Government documents. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this document to the extent specified herein.

Federal Specifications:

TT-C-495	-	Coatings, Exterior, for Tinned Food Cans
PPP-B-636	-	Boxes, Shipping, Fiberboard

Beneficial comments (recommendations, additions, deletions) and any pertinent data that may be of use in improving this document should be addressed to U.S. Army Natick Research, Development and Engineering Center, Natick, MA 01760-5014, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8940

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:11Z
Check the source to verify that this is the current version before use.

(Activities outside the Federal Government may obtain copies of Federal specifications, standards, and commercial item descriptions as outlined under General Information in the Index of Federal Specifications, Standards and Commercial Item Descriptions. The Index, which includes cumulative bimonthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification, other Federal specifications, and commercial item descriptions required by activities outside the Federal Government for bidding purposes are available without charge from General Services Administration Business Service Centers in Boston, MA; New York, NY: Philadelphia, PA; Washington, DC; Atlanta, GA; Chicago, IL; Kansas City, MO; Fort Worth, TX; Denver, CO; San Francisco, CA; Los Angeles, CA; and Seattle, WA.

(Federal Government activities may obtain copies of Federal standardization documents, and the Index of Federal Specifications, Standards and Commercial Item Descriptions from established distribution points in their agencies.)

Military Specifications:

MIL-L-1497	-	Labeling of Metal Cans for Subsistence Items
MIL-L-35078	-	Loads, Unit; Preparation of Semiperisable Subsistence Items; Clothing, Personal Equipment and Equipage; General Specification for.

Military Standards:

MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-900	-	Bacterial Standards for Starches, Flours, Cereals, Alimentary Pastes, Dry Milks and Sugars Used in the Preparation of Thermostabilized Foods for the Armed Forces

(Copies of Military specifications and standards required by contractors in connection with specific acquisition functions should be obtained from the procuring activity or as directed by the contracting officer.)

Federal Regulations:

U.S. Department of Health and Human Services

Federal Food, Drug and Cosmetic Act and regulations promulgated thereunder (21 CFR Parts 1-199)

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:11Z
Check the source to verify that this is the current version before use.

U.S. Department of Agriculture (USDA)

U.S. Standards for Condition of Food Containers

(Application for copies should be addressed to the Director, Market Research and Development Division, Agricultural Marketing Service, U.S. Department of Agriculture, Washington, DC 20250.)

U.S. Standards for Grades of Butter

(Application for copies should be addressed to the Dairy Standardization Section, Dairy Division, Room 2750-S, Agricultural Marketing Service, U.S. Department of Agriculture, Washington, DC 20250.)

Environmental Protection Agency (EPA)

National Interim Primary Drinking Water Regulations

(Application for copies should be addressed to the Office of Drinking Water WH550, Environmental Protection Agency, Washington, DC 20460.)

2.2 Other publications. Unless otherwise specified, the following documents of the issue in effect on the date of invitation for bids or request for proposal form a part of this document to the extent specified herein.

Association of Official Analytical Chemists (AOAC)

Official Methods of Analysis of the Association of Official Analytical Chemists

(Application for copies should be addressed to the Association of Official Analytical Chemists, 1111 North 19th Street, Suite 210, Arlington, VA 22209.)

National Academy of Sciences

Food Chemicals Codex

(Application for copies should be addressed to the National Academy Press, 2101 Constitution Avenue, N.W., Washington, DC 20418.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.3, 6.1, and 6.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:11Z
Check the source to verify that this is the current version before use.

3.2 Ingredients. All ingredients shall be clean, sound, wholesome, and free from foreign material, evidence of rodent or insect infestation, extraneous material, off-odors, off-flavors, and off-colors.

3.2.1 Noodles, egg (fettuccini), enriched. The egg noodles shall meet the FDA Standard of Identity for Enriched Egg Noodles. The egg noodles shall be dried with no checking or cracking. The egg noodles shall have the following dimensions:

Length:	4.0 inches ± 0.5 (½) inch.
Width:	0.25 (¼) inch ± 0.0625 (1/16) inch.
Thickness:	0.040 inch ± 0.003 inch.

The egg noodles shall conform to the following analytical requirements:

Moisture:	Not greater than 12.00 percent.
Ash:	Not greater than 0.98 percent (moisture-free basis).
Protein:	Not less than 13.00 percent (moisture-free basis).
Egg solids:	Not less than 5.50 percent by weight.
Lipid phosphorus:	Not less than 0.136 percent if prepared with egg yolk solids; not less than 0.101 percent if prepared with the whole eggs.

The egg noodles shall comply with bacterial standards specified in MIL-STD-900.

3.2.2 Water. Water used for formulation, ice making, and washing shall conform to the National Interim Primary Drinking Water Regulations.

3.2.3 Butter. Butter shall be lightly salted and shall be U.S. Grade A as defined in the U.S. Standards for Grades of Butter.

3.2.4 Starch, waxy maize, modified. The starch shall be white odorless, finely pulverized, modified waxy maise starch for use in canned foods. The modified starch shall demonstrate initial viscosity development in the temperature range 140 to 170°F and be fully hydrated at common retort temperature. The starch shall resist breakdown at low pH, under shear stress, and under conditions of cold storage. The starch shall be bland with essentially no cereal or starch taste and shall comply with MIL-STD-900.

3.2.5 Salt. Salt shall be non-iodized, clear, white, refined, sodium chloride with or without anticaking agents.

3.2.6 Monosodium glutamate (MSG). Monosodium glutamate shall comply with Food Chemicals Codex.

3.2.7 Sugar. Sugar shall be clean, refined, sucrose, granulated, cane or beet, or a combination of both and shall comply with MIL-STD-900.

3.2.8 Lecithim. Lecithim shall comply with the Food Chemicals Codex.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:11Z
Check the source to verify that this is the current version before use.

3.2.9 Color, annatto, dry. The annatto color shall be a reddish orange water soluble powder of the extractive of Annatto bixa arellana. The powder shall contain less than 5 percent moisture. One hundred percent shall pass through a U.S. No. 10 Standard sieve and shall be free from hard lumps. The total color (as percent Norbixin) shall be 15.0 ± 1 percent.

3.3 Preparation and further processing.

3.3.1 Noodle preparation. The dry noodles shall be blanched in boiling water until the noodle weight increases two times (100 ± 3 percent). The noodles shall be immediately cooled to less than 90°F and rinsed to remove excess starch. The noodles shall be placed in trays within 2 hours after blanching has been accomplished.

3.3.2 Sauce preparation. The sauce shall be formulated and prepared as follows:

Ingredient	Percent
Water	88.65
Butter	7.00
Starch	2.00
Salt	1.50
Sugar	0.60
Lecithin	0.243
Annatto, dry	0.007
	100.00

a. Add butter and approximately 80 percent of the water to the processing vessel. Heat to 180°F.

b. Add salt, sugar, and lecithin. Simmer until all ingredients are in the fluid state.

c. Prepare a starch slurry using the reserved water and add slowly with constant agitation.

d. Heat entire contents to 180°F and hold for 5 minutes.

e. Add color and blend until color of sauce is uniform.

f. Adjust formula volume with water to compensate for evaporation losses.

g. The sauce shall be placed in tray pack cans within 3 hours after the heating at 185°F is completed. The temperature of the sauce shall not fall below 150°F at any time prior to filling into tray pack cans.

3.4 Tray pack filling and sealing. Each tray pack can shall be filled with product so as to conform to the following requirements;

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:11Z
Check the source to verify that this is the current version before use.

a. Each tray pack can shall be filled with 42 ± 1 ounces of blanched noodles and filled with sauce to not less than 106 ounces.

NOTE: The noodles and sauce may be filled in any order which will ensure compliance with finished product requirements.

b. The temperature of the sauce at filling shall be not less than 150°F.

c. Each can shall be hermetically sealed (under a vacuum of not less than 10 inches of mercury) immediately after filling.

3.5 Tray pack thermoprocessing. The filled and sealed tray pack cans shall be thermostabilized in a stationary retort at 240°F or below or alternatively at 260°F in a rotary type retort with rapid rotation (approximately 24 RPM). Under both methods the tray pack cans shall be thermostabilized with a sterilization value (F_o) of not less than 6 has been achieved. The filled and sealed thermoprocessed tray pack cans shall show no evidence of can swelling when tested for sterility as specified in 4.6.4.

3.6 Finished product requirements. The finished product shall comply with the following requirements.

a. There shall be no foreign material such as, but not limited to, dirt, insects, insect parts, hair, wood, paper, paint, glass, or metal.

b. There shall be no foreign odor or flavor such as, but not limited to, burnt, scorched, stale, sour rancid, musty, or moldy.

c. There shall be no color foreign to the product.

d. The salt content of the finished product shall not exceed 1.5 percent.

e. No individual can shall have a net weight of less than 104 ounces.

f. The average net weight shall be not less than 106 ounces.

g. The noodles shall be distinct strips which readily separate.

h. Noodles shall be tender but not mushy or hard.

i. Noodles shall be a uniform light yellow color.

3.6.1 Palatability. The finished product shall be equal to or better than the approved preproduction sample (see 6.1) in palatability and overall appearance.

3.7 Plant qualification. The product shall be prepared, processed, and packaged in establishments meeting the requirements of Title 21, Code of Federal

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:11Z
Check the source to verify that this is the current version before use.

Regulations, Part 110, "Current Good Manufacturing Practice in Manufacturing, Processing, Packaging or Holding of Human Foods", and the plant sanitation requirements of the appropriate Government inspection agency."

3.8 Federal Food, Drug, and Cosmetic Act. All deliveries shall conform in every respect to the provisions of the Federal Food, Drug, and Cosmetic Act, and regulations promulgated thereunder.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor's responsibility. Inspection and acceptance by the USDA shall not relieve the contractor of obligation and responsibility to deliver a product complying with all requirements of this specification. The contractor shall assure product compliance prior to submitting the product to the USDA for any inspection.

4.2 Inspection and certification. Product acceptability shall be determined by the USDA. The USDA will determine the degree of supervision necessary to assure compliance with the requirements of this specification.

4.3 First article inspection. When a first article is required (see 6.1), it shall be inspected in accordance with the quality assurance provisions of this specification and evaluated for overall appearance and palatability. Any failure to conform to the quality assurance provisions of this specification or any appearance or palatability failure shall be cause for rejection of the first article.

4.4 Component and material inspection. Components and materials shall be inspected in accordance with the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or other applicable purchase document.

4.4.1 Ingredient and component examination. Conformance of ingredients and components to identity, condition, and other requirements specified in 3.2 shall be certified by the ingredient supplier or ingredient manufacturer, or compliance be evident by examination of pertinent labels, markings, U.S. Grade Certificates, certificates of analyses, or other such valid documents acceptable to the inspection agency. In addition, prior to use, each ingredient shall be examined organoleptically as necessary to determine conformance to the condition requirements. Any nonconformance to an identity, condition, or other requirement shall be cause for rejection of the ingredient or component lot or of any involved product.

4.5 In-process examination. In-process examination shall be performed to determine conformance to the preparation, processing, can interior coating, filling, sealing, and packing requirements. Any nonconformance revealed by actual examination or by review of records of time, temperature, and formulation or of other valid documents shall be cause for rejection of the involved product.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:11Z
Check the source to verify that this is the current version before use.

4.6 Tray pack inspection. The inspection lot shall include only tray packs produced in one workshift. The USDA reserves the right to separate the inspection lot into smaller inspection lots.

4.6.1 Net weight inspection. Randomly select 30 filled and sealed tray pack cans from the inspection lot and weigh separately. Subtract the average tare weight (determined by randomly selecting and weighing 30 of the empty tray pack cans and lids used in preparing the product and dividing the total weight by 30) from the weight of each tray pack in the sample. The results shall be reported to the nearest 1 ounce. If the average net weight is less than 106 ounces or if the net weight of any individual can is less than 104 ounces, the lot shall be rejected.

4.6.2 Product inspection. The sample size shall be as indicated by the double sampling plan specified in table I. The tray pack cans shall be selected at random from the lot. The tray pack cans shall be heated at least 30 minutes in 160° to 180°F water, opened, and inspected for the defects listed in table II.

TABLE I. Double sampling plan inspection 1/

Lot size (cans)	Sample size (No. of cans)	Cumulative sample	Acceptance number	Rejection number
0-3200	8	-	0	2
	8	16	1	2
3201-35000	13	-	0	3
	13	26	3	4

1/ a. If no defects are found in the first sample, the lot shall be accepted.

b. If the number of defects found in the first sample equals or exceeds the rejection number, the lot shall be rejected.

c. If the number of defects found in the first sample exceeds the acceptance number but is less than the rejection number, the second sample shall be inspected. Defects found in the first and second samples shall be combined and if the number of defects in the cumulative sample equals or exceeds the rejection number, the lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:11Z
Check the source to verify that this is the current version before use.

TABLE II. Product inspection 1/ 2/

Category	Defect
Major	
101	Noodles not distinct strips.
102	Noodles not readily separated.
103	Noodles hard or mushy.
104	Noodle color not typical light yellow noodle color.
105	Color not uniform.

1/ The presence of foreign material (e.g. glass, dirt, insect parts, hair, wood, metal), foreign odor or flavor (e.g. burnt, scorched, moldy, rancid, sour, stale), or foreign color shall be cause for rejection of the lot.

2/ Product not equal to or better than the approved preproduction sample (see 6.1) in palatability and overall appearance shall be cause for rejection of the lot. (This comparison shall be performed only when deemed necessary by an Agricultural Marketing Service (AMS) agent.)

4.6.3 Salt content testing. Nine tray packs shall be selected at random from the lot and distributed as follows:

- Three for laboratory analysis
- Three for submission to the contractor
- Three for retention by an AMS agent as a reserve sample

The three tray packs for laboratory analysis shall be individually tested for salt content in accordance with the Official Methods of Analysis of the Association of Official Analytical Chemists, except that preparation of the sample shall be as follows. The cans shall be opened and the entire contents of each can shall be separately blended in a Waring blender or equivalent. The lot shall be rejected if the salt content of any individual tray pack is more than 1.5 percent. Analysis of reserve samples at the request of the contractor shall not be permitted unless the original laboratory analysis indicated that the involved lot will be rejected because of noncompliance with the salt content requirement. When the reserve samples are analyzed, the analysis for salt shall be made and will be considered final. Unused reserve samples shall be returned to the contractor for inclusion in subsequent lots.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:11Z
Check the source to verify that this is the current version before use.

4.6.4 Sterility testing. The sample size shall be one filled, sealed, and thermoprocessed tray pack can selected from each retort batch in the lot and shall be tested for sterility by incubating the cans at 95°F ± 2°F for 10 days. Any evidence of can swelling shall be considered a critical defect and cause rejection of the lot.

4.7 Can condition examination. Examination of filled and sealed tray pack cans shall be in accordance with the United States Standards for Condition of Food Containers, except that inspection for labeling shall be in accordance with MIL-L-1497 (see 5.4).

4.8 Shipping container examination. Shipping containers shall be examined for defects in assembly, closure, and reinforcement (when applicable) in accordance with the appendix of PPP-B-636. In addition, the following defects shall be classified as follows: Major: (1) National stock number, item description, contract number, or date of pack markings missing, incorrect, or illegible; (2) Reinforcement with nonmetallic strapping or tape is not used; Minor: (1) Other required markings missing, incorrect, or illegible; (2) Interior packing with fiberboard liner or pads not as specified; (3) Height of box liner less than inside depth dimension of box by more than 1/8 inch or extends above top edge of box; (4) Length or width of pads less than box dimensions by more than 1/8 inch; (5) Arrangement or number of cans not as specified.

4.9 Unit load inspection. Inspection of unit loads shall be in accordance with the quality assurance provisions of MIL-L-35078.

5. PREPARATION FOR DELIVERY

5.1 Packaging. The product shall be packaged in accordance with level A or C as specified (see 6).

5.1.1 Level A. A size 1001 by 1206 by 200 tray pack can shall be filled with 106 ounces of the food product sealed and thermoprocessed as specified in 3.4 and 3.5. The base plate of the can shall be electrolytic chromium-coated steel and shall be of sufficient temper to protect the product during shipment and storage. The base place weight of the body and end of each can shall be 90 pounds per base box. The entire inside area of the can shall be coated. Scratches or fractures shall not penetrate through the interior can coating. The interior can coating shall not peel or blister when in contact with the product. The interior can coating shall neither affect nor be affected by the packaged product. A certificate of conformance shall be furnished to certify compliance with the interior can coating requirements. The can shall be coated overall on the outside with a coating conforming to type I of TT-C-495.

5.1.2 Level C. The product shall be packaged as specified in 5.1.1, except that cans with commercial exterior coating will be acceptable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:11Z
Check the source to verify that this is the current version before use.

5.2 Packing. The product shall be packed in accordance with level A, B or C as specified (see 6.1).

5.2.1 Level A packing. Four cans of product, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard box, constructed and closed in accordance with style RSC-L, grade V2s of PPP-B-636. The cans shall be packed flat, four in depth within the box. The inside of each box shall be provided with a box liner and five fiberboard pads. The height of the box liner shall be equal to the full inside depth of the box (+0 inch, -1/8 inch). The pads shall be not less than 1/8 inch of the full length and width dimensions of the box and shall be fabricated of grade V3c fiberboard. The pads shall be placed between the cans and on the top and bottom of the stacked cans. Each fiberboard box shall be reinforced with nonmetallic strapping or pressure-sensitive adhesive filament reinforced tape in accordance with the appendix of PPP-B-636. Shipping container shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.1). Strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.2.2 Level B packing. Four cans of product, packaged as specified in 5.1, shall be packed as specified in 5.2.1, except the box shall be constructed of grade V3c, V3s, or V4s fiberboard.

5.2.3 Level C packing. Four cans of product, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard box constructed and closed in accordance with style RSC-L, class domestic, grade 275 of PPP-B-636. The cans shall be packed flat, four in depth within the box. The inside of each box shall be provided with a box liner and five fiberboard pads. The height of the box liner shall be equal to the full inside depth of the box (+0 inch, -1/8 inch). The pads shall be placed between the cans and on the top and bottom of the stacked cans. The pad dimensions shall be not less than 1/8 inch of the full length and width dimensions of the box and shall be fabricated of the same material as the box.

5.3 Unit loading. When specified (see 6.1), the product, packed as specified in 5.2.2 and 5.2.3, shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified. When unit loads are strapped, the strapping shall be limited to nonmetallic strapping.

5.4 Labeling. Each package shall be labeled in accordance with MIL-L-1497. In addition, the name of the product shall be marked, stamping is permitted, on one 1001 by 200 side of the can. The labeling shall be legible when examined in accordance with 4.7 after submerging the can in boiling water for 30 minutes. Paper labels are not permitted. Cans shall show the following statements:

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:11Z
Check the source to verify that this is the currentversion before use.

TO HEAT

a. To heat in water: Submerge sealed can in boiling water. Bring to a boil again and continue boiling for 40 to 45 minutes. Avoid overheating to the point where internal pressure is evident (can shows evidence of bulging). Remove from water and open lid for serving. Caution: Use care when opening as pressure may have been generated with the can.

b. To heat in oven: Either punch several holes in lid of tray can or open can in usual manner leaving the loose lid in place to prevent moisture loss. Place in a 350°F oven for approximately 35 to 40 minutes until contents reach an internal temperature of 165°F.

WARNING: Do not place closed can in oven, as heating will increase internal pressure which may cause the can to burst.

YIELD

Approximately 18 servings of 1/2 cup each

5.5 Marking.

5.5.1 Shipping containers. In addition to any special marking required by the contract, shipping containers shall be marked in accordance with MIL-STD-129.

5.5.2 Unit loads. Unit loads shall be marked in accordance with MIL-L-35078. In addition, the following precautionary marking in capital letters larger than other markings shall be included:

CAUTION: DO NOT STACK PALLETS IN TRANSIT OR MORE THAN TWO HIGH IN STORAGE

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification.
b. When a first article is required (see 3.1, 4.3, and 6.3).
c. Provisions for approved preproduction samples (see 3.6.1 and 6.3).
d. Level of packaging and packing required (see 5.1 and 5.2).
e. Type and class of unit load (see 5.2.1 and 5.3).

6.2 Appropriate level of pack. Based on the conditions known or expected to be encountered during shipment, handling, and storage of the specific item being procured, the procuring activity should select the appropriate level of pack in accordance with the criteria established in AR 700-15/NAVSUPINST 4030.28/AFR 71-6/MCO 4030.33A/DLAR 4145.7.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:11Z
Check the source to verify that this is the current version before use.

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provision of FAR 52.209. The first article shall be a preproduction sample. The contracting officer should include specific instructions in all procurement instruments regarding arrangements for selection, inspection, and approval of the first article.

Preparing activity:

Army - GL

Project No. 8940-A506

U.S. GOVERNMENT PRINTING OFFICE: 1986 - 605-036/42783

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:11Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
N-N-002182A(Army-GL)	

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

NATICK OP-1, Feb 86

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:11Z
Check the source to verify that this is the current version before use.