INTERIM AMENDMENT
TO
FEDERAL SPECIFICATION

PAD, HEATING, CHEMICAL

This interim amendment was developed by the Defense Personnel Support Center (DM), Philadelphia, PA 19101, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized the use of the interim amendment as a valid exception to Federal specification O-P-46E, dated November 9, 1976.

PAGE 6

3.2.4 Heating mixture. Delete the second sentence entirely.

3.3.1 Inner case. In Direction 1, insert "VIGOROUSLY" preceding "SHAKE".

PAGE 7

3.3.1 Inner case. In Direction 5, delete the second sentence entirely.

PAGE 8

3.4 Heating requirements. After the first sentence, add "During the heating cycles, the pads shall emit no foreign, pungent odor, other than the characteristic one from the warm coating of synthetic rubber."

3.4.1 Initial temperature. At the end of the paragraph, add "The time to reach the initial temperature shall not exceed 10 minutes after the final agitation."

FSC 6530

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:12Z
Check the source to verify that this is the current version before use.

PAGE 9

4.1.2.1.1 First article inspection. In the second sentence, delete "test" and substitute "test(s)".

PAGE 11

4.3.1 Classification of defects. In Table III, for Major 107, delete the period and add "or bartacking."

PAGE 12

4.4.1.1 Equipment and conditions. In subparagraph b, delete "Type I 30 AWG thermocouples iron-constantan" and substitute "Type T 30 AWG thermocouples (copper-constantan)". In subparagraph d, delete "70°" and substitute "68°".

PAGE 13

4.4.1.2 Procedure. The following subparagraphs shall be revised as indicated:

a. In the first sentence, delete "tap water" and substitute "distilled or de-ionized water at room temperature".

b. In the last sentence, delete "packet" and substitute "pocket".

c. Delete "reading initial temperature" and substitute "final placement in pocket (see subparagraph e below)".

d. Delete the last sentence entirely.

e. In the second sentence, following "after which" insert "the pads shall be removed from the blanket and vigorously agitated for another 3 minutes. The thermocouple shall be attached as described in Procedure b, the pads shall be placed in the blanket again, and". Delete the last two sentences entirely.

PAGE 14

4.4.2.2 High-temperature aging resistance. Delete "500 hours" and substitute "166 ± 1 hours".

Preparing activity:
Defense Logistics Agency-DM

Project No. 6530-1432

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:12Z
Check the source to verify that this is the current version before use.