MIL-D-63406 (AR)
AMENDMENT 1
15 August 1983

MILITARY SPECIFICATION

DELAY MODULE, IMPACT, METAL PARTS
ASSEMBLY, AND PACKING

This amendment forms a part of Military Specification MIL-D-63406 (AR), dated 18 March, 1982, and is approved for use by the US Army Armament Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 5

CD 103, change to read as follows:

"Height from top of housing to bottom of housing cover, max."

CD 201: Under AQL, delete "3.7", under requirement paragraph, change "Visual" to "3.7", and under Inspection Method add "Visual".

Add CD 106 as follows:

"106. Length to slider ball mating surface 0.40% 3.2 Gage."

PAGE 12

CD 105, change to read:

"Length of locking surface, min."

PAGE 13

Change the CD for Profile of point from "201" to "202".

PAGE 17

CD 101: Delete "min."

CD 103, change to read: "Distance across tabs, max."

PAGE 18

CD 101, change to "Thickness, max."

FSC 1390

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:48Z
Check the source to verify that this is the current version before use.

PAGE 20

CD 105: Delete "max."

PAGE 21

CD 104: Delete "min."

CD 106, change to read: "Width across ball slots, min."

CD 203, change to read: "Depth of pin slot."

PAGE 22

CD 101: Change "pushout" to "pullout".

PAGE 23

CD 103: Change to read: "Height from top of housing to the bottom of housing cover, max."

Custodian:
Army - AR

Preparing activity:
Army - AR

(Project 1390-A399)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:48Z
Check the source to verify that this is the current version before use.