MILITARY SPECIFICATION

FUZE, BASE DETONATING, M578
LOADING, ASSEMBLING AND PACKING FOR RENOVATION

This Amendment forms a part of Military Specification MIL-F-63253 (AR) dated 28 November 1977.

PAGE 3

3.7.1, Arming time .020 to .040 should be .026 to .040.

PAGE 6

Table I under column paragraph Reference/Inspection method for Arming Delay Assembly, loaded, Change: 4.5.7 to 4.5.6 (3 places).

PAGE 9

4.4.2.3, Add Major 103 upper radius of lead charge cavity, max. AQL 0.40% requirement paragraph 3.2, Inspection Method, Gage.

PAGE 13

4.4.2.6, Major 101 - Change AQL 0.40% to 100%.

PAGE 15

4.4.2.8, add Critical 4 segments not springloaded or open. Requirement paragraph 3.2, inspection method - visual/manual.

PAGE 16

4.4.2.9, in Critical 2, delete "missing or" add Critical 5, both locking segments missing. Number sample units, (a), requirement paragraph 3.4, Inspection Method test 4.5.4.

delete Major 101

to note (a) add as discernible in one view.

FSC: 1315

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:28Z
Check the source to verify that this is the current version before use.

Add the following paragraphs:

4.5.4.1, Radiographic interpretation of explosive defects (see 3.4 e).

4.5.4.1.1, Disjunctures - A radiographic projection of a disjuncture in the booster charge will only be allowed to appear at the juncture of the two pellets. The maximum allowable width of a disjuncture between pellets shall be one sixteenth inch (0.0625 inch) and shall only be within a three sixteenths inch (.1875 inch) band centered at the junction of the pellets.

4.5.4.1.2 Low Density Area - The radiographic projection of a low density area shall only be allowed to appear in three bands (zones) in the booster charge. Two of these bands shall be of one eighth inch (.125) maximum width at the top and bottom (one band each end) of the booster charge. The remaining band shall be located in the booster charge as specified for disjunctures in paragraph 4.5.4.1.1 above. The total aggregation of low density areas shall not exceed one-sixteenth square inch in any band.

4.5.4.1.3 Any low density area or disjuncture which extends through the boundary of any band as described herein shall also be cause for the rejection of a renovated fuze. The preparation and use of a suitable template for use in this determination is suggested.

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project Number: 1315-A336

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:28Z
Check the source to verify that this is the current version before use.