MIL-F-44272
5 May 1987

MILITARY SPECIFICATION

FLAVORINGS, FRUIT, IODINE COMPATIBLE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers iodine compatible, fruit flavorings for drinking water treated with iodine, water purification tablets. The product is intended for use by the Department of Defense as a component of operational rations.

1.2 Classification. The product shall be of the following groups and types, as specified (see 6.1):

Group A - Single flavor type
Group B - Variety of flavors (types I, II and III)
Group C - Variety of flavors (types IV, V, and VI)

Type I - Apple
Type II - Peach
Type III - Raspberry
Type IV - Cherry
Type V - Grape
Type VI - Orange

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8960

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:06Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Documents. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

L-P-378	-	Plastic Sheet and Strip, Thin Gauge, Polyolefin
QQ-A-1876	-	Aluminum Foil
PPP-B-26	-	Bag, Plastic (General Purpose)
PPP-B-636	-	Boxes, Shipping, Fiberboard

MILITARY

MIL-L-10547	-	Liners, Case, and Sheet, Overwrap; Water-Vaporproof or Waterproof, Flexible
MIL-L-35078	-	Loads, Unit: Preparation of Semiperishable Subsistence Items; Clothing, Personal Equipment and Equipage; General Specification For

STANDARDS

FEDERAL

FED-STD-101	-	Test Procedures for Packaging Materials
FED-STD-595	-	Colors

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage

(Copies of documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.1.2 Other Government documents. The following other Government documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:06Z
Check the source to verify that this is the current version before use.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES

Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder (21 CFR Parts 1-199)

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

2.2 Other publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issues of the nongovernment documents which are current on the date of the solicitation.

AMERICAN ASSOCIATION OF CEREAL CHEMISTS (AACC)

Approved Methods of the American Association of Cereal Chemists

(Application for copies should be addressed to the American Association of Cereal Chemists, 3340 Pilot Knob Road, St. Paul, MN 55121.)

ASSOCIATION OF OFFICIAL ANALYTICAL CHEMISTS (AOAC)

Official Methods of Analysis of the Association of Official Analytical Chemists

(Application for copies should be addressed to the Association of Official Analytical Chemists, 1111 North 19th Street, Suite 210, Arlington, VA 22209.)

FLAVOR EXTRACT MANUFACTURE ASSOCIATION (FEMA)

Flavor Extract Manufacture Association Lists

(Application for copies should be addressed to the Flavor Extract Manufacture Association, 900 17th Street, N.W., Washington, DC 20006.)

NATIONAL ACADEMY OF SCIENCES

Food Chemicals Codex

(Application for copies should be addressed to the National Academy Press, 2101 Constitution Avenue, Washington, DC 20148.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Association, Inc., Traffic Department, 2200 Mill Road, Alexandria, VA 22314.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:06Z
Check the source to verify that this is the current version before use.

UNIFORM CLASSIFICATION COMMITTEE, INC.

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1120, 222 South Riverside Plaza, Chicago, IL 60606.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence. Nothing in this document, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.4, 6.1, and 6.3).

3.2 Ingredients. All ingredients shall be clean, sound, wholesome, and free from foreign material, evidence of rodent and insect infestation, off-odors, off-flavors, and off-colors.

3.2.1 Flavors. All natural or artificial flavors, or blends thereof, shall be spray-dried and comply with the Flavor Extract Manufacture Association Lists. The flavor shall be compatible and not react with iodine, water purification tablets. All volatile flavors shall be entrapped or encapsulated in such a manner that the flavors are protected from oxidation, rancidity, evaporation, and other type of deterioration.

3.2.2 Sugar, superfine, granulated. Superfine granulated sugar shall be white and refined, and shall contain not less than 99.5 percent sucrose, not more than 0.04 percent ash, and not more than 0.10 percent moisture. Not more than 5 percent of the sugar shall be retained on a U.S. Standard No. 40 sieve, not more than 20 percent shall pass through a U.S. Standard No. 140 sieve, and not more than 5 percent shall pass through a U.S. Standard No. 200 sieve.

3.2.3 Citric acid. Citric acid shall be anhydrous, fine granular and shall conform to the requirements of the Food Chemicals Codex.

3.2.4 Sodium citrate. Sodium citrate shall be dihydride, fine granular and shall conform to the requirements of the Food Chemicals Codex.

3.3 Formulation. Water flavorings shall be blends of the specified ingredients in the percentages specified below. The product shall not contain coloring materials, ascorbic acid and/or other ingredients that interfere with treatment of water by the iodine, water purification tablet method.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:06Z
Check the source to verify that this is the current version before use.

Percent by weight

Ingredient	Type I Apple	Type II Peach	Type III Raspberry	Type IV Cherry	Type V Grape	Type VI Orange
Sugar	95.96	96.88	97.58	96.79	95.38	94.79
Citric acid	3.33	2.50	2.08	2.75	3.12	3.13
Flavor	0.54 1/	0.42 2/	0.17 3/	0.29 4/	1.25 5/	1.83 6/
Sodium citrate	0.17	0.20	0.17	0.17	0.25	0.25

1/ Apple flavor - Hercules' Natural and Artificial Apple #610871U or equal flavor.

2/ Peach flavor - Virginia Dare Artificial Peach #512 or equal flavor.

3/ Raspberry flavor - Ungerers' Artificial Raspberry #14057 or equal flavor.

4/ Cherry flavor - Fritzsche, Dodge & Olcott, Inc. Aromalok^{R} Artificial Cherry flavor #182337 or equal flavor.

5/ Grape flavor - Fritzsche, Dodge & Olcott, Inc. Aromalok^{R} Artificial Grape flavor #182111 or equal flavor.

6/ Orange flavor - Fritzsche, Dodge & Olcott, Inc. Aromalok^{R} Natural and Artificial Orange flavor #181330 or equal flavor.

3.4 Finished product requirements.

3.4.1 Dry mix product. The dry mix finished product shall comply with the following requirements:

a. There shall be no foreign material such as, but not limited to, dirt insect, insect parts, hair, wood, paper, paint, glass, or metal.

b. There shall be no foreign odor or flavor such as, but not limited to, stale, sour, rancid, musty, or moldy.

c. There shall be no color foreign to the product.

d. The average net weight shall be not less than 24.0 grams.

e. No individual envelope shall contain less than 23.3 grams or greater than 25.2 grams of product.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:06Z
Check the source to verify that this is the current version before use.

f. The product shall be a uniformly blended, free flowing mixture.

g. The product shall not contain lumps which do not fall apart under light finger pressure.

h. The moisture content of the product shall be not greater than 2.0 percent.

3.4.2 Prepared beverage. When the product is prepared as specified in footnote 3 of table II, the beverage shall comply with the following requirements:

a. There shall be no evidence of undissolved flavor (granular particulates).

b. There shall be no evidence of coagulation, sedimentation, gelation, or surface frothing.

c. The beverage shall be color free.

d. The odor shall be characteristic of the specified flavor.

e. The flavor shall be characteristic of the specified flavor.

f. The acidity, expressed as anhydrous citric acid, shall be not less than 0.06 percent nor greater than 0.10 percent.

3.4.3 Palatability. The finished product shall be equal to or better than the approved preproduction sample (see 6.1) in palatability and overall appearance.

3.5 Plant qualification. The product shall be prepared, processed, and packaged in establishments meeting the requirements of Title 21, Code of Federal Regulations, Part 110, "Current Good Manufacturing Practice in Manufacturing, Processing, Packaging or Holding of Human Foods", and the plant sanitation requirements of the appropriate Government inspection agency.

3.6 Federal Food, Drug, and Cosmetic Act. All deliveries shall conform in every respect to the provisions of the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor's responsibility. Inspection and acceptance by the USDA shall not relieve the contractor of obligation and responsibility to deliver a product complying with all requirements of this document. The contractor shall assure product compliance prior to submitting the product to the USDA for any inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:06Z
Check the source to verify that this is the current version before use.

4.2 Inspection and certification. Product acceptability shall be determined by the USDA. The USDA will determine the degree of supervision necessary to assure compliance with the requirements of this document.

4.3 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4).
b. Quality conformance inspection (see 4.5).

4.4 First article inspection. When a first article is required (see 6.1), it shall be inspected in accordance with the quality assurance provisions of this document and evaluated for overall appearance and palatability. Any failure to conform to the quality assurance provisions of this document or any appearance or palatability failure shall be cause for rejection of the first article.

4.5 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.5.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.5.1.1 Ingredient and component examination. Conformance of ingredients and components to identity, condition, and other requirements specified in 3.2 shall be certified by the ingredient supplier or ingredient manufacturer, or compliance be verified by examination of pertinent labels, markings, U.S. Grade Certificates, certificates of analyses, or other such valid documents acceptable to the inspection agency. If necessary, each ingredient shall be examined organoleptically or inspected according to generally recognized test methods, such as the standard methods described in the official Methods of Analysis of the Association of Official Analytical Chemists and in the Approved Methods of the American Association of Cereal Chemists, to determine conformance to the condition requirements. Any nonconformance to an identity, condition, or other requirement shall be cause for rejection of the ingredient or component lot or of any involved product.

4.5.1.2 Material certification. Material listed below shall be accepted on the basis of a contractor's certificate of conformance to the indicated requirements.

Source: https://assist.dla.mil -- Downloaded: 202640-22T01:06Z
Check the source to verify that this is the current version before use.

Material requirement	Requirement paragraph	Test procedure
Envelope		
Thickness of - polyethylene	5.1.1.1	As specified in L-P-378 except that a machinist's micrometer may be used provided that its graduation and accuracy conform to the requirement of L-P-378
- Aluminum foil	5.1.1.1	As specified in QQ-A-1876
Basis weight of paper	5.1.1.1	Method 5022 of FED-STD-101
Laminated material construction	5.1.1.1	Laboratory evaluation
Color of laminated material	5.1.1.1	Visual evaluation
Plastic bag		
Thickness of polyethylene	5.1.1.2	As specified in L-P-378 except that a machinist's micrometer may be used provided that its graduation and accuracy conform to the requirement of L-P-378
Color of polyethylene	5.1.1.2	Visual evaluation

4.5.2 In-process examination. In-process examination shall be performed to determine conformance to formulation and packaging requirements. Any nonconformance revealed by actual examination or by review of records of formulation or of other valid documents shall be cause for rejection of the involved product.

4.5.3 Net weight examination. The net weight of the filled and sealed envelopes shall be determined by weighing each sample unit on a suitable scale tared with an average weight of representative empty envelopes. Any individual net weight of less than 23.3 grams or greater than 25.2 grams shall be scored as a minor defect. The lot size shall be expressed in envelopes. The sample unit shall be one filled and sealed envelope. The inspection level shall be S-3 and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5. Results shall be reported to the nearest 0.1 gram. In addition, the lot shall be rejected if the sample average net weight is less than 24.0 grams.

Source: https://assist.dla.mil -- Downloaded: 202610-22T01:06Z
Check the source to verify that this is the currentversion before use.

4.5.4 Envelope examination. The filled and sealed envelopes shall be examined for the defects listed in table I. The lot size shall be expressed in envelopes. The sample unit shall be one filled and sealed envelope. The inspection level shall be I and the AQL, expressed in terms of defects per hundred units, shall be 0.65 for major defects and 2.5 for minor defects.

TABLE I. Envelope defects

Category		Defect
Major	Minor	
101		Tear, hole, sifter, or open seal
102		Not material specified
103		Not formed as specified
104		Inside dimensions not as specified
105		Seals not produced by heat
106		Any seal width less than 1/8 inch
107		Not clean
108		Objectionable odor
109		Color not as specified
110		Excess air not removed
111		Nomenclature or directions for use missing, incorrect, or illegible
	201	Other required label information missing, incorrect, or illegible

4.5.5 Envelope leakage, delamination, and seal separation testing. The filled and sealed envelopes shall be tested by placing them in a dry desiccator or similar apparatus and subjecting them to a differential vacuum of 26 inches of mercury (atmospheric pressure is 29.9 inches of mercury) for 30 seconds. Any envelope that does not swell to form a tightly distended package having at least one distorted edge while under the vacuum shall be considered evidence of leakage. After leakage testing, each envelope shall be visually examined for evidence of delamination and seal separation. Any leakage, delamination, or any seal separation of more than 1/16 inch from the product edge of any seal in any envelope shall be classified as a major defect. The lot size shall be expressed in envelopes. The sample unit shall be one filled and sealed envelope. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 1.0.

4.5.6 Product examination. The product shall be examined for the defects listed in table II. Each flavor shall be considered a separate lot. The lot size shall be expressed in envelopes. The sample unit shall be the contents of one filled and sealed envelope. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:06Z
Check the source to verify that this is the current version before use.

TABLE II. Product defects 1/ 2/

Category	Defect
Major	Dry form
101	Not free flowing
102	Not uniformly blended
103	Presence of lumps which do not fall apart with light finger pressure
	Prepared beverage 3/
104	Evidence of undissolved flavor (granular particulates)
105	Evidence of coagulation, sedimentation, gelation, or surface frothing
106	Not color free
107	Odor not characteristic of the specified flavor
108	Flavor not characteristic of the specified flavor

1/ The presence of foreign material (e.g. metal, glass, wood, dirt, hair, insects, insect parts), foreign odor or flavor (e.g. stale, sour, rancid, oxidized, moldy), or foreign color shall be cause for rejection of the lot.

2/ Product not equal to or better than the approved preproduction sample (see 6.1) in palatability and overall appearance shall be cause for rejection of the lot. (This comparison shall be performed only when deemed necessary by an Agricultural Marketing Service (AMS) agent.)

3/ The contents of one envelope shall be added to 32 fluid ounces of water (40° to 50°F). The mixture shall be gently agitated and allowed to stand for approximately 2 minutes.

4.5.7 Product testing. The finished product shall be tested for the characteristics specified in table III. Each flavor shall be tested separately. The sample for testing shall be a 1-pound composite derived from the number of envelopes indicated by inspection level S-4. Lot size shall be expressed in envelopes. Any test failure shall be cause for rejection of the lot.

TABLE III. Product tests

Characteristic	Requirement paragraph	Test method	Results reported to nearest
Moisture content	3.4.1 h.	1/	0.1 percent
Acid content	3.4.2 f.	2/	0.01 percent

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:06Z
Check the source to verify that this is the current version before use.

1/ The moisture content shall be determined in accordance with the Vacuum Drying- Official Final Action method in the Official Methods of Analysis of the Association of Official Analytical Chemists, chapter: Sugar and Sugar Products, section: Sugars and Sirups.

2/ The acid content shall be determined in accordance with the Titratable Acidity (Glass Electrode) method in the Official Methods of Analysis of the Association of Official Analytical Chemists, chapter: Fruits and Fruit Products.

4.5.8 Plastic bag examination. The filled and sealed plastic bags shall be examined for the defects listed in table IV. The lot size shall be expressed in plastic bags. The sample unit shall be one filled and sealed plastic bag. The inspection level shall be I and the AQL, expressed in terms of defects per hundred units, shall be 0.65 for major defects and 2.5 for minor defects.

TABLE IV. Plastic bag defects

Category		Defect
Major	Minor	
101		Tear, hole, or open seal
102		Not material specified
103		Not fabricated in type or style specified
104		Dimensions not as specified
105		Any seal width less than 1/8 inch
106		Closure not style specified
107		Not clean
108		Objectionable odor
109		Color not as specified
110		Excess air not removed
	201	Interlocking closure seal not located as specified
	202	Markings missing, incorrect, or illegible

4.5.9 Plastic bag leakage and seal separation testing. The filled and sealed plastic bags shall be tested by placing them in a dry desiccator or similar apparatus and subjecting them to a differential vacuum of 20 inches of mercury (atmospheric pressure is 29.9 inches of mercury) for 30 seconds. Any bag that does not swell to form a distended package while under the vacuum shall be considered evidence of leakage. After leakage testing, each bag shall be examined for evidence of seal separation. Any leakage or any seal separation of more than 1/16 inch from the inside edge of any seal in any bag, shall be classified as a major defect. The lot size shall be expressed in bags. The sample unit shall be one filled and sealed bag. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 1.0.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:06Z
Check the source to verify that this is the current version before use.

4.5.10 Plastic bag contents examination. Plastic bags shall be examined for the defects listed in table V. The lot size shall be expressed in bags. The sample unit shall be one filled and sealed bag. The inspection level shall be S-4 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

TABLE V. Plastic bag contents defects

Category	Defect
Minor	
201	Less than required number of envelopes per plastic bag
202	Flavor or variety of flavors, not as specified

4.5.11 Shipping container examination. When shipping containers are required to be in accordance with PPP-B-636, examination for defects in assembly, closure, and reinforcement shall be in accordance with the appendix of PPP-B-636. In addition, the following defects shall be classified as follows:

Major: National stock number, item description, contract number, or date of pack markings missing, incorrect, or illegible.
Number of plastic bags not as specified.
Reinforced with other than nonmetallic strapping or tape.

Minor: Other required markings missing, incorrect, or illegible.
Container not snug-fitting.

Level C shipping containers shall be examined for the markings and number of plastic bag defects specified above and for the closure method specified in 5.2.2.

4.5.12 Case liner examination. Case liners shall be examined in accordance with the examination criteria in the appendix of MIL-L-10547.

4.5.13 Unit load inspection. Inspection of unit loads shall be in accordance with the quality assurance provisions of MIL-L-35078.

5. PACKAGING

5.1 Preservation. The product shall be preserved in accordance with level A.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:06Z
Check the source to verify that this is the current version before use.

5.1.1 Level A.

5.1.1.1 Unit pack (envelopes). A net weight of 24.0 grams of product, of one flavor only, shall be unit packed in a four-seal style envelope fabricated and closed by heat sealing. Each seal shall be a minimum 1/8 inch wide. Excess air shall be expelled prior to closure sealing. The inside dimensions of the envelope shall be 3-1/8 inches by 2-5/8 inches ± 1/8 inch in either direction. The envelope material shall be made by extruding or laminating 0.001-inch thick polyethylene to 0.00035-inch thick aluminum foil and laminating the plain side of the foil to sulfite or kraft paper having a basis weight of 25 pounds per ream. The adhesive, for laminating the foil to the paper, shall be a suitable, odorless, and permanently water resistant material other than wax. The outside of the envelope shall be a natural kraft or similar brown color. The filled and sealed envelope shall not leak, show evidence of delamination, or have seal separation of more than 1/16 inch from the product edge of any seal when tested in accordance with 4.5.5

5.1.1.2 Intermediate pack (plastic bags). Eight envelopes (see 5.1.1.1) of a single flavor (group A) or of a variety of flavors (group B; 3 type I, 3 type II, 2 type III; or group C: 3 type IV, 3 type V, 2 type VI), shall be packed in a plastic bag. The bag shall be made from food approved 0.004-inch thick polyethylene in accordance with type II, style 3 of PPP-B-26, except that the polyethylene shall be colored overall with a color in the number range from 24052 through 24087 inclusive or in the number range from 34052 to 34108 inclusive or 20045, 20062, or 30045 of FED-STD-595, or white when specified (see 6.1). The inside dimensions of the bag shall be 4-1/4 inches wide by 7-1/8 inches long, +1/4, -1/8 inch in either direction. The bag manufacturer's seals shall be not less than 1/8 inch wide. Excess air shall be expelled prior to closure sealing. The interlocking seal shall be effected by applying pressure with the fingers to the seal area. The inside edge of the interlocking closure seal shall be located not more than 3/4 inch or less than 1/2 inch from the open end of the bag. The bag seals shall not fail or peel back more than 1/16 inch from the inside edge, and the bag shall not leak when tested in accordance with 4.5.9.

5.2 Packing. Nine hundred and sixty envelopes (120 plastic bags), preserved as specified in 5.1, shall be packed in a snug-fitting shipping container in accordance with level A or C, as specified (see 6.1).

5.2.1 Level A packing. The shipping container shall be a fiberboard box, constructed and closed in accordance with style RSC-SL, grade V2s of PPP-B-636. The contents of each container shall be enclosed in a waterproof case liner, fabricated and closed in accordance with MIL-L-10547 for subsistence items. Each fiberboard box shall be reinforced with nonmetallic strapping or pressure-sensitive adhesive filament-reinforced tape in accordance with the appendix of PPP-B-636. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.1). When unit loads are strapped, strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:06Z
Check the source to verify that this is the current version before use.

5.2.2 Level C packing. The shipping container shall be in accordance with National Motor Freight Classification or Uniform Freight Classification, as applicable, except that the closure of fiberboard boxes shall be in accordance with method II as specified in the appendix of PPP-B-636.

5.3 Unit loading. When specified (see 6.1), the product, packed as specified in 5.2.2, shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified. When unit loads are strapped, the strapping shall be limited to nonmetallic strapping except for type II, class F loads.

5.4 Labeling and marking.

5.4.1 Envelopes. Envelopes shall be labeled in accordance with the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder. The labeling shall be in contrasting color to the color of the envelope to facilitate reading and shall contain the following information:

FLAVORINGS, FRUIT, IODINE COMPATIBLE
(for drinking water treated with iodine, water purification tablets)

FLAVOR (as applicable)
NET WEIGHT: 24 grams
INGREDIENTS: (as applicable)
DIRECTIONS: Add entire contents of this package to one full canteen of water (32 fluid ounces). Shake well to dissolve.

Name and address of manufacturer.

5.4.2 Plastic bags. Each plastic bag shall be printed on at least one face in permanent ink in clear black letters not less than 3/16 inch high, as follows:

NAME OF PRODUCT
FLAVOR(S)
NUMBER AND NET WEIGHT OF ENVELOPES

5.4.3 Shipping containers. Shipping containers shall be marked in accordance with MIL-STD-129.

5.4.4 Unit loads. Unit loads shall be marked in accordance with MIL-L-35078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:06Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. Group of product required (see 1.2).
c. Type of product required when group A is specified (see 1.2).
d. When a first article is required (see 3.1, 4.4, and 6.3).
e. Provisions for approved preproduction samples (see 3.4.3 and 6.3).
f. When color of polyethylene for plastic bag is required to be white (see 5.1.1.2).
g. Level of packing required (see 5.2).
h. Type and class of unit load when unit loading is required (see 5.2.1 and 5.3).

6.2 Appropriate level of pack. Based on the conditions known or expected to be encountered during shipment, handling, and storage of the specific item being procured, the procuring activity should select the appropriate level of pack in accordance with the criteria established in AR 700-15/NAVSUPINST 4030.28/AFR 71-6/MCO 4030.33A/DLAR 4145.7.

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should include specific instructions in all acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.4 Subject term (key word) listing.

Drinking water
Flavorings
Iodine compatible
Water purification

Custodians:

Army - GL
Navy - SA
Air Force - 50

Preparing activity:

Army - GL

Project No. 8960-A068

Review activities:

Army - MD, TS
Navy - MC, MS
DP - SS

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:06Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-F-44272	Flavorings, Fruit, Iodine Compatible

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

Source: https://assist.dla.mil -- Downloaded: 20260-22T01:06Z
Check the source to verify that this is the current version before use.