INCH-POUND

MIL-H-44265A
5 February 1990
SUPERSEDING
MIL-H-44265
22 December 1986

MILITARY SPECIFICATION

# HOOD, COMBAT VEHICLE CREWMEN'S (BALACLAVA)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

## 1. SCOPE

1.1 Scope. This specification covers one type and size of balaclava combat vehicle, crewmens hood made of fire-resistant materials.

## 2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

| | | |
|---|---|---|
| A-A-50083 | - | Bag, Plastic, Folded Garment |
| DDD-L-20 | - | Label: For Clothing, Equipage, and Tentage (General Use) |
| PPP-B-636 | - | Boxes, Shipping, Fiberboard |

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8415

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:04Z
Check the source to verify that this is the current version before use.

MILITARY

| | | |
|---|---|---|
| MIL-C-3735 | - | Cuffs, Knit, Wrist and Ankle, and Cloth, Knitted |
| MIL-L-35078 | - | Loads, Unit: Preparation of Semiperishable Subsistence Items; Clothing, Personal Equipment and Equipage; General Specification For |
| MIL-C-43303 | - | Cord, Elastic Cotton |
| MIL-T-43636 | - | Thread, Aramid |
| MIL-W-43685 | - | Webbing, Tape, Textile, Aramid Fiber |
| MIL-C-44236 | - | Cloth, Knitted, Aramid, Bi-Ply |
| MIL-C-44263 | - | Cloth, Laminated, Waterproof, Moisture Vapor Permeable and Flame Resistant (Wt. 3.4 oz) |

STANDARDS

FEDERAL

| | | |
|---|---|---|
| FED-STD-751 | - | Stitches, Seams, and Stitchings |

MILITARY

| | | |
|---|---|---|
| MIL-STD-105 | - | Sampling Procedures and Tables for Inspection by Attributes |
| MIL-STD-129 | - | Marking for Shipment and Storage |
| MIL-STD-147 | - | Palletized Unit Loads |
| MIL-STD-731 | - | Quality of Wood Members for Containers and Pallets |

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:04Z
Check the source to verify that this is the current version before use.

THE COLOR ASSOCIATION OF THE UNITED STATES

Standard Color Card of America

Department of Defense Standard Color Card for Sewing Threads

(Color cards may be available from the Color Association of the United States, 343 Lexington Avenue, New York, NY 10016-0927. If color cards are not available from the Color Association, individual color samples may be obtained from the contracting activity or as directed by the contracting activity.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.3.

3.2 Guide sample. Guide samples, when furnished, are solely for guidance and information to the contractor (see 6.4). Variation from this specification may appear in the sample, in which case this specification shall govern.

3.3 Materials. It is encouraged that recycled material be used when practical as long as it meets the requirements of this specification.

3.3.1 Cloth, knit, aramid. The outer shell of the hood (cover fabric) shall be knit, aramid, Olive Green 106 cloth conforming to type IV, class 3 of MIL-C-3735.

3.3.2 Cloth, knitted, aramid, bi-ply. The bib, the lining (layer next to head), and the center strip insert and side vent insert of the interlining shall be bi-ply aramid, Olive Green 106 cloth conforming to MIL-C-44236.

3.3.3 Cloth, laminated, waterproof, moisture vapor permeable and flame resistant. The interlining (middle layer) of the hood shall be a natural color and conform to MIL-C-44263.

3.3.4 Elastic cord. The elastic cord for the face opening shall conform to class 2 of MIL-C-43303. The color shall be Olive Drab 7.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:04Z
Check the source to verify that this is the current version before use.

3.3.5 Webbing, aramid. The aramid webbing for the pull tab shall conform to type II of MIL-W-43685, except for Test Method 5660, the test specimen shall be exposed for 6 standard fading hours and at the end of each 3 hour exposure period, a new piece of calibration paper shall be placed in the machine. The color shall be Olive Green 106.

3.3.6 Thread, aramid. The aramid thread shall conform to size B of MIL-T-43636. The color shall be Olive Drab S-1, C.A. 66022.

3.3.7 Label. The label shall conform to type VI, class 14 of DDD-L-20. Fastness to laundering requirements of DDD-L-20 shall apply. The label shall contain the following information in capital letters:

HOOD, COMBAT VEHICLE CREWMEN'S (BALACLAVA)

WASHING INSTRUCTIONS: LAUNDER IN ACCORDANCE WITH NATICK FORMULA I.

DO NOT TUMBLE DRY OR WRING/TWIST.

HAND WASH IN WARM WATER USING MILD DETERGENT.

RINSE IN CLEAR WARM WATER AND HANG TO DRIP DRY AT ROOM TEMPERATURE.

DO NOT DRY CLEAN.

The contractor shall insert the Date of Manufacture with indelible ink.

3.4 Design. The hood shall be the pull-over-the-head type with attached bib. The hood shall have a facial opening which may be adjusted by means of a pull tab.

3.5 Figure 1. Figure 1 is furnished for information only. If there are any inconsistencies between the written specification and the figure, the written specification shall control.

3.6 Patterns. Standard patterns, which provide an allowance for all seams, will be furnished by the Government and shall be used by the contractor as a guide for cutting working patterns only. The standard patterns shall not be altered in any way (except as indicated in 3.7.2) and the working patterns shall be cut to conform exactly to the standard patterns.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:04Z
Check the source to verify that this is the current version before use.

3.6.1 Pattern parts. The pattern parts, cutting quantities, and materials for the parts shall be as specified below:

Components for outer cover

| Material | Item | Nomenclature of part | Parts per hood |
|---|---|---|---|
| Cloth, knit, aramid | 1 | Side cover | 2 |
| | 2 | Center top cover | 1 |
| | 3 | Center neck cover | 1 |

Components for lining

| Material | Item | Nomenclature of part | Parts per hood |
|---|---|---|---|
| Cloth, knitted, aramid, bi-ply | 1 | Side lining | 2 |
| | 2 | Center top lining | 1 |
| | 3 | Center neck lining | 1 |

Components for interlining

| Material | Item | Nomenclature of part | Parts per hood |
|---|---|---|---|
| Cloth, laminated, waterproof, moisture vapor permeable and flame resistant | 1 | Side interlining | 2 |
| | 2 | Center interlining | 2 |
| Cloth, knitted, aramid, bi-ply | 3 | Side vent insert | 2 |
| | 4 | Center strip insert | 1 |

Components for bib

| Material | Item | Nomenclature of part | Parts per hood |
|---|---|---|---|
| Cloth, knitted, aramid, bi-ply | 1 | Front bib | 1 |
| | 2 | Back bib | 1 |

3.7 Construction. The construction shall conform to the requirements specified in table I and herein.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:04Z
Check the source to verify that this is the current version before use.

3.7.1 Stitches, seams, and stitching. All stitches, seams, and stitching shall conform to FED-STD-751. The type of seam, stitching, and stitches per inch shall be as specified in table I. Seam allowances shall be maintained with seams sewn so that no raw edges, run-offs, twists, pleats, puckers, or open seams occur. All seams shall start and end evenly. Thread tension shall be maintained so that there is no tight or loose stitching.

3.7.1.1 Type 301 stitching. Ends of all stitching shall be backstitched or overstitched 1/2 inch minimum except when caught in other stitching or turned under in a hem. Thread tension shall be maintained so that there will be no loose stitching resulting in loose bobbin or top thread, or excessively tight stitching resulting in puckering of the materials sewn. The lock shall be embedded in the materials sewn.

3.7.1.1.1 Repairs of type 301 stitching. Repairs of type 301 stitching shall be as follows:

a. When thread breaks or bobbin run-outs occur during sewing, the stitching shall be repaired by restarting the stitching a minimum of 1 inch back of the end of the stitching. 1/

b. Thread breaks or two or more consecutive skipped or run-off stitches noted during inspection of the item (in-process or end item) shall be repaired by overstitching. The stitching shall start a minimum of 1 inch in back of the defective area and continue a minimum of 1 inch beyond the defective area on to the existing stitching. Loose or excessively tight stitching shall be repaired by removing the defective stitching, without damaging the materials, and restitching in the required manner. 1/

1/ When making the above repairs, the ends of the stitching are not required to be backstitched.

3.7.1.2 Type 401 stitching. Thread tension shall be maintained so that there will be no loose stitching. Both ends of all seams or stitching produced with 401 stitch type, when not turned under in a hem or held down by other stitching, shall have a 1/2 to 3/4 inch chain extending beyond each end. The looper (under thread) shall be hidden between the cover and lining assembly. All repairs shall be in accordance with 3.7.1.1.1a and 3.7.1.1.1b. Repairs may be made using 301 stitch type.

3.7.1.3 Types 502, 503, 504, 515, 516, and 519 stitching. Thread tension shall be maintained so that there will be no loose stitching. All repairs shall be in accordance with 3.7.1.1.1a and 3.7.1.1.1b except substitute 3/4 inch for 1 inch wherever 1 inch appears.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:04Z
Check the source to verify that this is the current version before use.

3.7.2 Use of automated apparel equipment. Automated apparel equipment may be used to perform any of the operations specified in table I, providing that the seam and stitch type are as specified and the finished component conforms to the required configuration. When a government furnished shaper pattern is forwarded, the component shall conform to that pattern.

3.7.3 Stitches per inch. The minimum and maximum number of stitches per inch shall be as specified in table I.

3.8 Manufacturing operation requirements. The hood shall be manufactured in accordance with operation requirements specified in table I. The contractor is not required to follow the exact sequence of operations. Any additional basting or holding stitching used to facilitate manufacture is permissible, provided the thread is removed or does not show on the finished hood (see 6.5).



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:04Z
Check the source to verify that this is the current version before use.

| NO. | TABLE I. MANUFACTURING OPERATIONS REQUIREMENTS | STITCH TYPE | SEAM AND STITCHING TYPE | STITCHES PER INCH | THREAD | | |
|---|---|---|---|---|---|---|---|
| | | | | | NEEDLE | BOBBIN/ LOOPER | COVER |
| 1. | Cut hood.<br><br>a. Cut the hood in strict accordance with patterns which show shape, cutting directional lines, placement of components and notches for proper assembly. Directional lines on knit fabric shall be placed in the wales direction, with the exception of the front and back bib, which may be placed in the direction of either the wales or courses as specified on the pattern pieces. Directional lines on the laminated fabric shall be in the warp direction.<br><br>NOTE: Care should be taken when cutting to prevent ravelling while handling.<br><br>b. The cover layer parts of each hood shall be cut from the same piece of material. The lining and bib parts for each hood shall be cut from the same piece of material.<br><br>c. Cut elastic cord 18 ± 1/4 inches in length. Cut the webbing for pull tab 3-1/2 ± 1/4 inches in length.<br><br>NOTE: Use of a ballpoint needle for stitching operations has been found to prevent the cutting of yarns (See 6.5). | | | | | | |
| 2. | Replacement of defective components.<br><br>During the spreading, cutting, and manufacturing process, components having material defects or damages that are classified as defects in 4.4.2.2 | | | | | | |

NATICK Form 903
1 Dec 76 EDITION OF 1 OCT 76 WILL BE USED UNTIL EXHAUSTED.





Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:04Z
Check the source to verify that this is the current version before use.

| NO. | TABLE I. (cont'd)<br>MANUFACTURING OPERATIONS REQUIREMENTS | STITCH TYPE | SEAM AND STITCHING TYPE | STITCHES PER INCH | THREAD | | |
|---|---|---|---|---|---|---|---|
| | | | | | NEEDLE | BOBBIN/ LOOPER | COVER |
| 2. | Replacement of defective components. (cont'd)<br><br>and 4.4.3 shall be removed from production and replaced with nondefective and properly matched components. | | | | | | |
| 3. | Marking.<br><br>Mark, ticket or bundle all components, except those cut from ends, to insure a uniform shade and size throughout the hood. Any method of marking may be used except:<br><br>a. Corrosive metal fastening devices.<br>b. Sew-on type tickets.<br>c. Adhesive type tickets which leave traces of paper or adhesive on the material upon removal of the tickets. | | | | | | |
| 4. | Make pull tab.<br><br>Fold one end of pull tab with raw edge turned under and center one 3/4 ± 1/16 inch bartack across width of tab with bartack 1/16 to 1/8 inch from turned edge. | Bartack | EFb-1 | 38-42 per bartack | B | B | |
| 5. | Make bib.<br><br>a. Join front bib and back bib (with face side of fabric 1/ toward wearer) at shoulder seams with safety stitch. The stitch gauge for overedge stitching shall be 1/8 to 3/16 inch and the stitch margin for the chain stitch shall be 3/8 ± 1/16 inch. Seam allowances shall finish inside of hood. | 515, 516, or 519 | SSa-2 | 6-10 | B | B | |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:04Z
Check the source to verify that this is the current version before use.

| NO. | TABLE I. (cont'd)<br>MANUFACTURING OPERATIONS REQUIREMENTS | STITCH TYPE | SEAM AND STITCHING TYPE | STITCHES PER INCH | THREAD | | |
|---|---|---|---|---|---|---|---|
| | | | | | NEEDLE | BOBBIN/ LOOPER | COVER |
| 5. | Make bib. (cont'd) | | | | | | |
| | 1/ The bi-ply fabric used for the lining and bib has tuck stitches joining the plies together. The side of the fabric which has the tuck stitch loop shall be considered the face side of the fabric. | | | | | | |
| | b. Overedge stitch the bottom edges of bib assembly using 1/8 to 3/16 inch gauge. | 502 or 503 | EFd-1 | 6-10 | B | B | |
| 6. | Make cover layer. | | | | | | |
| | a. Join edge of each side cover to center top cover from base of hood at back of neck to face opening distributing fullness of side cover into center top cover between notches. The stitch margin shall be 3/8 ± 1/16 inch. | 401 | SSz-3(a) | 8-12 | B | B | |
| | b. Spread seams open and stitch on each side of joining seam with one row of stitching 1/8 ± 1/16 inch from joining seam catching turned seam allowances. | 401 | SSz-3(b) | 8-12 | B | B | |
| | c. Join front edge of each side cover to center neck cover from base of hood at throat to face opening forming tuck as indicated by marks on pattern. The tuck shall finish down. The tuck should finish 5/8 ± 1/8 inch. The stitch margin shall be 3/8 ± 1/16 inch. | 401 | SSz-3(a) | 8-12 | B | B | |
| | d. Spread seams open and stitch on each side of joining seam with one row of stitching 1/8 ± 1/16 inch from joining seam catching turned seam allowances. | 401 | SSz-3(b) | 8-12 | B | B | |





Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:04Z
Check the source to verify that this is the current version before use.

| NO. | TABLE I. (cont'd) MANUFACTURING OPERATIONS REQUIREMENTS | STITCH TYPE | SEAM AND STITCHING TYPE | STITCHES PER INCH | THREAD | | |
|---|---|---|---|---|---|---|---|
| | | | | | NEEDLE | BOBBIN/ LOOPER | COVER |
| 6. | Make cover layer. (cont'd) | | | | | | |
| | e. Position pull tab on outside of center neck cover with pull tab centered between joining seams and with raw edge of pull tab and top raw edge of center neck cover aligned. The turned edge of pull tab shall face wearer. Overedge stitch the face opening edges using 1/8 to 3/16 inch gauge while simultaneously catching the pull tab in overedge stitching. | 401, 503 or 504 | SSa-1 EFd-1 | 8-12 6-10 | B B | B B | |
| 7. | Make lining and attach label. | | | | | | |
| | NOTE: The face side of the lining fabric shall finish towards the wearer. | | | | | | |
| | a. Center label between sides of center top lining with bottom edge of label 2-1/4 ± 1/4 inches from bottom edge of center top lining. Attach label to face side of lining with one row of stitching on all four sides 1/4 ± 1/16 inch from edge of label. The stitching shall not penetrate the printing on the label. | 301 or 401 | LSbj-1 | 8-12 | B | B | |
| | b. Join edge of each side lining to center top lining from base of hood at back of neck to face opening distributing fullness of side lining into center top lining between notches. The stitch margin shall be 3/8 ± 1/16 inch. | 401 | SSz-3(a) | 8-12 | B | B | |
| | NOTE: Stitch take-up is greater on lining cloth than on cover cloth. Appropriate tension shall be maintained to assure the length of joining seams of lining are the same length as joining seams of the cover. | | | | | | |





Source: https://assist.dla.mil/ Downloaded: 2026-10-22T01:04Z
Check the source to verify that this is the current version before use.

| NO. | TABLE I. (cont'd) MANUFACTURING OPERATIONS REQUIREMENTS | STITCH TYPE | SEAM AND STITCHING TYPE | STITCHES PER INCH | THREAD | | |
|---|---|---|---|---|---|---|---|
| | | | | | NEEDLE | BOBBIN/ LOOPER | COVER |
| 7. | Make lining and attach label. (cont'd) | | | | | | |
| | c. Spread seams open and stitch on each side of joining seam with one row of stitching 1/16 to 1/8 inch from joining seam catching the turned seam allowances. | 401 | SSz-3(b) | 8-12 | B | B | |
| | d. Join front edge of each side lining to center neck lining from base of hood at throat to face opening forming tuck as indicated by marks on pattern. The tuck shall finish down. The stitch margin shall be 3/8 ± 1/16 inch. | 401 | SSz-3(a) | 8-12 | B | B | |
| | e. Spread seams open and stitch on each side of joining seam with one row of stitching 1/16 to 1/8 inch from joining seam catching turned seam allowances. | 401 | SSz-3(b) | 8-12 | B | B | |
| 8. | Make interlining. | | | | | | |
| | NOTE: The plastic film side of the laminated fabric shall face the lining. | | | | | | |
| | a. Overedge the bottom edge of side vent inserts and top and bottom edges of center strip insert using 1/8 to 3/16 inch gauge. | 503 or 504 | EFd-1 | 6-10 | B | B | |
| | b. Slash side interlining in accordance with mark on pattern. | | | | | | |
| | c. Position side vent insert under slashed opening of side interlining with edges of slash overlapping side vent insert 1/2 ± 1/16 inch (the insert shall be against the plastic film side of side interlining). | 301 or 401 | LSa-2 | 8-12 | B | B | |







Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:04Z
Check the source to verify that this is the current version before use.

| NO. | TABLE I. (cont'd) MANUFACTURING OPERATIONS REQUIREMENTS | STITCH TYPE | SEAM AND STITCHING TYPE | STITCHES PER INCH | THREAD | | |
|---|---|---|---|---|---|---|---|
| | | | | | NEEDLE | BOBBIN/ LOOPER | COVER |
| 8. | Make interlining. (cont'd) | | | | | | |
| | Attach the side vent insert to side interlining with two rows of stitching along sides and across top of vent insert (creating a triangular effect). The distance between the two rows of stitching shall be 1/16 to 1/8 inch with the first row 1/4 ± 1/16 inch from the raw edges of the interlining slash. | | | | | | |
| | d. Lap edge of each side interlining (film side down) 3/4 ± 1/16 inch over corresponding edge of each center interlining from base of hood at back of neck to face opening. Join the interlinings with one row of stitching 3/8 ± 1/16 inch from raw edge of side interlining. | 301 | LSa-1 | 8-12 | B | B | |
| | e. Lap back edge of each center interlining (film side down) 1/2 ± 1/16 inch over corresponding edge of center strip insert from base of hood at back of neck to face opening. Join edge of each interlining to insert with two rows of stitching 1/16 to 1/8 inch apart with the first row of stitching 1/4 ± 1/16 inch from raw edge of center interlining. | 301 or 401 | LSa-2 | 8-12 | B | B | |
| 9. | Join interlining to lining. | | | | | | |
| | NOTE: The film side of interlining fabric shall face the back side of lining fabric. | | | | | | |
| | a. Align front raw edge of each side interlining with corresponding raw edge of turned seam allowance of center neck lining joining seam, then join interlining to lining with one row of stitching 3/8 ± 1/16 inch from aligned raw edges. | 401 | SSa-1 | 8-12 | B | B | |

NATICK Form 903
1 Dec 76 EDITION OF 1 OCT 76 WILL BE USED UNTIL EXHAUSTED.





Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:04Z
Check the source to verify that this is the current version before use.

| NO. | TABLE I. (cont'd) MANUFACTURING OPERATIONS REQUIREMENTS | STITCH TYPE | SEAM AND STITCHING TYPE | STITCHES PER INCH | THREAD | | |
|---|---|---|---|---|---|---|---|
| | | | | | NEEDLE | BOBBIN/ LOOPER | COVER |
| 9. | Join interlining to lining. (cont'd) | | | | | | |
| | b. With face opening edges of lining and interlining aligned, join lining to interlining by stitching around face opening 3/16 ± 1/16 inch from aligned raw edges. | 401 | SSa-1 | 8-12 | B | B | |
| | c. Attach center interlining to center top lining with two 1/2 ± 1/16 inch long bartacks positioned parallel to joining seams of center to side linings as indicated by marks on patterns.<br><br>NOTE: The bartacks shall be superimposed on the existing stitching which is intended to catch the turned under seam allowance. | Bartack | | 24-28 per bartack | B | B | |
| 10. | Join lining/interlining assembly to cover. | | | | | | |
| | a. Position assembly and cover, face opening to face opening. (Note: The face side of lining shall be placed against outside surface of cover). With raw edges of face opening aligned, join cover to assembly by stitching around face opening 3/8 ± 1/16 inch from raw edges catching end of pull tab in the stitching. The center strip insert shall be centered between the joining seams of center top cover and side covers.<br><br>NOTE: Ends of seams of cover and assembly are staggered and are not intended to line up with one another. | 401 | SSe-2(a) | 8-12 | B | B | |





NATICK Form 903
1 Dec 76 EDITION OF 1 OCT 76 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:04Z
Check the source to verify that this is the current version before use.

| NO. | TABLE I. (cont'd)<br>MANUFACTURING OPERATIONS REQUIREMENTS | STITCH TYPE | SEAM AND STITCHING TYPE | STITCHES PER INCH | THREAD | | |
|---|---|---|---|---|---|---|---|
| | | | | | NEEDLE | BOBBIN/ LOOPER | COVER |
| 10. | Join lining/interlining assembly to cover. (cont'd) | | | | | | |
| | b. Center abutted ends of elastic cord on seam allowance at center top cover and attach to cover seam allowance with a 1/2 ± 1/16 inch bartack placed through each end of elastic cord. The long dimension of each bartack shall be in the length direction of the cord. | Bartack | | 24-28 per bartack | B | B | |
| | c. Turn hood to finished position, work out edges, and stitch around face opening 3/4 to 7/8 inch from turned edges, creating a tunnel for elastic. The looper thread shall be visible on the exterior cover of the hood. Do not catch elastic in stitching. Pull tab shall be caught in the tunnel stitching. | 401 | SSe-2(b) | 8-12 | B | B | |
| 11. | Bartack pull tab. | | | | | | |
| | a. Center a 3/4 ± 1/16 inch bartack across width of pull tab 1/8 ± 1/16 inch from turned edge of face opening. | Bartack | | 38-42 per bartack | B | B | |
| | b. Center a 3/4 ± 1/16 inch bartack across pull tab with bartack superimposed on tunnel stitching. The drawcord shall be between the two bartacks, floating freely inside the tunnel at this point. | Bartack | | 38-42 per bartack | B | B | |
| 12. | Join bib to cover/interlining/lining assembly. | | | | | | |
| | a. With bottom edges of lining, cover, and top bib even, join lining to cover with overedge stitch around the bottom. The stitch gauge shall be 3/16 to 1/4 inch. | 503 or 504 | SSa-1 | 6-10 | B | B | |



Source: https://assist.dla.mil Downloaded: 2026-10-22T01:04Z
Check the source to verify that this is the current version before use.

| NO. | TABLE I. (cont'd) MANUFACTURING OPERATIONS REQUIREMENTS | STITCH TYPE | SEAM AND STITCHING TYPE | STITCHES PER INCH | THREAD | | |
|---|---|---|---|---|---|---|---|
| | | | | | NEEDLE | BOBBIN/ LOOPER | COVER |
| 12. | Join bib to cover/interlining/lining assembly. (cont'd) | | | | | | |
| | NOTE: Ends of seams of cover and lining are staggered and are not intended to line up with one another. | | | | | | |
| | b. With edges of top of bib and bottoms of cover and lining even, stitch 3/8 ± 1/16 inch from edges. In joining, the side seams of bib shall be centered between the joining seams of side covers. Seam allowances shall finish inside of hood. | 401 | LSq-2(a) | 8-12 | B | B | |
| | c. Position seams so that they face bottom of hood, and top stitch 3/16 to 1/4 inch from turned edge. | 401 | LSq-2(b) | 8-12 | B | B | |
| 13. | Clean hood. | | | | | | |
| | Unless otherwise specified, trim all ends to a length of not more than 1/4 inch. Remove all loose threads, spots, stains, and shade markings. | | | | | | |







Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:04Z
Check the source to verify that this is the current version before use.

3.9 Finished measurements. The hood shall conform to the measurements specified in table II.

TABLE II. Finished measurements (inches)

| Area to be measured | Measurement | Tolerance |
|---|---|---|
| Length 1/ | 24 | ± 1 |
| Width 2/ | 9 | ± 3/4 |
| Face opening 3/ | 9-1/2 | ± 1/2 |

1/ Place hood face side up on a flat surface, align bottom edges of front and back of bib and butt top and bottom edges of face opening. With hood in this position measure length in a straight line from folded edge of crown at highest point to bottom of hood at lowest point on bib.

2/ With hood positioned as indicated in footnote 1/, measure across the hood in a straight line from folded edge to folded edge. The line of measurement shall be perpendicular to the length measurement and 1/2 to 1 inch below the tuck.

3/ Fold hood in half lengthwise so fold runs in the length direction of the center top cover and center neck cover. Place folded hood on flat surface with edges of face opening even. Place one hand on neck end of face opening, holding hood against surface. With other hand, slide top of hood along surface toward back of hood until curvature along side edges of face opening approximates a straight line. With hood in this position measure along the edge of face opening from fold at center of top cover to fold at center of neck cover.

3.10 Workmanship. The finished hood shall conform to the quality of product established by this specification. The occurrence of defects shall not exceed the applicable acceptable quality levels.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:04Z
Check the source to verify that this is the current version before use.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in this specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for ensuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point, or at all points in the manufacturing process necessary to ensure compliance with all dimensional requirements.

4.1.3 Certificates of compliance. When certificates of compliance are submitted, the Government reserves the right to inspect such items to determine the validity of the certification.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 3.1 and 6.2), it shall be examined for the defects specified in 4.4.3 and 4.4.4.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.4.2 In-process inspection.

4.4.2.1 Working patterns examination. Examination of the working patterns shall be made to assure they conform to the Government patterns in all respects.

4.4.2.2 Cover interlining and lining assembly examination. Prior to turning the hood to the finished position and prior to attaching the bib, the assembly shall be examined for the defects listed below. The lot size shall be expressed



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:04Z
Check the source to verify that this is the current version before use.

in units of hood assemblies. The sample unit shall be one hood assembly. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 4.0.

| Examine | Defect |
|---|---|
| Construction and workmanship (interlining) | Any component omitted or misplaced<br>Any operation omitted or not properly performed<br>Component not cut in accordance with directional lines of pattern |
| Material (interlining) | Any cut, hole, or tear<br>Not as specified |
| Seams and stitching | Open seam.<br>- 1/2 inch or less<br>- More than 1/2 inch |
| NOTE: | A seam shall be classified as open when one or more stitches joining a seam are broken or when two or more consecutive skipped or run-off stitches occur. |
| | Seam not repaired as specified<br>Loose stitching resulting in a loosely secured seam<br>Tight tension resulting in cutting of material or breaking of stitches when normal pull is applied<br>Seam type not as specified<br>Stitch gauge or stitch margin not as specified<br>More or less than specified number of stitches per inch<br>Ends of seams not secured as specified (does not apply to seams to be secured in subsequent operation)<br>Bartack missing, not length specified, not positioned as specified, or incorrect number of stitches per inch<br>Any part caught in unrelated operation or stitching<br>Looper thread of 401 stitch not hidden between the cover and lining assembly<br>Raw edges:<br>- 1/2 inch or less<br>- More than 1/2 inch |
| Interlining | Plastic film side of interlining not toward lining |
| Elastic cord | Missing or not attached as specified |
| Pull tab | Missing or not attached as specified |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:04Z
Check the source to verify that this is the current version before use.

4.4.3 End item visual examination. The end items shall be examined for the defects listed in table III. The lot size shall be expressed in units of hoods. The sample unit shall be one hood. The inspection level shall be II and the AQL, expressed in terms of defects per hundred units, shall be 2.5 for major defects and 4.0 for total (major and minor combined) defects.

TABLE III. End item visual defects

| Examine | Defect | Classification Major | Minor |
|---|---|---|---|
| Material (lining, cover, and bib) | Any cut, hole, tear, needle chew, or weakening defect in material | 101 | |
| | Variation in shade within a part or between parts | | 201 |
| | Any mend or patch | | 202 |
| Cleanness | Spot or stain on outside | | 203 |
| | Thread ends not trimmed as specified or loose threads not removed | | 204 |
| | Any shade marking not removed | | 205 |
| | Any holding or basting threads visible on outside of hood | | 206 |
| Component and assembly | Any component not cut in accordance with directional lines on patterns | 102 | |
| | Face side of lining or face side of bib not toward wearer | 103 | |
| | Any operation not performed as specified | 104 | |
| | Any part caught in an unrelated operation or stitching | 105 | |
| Seams and stitchings | Open seam | | |
| | - 1/2 inch or less | | 207 |
| | - More than 1/2 inch | 106 | |
| NOTE: | A seam shall be classified as open when one or more stitches joining a seam are broken or two or more consecutive skipped or run-off stitches occur. | | |
| | Seam not repaired as specified | | 208 |
| | Loose stitching resulting in a loosely secured seam | 107 | |
| | Tight tension resulting in cutting of material or breaking of stitches when normal pull is applied | 108 | |
| | Seam type not as specified | | 209 |
| | Stitch gauge or stitch margin not as specified | | 210 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:04Z
Check the source to verify that this is the current version before use.

TABLE III. End item visual defects (cont'd)

| Examine | Defect | Classification Major | Minor |
|---|---|---|---|
| Seams and stitchings (cont'd) | More or less than specified number of stitches per inch | | 211 |
| | Ends of seams not secured as specified | | 212 |
| | Seam twisted, puckered, or pleated | 109 | |
| | Raw edges: | | |
| | - 1/2 inch or less | | 213 |
| | - More than 1/2 inch | 110 | |
| | Any bartack missing, not length specified, or incorrect number of stitches per inch | 111 | |
| | Any bartack not positioned as specified, except on center top lining | 112 | |
| | Bartacks on center top lining not positioned as indicated on patterns | 113 | |
| | Looper thread of 401 stitch not hidden between the cover and lining assembly | 114 | |
| Elastic cord | Cord caught in stitching other than where specified, or caught in bartack stitching | 115 | |
| Tuck on center neck cover | Missing | 116 | |
| | Not size specified | | 214 |
| Pull tab | Not secured as specified | 117 | |
| | Turned end does not face wearer | | 215 |
| Label | Missing, illegible, or incorrect | 118 | |
| | Not positioned as specified | | 216 |
| | Not stitched on four sides | | 217 |

4.4.4 End item dimensional examination. The end items shall be examined for conformance to the dimensions specified in table II. Any dimension not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of hoods. The sample unit shall be one hood. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

4.4.5 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:04Z
Check the source to verify that this is the current version before use.

| Examine | Defect |
|---|---|
| Marking (exterior and interior) | Omitted; incorrect; illegible; of improper size, location, sequence, or method of application |
| Materials | Any component missing, damaged, or not as specified |
| Workmanship | Inadequate application of components such as: incomplete sealing or closure of flap, improper taping, loose strapping or inadequate stapling<br>Bulged or distorted container |
| Content | Number of hoods per shipping container is more or less than specified 1/ |

1/ For this defect, one shipping container shall be examined.

4.4.6 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

| Examine | Defect |
|---|---|
| Finished dimensions | Length, width, or height exceeds specified maximum requirement |
| Palletization | Pallet pattern not as specified<br>Interlocking of loads not as specified<br>Load not bonded as specified |
| Weight | Exceeds maximum load limits |
| Marking | Omitted; incorrect; illegible; of improper size, location, sequence, or method of application |

## 5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial, as specified (see 6.2).

5.1.1 Level A preservation. Each hood shall be laid flat and folded in half to measure approximately 10 by 6 inches. Each hood shall be unit packed in a snug-fitting, flat style, clear polyethylene film bag conforming to A-A-50083.

5.1.2 Commercial preservation. Hoods shall be preserved in accordance with ASTM D 3951.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:04Z
Check the source to verify that this is the current version before use.

5.2 Packing. Packing shall be level A, B, or Commercial, as specified (see 6.2).

5.2.1 Level A packing. Ninety-six hoods, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC-L, grade V2s of PPP-B-636. The inside of each shipping container shall be fitted with a box liner conforming to type CF, class weather-resistant, variety DW, grade V15c of PPP-B-636. Level A unit packs shall be packed flat, four in length, two in width, and twelve in depth within the shipping container. Inside dimensions of each shipping container shall approximate 24 inches in length, 20 inches in width, and 18 inches in depth. Approximate dimensions are furnished as a guide only. Each shipping container shall be closed in accordance with method III, waterproofed in accordance with method V, and reinforced as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.5. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.2). Strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.2.2 Level B packing. Ninety-six hoods, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC-L, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. The inside of each shipping container shall be fitted with a box liner conforming to type CF, class domestic, variety DW, grade 275 of PPP-B-636. Level A unit packs shall be packed flat, four in length, two in width, and twelve in depth within the shipping container. Inside dimensions of each shipping container shall approximate 24 inches in length, 20 inches in width, and 18 inches in depth. Approximate dimensions are furnished as a guide only. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.5.

5.2.2.1 Weather-resistant fiberboard containers. When specified (see 6.2), the shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.5.

5.2.3 Commercial packing. The hoods, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Palletization. When specified (see 6.2), hoods packed as specified in 5.2.2 and 5.2.3, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Pallet types shall be type I (4-way entry), type IV, or type V in accordance with MIL-STD-147. Pallets shall be fabricated from wood groups I, II, III, or IV of MIL-STD-731. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means C and D or film bonding means F or G. Pallet pattern shall be number 90 in accordance with appendix of MIL-STD-147.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:04Z
Check the source to verify that this is the current version before use.

5.4 Marking. In addition to any special marking required by the contract or purchase order, shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

5.4.1 Unit packs. Polyethylene bagged unit packs shall have the required identification information legibly printed or stamped in black directly on the bag across the center face or on a white paper label inserted within the bag so as to permit ready identification.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The hood is for use by combat vehicle crewmen and is intended to provide protection against wind, cold, and flame.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. When a first article is required (see 3.1, 4.3, and 6.3).
d. Levels of preservation and packing (see 5.1 and 5.2).
e. Type and class of unit load required (see 5.2.1).
f. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
g. When palletization is required (see 5.3).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.4 Samples. For access to samples, address the contracting activity issuing the invitation for bids or request for proposal.

6.5 Recommended needles. Materials used to construct this item are susceptible to running. It is recommended that the following needles be used since they have been found to alleviate this problem.

Schmetz U4 147 GS S4 7475 - for double needle machines

Schmetz #19 135 x 17 SU12 - for single needle machines



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:04Z
Check the source to verify that this is the current version before use.

6.6 Subject term (key word) listing.

Cold weather clothing
Flame protection
Head covering

6.7 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:

Army - GL
Navy - NU
Air Force - 99

Preparing activity:

Army - GL

(Project 8415-0690)

Review activities:

Army - MD
Air Force - 82
DLA - CT

User activity:

Navy - MC
Air Force - 45



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:04Z
Check the source to verify that this is the current version before use.

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

*(See Instructions – Reverse Side)*

| 1. DOCUMENT NUMBER | 2. DOCUMENT TITLE |
|---|---|
| MIL-H-44265A | HOOD, COMBAT VEHICLE CREWMEN'S (BALACLAVA) |

| 3a. NAME OF SUBMITTING ORGANIZATION | 4. TYPE OF ORGANIZATION *(Mark one)* |
|---|---|
| | ☐ VENDOR |
| b. ADDRESS *(Street, City, State, ZIP Code)* | ☐ USER |
| | ☐ MANUFACTURER |
| | ☐ OTHER *(Specify)* _____ |

5. PROBLEM AREAS

a. Paragraph Number and Wording

b. Recommended Wording

c. Reason/Rationale for Recommendation

6. REMARKS

| 7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional | b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional |
|---|---|
| c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional | 8. DATE OF SUBMISSION *(YYMMDD)* |

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:04Z
Check the source to verify that this is the current version before use.

**INSTRUCTIONS:** In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

*NOTE* This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

*(Fold along this line)*

*(Fold along this line)*

DEPARTMENT OF THE ARMY

Commander
US Army Natick RD&E Center
ATTN: STRNC-ES
Natick, MA 01760-5014

OFFICIAL BUSINESS

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

**BUSINESS REPLY MAIL**
FIRST CLASS PERMIT NO 12062 WASHINGTON D C
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick RD&E Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:04Z
Check the source to verify that this is the current version before use.