INCH-POUND

MIL-H-44298B
3 September 1993
SUPERSEDING
MIL-H-44298A
9 April 1990

MILITARY SPECIFICATION

HAM SLICES, CHUNKED AND FORMED, SMOKE FLAVORING ADDED, THERMOSTABILIZED, TRAY PACK

This specification is approved for use by all Department and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers chunked and formed, smoke flavoring added ham slices, thermostabilized in tray pack cans for use by the Department of Defense as a component of operational rations.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.1).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5018 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8905

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:17Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

PPP-B-636	-	Boxes, Shipping, Fiberboard

MILITARY

MIL-L-1497	-	Labeling of Metal Cans for Subsistence Items
MIL-L-35078	-	Loads, Unit: Preparation of Semiperishable Subsistence Items; Clothing, Personal Equipment and Equipage; General Specification for
MIL-C-44340	-	Can, Tray Pack

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-900	-	Bacterial Standards for Starches, Flours, Cereals, Alimentary Pastes, Dry Milks, and Sugars Used in the Preparation of Thermostabilized Foods for the Armed Forces

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

ENVIRONMENTAL PROTECTION AGENCY (EPA)

National Primary Drinking Water Regulations

(Copies are available from the Office of Drinking Water, Environmental Protection Agency, WH550D, 401 M Street, S.W., Washington, DC 20460.)

U.S. DEPARTMENT OF AGRICULTURE (USDA)

Meat and Poultry Inspection Regulations (9 CFR Parts 301-399)

(Copies are available from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402-0001.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:17Z
Check the source to verify that this is the current version before use.

Institutional Meat Purchase Specifications for Fresh Pork, Series 400

(Copies are available from the Director, Livestock and Seed Division, Agricultural Marketing Service, U.S. Department of Agriculture, Room 2603, South Building, P. O. Box 96456, Washington, DC 20090-6456.)

U.S. Standards for Condition of Food Containers

(Copies are available from the Chairperson, Condition of Container Committee, Agricultural Marketing Service, U.S. Department of Agriculture, Room 2506, South Building, P. O. Box 96456, Washington, DC, 20090-6456.)

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES (HHS), U.S. FOOD AND DRUG ADMINISTRATION (FDA)

Federal Food, Drug, and Cosmetic Act and Regulations Promulgated Thereunder (21 CFR Parts 1-199)

(Copies are available from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402-0001.)

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN ASSOCIATION OF CEREAL CHEMISTS (AACC)

Approved Methods of the American Association of Cereal Chemists

(Application for copies should be addressed to the American Association of Cereal Chemists, 3340 Pilot Knob Road, St. Paul, MN 55121.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM D 3330 - Peel Adhesion of Pressure-Sensitive Tape

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

AOAC INTERNATIONAL

Official Methods of Analysis of the AOAC

(Application for copies should be addressed to the AOAC International, 2200 Wilson Boulevard, Suite 400, Arlington, VA 22201-3301.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:17Z
Check the source to verify that this is the current version before use.

NATIONAL ACADEMY OF SCIENCES

Food Chemicals Codex

(Application for copies should be addressed to the National Academy Press, 2101 Constitution Avenue, N.W., Washington, DC 20418.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.1), a sample shall be subjected to first article inspection (see 6.2) in accordance with 4.4.

3.2 Ingredients. All ingredients shall be clean, sound, wholesome, and free from foreign material, evidence of rodent or insect infestation, extraneous material, off-odors, off-flavors, and off-colors.

3.2.1 Ham. The ham shall be the equivalent of an Institutional Meat Purchase Specifications (IMPS) No. 402B ham, except ham tying shall not be necessary, and all the shank meat shall be removed and excluded. The ham shall be within the weight range of 8 pounds to 14 pounds and a maximum average fat thickness of 1/4 inch.

3.2.1.1 Ham, chilled. Raw ham, in the bone-in or boneless form, shall be received in the fresh-chilled state. The ham shall not have been previously frozen. The fresh-chilled ham shall be held for not more than four days after initial chilling, at a temperature not to exceed 40°F prior to preparation and further processing (see 3.3).

3.2.1.2 Ham, frozen. Raw ham, in the bone-in or boneless form, shall be received in the frozen state. The ham shall be held for not more than 120 days after initial freezing at a temperature not to exceed 0°F prior to preparation and further processing (see 3.3).

3.2.1.2.1 Frozen meat tempering/thawing. Tempering/thawing of frozen ham shall comply with the following:

- microwave tempered/thawed frozen ham is permitted provided excellent condition of the ham, as determined by USDA, is maintained

Source: https://assist.dla.mil -- Downloaded: 202640-22T01:17Z
Check the source to verify that this is the current version before use.

- regardless of the process used, frozen ham shall be tempered/thawed to an internal temperature not to exceed 40°F
- tempered/thawed ham shall not be refrozen

3.2.2 Water. Water used for formulation, ice making, and washing shall conform to the National Primary Drinking Water Regulations.

3.2.3 Salt. Salt shall be noniodized, white, refined sodium chloride with or without anticaking agents and shall comply with the purity standards for sodium chloride of the Food Chemicals Codex.

3.2.3.1 Salt tablets. Salt tablets shall be noniodized, white, refined sodium chloride and shall comply with the purity standards for sodium chloride of the Food Chemicals Codex.

3.2.4 Sugar, white, granulated. Sugar shall be white, refined, granulated cane or beet sugar, or a combination thereof, and shall comply with MIL-STD-900.

3.2.5 Sodium tripolyphosphate. Sodium tripolyphosphate shall comply with the Food Chemicals Codex.

3.2.6 Sodium ascorbate. Sodium ascorbate shall comply with the Food Chemicals Codex.

3.2.7 Sodium erythorbate. Sodium erythorbate shall comply with the Food Chemicals Codex.

3.2.8 Flavoring, smoke, single strength. Single strength smoke flavoring shall be an oil-based liquid with a density of 7.6 pounds per gallon, a stability of greater than 30 hours (A.O.M.), and a phenolic level (dimethoxyphenol) of 7.3 mg to 8.1 mg per mL. The smoke flavoring shall have a mellow hickory smoke aroma (see 6.4.1).

3.2.9 Sodium nitrite. Sodium nitrite shall comply with the Food Chemicals Codex.

3.3 Preparation and processing. Processing shall be on a continuous basis.

3.3.1 Preparation of the cured ham. The ham shall be prepared as follows:

a. Boned and trimmed ham which meets the requirements of 3.2.1 shall be further trimmed, if necessary, to ensure compliance with the finished product requirements (see 3.6).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:17Z
Check the source to verify that this is the current version before use.

b. The boned and trimmed ham shall be reduced in size to chunk-type pieces by mechanically grinding once through a kidney-shaped plate, having openings measuring 2.5 inches or more in the least dimensions, and using a two-bladed knife that yields pieces weighing at least 2 ounces.

3.3.1.1 Mixing. The chunked ham pieces shall be mechanically mixed with the following cure ingredients for approximately 15 minutes or until the product becomes moderately tacky.

Ingredient	Pounds per 100 pounds of ham
Water or ice	3.0000
Salt 1/	2.5000
Sugar, white, granulated	1.0000
Sodium tripolyphosphate	0.2500
Sodium ascorbate and/or sodium erythorbate	0.0550
Flavoring, smoke, single strength	0.0400
Sodium nitrite 2/	0.0156

1/ The total amount of salt in the formula shall be adjusted, as necessary, to produce a product that complies with the finished product salt requirements (see 3.6).

2/ Sodium nitrite shall be of sufficient strength to ensure a complete cure without exceeding 156 parts per million of nitrite in the cured ham during preparation.

The mixture shall be held prior to or after the stuffing operation at an internal temperature of 38°F to 42°F for not less than 4 hours nor more than 72 hours before cooking to ensure uniform cure dispersion in the mixture.

3.3.1.2 Stuffing and forming. The mixed meat shall immediately be tightly stuffed into casings of a type and size to accommodate the cooking method and the finished product meat dimension requirements. Alternatively, the mixed meat may be formed in stainless steel molds to a size which will ensure compliance with finished product meat dimension requirements.

3.3.1.3 Cooking. The formed ham logs shall be cooked by one of the following methods to provide a product meeting the finished product requirements.

a. Cookhouse method. The ham logs shall be cooked in a cookhouse (smokehouse without smoke) at a temperature range of 160°F to 162°F and 100 percent relative humidity until the internal product temperature reaches 150°F to 152°F.

b. Water cooking method. Water cooking is permitted only for the ham logs in casings provided they are cooked in water until the internal temperature of the log reaches 150°F to 152°F.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:17Z
Check the source to verify that this is the current version before use.

3.3.1.4 Cooling and storage. Immediately after completion of the cooking process, the cooked ham logs shall be placed in an ice water bath or cooled by other commercially acceptable cooling methods and rapidly cooled to 130°F or below. The ham logs shall be further cooled from 130°F to 80°F or below within two hours, and further cooled from 80°F to 40°F or below within four hours. The cooled, cooked ham logs shall be held for not more than 48 hours at an internal temperature of 28°F to 40°F after removal from the cooking process and prior to slicing. Alternatively, if the cooked ham logs are to be held for more than 48 hours, they shall be mechanically stuffed and vacuum-sealed in heat-sealable casing materials made from FDA and USDA food approved laminate consisting of 0.0005-inch-thick polyester and 0.0015-inch-thick medium density polyethylene. The cooled, cooked ham logs shall be maintained at an internal temperature of 28°F to 40°F for a period of not more than 60 days (canned or cooked pullman-style hams may be held for not more than 90 days) from the date of pack until slicing.

3.3.1.5 Slicing. The ham logs shall be sliced to a uniform size, shape, and thickness to ensure compliance with finished product requirements (see 3.6). The ham slices shall be filled into the tray pack cans within four hours after being sliced. End slices shall not be used.

3.3.1.6 Alternate processing for cured ham. Cured hams processed by methods other than the chunking method described in 3.3.1(b), such as sectioned and formed, or massaging of intact ham muscle, shall be acceptable. If using an alternate processing method, the preparation and processing techniques of this specification, except for chunking, shall be required.

3.3.1.7 Alternate cured ham product Canned or cooked pullman-style hams which meet the requirements of 3.3.1 and 3.3.1.1 and can be sliced to the requirements of 3.3.1.5 shall be acceptable.

3.3.2 Brine preparation. The brine shall be prepared in a manner to ensure compliance with finished product salt requirements. (At the time of filling, salt tablets may be substituted for granular salt in brine preparation.) The brine shall be made fresh daily, and the brine remaining at the end of a production day shall be discarded.

3.4 Tray pack filling and sealing. Each tray pack can (see 5.1.1) shall be filled with product to conform to the finished product requirements and to the following requirements:

a. Not less than 54 ham slices shall be shingled in two rows, lengthwise, in the tray pack can.

b. The product at the time of filling shall be in the temperature range of 28°F to 40°F.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:17Z
Check the source to verify that this is the current version before use.

c. Each tray pack can shall be filled with the product and brine to a total can content weight of 106 ounces. Brine may be filled hot or cold.

d. Immediately after filling, each can shall be sealed in accordance with the can manufacturer's guidelines/requirements and 21 CFR, Part 113, Subpart D, or 9 CFR, Part 318, Subpart G, as applicable (see 4.5.5), and under a vacuum established by a processing authority and specified in the scheduled process so as to ensure compliance with the finished product requirement (see 3.6s).

e. The filled and sealed tray pack cans shall be in the retort process within two hours after sealing.

3.5 Tray pack thermoprocessing. The filled and sealed tray pack cans shall be thermostabilized by retorting until a sterilization value (F_o) of not less than 6 has been achieved.

3.6 Finished product requirements. The finished product shall comply with the following requirements:

a. There shall be no foreign material such as, but not limited to, dirt, insect parts, hair, wood, glass, or metal.

b. There shall be no foreign odor or flavor such as, but not limited to, burnt, scorched, stale, sour, rancid, or moldy.

c. There shall be no color foreign to the product.

d. No individual can shall have a total can content weight of less than 104 ounces.

e. The average total can content weight shall be not less than 106 ounces.

f. Drained weight of 54 intact ham slices in any individual tray pack can shall be not less than 56.0 ounces.

g. The average drained weight of the slices shall be not less than 58.0 ounces.

h. No individual can shall contain less than 54 intact slices.

i. Ham slices shall approximate the size and shape shown in figure 1 or 2.

j. The texture of the slices shall not be dry, rubbery, or mushy.

Source: https://assist.dla.mil -- Downloaded: 202640-22T01:17Z
Check the source to verify that this is the current version before use.

k. The average fat content of the drained product shall be not greater than 12.0 percent, and no individual tray pack drained product shall have a fat content greater than 14.0 percent.

l. The salt content of any individual tray pack drained product shall be not less than 1.5 percent nor greater than 2.5 percent.

m. The product shall show no evidence of excessive heating (materially darkened or scorched).

n. No individual can shall contain a bone piece measuring 0.3 inch or more in any dimension.

o. No individual can shall have slices with adherent fat or a fat pocket measuring more than 0.5 inch by 0.5 inch.

p. No individual can shall have slices with a void area or air pocket measuring more than 0.5 inch by 0.5 inch.

q. Total weight of cartilage, coarse connective tissue, section of tendons or ligaments, and glandular material, collectively, in any individual can shall be not more than 2.0 ounces.

r. The ham slice shall not contain finely ground, flaked, or otherwise comminuted product.

s. Filled, sealed, and retorted cans shall show evidence of proper vacuum as determined by concavity of the can lid (see 4.5.6).

3.6.1 Palatability. The finished product shall be equal to or better than the approved preproduction sample (see 6.1) in palatability and overall appearance.

3.7 Plant qualification. The pork component and the finished product shall originate and be produced, processed, and stored in plants regularly operating under the Meat and Poultry Inspection Regulations of the U.S. Department of Agriculture.

3.8 Federal Food, Drug, and Cosmetic Act. All deliveries shall conform in every respect to the provisions of the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor's responsibility. Inspection and acceptance by the USDA shall not relieve the contractor of obligation and responsibility to deliver a product complying with all requirements of this specification. The

Source: https://assist.dla.mil -- Downloaded: 202610-22T01:17Z
Check the source to verify that this is the current version before use.

contractor shall ensure product compliance prior to submitting the product to the USDA for any inspection.

4.2 Inspection and certification. Product acceptability shall be determined by the USDA. The USDA will determine the degree of inspection and supervision necessary to ensure compliance with the requirements of this specification.

4.3 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4).
b. Quality conformance inspection (see 4.5).

4.4 First article inspection. When a first article is required (see 6.1), it shall be inspected in accordance with the quality assurance provisions of this specification and evaluated for overall appearance and palatability. Any failure to conform to the quality assurance provisions of this specification or any appearance or palatability failure shall be cause for rejection of the first article.

4.5 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.5.1 Component and material examination. In accordance with 4.1, components and materials shall be examined in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.5.1.1 Ingredient and component examination. Conformance of ingredients and components to identity, condition, and other requirements specified in 3.2 shall be certified by the ingredient supplier or ingredient manufacturer, and compliance shall be verified by examination of pertinent labels, markings, U.S. Grade Certificates, certificates of analyses, or other such valid documents acceptable to the inspection agency. If necessary, each ingredient shall be examined organoleptically or inspected according to generally recognized test methods, such as the standard methods described in the Official Methods of Analysis of the AOAC International, and in the approved methods of the American Association of Cereal Chemists, to determine conformance to the requirements. Any nonconformance to an identity, condition, or other requirement shall be cause for rejection of the ingredient or component lot or of any involved product.

4.5.2 In-process examination. In-process examination shall be performed to determine conformance to the preparation, processing, can interior coating, filling, sealing, and packaging requirements. Any nonconformance revealed by actual examination or by review of records of time, temperature,

Source: https://assist.dla.mil -- Downloaded: 202640-22T01:17Z
Check the source to verify that this is the currentversion before use.

and formulation or of other valid documents shall be cause for rejection of the involved product.

4.5.3 Tray pack inspection. The USDA reserves the right to separate the inspection lot into smaller inspection lots.

4.5.3.1 Total can content weight examination. Randomly select 30 filled and sealed tray pack cans from the inspection lot and weigh separately. Subtract the average tare weight (determined by randomly selecting and weighing 30 of the empty tray pack cans and lids used in preparing the product and dividing the total weight by 30) from the weight of each tray pack in the sample. The results shall be reported to the nearest 1 ounce. If the average total can content weight is less than 106 ounces or if the total can content weight of any individual can is less than 104 ounces, the lot shall be rejected.

4.5.3.2 Double sampling plan for product examination. The finished product shall be examined for the defects listed in table I utilizing the double sampling plans indicated in MIL-STD-105. The lot size shall be expressed in tray pack cans. The sample unit shall be one filled and sealed tray pack can. The inspection level shall be S-3 and the Acceptable Quality Level (AQL), expressed in terms of defects per hundred units, shall be 4.0 for major defects and 6.5 for minor defects. The sample cans shall be heated in accordance with the heating instructions on the can label.

TABLE I. Product defects 1/ 2/

Category		Defect
Major	Minor	
101		Less than 54 intact slices in any individual can
102		Drained weight of 54 intact slices in any individual tray pack can is less than 56.0 ounces 3/ 4/
103		Texture of the slice is dry, rubbery, or mushy
104		Product shows evidence of excessive heating (materially darkened or scorched)
105		Presence of a bone piece measuring 0.3 inch or more in any dimension

Source: https://assist.dla.mil -- Downloaded: 202610-22T01:17Z
Check the source to verify that this is the current version before use.

TABLE I. Product defects 1/ 2/ (cont'd)

Category		Defect
Major	Minor	
106		Total weight of cartilage, coarse connective tissue, section of tendons or ligaments, and glandular material, collectively, in any individual can is more than 2.0 ounces
107		Slices not approximating the size and shape shown in figures 1 or 2 5/
108		More than five slices have adherent fat or a fat pocket measuring more than 0.5 inch by 0.5 inch
109		More than five slices have a void area or air pocket measuring more than 0.5 inch by 0.5 inch
	201	Five or less slices have adherent fat or a fat pocket measuring more than 0.5 inch by 0.5 inch
	202	Five or less slices have a void area or air pocket measuring more than 0.5 inch by 0.5 inch
	203	Slice contains finely ground, flaked, or otherwise comminuted product
	204	Slices not arranged in a shingled manner

1/ The presence of any foreign material (for example, glass, dirt, insect parts, hair, wood, metal), foreign odor or flavor (for example, burnt, scorched, moldy, rancid, sour, stale), or foreign color shall be cause for rejection of the lot.

2/ Product not equal to or better than the approved preproduction sample in palatability and overall appearance shall be cause for rejection of the lot.

3/ To determine drained weight, the contents of the tray pack can shall be poured into a U.S. Standard 1/2 inch sieve in a manner that will distribute the product over the sieve without breaking the ham slices. Sieve area shall be such that the distributed product does not completely cover all the openings of the sieve. The sieve shall be tilted at

Source: https://assist.dla.mil -- Downloaded: 202610-22T01:17Z
Check the source to verify that this is the current version before use.

approximately a 45° angle and allowed to drain for two minutes before determining the drained weight by subtracting the sieve tare weight from the gross weight. The drained weight shall be reported to the nearest 0.1 ounce.

4/ The lot shall be rejected if the sample average drained weight is less than 58.0 ounces.

5/ Ham slices approximating the shape of figure 2 which have broken corners shall not be considered as intact slices.

4.5.3.3 Fat and salt content testing. Three filled and sealed tray pack cans shall be selected at random from the lot. The product shall be tested for fat content in accordance with the Official Methods of Analysis of the AOAC, methods 976.21, 985.15, or 960.39, and for salt content in accordance with Official Methods of Analysis of the AOAC, method 935.47, except that the preparation of the samples shall be as follows: The unopened tray pack cans shall be gently warmed in a water bath to melt fat adhering to the inside of the cans. The tray pack cans shall be opened and the brine solution drained. The remaining drained contents of each can shall be separately blended in a Waring Blendor or equivalent. The test results shall be reported to the nearest 0.1 percent. Any result failing to conform to the fat or salt requirements in 3.6 shall be classified as a major defect and shall be cause for rejection of the lot.

4.5.4 Can condition examination. Examination of filled and sealed tray pack cans shall be in accordance with the U.S. Standards for Condition of Food Containers, except that the inspection for labeling shall be in accordance with 4.5.4.1. In addition, scratches, scuffs, or abrasions that occur on the outside coating as a result of the filling, sealing, and thermoprocessing of the tray pack cans shall not be scored as a defect.

4.5.4.1 Can label examination. Labels shall be examined for defects in accordance with MIL-L-1497 (see 5.4), except, for self-adhering labels, the following additional defects shall apply:

Major:	Label torn or scratched so as to obliterate any of the markings
Minor:	Air bubbles under label Label not properly adhered to can, for example, label raised or peeled back from edges or corners

4.5.4.2 Label adhesive examination. When self-adhering labels are used, the adhesive shall be tested in accordance with ASTM D 3330.

4.5.5 Can closure examination. Can closures shall be examined visually and by teardowns in accordance with the can manufacturer's guidelines/ requirements and 21 CFR, Part 113, Subpart D, or 9 CFR, Part 318, Subpart G,

Source: https://assist.dla.mil -- Downloaded: 202610-22T01:17Z
Check the source to verify that this is the current version before use.

as applicable. Any nonconformance based on observation of can seam teardowns or on record of can seam teardowns shall be classified as a major defect and shall be cause for rejection of any involved product.

4.5.6 Vacuum examination. Cans shall be allowed to cool to 75°F ± 5°F, held for at least 24 hours after sealing, and then examined for vacuum retention. To examine, lay a straight edge in the center of the lid along the length of the tray pack. Both ends of the straight edge shall touch the lid at the inside edge of the double seam. There shall be a visible gap between the straight edge and the lid for the entire distance of the label panel. Using a shorter straight edge, the same procedure shall be used across the width, in the center of the tray pack can. When examining a ribbed lid, lay the straight edge only between the two center ribs along the length of the can. The inspection lot shall include only tray packs produced in a single shift on a single sealing machine. The sample size shall be 50 cans. Any nonconformance shall be classified as a major defect and shall be cause for rejection of the lot.

4.5.7 Shipping container examination. Shipping containers shall be examined for defects in assembly, closure, and reinforcement (when applicable) in accordance with PPP-B-636. In addition, the following defects shall be classified as follows:

Major:	National stock, number, item description, contract number, or date of pack markings missing, incorrect, or illegible.
	Reinforced with other than nonmetallic strapping or tape.
	Dimensions of pads not as specified.
	Interior packing with fiberboard liner or pads not as specified.
Minor:	Other required markings missing, incorrect, or illegible.
	Arrangement or number of cans not as specified.

4.5.8 Unit load inspection. Inspection of unit loads shall be in accordance with the quality assurance provisions of MIL-L-35078.

5. PACKAGING

5.1 Preservation. The product shall be preserved in accordance with level A.

5.1.1 Level A. One hundred and six ounces of product shall be filled into a tray pack can conforming to MIL-C-44340 and sealed and thermoprocessed as specified in 3.4 and 3.5.

5.2 Packing. The product shall be packed in accordance with level A, B, or C as specified (see 6.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:17Z
Check the source to verify that this is the current version before use.

5.2.1 Level A packing. Four cans of product, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard box, constructed and closed in accordance with style RSC-L or HSC-L with an HSC full depth cover, grade V2s of PPP-B-636. The cans shall be packed flat, four in depth within the box, with the first two cans placed with the lids together and the next two cans with the lids together. The inside of each box shall be provided with a box liner and five fiberboard pads fabricated of grade V3c fiberboard. The height of the box liner shall be equal to the full inside depth of the box (+0 inch, -1/8 inch). Flute direction of the box liner shall be vertical. The pads shall be placed between the cans and on the top and bottom of the stacked cans. The pad dimensions shall be not less than 1/8 inch of the full length and width dimensions of the box. Each box shall be reinforced with nonmetallic strapping or pressure-sensitive adhesive filament-reinforced tape in accordance with the appendix of PPP-B-636. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.1), except that the unit load shall consist of 48 boxes with 12 boxes per course and four courses per load with all courses having the same pattern. Boxes may be stacked by interlocking and reversing each tier, or by columnar stacking with paperboard or fiberboard sheets placed between each tier. When unit loads are strapped, strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.2.2 Level B packing. Four cans of product, preserved as specified in 5.1, shall be packed as specified in 5.2.1, except the box shall be constructed of grade V3c, V3s, or V4s fiberboard.

5.2.3 Level C packing. Four cans of product, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard box, constructed and closed in accordance with style RSC-L, class domestic, grade 275 of PPP-B-636. The cans shall be packed flat, four in depth within the box, with the first two cans placed with the lids together and the next two cans with the lids together. The inside of each box shall be provided with a box liner and five fiberboard pads. The height of the box liner shall be equal to the full inside depth of the box (+0 inch, -1/8 inch). Flute direction of the box liner shall be vertical. The pads shall be placed between the cans and on the top and bottom of the stacked cans. The pad dimensions shall be not less than 1/8 inch of the full length and width dimensions of the box and shall be fabricated of class domestic, grade 175 fiberboard.

5.3 Unit loading. When specified (see 6.1), the product, packed as specified in 5.2.2 or 5.2.3, shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified except that the unit load shall consist of 48 boxes with 12 boxes per course and four courses per load with all courses having the same pattern. Boxes may be stacked by interlocking and reversing each tier, or by columnar stacking with paperboard or fiberboard sheets placed between each tier. When unit loads are strapped, strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

Source: https://assist.dla.mil -- Downloaded: 202610-22T01:17Z
Check the source to verify that this is the currentversion before use.

5.4 Labeling. Each tray pack can shall be labeled in accordance with MIL-L-1497 and with the following:

- Official establishment number (for example, EST 38) or a three letter code identifying the establishment
- Lot number 1/
- Production shift number 1/
- Retort identification number 1/
- Retort cook number 1/

1/ The lot number shall be expressed as a four digit Julian code. The first digit shall indicate the year of production and the next three digits shall indicate the day of the year (for example, March 19, 1990 would be coded as 0078). The Julian code shall represent the day the product was packaged and processed. Sub-lotting (when used) shall be represented by an alpha character immediately following the four digit Julian code. Following the four digit Julian code and the alpha character (when used), the other required code information shall be printed in the sequence as listed above.

In addition, the name of the product shall be marked, stamping is permitted, on one 1001 by 200 end of the can. The labeling shall be legible when examined as specified in 4.5.4 after preparation of product in accordance with heating instructions. Paper labels are not permitted. In addition, cans shall show the following statements:

TO HEAT IN WATER: Submerge unopened can in boiling water. Simmer gently 25 to 30 minutes. Avoid overheating (can shows evidence of bulging).

CAUTION: Use care when opening as pressure may have been generated within the can.

TO HEAT IN OVEN: Either punch several holes in lid of can or open can in usual manner leaving the loose lid in place. Place in a 350°F oven 30 to 40 minutes.

WARNING: Do not place unopened can in oven. This may cause the can to burst.

YIELD: Serves 18 portions of 3 slices each.

As an alternate labeling method, a preprinted, self-adhering 0.002-inch-thick clear polyester label printed with indelible black ink may be used. Self-adhering labels shall be applied after retorting. Pressure-sensitive adhesive shall require no preparation prior to application. Labels shall tack quickly and adhere without curling or breaking. The adhesive shall have a minimum adhesion of 60 ounces per inch width when examined as specified in 4.5.4.2. When self-adhering labels are used, the tray pack cans shall be labeled with the Julian code and a product code prior to retorting.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:17Z
Check the source to verify that this is the current version before use.

5.5 Marking.

5.5.1 Shipping containers. In addition to any special marking required by the contract or purchase order, shipping containers shall be marked in accordance with MIL-STD-129.

5.5.2 Unit loads. Unit loads shall be marked in accordance with MIL-L-35078. In addition, the following precautionary markings in capital letters larger than other markings shall be included:

CAUTION: DO NOT STACK PALLETS IN TRANSIT, OR MORE THAN TWO HIGH IN STORAGE, UNLESS PALLET RACKS ARE USED.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. When a first article is required (see 3.1, 4.4, and 6.2).
d. Provisions for approved preproduction samples (see 3.6.1 and 6.2).
e. Level of packing required (see 5.2).
f. Type and class of unit load when unit loading is required (see 5.2.1 and 5.3).

6.2 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of Federal Acquisition Regulation (FAR) 52.209-4. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.3 Appropriate level of pack. Based on the conditions known or expected to be encountered during shipment, handling, and storage of the specific item being procured, the procuring activity should select the appropriate level of pack in accordance with the criteria established in AR 700-15/NAVSUPINST 4030.28/AFR 71-6/MCO 4030.33A/DLAR 4145.7.

6.4 Ingredient information.

6.4.1 Flavoring, smoke, single strength. It has been found that CharOil Hickory (single strength) manufactured by Red Arrow Products Company, P.O. Box 1537, Manitowoc, WI 54221-1537 meets the requirements of 3.2.8 and

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:17Z
Check the source to verify that this is the current version before use.

performs satisfactorily in this product. The 0.0400 pounds per 100 pounds is based on the phenolic levels specified in 3.2.8. The tray pack ham producer is cautioned to verify these requirements prior to formulation of the ham cure ingredients.

6.5 Subject term (key word) listing.

Canned food
Combat field feeding
Food processing
Meat
Operational rations
Shelf stable

6.6 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:

Army - GL
Navy - SA
Air Force - 50

Preparing activity:

Army - GL

(Project 8905-1113)

Review activities:

Army - MD, QM
Navy - MC
DLA - SS

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:17Z
Check the source to verify that this is the current version before use.




FIGURE 1

HAM SLICE SHAPE




FIGURE 2

ALTERNATE HAM SLICE SHAPE

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:17Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-H-44298B	1993 September 3

3. DOCUMENT TITLE

HAM SLICES, CHUNKED AND FORMED, SMOKE FLAVORING ADDED, THERMOSTABILIZED, TRAY PACK

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code) (1) Commercial	(2) AUTOVON/DSN
U.S. Army Natick RD&E Center	508-651-4501	256-4501
c. ADDRESS (Include Zip Code) Commander, U.S. Army Natick RD&E Center ATTN: SATNC-WRE Natick, MA 01760-5018	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 2020-10-22T01:17Z
Check the source to verify that this is the current version before use.