INCH-POUND

MIL-R-44274B
16 August 1993
SUPERSEDING
MIL-R-44274A
7 April 1989

MILITARY SPECIFICATION

RICE, WHITE, THERMOSTABILIZED, TRAY PACK

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers white rice, thermostabilized in tray pack cans for use by the Department of Defense as a component of operational rations.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.1).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5018 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8920

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:07Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

PPP-B-636 - Boxes, Shipping, Fiberboard

MILITARY

MIL-L-1497 - Labeling of Metal Cans for Subsistence Items
MIL-L-35078 - Loads, Unit: Preparation of Semiperishable Subsistence Items; Clothing, Personnel Equipment and Equipage; General Specification for
MIL-C-44340 - Can, Tray Pack

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

ENVIRONMENTAL PROTECTION AGENCY (EPA)

National Primary Drinking Water Regulations

(Copies are available from the Office of Drinking Water, Environmental Protection Agency, WH550D, 401 M Street, S.W., Washington, DC 20460.)

U.S. DEPARTMENT OF AGRICULTURE (USDA)

U.S. Standards for Milled Rice (7 CFR Part 68)

(Copies are available from the Federal Grain Inspection Service, APHIS, Printing and Distribution Section, 6505 Belcrest Road, Room G-110, Federal Building, Hyattsville, MD 20782.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:07Z
Check the source to verify that this is the current version before use.

U.S. Standards for Condition of Food Containers

(Copies are available from the Chairperson, Condition of Container Committee, Agricultural Marketing Service, U.S. Department of Agriculture, Room 2506, South Building, P.O. Box 96456, Washington, DC 20090-6456.)

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES (HHS), U.S. FOOD AND DRUG ADMINISTRATION (FDA)

Federal Food, Drug, and Cosmetic Act and Regulations Promulgated Thereunder (21 CFR Parts 1-199)

U.S. Standards of Identity for Margarine (21 CFR Part 166)

(Copies are available from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402-0001.)

2.2 Non-Government publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.1).

AMERICAN ASSOCIATION OF CEREAL CHEMISTS (AACC)

Approved Methods of the American Association of Cereal Chemists

(Application for copies should be addressed to the American Association of Cereal Chemists, 3340 Pilot Knob Road, St. Paul, MN 55121.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3330 - Peel Adhesion of Pressure-Sensitive Tape

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

AOAC INTERNATIONAL

Official Methods of Analysis of the AOAC

(Application for copies should be addressed to the AOAC International, 2200 Wilson Boulevard, Suite 400, Arlington, VA 22201-3301.)

NATIONAL ACADEMY OF SCIENCES

Food Chemicals Codex

(Application for copies should be addressed to the National Academy Press, 2101 Constitution Avenue, N.W., Washington, DC 20418.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:07Z
Check the source to verify that this is the current version before use.

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.1), a sample shall be subjected to first article inspection (see 6.2) in accordance with 4.4.

3.2 Ingredients. All ingredients shall be clean, sound, wholesome, and free from foreign material, evidence of rodent or insect infestation, extraneous material, off-odors, off-flavors, and off-colors.

3.2.1 Rice, long-grain, parboiled. Rice shall be parboiled, long-grain milled rice, U.S. No. 2 or better of the U.S. Standards for Milled Rice, and be of varieties which are suitable for canning (see 6.3). The rice shall contain not more than 2 percent of kernels having white ungelatinized areas and not less than 10 percent or more than 15 percent moisture.

3.2.2 Margarine. Margarine shall conform to the FDA Standards of Identity for Margarine and shall possess a fine and pleasing flavor. The body shall be smooth, firm, and homogeneous. The margarine shall possess a uniform medium yellow color and may be salted or unsalted.

3.2.3 Lecithin. Lecithin shall comply with the Food Chemicals Codex.

3.2.4 Salt. Salt shall be non-iodized, white, refined, sodium chloride with or without anticaking agents and shall comply with the purity standards for sodium chloride of the Food Chemicals Codex.

3.2.5 Water. Water used for formulation, ice making, and washing shall conform to the National Primary Drinking Water Regulations.

3.3 Preparation and processing. Processing shall be on a continuous basis.

3.3.1 Preparation of rice. The rice shall be prepared using the following steps:

a. The rice shall be placed in an excess quantity of 190°F water and blanched until the rice weighs approximately 2-1/2 times its original dry weight. Note: The blanching process must be carefully controlled in order to meet the finished product moisture content requirement.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:07Z
Check the source to verify that this is the current version before use.

b. The blanched rice shall be thoroughly rinsed with clean, cool water to remove all excess rice starch.

c. The blanched, rinsed rice shall be thoroughly drained.

Alternatively, the rice may be prepared using the following steps:

a. The rice shall be soaked in an excess quantity of water for 12 hours (± 2 hours) under refrigeration (32°F to 50°F).

b. The soaked rice shall be thoroughly drained.

c. The drained, soaked rice shall be blanched in an excess quantity of 190°F water, until the rice weighs approximately 2-1/2 times its original dry weight. Note: The blanching process must be carefully controlled in order to meet the finished product moisture content requirement.

d. The blanched rice shall be thoroughly rinsed with clean, cool water to remove all excess rice starch.

e. The blanched, rinsed rice shall be thoroughly drained.

3.3.2 Preparation of the margarine sauce. The margarine sauce shall be formulated and prepared as follows:

Ingredient	Percent by weight
Margarine	97.2
Lecithin	2.8

a. The margarine shall be completely and carefully melted in a manner that prevents margarine burn-on.

b. The lecithin shall be thoroughly mixed with the melted margarine to form a smooth sauce.

3.3.3 Finished product preparation. The rice, margarine sauce, and salt shall be combined and thoroughly mixed in the following proportions:

Ingredient	Percent by weight
Rice	88.0
Margarine sauce	10.8
Salt 1/	1.2

1/ The total amount of salt in the formulation shall be adjusted as necessary to produce a product that complies with the finished product salt requirements (see 3.6).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:07Z
Check the source to verify that this is the current version before use.

3.4 Tray pack filling and sealing. Each tray pack can (see 5.1.1) shall be filled with product such as to conform to the finished product requirements and to the following requirements:

a. Immediately after filling, each can shall be sealed in accordance with the can manufacturer's guidelines/requirements and 21 CFR, Part 113, Subpart D, or CFR 9, Part 318, Subpart G, as applicable (see 4.5.5), and under a vacuum established by a processing authority and specified in the scheduled process so as to ensure compliance with the finished product requirement (see 3.6).

b. The filled and sealed tray pack cans shall be in the retort process within two hours after sealing.

3.5 Tray pack thermoprocessing. The filled and sealed tray pack cans shall be thermostabilized by retorting at a temperature of 250°F or below until a sterilization value (F_o) of not less than 6 has been achieved. The filled and sealed thermoprocessed tray pack cans shall show no evidence of can swelling when tested for sterility as specified in 4.5.3.5.

3.6 Finished product requirements. The finished product shall comply with the following requirements:

a. There shall be no foreign material such as, but not limited to, dirt, insect parts, hair, wood, glass, or metal.

b. There shall be no foreign odor or flavor such as, but not limited to, burnt, scorched, stale, sour, rancid, musty, or moldy.

c. There shall be no color foreign to the product.

d. The average net weight shall be not less than 98 ounces.

e. No individual can shall contain less than 96 ounces of product.

f. The rice shall be white to slightly off-white in color.

g. Texture of rice shall not be hard, mushy, or pasty.

h. Appearance of rice shall be slightly fluffy with distinct, uniform rice grains.

i. The product shall show no evidence of excessive heating (materially darkened or scorched).

j. The salt content of any individual tray pack shall be not greater than 1.5 percent nor less than 0.5 percent.

k. The moisture content shall be not greater than 66 percent and not less than 60 percent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:07Z
Check the source to verify that this is the current version before use.

1. Filled, sealed, and retorted cans shall show evidence of proper vacuum as determined by concavity of the can lid (see 4.5.6).

3.6.1 Palatability. The finished product shall be equal to or better than the approved preproduction sample (see 6.1) in palatability and overall appearance.

3.7 Plant qualification. The product shall be prepared, processed, and packaged in establishments meeting the requirements of Title 21, Code of Federal Regulations, Part 110, "Current Good Manufacturing Practice in Manufacturing, Processing, Packaging or Holding of Human Food", and the plant sanitation requirements of the appropriate Government inspection agency.

3.8 Federal Food, Drug, and Cosmetic Act. All deliveries shall conform in every respect to the provisions of the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor's responsibility. Inspection and acceptance by the USDA shall not relieve the contractor of obligation and responsibility to deliver a product complying with all requirements of this specification. The contractor shall ensure product compliance prior to submitting the product to the USDA for any inspection.

4.2 Inspection and certification. Product acceptability shall be determined by the USDA. The USDA will determine the degree of inspection and supervision necessary to ensure compliance with the requirements of this specification.

4.3 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4).
b. Quality conformance inspection (see 4.5).

4.4 First article inspection. When a first article is required (see 6.1), it shall be inspected in accordance with the quality assurance provisions of this specification and evaluated for overall appearance and palatability. Any failure to conform to the quality assurance provisions of this specification or any appearance or palatability failure shall be cause for rejection of the first article.

4.5 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.5.1 Component and material examination. In accordance with 4.1, components and materials shall be examined in accordance with all the

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:07Z
Check the source to verify that this is the current version before use.

requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.5.1.1 Ingredient and component examination. Conformance of ingredients and components to identity, condition, and other requirements specified in 3.2 shall be certified by the ingredient supplier or ingredient manufacturer, and compliance shall be verified by examination of pertinent labels, markings, U.S. Grade Certificates, certificates of analyses, or other such valid documents acceptable to the inspection agency. If necessary, each ingredient shall be examined organoleptically or inspected according to generally recognized test methods such as the methods described in the Official Methods of Analysis of the AOAC and in the Approved Methods of the American Association of Cereal Chemists, to determine conformance to the requirements. Any nonconformance to an identity, condition, or other requirement shall be cause for rejection of the ingredient or component lot or of any involved product.

4.5.2 In-process examination. In-process examination shall be performed to determine conformance to preparation, processing, can interior coating, filling, sealing, and packaging requirements. Any nonconformance revealed by actual examination or by review of records of time, temperature, and formulation or of other valid documents shall be cause for rejection of the involved product.

4.5.3 Tray pack inspection. The USDA reserves the right to separate the inspection lot into smaller inspection lots.

4.5.3.1 Net weight examination. Randomly select 30 filled and sealed tray pack cans from the inspection lot and weigh separately. Subtract the average tare weight (determined by randomly selecting and weighing 30 of the empty tray pack cans and lids used in preparing the product and dividing the total weight by 30) from the weight of each tray pack in the sample. The results shall be reported to the nearest 1 ounce. If the average net weight is less than 98 ounces or if the net weight of any individual can is less than 96 ounces, the lot shall be rejected.

4.5.3.2 Double sampling plan for product inspection. The finished product shall be examined for the defects listed in table I utilizing the double sampling plans indicated in MIL-STD-105. The lot size shall be expressed in tray pack cans. The sample unit shall be one filled and sealed tray pack can. The inspection level shall be S-3 and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 4.0 for major defects. The sample cans shall be heated in accordance with the heating instructions on the can label.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:07Z
Check the source to verify that this is the current version before use.

TABLE I. Product defects 1/ 2/

Category	Defect
Major	
101	Color not white to slightly off-white
102	Texture of rice hard, mushy, or pasty
103	Appearance not slightly fluffy with distinct, uniform rice grains
104	Product shows evidence of excessive heating (materially darkened or scorched)

1/ The presence of foreign material (for example, dirt, insect parts, hair, wood, glass, metal), foreign odor or flavor (for example, burnt, scorched, stale, sour, rancid, musty, moldy), or foreign color shall be cause for rejection of the lot.

2/ Product not equal to or better than the approved preproduction sample in palatability and overall appearance shall be cause for rejection of the lot (see 3.6.1).

4.5.3.3 Salt content testing. Three filled and sealed tray pack cans shall be selected at random from the lot. The tray pack cans shall be individually tested for salt content in accordance with the Official Methods of Analysis of the AOAC, method 935.47, except that the preparation of the samples shall be as follows: The cans shall be opened and the entire contents of each can shall be separately blended to uniformity in a Waring Blendor or equivalent. The blending must be rapid and conducted in such a way that minimum heat is transferred to the product and that the product has minimum exposure to atmospheric moisture. The test results shall be reported to the nearest 0.01 percent. Any result failing to conform to the salt requirement in 3.6 shall be classified as a major defect and shall be cause for rejection of the lot.

4.5.3.4 Moisture content testing. The prepared samples from each of the three tray pack cans used in salt testing shall be tested for moisture content in accordance with the Official Methods of Analysis of the AOAC, Method 920.151. The tests should be performed with the addition of sand. The results shall be calculated as percent moisture and reported to the nearest 0.1 percent. Any test result greater than 66.0 percent or less than 60.0 percent shall be cause for rejection of the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:07Z
Check the source to verify that this is the current version before use.

4.5.3.5 Commercial sterility testing. The sample size shall be one filled, sealed, and thermoprocessed tray pack can selected from each retort batch in the lot. The sample cans shall be tested for sterility by incubating the cans at 95°F ± 5°F for 10 days. Any evidence of can swelling shall be classified as a critical defect and shall be cause for rejection of the lot.

4.5.4 Can condition examination. Examination of filled and sealed tray pack cans shall be in accordance with the U.S. Standards for Condition of Food Containers, except that inspection for labeling shall be in accordance with 4.5.4.1. In addition, scratches, scuffs, or abrasions that occur on the outside coating as a result of the filling, sealing, and thermoprocessing of the tray cans shall not be scored as a defect.

4.5.4.1 Can label examination. Labels shall be examined for defects in accordance with MIL-L-1497 (see 5.4), except, for self-adhering labels, the following additional defects shall apply:

Major: Label torn or scratched so as to obliterate any of the markings.

Minor: Air bubbles under label.
Label not properly adhered to can, for example, label raised or peeled back from edges or corners.

4.5.4.2 Label adhesive examination. When self-adhering labels are used, the adhesive shall be tested in accordance with ASTM D 3330.

4.5.5 Can closure examination. Can closures shall be examined visually and by teardowns in accordance with the can manufacturer's guidelines/ requirements and 21 CFR, Part 113, Subpart D, or 9 CFR, Part 318, Subpart G, as applicable. Any nonconformance based on observation of can seam teardowns or on record of can seam teardowns shall be classified as a major defect and shall be cause for rejection of any involved product.

4.5.6 Vacuum examination. Cans shall be allowed to cool to 75°F ± 5°F, held for at least 24 hours after sealing, and then examined for vacuum retention. To examine, lay a straight edge in the center of the lid along the length of the tray pack. Both ends of the straight edge shall touch the lid at the inside edge of the double seam. There shall be a visible gap between the straight edge and the lid for the entire distance of the label panel. Using a shorter straight edge, the same procedure shall be used across the width, in the center of the tray pack can. When examining a ribbed lid, lay the straight edge only between the two center ribs along the length of the can. The inspection lot shall include only tray packs produced in a single shift on a single sealing machine. The sample size shall be 50 cans. Any nonconformance shall be classified as a major defect and shall be cause for rejection of the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:07Z
Check the source to verify that this is the current version before use.

4.5.7 Shipping container examination. Shipping containers shall be examined for defects in assembly, closure, and reinforcement (when applicable) in accordance with PPP-B-636. In addition, the following defects shall be classified as follows:

Major: National stock number, item description, contract number, or date of pack markings missing, incorrect, or illegible.
Reinforced with other than nonmetallic strapping or tape.
Dimensions of pads not as specified.
Interior packing with fiberboard liner or pads not as specified.

Minor: Other required markings missing, incorrect, or illegible.
Arrangement or number of cans not as specified.

4.5.8 Unit load examination. Examination of unit loads shall be in accordance with the quality assurance provisions of MIL-L-35078.

5. PACKAGING

5.1 Preservation. The product shall be preserved in accordance with level A.

5.1.1 Level A. Ninety-eight ounces of food product shall be filled into a tray pack can conforming to MIL-C-44340 and sealed and thermoprocessed as specified in 3.4 and 3.5.

5.2 Packing. The product shall be packed in accordance with level A, B, or C, as specified (see 6.1).

5.2.1 Level A packing. Four cans of product, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard box, constructed and closed in accordance with style RSC-L or HSC-L with a HSC full depth cover, grade V2s of PPP-B-636. The cans shall be packed flat, four in depth within the box, with the first two cans placed with the lids together and the next two cans with the lids together. The inside of each box shall be provided with a box liner and five fiberboard pads fabricated of grade V3c fiberboard. The height of the box liner shall be equal to the full inside depth of the box (+0 inch, -1/8 inch). Flute direction of the box liner shall be vertical. The pads shall be placed between the cans and on the top and bottom of the stacked cans. The pad dimensions shall be not less than 1/8 inch of the full length and width dimensions of the box. Each box shall be reinforced with nonmetallic strapping or pressure-sensitive adhesive filament-reinforced tape in accordance with the appendix of PPP-B-636. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.1), except that the unit load shall consist of 48 boxes with 12 boxes per course and four courses per load with all courses having the same pattern. Boxes may be stacked by interlocking and reversing each tier, or by columnar stacking with paperboard or fiberboard sheets placed between each tier. When unit loads are strapped, strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:07Z
Check the source to verify that this is the current version before use.

5.2.2 Level B packing. Four cans of product, preserved as specified in 5.1, shall be packed as specified in 5.2.1, except the box shall be constructed of grade V3c, V3s, or V4s fiberboard.

5.2.3 Level C packing. Four cans of product, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard box, constructed and closed in accordance with style RSC-L, class domestic, grade 275 of PPP-B-636. The cans shall be packed flat, four in depth within the box, with the first two cans placed with the lids together and the next two cans with the lids together. The inside of each box shall be provided with a box liner and five fiberboard pads. The height of the box liner shall be equal to the full inside depth of the box (+0 inch, -1/8 inch). Flute direction of the box liner shall be vertical. The pads shall be placed between the cans and on the top and bottom of the stacked cans. The pad dimensions shall be not less than 1/8 inch of the full length and width dimensions of the box and shall be fabricated of class domestic, grade 175 fiberboard.

5.3 Unit loading. When specified (see 6.1), the product, packed as specified in 5.2.2 or 5.2.3, shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified, except that the unit load shall consist of 48 boxes with 12 boxes per course and four courses per load with all courses having the same pattern. Boxes may be stacked by interlocking and reversing each tier, or by columnar stacking with paperboard or fiberboard sheets placed between each tier. When unit loads are strapped, strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.4 Labeling and marking. Nutrition labeling shall be in accordance with the provisions of 21 CFR Part 101.9, Nutrition Labeling of Food. Each tray pack can shall be labeled in accordance with MIL-L-1497 and with the following:

- Official establishment number (for example, EST 38) or a three-digit letter code identifying the establishment
- Lot number 1/
- Production shift number 1/
- Retort identification number 1/
- Retort cook number 1/

1/ The lot number shall be expressed as a four digit Julian code. The first digit shall indicate the year of production and the next three digits shall indicate the day of the year (for example, March 19, 1992 would be coded as 2078). The Julian code shall represent the day the product was packaged and processed. Sub-lotting (when used) shall be represented by an alpha character immediately following the four digit Julian code. Following the four digit Julian code and the alpha character (when used), the other required code information shall be printed in the sequence as listed above.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:07Z
Check the source to verify that this is the current version before use.

In addition, the name of the product shall be marked, stamping is permitted, on one 1001 by 200 end of the can. The labeling shall be legible when examined as specified in 4.5.4.1 after preparation of the product in accordance with heating instructions. Paper labels are not permitted. In addition, cans shall show the following statements:

TO HEAT IN WATER: Submerge unopened can in boiling water. Simmer gently 50 to 60 minutes. Avoid overheating (can shows evidence of bulging).

CAUTION: Use care when opening as pressure may have been generated within the can.

TO HEAT IN OVEN: Either punch several holes in lid of can or open in usual manner leaving the loose lid in place. Place in a 350°F oven 50 to 60 minutes.

WARNING: Do not place unopened can in oven. This may cause the can to burst.

YIELD: Serves 18 portions of 2/3 cup each.

As an alternate labeling method, a preprinted, self-adhering, 0.002-inch thick, clear, polyester label printed with indelible black ink may be used. Self-adhering labels shall be applied after retorting. Pressure-sensitive adhesive shall require no preparation prior to application. Labels shall tack quickly and adhere without curling or breaking. The adhesive shall have a minimum adhesion of 60 ounces per inch width when examined as specified in 4.5.4.2. When self-adhering labels are used, the tray pack cans shall be labeled with the Julian code and a product code prior to retorting.

5.5 Marking.

5.5.1 Shipping containers. In addition to any special marking required by the contract or purchase order, shipping containers shall be marked in accordance with MIL-STD-129.

5.5.2 Unit loads. Unit loads shall be marked in accordance with MIL-L-35078. In addition, the following precautionary markings in capital letters larger than other markings shall be included:

CAUTION: DO NOT STACK PALLETS IN TRANSIT OR MORE THAN TWO HIGH IN STORAGE, UNLESS PALLET RACKS ARE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:07Z
Check the source to verify that this is the current version before use.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Issue of DODISS to be cited in the solicitation and, if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. When a first article is required (see 3.1, 4.4, and 6.2).
d. Provisions for approved preproduction samples (see 3.6.1 and 6.2).
e. Levels of packing required (see 5.2).
f. Type and class of unit load when unit loading is required (see 5.2.1 and 5.3).

6.2 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209-4. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.3 Ingredient information.

6.3.1 Rice. It has been found that Uncle Ben's Parboiled, Converted Rice, Uncle Ben's Inc., and Riviana Parboiled PB-S, Riviana Foods, Inc. meet the requirements of 3.2.1 and performs satisfactorily in this product.

6.4 Subject term (key word) listing.

Canned food
Combat field feeding
Operational rations
Shelf stable

6.5 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:07Z
Check the source to verify that this is the current version before use.

Custodians:

Army - GL
Navy - SA
Air Force - 50

Review activities:

Army - MD, QM
Navy - MC
DLA - SS

Preparing activity:

Army - GL

(Project 8920-0554)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:07Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-R-44274B	1993 August 16

3. DOCUMENT TITLE

RICE, WHITE, THERMOSTABILIZED, TRAY PACK

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code) (1) Commercial	(2) AUTOVON/DSN
U.S. Army Natick RD&E Center	508-651-4501	256-4501
c. ADDRESS (Include Zip Code) Commander, U.S. Army Natick RD&E Center ATTN: SATNC-WTP Natick, MA 01760-5018	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:07Z
Check the source to verify that this is the current version before use.