MIL-C-60264 (MU)
1 April 1966
SUPERSEDING
FA-PD-MI-2478, Rev 1
18 April 1963

MILITARY SPECIFICATION
CUTTER, POWDER ACTUATED, REEFING LINE, XM11, ASSEMBLY

1. SCOPE

1.1 This specification covers Cutter, Powder Actuated, Reefing Line, XM11, Assembly, loaded with Cartridge, Powder Actuated Cutter, XM131, for use in connection with cargo parachute controlled airdrops.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS
Military
MIL-A-2550 - Ammunition and Special Weapons, General Specification For
MIL-W-5625 - Webbing; Nylon Tubular

STANDARDS
Military
MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109 - Quality Assurance Terms and Definitions
MIL-STD-1167 - Ammunition Data Card

DRAWINGS
Munitions Command
D10520537 - Cutter, Powder Actuated, Reefing Line, XM11, Assembly
C8864327 - Carton, Packing Ammunition for Cutters, Powder Actuated, Reefing Line, M9, XM10, XM11, XM12, M13 with Cartridge
C8864326 - Box, Packing Ammunition for Cutters, Powder Actuated, Reefing Line, M9, XM10, XM11, XM12 or M13, with Cartridge
IEL-10520537 - Index to Inspection Equipment List for Cutter, Powder Actuated, Reefing Line, XM11, Assembly

(Copies of specifications, standards, drawings and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

FSC 1377

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:24Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 General.- Materials, parts and assemblies shall comply with the requirements specified on the applicable drawings and referenced specifications.

3.2 Functional.

3.2.1 The cutter shall not fail to fire.

3.2.2 The cutter shall function without mechanical failure (see 6.1).

3.2.3 Ballistics.- The cutter loaded with an accepted XM131 cartridge, temperature conditioned as required in Table I, shall completely sever two lines of 1/2 inch, 1000-pound tubular nylon webbing fabricated in accordance with MIL-W-5625, within the delay time specified in Table I.

Table I

Temperature	Delay Time, Seconds (see 6.2)
-65° to -70° F	7.2 max
65° to 75° F	5.4 min to 6.6 max
160° to 165° F	4.8 min

3.3 Workmanship.- The requirements for workmanship are as specified on the applicable drawings, referenced specifications and the following:

3.3.1 Metal defects.- The part shall be free from cracks, splits, cold shuts, inclusions, porosity and other metal defects.

3.3.2 Burr.- The part shall not have a burr which might interfere with the assembly or function of the item or which might be injurious to personnel handling the item.

3.3.3 Foreign matter.- The part or assembly shall not contain chips, dirt, grease, rust, corrosion or other foreign matter.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:24Z
Check the source to verify that this is the current version before use.

4.1.1 Quality assurance terms and definitions.- Reference shall be made to MIL-STD-109 to define quality assurance terms used.

4.1.2 Inspection.- Inspection shall be in accordance with MIL-A-2550.

4.2 Inspection provisions.

4.2.1 Lot.

4.2.1.1 Submission of product.- The product shall be submitted in accordance with MIL-STD-105.

4.2.1.2 Size of lot.- A lot shall consist of an identifiable group of assembled units containing metal parts assemblies produced by a homogeneous process and loaded with a single lot of cartridges.

4.2.2 Examination.- One hundred percent examination shall be performed for all critical defects. Examination for major and minor defects shall be performed on a defect basis in accordance with the classification of defects, using the sampling plan and associated criteria in Table II. All nonconforming material shall be rejected. The total number of allowable defects per class for either the major or minor classification shall not exceed the acceptance number of Table II. Four power magnification may be used for inspection of such defects as burr and foreign matter.

Table II

Lot Size	Sample Size	Major		Minor	
		Accept	Reject	Accept	Reject
1 - 300	100% Examination	-	-	-	-
301 - 800	50	0	1	1	2
801 -1800	90	1	2	2	3

4.2.2.1 Cartridge, Reefing Line Cutter, XM131, Drawing D10520499.

Defect	Method of Inspection
CRITICAL	
1. Mixed cartridges	Visual
2. Metal defective	Visual
3. "O" ring missing	Visual
4. Marking missing, incorrect or illegible	Visual
MAJOR	
101. "O" ring split, cut or cracked	Visual
102. Foreign matter	Visual
MINOR	
201. Case scratched or dented	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:24Z
Check the source to verify that this is the current version before use.

4.2.2.2 Cutter, Powder Actuated, Reefing Line, XM11, Assembly, Drawing D10520537.

Defect	Method of Inspection
CRITICAL	
1. Firing pin not cocked	X-ray - Manual 1/
2. Any part missing	X-ray Visual 1/
3. Improper assembly	X-ray Visual 1/
4. Mixed reefing line cutter	Visual
5. Marking missing, incorrect or illegible	Visual
MAJOR	
101. Front of anvil not flush or slightly below reefing line holes	Visual
102. Metal defective	Visual
103. Security of assembly	Manual
MINOR	
201. Reefing line holes obstructed	Visual
202. Protective finish inadequate or defective	Visual
203. Burr	Visual
204. Foreign matter	Visual

Note.- 1/ The cutter shall be X-rayed with the long axis of the reefing line cutter perpendicular to the rays of the X-ray machine.

4.2.2.3 Carton, Packing, Ammunition, for Cutter, Powder Actuated, Reefing Line, M9, XM10, XM11, XM12 and M13 with Cartridge, Drawing C8864327.

CRITICAL
None defined.

MAJOR
None defined.

MINOR	
201. Contents loose	Manual and Visual
202. Quantity of contents incorrect	Visual
203. Separation or filler missing	Visual
204. Cut or damaged through all carton layers	Visual
205. Marking missing, incorrect or illegible	Visual
206. Carton sealing defective, improper or missing	Visual

4.2.2.4 Box, Packing, Ammunition for Cutter, Powder Actuated, Reefing Line, M9, XM10, XM11, XM12 and M13 with Cartridge, Drawing C8864327.

CRITICAL
None defined.

MAJOR
None defined.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:24Z
Check the source to verify that this is the current version before use.

4.2.2.4 (cont)

Defect	Method of Inspection
MINOR	
201. Contents loose	Manual and Visual
202. Quantity of contents incorrect	Visual
203. Contents of box exposed.	Visual
204. Box damaged	Visual
205. Strapping missing, loose, broken or improperly applied	Visual
206. Marking missing, incorrect or illegible	Visual
207. Car seal missing, unsealed or improperly positioned	Visual

4.2.3 Inspection testing.- The following tests shall be performed in accordance with the provisions of 4.3.

4.2.3.1 Function.- The following tests shall be performed by the Government:

4.2.3.1.1 Ballistics.- Thirty assembled reefing line cutters of each lot shall be grouped, temperature conditioned as specified in Table III and 4.3.1.2 and then tested in accordance with 4.3.1.1. Failure of any reefing line cutter to comply with the requirements of 3.2 shall be cause for rejection of the lot.

Table III

Temperature	Sample Size
-65° to -70° F	10
65° to 75° F	10
160° to 165° F	10

4.2.4 Inspection equipment.- The examination and tests shall be made using the equipment listed on IEL-10520537.

4.3 Test methods and procedures.

4.3.1 Function.

4.3.1.1 Ballistics.- The test sample shall be rigidly supported in the test fixture. The sample shall be tested within five minutes after removal from the conditioning chamber. When this time limit is exceeded, the sample shall be reconditioned in accordance with 4.3.1.2.

4.3.1.2 Temperature conditioning.- A standard XM11 Reefing Line Cutter, [illegible] loaded with a dummy XM131 Cartridge, containing a temperature sensitive element, [illegible] shall be placed in the conditioning chamber at the same time as the samples. The conditioning time shall be a minimum of one hour longer than the time necessary to bring the element contained in the dummy cartridge to the required temperature.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:24Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Packing and marking.- Packing and marking shall be in accordance with Drawings C8864326 and C8864327.

5.2 Data card.- Data card information shall be as specified in MIL-STD-1167

6. NOTES

6.1 A mechanical failure is defined as any deformation or breakage of a part, the occurrence of which is other than a design function.

6.2 Delay time is defined as the time elapsed between initiation of the cable withdrawal and complete severing of the reefing line.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1377-A014

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:24Z
Check the source to verify that this is the current version before use.

To detach this form, cut along this line

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NO.

QUANTITY OF ITEMS PROCURED

DOLLAR AMOUNT

$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*

DATE

DD FORM 1 OCT 64 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:24Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

Frankford Arsenal
Philadelphia, Pa. 19137

OFFICIAL BUSINESS

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

Commanding Officer
Frankford Arsenal
ATTN: SMUFA-N1100
Philadelphia, Pa. 19137

FOLD

To detach this form, cut along this line

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:24Z
Check the source to verify that this is the current version before use.