MILITARY SPECIFICATION:

PACKING, PREFORMED

1. SCOPE

1.1 This specification covers requirements, quality assurance provisons, and the preparation for delivery criteria for one type of packing, preformed used on M500 container for 8 inch projectiles.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-P-116 - Preservation, Methods of

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1168 - Lot Numbering of Ammunition
MIL-STD-1169 - Packaging, Packing and Marking for Shipments of Inert Ammunition Components

DRAWINGS

ORDNANCE CORPS

8795695 - Packing, Preformed
8808362 - Packing and Marking for Storage and Shipments
8883537 - Bag, Packing for Repair Parts

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:09Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The packing shall comply with all requirements specified on the drawing (dwg) 8795695, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3.3 Tool manufacturing control (T.M.C.). When T.M.C. is specified herein, five consecutive parts which comply with drawing dimensions will constitute proper initial tool control acceptance. During normal production, five parts shall be selected at the start and at the end of each day's production (for a minimum of 10 parts) and examined as specified in the applicable paragraph in 4.3.2.1. In addition, five consecutive parts shall be examined as specified in the applicable paragraph in 4.3.2.1 whenever the manufacturing tool requires maintenance. Failure of any part to comply with any of the examinations specified in 4.3.2.1 shall reject the lot of production under consideration.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection. Not applicable

4.3 Qaulity conformance inspection.

4.3.1 Lot formation.

4.3.1.1 Production lot. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specificahion revision. Drawing, specification and process changes not affecting safety, performance, storage, or interchangeability, as determined by the Government, shall not necessitate changing

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:09Z
Check the source to verify that this is the current version before use.

the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

4.3.1.2 Inspection lot. A lot or batch and its formation, size, and presentation is described in MIL-STD-105, Section 5. Accordingly, a lot shall mean an inspection lot and a batch shall mean an inspection batch for the purpose of this specification. The manner in which each inspection lot or batch is to be presented and identified by the contractor, shall be designated or approved by the Government representative.

4.3.2 Product inspection examination. Critical characteristics shall require 100 percent inspection of all items in the inspection lot. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table (see Table I and Table II), and inspected for all characteristics in the applicable classification. Any characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Table I
Major Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

Table II
Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-9	all	14-16	12	28-33	16	77-121	20
10	9	17-18	13	34-41	17	122-273	21
11	10	19-22	14	42-54	18	over 273	22
12-13	11	23-27	15	55-76	19		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:09Z
Check the source to verify that this is the current version before us

4.3.2.1 Classification of characteristics (see 3.2). Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Packing, preformed (see dwg 8795695).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Inside diameter	TMC (see 3.3)
	102. Width of formed portion	TMC (see 3.3)
	103. Height of formed portion	TMC (see 3.3)
	104. Radius of formed portion	TMC (see 3.3)
	105. Diameter (alternative construction)	TMC (see 3.3)
	106. No cracks or holes	Visual
	107. Material (see 3.1)	Visual
Minor:		
	201. Workmanship (see 3.4)	Visual/Manual

4.3.2.1.2 Preparation for delivery (see 5.1)

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Material (see 3.1)	Visual
	102. Length before packing, min	*Measure
	103. Width before packing, min	*Measure
	104. Proper heat seal	Visual/Manual
	105. Properly packed	Visual/Manual
	106. No tear, crack or hole in bag	Visual
	107. Objective evidence (see 6.2) for heat seal test in accordance with MIL-P-116	Visual

*Measure with suitable scale.

Minor:		
	201. Marking	Visual
	202. Workmanship (see 3.4)	Visual/Manual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:09Z
Check the source to verify that this is the current version before use.

4.3.2.1.4 Packing and marking for storage and shipments (see 8808362).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Gross load weight, max	*Measure
102.	Contents tight in package	Manual
103.	Correctly packed	Visual/Manual
104.	Material (see 3.1)	Visual

*Determine weight with suitable scale.

Minor:		
201.	Marking	Visual
202.	Workmanship (see 3.4)	Visual/Manual

4.3.3 Testing. Not applicable
4.3.4 Acceptance inspection equipment. Not applicable
4.4 Test methods. Not applicable

5. PREPARATION FOR DELIVERY

5.1 Production items.
5.1.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).
5.1.1.1 Level A. The packing shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169(MU).
5.1.1.2 Level C. The packing shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169(MU).
5.1.2 Packing.
5.1.2.1 Levels A and C. The packing shall be packed in accordance with the applicable instructions contained in MIL-STD-1169(MU).
5.1.3 Marking. Marking shall be in accordance with MIL-STD-1169(MU).
5.2 Repair parts.
5.2.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).
5.2.1.1 Level A. The packing shall be packaged in accordance with dwg 8883537 and 8808362 using the specified moisture barrier.
5.2.1.2 Level C. The packing shall be packaged in accordance with dwg 8808362 except that the moisture barrier may be omitted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:09
Check the source to verify that this is the current version before

5.2.2 Packing.

5.2.2.1 Level A and C. The packing shall be packed in accordance with dwg 8883537 and 8808362

5.2.3 Marking. Marking shall be as specified in accordance with dwg 8883537 and 8808362 as applicable.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification.
b. Production or Repair Part.
c. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

Custodian:
Army - MU

Preparing activity:
Army - MU

Project No. 5530-A040

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:09Z
Check the source to verify that this is the current version before use.