MILITARY SPECIFICATION

CARRIER, GUIDED MISSILE EQUIPMENT,
M667; PROCESSING FOR STORAGE
AND SHIPMENT OF

This amendment forms a part of Military Specification MIL-C-63084B(AT) dated 27 October 1978, and is approved for use by the U.S. Army Tank-Automotive Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 6

3.1.7.1 Interior of vehicle. Delete paragraph in its entirety and substitute:

3.1.7.1 "Interior of vehicle. Interior surfaces of vehicle shall be cleaned with solution of detergent conforming to P-D-220 or Type I of MIL-D-16791 and water. Solution temperature shall not exceed 210°F and pressure shall not exceed 5 PSI measured 4 inches from the nozzle. After cleaning, cleaned surfaces shall be rinsed with clean water and dried. Care shall be taken during cleaning and rinsing operations to assure that no solution or water enters instruments, connections, or other components susceptible to water damage. Solution or water shall not accumulate and remain in cavities that cannot be drained. Vehicles with decals, markers, and straps and floor plates installed, shall only be hand cleaned with solution of P-D-220 or Type I of MIL-D-16791 and water to prevent damage to these components. Cleaned surfaces shall be hand rinsed and dried."

3.1.8.1 Relubrication. Line 1: Change 50 miles to "75 miles".

PAGE 15

3.5 Drive-on/drive-off capability. Line 2: After unloading, add: "(see 6.1)".

3.5.2 Batteries and electrolyte. Delete paragraph in its entirety and substitute:

3.5.2 "Batteries and Electrolyte. Batteries shall be filled with electrolyte, be fully charged, and battery cables connected (see 3.1.9.1 and 3.1.9.2). After vehicle self-movement for loading or placement in storage, the ground cable at battery shall be disconnected and secured to battery carrier, with 3/4 - inch tape conforming to type IV of PPP-T-97. A tag bearing the message, "Vehicle preserved for drive-away condition. Before

FSC PACK



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:15Z
Check the source to verify that this is the current version before use.

cranking, connect ground cable to battery terminal. Engine and fuel tanks not preserved", shall be located in a conspicuous location of driver compartment."

PAGE 17

6.1 Ordering data. Add:

"I. If vehicle drive-on/drive-off capability is required (see 3.5)."

Custodian:
Army - AT

Reviewer:
Army - SM

Preparing Activity:
Army - AT

Project No. PACK-A292



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:15Z
Check the source to verify that this is the current version before use.