INCH – POUND
MIL-C-70741 (AR)
w/AMENDMENT 3
3 November 2008
SUPERSEDING
MIL-C-70741 (AR)
w/AMENDMENT 2
6 July 2007

MILITARY SPECIFICATION

CONTAINER, METAL, PA117

This specification is approved for use by the U.S. Army Armament Research Development and Engineering Center (ARDEC), and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers requirements and quality assurance provisions for the manufacture of a family of metal containers used for packing 105MM howitzer ammunition and 105MM tank ammunition.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards and handbooks. The following specifications, standards and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

TT-C-490	- Cleaning Methods for Ferrous Surfaces and Pretreatments for Organic Coatings

Comments, suggestions, or questions on this document should be addressed to the Commander, U.S. Army ARDEC, ATTN: AMSRD-AAR-QES-E, Picatinny, NJ 07806-5000 or emailed to ardec-tdzn@pica.army.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at http://assist.daps.dla.mil.

AMSC N/A FSC 8140

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-W-12332	- Welding Resistance, Spot, Seam and Projection, for Fabricating Assemblies of Low-Carbon Steel
MIL-A-48078	- Ammunition, Standard Quality Assurance Provisions, General Specification for
MIL-A-70625	- Automated Acceptance Inspection Equipment for Non-Electronic Components, Design, Testing and Approval of

STANDARDS

MILITARY

MIL-STD-171	- Finishing of Metal and Wood Surfaces
MIL-STD-1235	- Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1261	- Welding Procedures for Constructional Steel.

(Unless otherwise indicated, Copies of these documents are available online at http://assist.daps.dla.mil/quicksearch/or http://assist.daps.dla.mil from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings and publications. The following other Government documents, drawings and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS (see 6.2)

US ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER

9378166	- Container, Ammunition, Metal PA117

(Copies of these drawings may be requested online at Drawing-request@pica.army.mil or from U.S. Army ARDEC, ATTN: AMSRD-AAR-AIS-TD, Picatinny, NJ 07806-5000.)

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the document which are DoD adopted are those listed in the issue of the DODISS cited in the

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS

ASTM – D2240	-	Indentation Hardness of Rubber and Plastics by Means of Durometer, Standard Method of Test for (DoD adopted)
ASTM – D3951	-	Commercial Packaging, Practice for (DoD adopted)
ASTM – E8	-	Tension Testing of Metallic Materials, Standard Method of
ASTM – E18	-	Rockwell Hardness and Rockwell Superficial Hardness of Metallic Materials, Test for

(Copies of ASTM standards are available online at http://www.astm.org or from American Society for Testing and materials, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence. Nothing in this document, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Materials. Materials and parts shall be in accordance with applicable drawings and specifications.

3.2 Containers. The containers (container assemblies) shall comply with all requirements specified on drawing 9378166 and associated drawings and with all requirements specified in applicable specifications and standards.

3.3 Welding. The welding shall comply with the requirements of MIL-W-12332 or MIL-STD-1261.

3.3.1 Tensile strength of body weld. The tensile strength of the longitudinal weld shall not be less than 65 percent of the tensile strength of body material.

3.3.2 Tensile strength of body material. The tensile strength of the body material shall not be less than 50,000 pounds per square inch (psi).

3.4 Painted surface. The painted surfaces of the container shall comply with the requirements of TT-C-490. However, the film thickness and salt spray requirements of TT-C-490 shall not apply to the interior surfaces, exterior surface welded spots and exterior surface sharp corners of the container. Bare spots are permissible on all bearing surfaces.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

3.5 Cover assembly. Upon assembly of the cover assembly to the body assembly (body weldment), the cover assembly shall freely engage and rotate within the body assembly. As the cover assembly is rotated with the “Y” handle in the open position, the “Y” handle shaft ends shall freely engage into the respective bayonet slots of the rim. When the “Y” handle is rotated-toward the closed position, the “Y” handle shall push the spring clip out of the way and snap into place (closed position) and the spring clip shall return to its original position locking the “Y” handle. When the “Y” handle is returned to the open position, it shall push the spring clip out of the way permitting a 180 degree rotation of the “Y” handle to the open position with the spring clip returning to its normal position. Rotation of the cover assembly will permit disengagement from the body assembly. While in the closed position, a 0.06 inch minimum diameter pin shall pass through the two aligned holes in the handle and shaft support.

3.6 Air pressure test.

3.6.1 Air pressure of unpainted cover assembly. The unpainted cover assembly shall withstand an internal air pressure, after stabilization, of three (3) psi +/- .5 psi for five (5) seconds minimum, without leakage occurring.

3.6.2 Air pressure of unpainted body assembly. The unpainted body assembly shall withstand an internal air pressure, after stabilization, of three (3) psi +/- .5 psi for five (5) seconds minimum, without leakage occurring.

3.7 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.8 Workmanship.

3.8.1 Containers. The containers shall be regular, smooth, and free from wrinkles, pin holes, cracks, rough spots, burrs, sharp edges and any other defect that might affect the serviceability, durability, and safety of the container.

3.8.2 Paint coating. The paint coating shall be in accordance with applicable drawings and comply with instructions in MIL–STD– 171.

3.8.3 Parts. All parts shall be free of chips, dirt, grease, rust and foreign material. The cleaning method used shall not be injurious to any of the parts nor shall any of the parts be contaminated by the cleaning agents used.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item:

a. First article inspection (See 4.3)
b. Quality conformance inspection (see 4.4)

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of fifteen (15) painted container assemblies, five (5) painted cover assemblies, five (5) unpainted cover assemblies, and ten (10) each of every subassembly and component (unpainted).

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

TABLE I – First article inspection

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE Assemblies and Components	SHEET 1 OF 3		DRAWING NUMBER See below NEXT HIGHER ASSEMBLY
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Container assemblies, painted (Dwg. 9378166)			
	a. Examination for defects	5	3.2	4.4.2.18
	b. Air pressure	15	3.2	4.5.6.2
	Body assembly (weldment), unpainted (Dwg. 9378171)			
	a. Examination for defects (except painted surface)	10	3.2	4.4.2.17
	b. Air pressure	5	3.6.2	4.5.6.1
	c. Weld strength of rim to body (see Note)	5	3.2	4.5.2/Dwg.
	Body assembly (weldment), painted (Dwg. 9378171) Painted surface	5	3.2	4.4.2.17
	Cover assembly, unpainted (Dwg. 9386824-2) Air pressure	5	3.6.1	4.5.6.1

NOTES:
The weld security inspections and spring tests shall be performed after the other inspections have been performed on the applicable samples.

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

TABLE I – First article inspection

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE Assemblies and Components	SHEET 2 OF 3		DRAWING NUMBER See below NEXT HIGHER ASSEMBLY
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Cover assembly, painted and prior to assembly of gasket (Dwg. 9386824-2) Examination for defects	5	3.2	4.4.2.10
	Cover assembly, after assembly of gasket (Dwg. 9386824-2) Examination for defects	5	3.2	4.4.2.11
	Body, unpainted (Dwg. 9386828-3) a. Examination for defects b. Tensile strength (see Note)	10 5	3.2 3.3.1	4.4.2.15 4.5.1/Dwg.
	Cover, weldment (Dwg. 9386822-2) a. Examination for defects	10	3.2	4.4.2.9

NOTES:
The weld security inspections and spring tests shall be performed after the other inspections have been performed on the applicable samples.

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

TABLE I – First article inspection

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE Assemblies and Components	SHEET 3 OF 3		DRAWING NUMBER See below NEXT HIGHER ASSEMBLY
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Spring, unpainted (Dwg. 9344042)			
	a. Examination for defects	10	3.2	4.4.2.1
	b. Embrittlement (see Note)	5	3.2	4.5.3/Dwg.
	c. Hardness (see Note)	5	3.2	4.5.4/Dwg.
	Gasket (Dwg. 12910349-3)			
	a. Examination for defects	10	3.2	4.4.2.8
	b. Hardness	5	3.2	4.5.5/Dwg.
	Remaining subassemblies and components			
	Examination for defects	10	3.2	Applicable subparagraph if 4.4.2

NOTES:
The weld security inspections and spring tests shall be performed after the other inspections have been performed on the applicable samples.

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots of containers shall contain material from lots with the same interfix number from one manufacturer.

4.4.2 Examinations and tests.

a. Classification of characteristics. Quality conformance examinations and tests are specified in the following Classification of Characteristics paragraphs. The contractor's quality program or detailed inspection system shall provide assurance of compliance of all characteristics with the applicable drawing and specification requirements utilizing as a minimum the conformance criteria specified herein. When O-1 inspection is specified herein, inspection criteria shall be in accordance with Table II below using the inspection levels cited in the Classification of Characteristics paragraphs. Samples shall be selected at random.

Table II. O-1 Attribute Plans

	Inspection Level					
Lot Size	I	II	III	IV	V	VI
2 to 8	*	*	*	*	5	3
9 to 15	*	*	*	13	5	3
16 to 25	*	*	*	13	5	3
26 to 50	*	*	32	13	5	3
51 to 90	*	*	32	13	12	4
91 to 150	*	125	32	13	12	5
151 to 280	*	125	32	30	14	6
281 to 500	*	125	32	30	17	7
501 to 1200	*	125	74	35	20	9
1201 to 3200	1250	125	74	43	24	10
3201 to 10000	1250	125	87	50	30	10
10001 to 35000	1250	296	109	61	36	10
35001 to 150000	1250	296	124	74	40	10
150001 to 500000	1250	346	156	91	40	10
500001 and over	1250	431	187	102	40	10

Numbers under inspection levels indicate sample size; asterisk indicates one hundred percent inspection. If sample size exceeds lot size, perform one hundred percent inspection. Accept on zero and reject on one or more for all inspection levels.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

b. Alternative inspection provisions. Alternative inspection procedures, methods, or equipment, such as statistical process control, tool control, other types of sampling procedures, etc., may be used by the contractor when they provide, as a minimum, the level of quality assurance required by the provisions specified herein. Prior to applying such alternative procedures, methods or equipment, the contractor shall describe them in a written proposal submitted to the Government for evaluation and approval (see 6.5). When required, the contractor shall demonstrate that the effectiveness of the proposed alternative(s) is equal to or better than the specified quality assurance provisions herein. In cases of dispute as to whether the contractor's proposed alternative(s) provide equal assurance, the provisions of this specification shall apply. All approved alternative inspection provisions shall be specifically incorporated into the contractor's quality program or detailed inspection systems as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.1	Spring		9344042
			NEXT HIGHER ASSEMBLY 9344044

CATEGORY	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	True position of holes	0-1, Level III	3.2	Gage
102	Radius of bend	0-1, Level III	3.2	Gage
Minor				
201	Evidence of poor workmanship	0-1, Level V	3.8	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.2	Support, Shaft		9944035-1
			NEXT HIGHER ASSEMBLY 9944044-1

CATEGORY	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Diameter of large hole, maximum (max.)	0-1, Level III	3.2	Gage
102	True position of large hole	0-1, Level III	3.2	Gage
103	True position of slot	0-1, Level III	3.2	Gage
104	True position of holes for spring	0-1, Level III	3.2	Gage
105	Distance between shaft support uprights	0-1, Level III	3.2	Gage
106	Material thickness	0-1, Level IV	3.2	Gage
Minor				
201	Radius not present at edges of tab	0-1, Level V	3.2	Visual
202	Evidence of poor workmanship	0-1, Level V	3.8	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE		SHEET 1 OF 1	DRAWING NUMBER
4.4.2.3	Handle			9344036-1
				NEXT HIGHER ASSEMBLY 9386824-2
CATEGORY	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Width of hexhole, max. (three readings, 60° apart)	0-1, Level III	3.2	Gage
102	True position of hexhole	0-1, Level III	3.2	Gage
103	Distance from center of hexholes to near edge of spring slot (Dim D)	0-1, Level III	3.2	Gage
104	Width of spring slot	0-1, Level III	3.2	Gage
Minor				
201	Evidence of poor workmanship	0-1, Level V	3.8	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.4	Shaft		9344037-2
			NEXT HIGHER ASSEMBLY 9386824-2

CATEGORY	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Width across flats of hexagon segment minimum (min.) (three readings, 60° apart)	0-1, Level III	3.2	Gage
102	Length of hexagon segment of shat, min.	0-1, Level III	3.2	Gage
103	Length of small diameter segment (two places)	0-1, Level III	3.2	Gage
104	Large diameter (two places)	0-1, Level III	3.2	Gage
105	Small diameter (two places)	0-1, Level III	3.2	Gage
106	Total length of large diameters and hexagon segments (Dim B)	0-1, Level III	3.2	Gage
107	Small diameter segment not tangent to large diameter segment and side of hexagon segment	0-1, Level III	3.2	Visual
Minor				
201	Evidence of poor workmanship	0-1, Level V	3.8	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.5	Washer		9344038
			NEXT HIGHER ASSEMBLY 9386824-2

CATEGORY	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Inside diameter	0-1, Level III	3.2	Gage
102	Height, min.	0-1, Level III	3.2	Gage
103	Outside diameter, min.	0-1, Level III	3.2	Gage
Minor				
201	Evidence of poor workanship	0-1, Level V	3.8	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.6	Retainer, Washer or Screw (with built in retainer washer)		9344041 or 13020941
			NEXT HIGHER ASSEMBLY 9386824-2

CATEGORY	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major 101	Height of retainer washer	0-1, Level III	3.2	Gage
Minor 201	Evidence of poor workmanship	0-1, Level V	3.8	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.7	Cover		9386821-2
			NEXT HIGHER ASSEMBLY 9386822-2

CATEGORY	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Outside diameter, max.	0-1, Level III	3.2	Gage
102	Width of groove	0-1, Level III	3.2	Gage
103	Depth from top of cover to recess	0-1, Level III	3.2	Gage
104	Length of threads, min., when applicable (see Note)	0-1, Level III	3.2	Gage
105	Flatness of bottom surface inner annular ring and surrounding air test hole	0-1, Level III	3.2	Gage
106	Material thickness	0-1, Level V	3.2	Gage
Minor				
201	Evidence of poor workmanship	0-1, Level V	3.8	Visual

NOTES:
Threads may be formed on cover (instead of cover assembly).

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.8	Gasket		12910349-3
			NEXT HIGHER ASSEMBLY 9386824-2

CATEGORY	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Inside diameter, max. (Dim A)	0-1, Level III	3.2	Gage
102	Large width	0-1, Level III	3.2	Gage
103	Middle width	0-1, Level III	3.2	Gage
104	Height of rectangular cross section	0-1, Level III	3.2	Gage
105	Material certification		3.2	Certification
Minor				
201	Evidence of poor workmanship	0-1, Level V	3.8	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.9	Cover Weldment		9386822-2
			NEXT HIGHER ASSEMBLY 9386824-2

CATEGORY	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Location of shaft support slot with respect to cover air hole	0-1, Level III	3.2	Gage
102	Weld missing, incomplete or visually inadequate	0-1, Level III	3.2	Visual/Manual
Minor				
201	Evidence of poor workmanship	0-1, Level V	3.8	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.10	Cover assembly, painted and prior to assembly of gasket		9386824-2
			NEXT HIGHER ASSEMBLY 9378166

CATEGORY	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	.725 Distance from top of shaft (in closed position) to inside surface of the gasket retainer section of cover (two places)(unpainted)	0-1, Level III	3.2	Gage
102	Length of thread (min.), when applicable (see Note)	0-1, Level III	3.2	Gage
103	Component missing or inadequately assembled	0-1, Level III	3.2	Visual
104	Rotating of shaft inadequate after crimping	0-1, Level III	3.2	Manual
105	Paint thickness, min.	0-1, Level IV	3.2	Gage
Minor				
201	Evidence of poor workmanship	0-1, Level V	3.8	Visual

NOTES:
Threads may be formed on cover (instead of cover assembly).

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.11	Cover Assembly		9386824-2
			NEXT HIGHER ASSEMBLY 9378166

CATEGORY	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major 101	Gasket not secured or secured improperly to cover	0-1, Level III	3.2	Visual/Manual
Minor 201	Evidence of poor workmanship	0-1, Level V	3.8	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.12	Rim		9386827-2
			NEXT HIGHER ASSEMBLY 9378171

CATEGORY	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Length of larger slot (on side of rim), max.		3.2	Gage
102	Width of larger slot (on side of rim), max.		3.2	Gage
103	Location of bayonet slot, four places (see Note)		3.2	Gage
104	Inside diameter of rim, two places (Dim E)		3.2	Gage
105	Outside dimension across flats, two places (Dim A)		3.2	Gage
106	Outside dimension across corners, two places (Dim D)		3.2	Gage
107	Radius at beginning of locking edge of bayonet slot missing		3.2	Visual
Minor				
201	Drainage hole missing		3.2	Visual
202	Step at inside of locking edge of bayonet slot missing		3.2	Visual
203	Evidence of poor workmanship		3.8	Visual

NOTES:
This inspection may be performed on the body weldments.

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.13	Ring		9386826-2
			NEXT HIGHER ASSEMBLY 9378171

CATEGORY	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Length of larger slot (on side of ring), max.	0-1, Level III	3.2	Gage
102	Width of larger slot (on side of ring), max.	0-1, Level III	3.2	Gage
103	Outside dimensions across flats, two places (Dim A)	0-1, Level III	3.2	Gage
104	Width of opening of container interlocking grip	0-1, Level III	3.2	Gage
Minor				
201	Location of interlocking cutouts	0-1, Level IV	3.2	Gage
202	Drainage hole missing	0-1, Level IV	3.2	Visual
203	Evidence of poor workmanship	0-1, Level V	3.8	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.14	Bottom		9378172
			NEXT HIGHER ASSEMBLY 9378171

CATEGORY	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Height, minimum (min.)	0-1, Level III	3.2	Gage
102	Material thickness	0-1, Level IV	3.2	Gage
Minor				
201	Evidence of poor workmanship	0-1, Level V	3.8	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.15	Body		9386828-3
			NEXT HIGHER ASSEMBLY 9378171

CATEGORY	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Length, min.	0-1, Level III	3.2	Gage
102	Inside diameter, min. (See Note)	0-1, Level III	3.2	Gage
103	Flatness of body end	0-1, Level III	3.2	Gage
104	Material thickness	0-1, Level IV	3.2	Gage
Minor				
201	Evidence of poor workmanship	0-1, Level V	3.8	Visual

NOTES:
This inspection may be performed on the body weldments.

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.16	Plug, Stacking		9386837
			NEXT HIGHER ASSEMBLY 9378171

CATEGORY	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Length of plug, min.	0-1, Level III	3.2	Gage
102	Width of plug, min.	0-1, Level III	3.2	Gage
Minor				
201	Evidence of poor workmanship	0-1, Level V	3.8	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.17	Body Assembly (weldment)		9378171
			NEXT HIGHER ASSEMBLY 9378166

CATEGORY	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	.885 Location of bayonet slot of rim with respect to edge of body (four places)		3.2	Gage
102	True position of slots of aft ring and rim		3.2	Gage
103	True position of stacking plugs of ring (s) and rim to each other		3.2	Gage
104	Inside diameter of body, min.		3.2	Gage
105	Body (seam) weld (if applicable) or weld of ring (s), rim or bottom to body missing, incomplete or visually inadequate		3.2	Visual
106	Shear load min. between stacking plug and rim		3.2	Gage
107	Shear load min. between stacking plug and ring		3.2	Gage
108	Paint thickness, min		3.2	Gage
Minor				
201	Marking missing, illegible or incorrect		3.2	5.3/Visual
202	Evidence of poor workmanship		3.8	Visual

NOTES:
1. Two per shift

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.18	Container Assembly		9378166
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Cover assembly assembled to body assembly	0-1, Level III	3.5	Visual/Manual
Minor				
201	Protective finish damaged, bare spots exposing metal, etc.	0-1, Level IV	3.2	Visual
202	Evidence of poor workmanship	0-1, Level V	3.8	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

4.4.3 Testing.

4.4.3.1 Tensile strength of body material and weld (see 3.3.1), Major defect. During the first half of a production shift and during the last half of a production shift, a body shall be randomly selected for this test. From each body, three (3) specimens shall be selected at random for determination of body material tensile strength. Also from each body, four (4) specimens, approximately equally spaced along the axis, shall be taken at right angles to the weld and the tensile strength of their welds shall be determined. Each of these values shall be compared with the lowest determined value of the body material tensile strength for compliance with the requirement of 3.3.1. If one or more specimens (longitudinal body weld or body material) fail to comply with 3.3.1 or 3.3.1.1, that sample body shall be classed defective and the quantity of bodies which were welded during this shift between this tensile strength test and the earlier tensile strength test (if applicable) shall be rejected. The test shall be performed as specified in 4.5.1.

4.4.3.2 Weld strength of rim to body (see Dwg. 93781711), Major defect. During the first half of a production shift and during the last half of a production shift, a body assembly shall be randomly selected for this test. From each body assembly, two (2) specimens of welded rim to body segments shall be taken at random. If any specimen fails to meet the requirement when tested in accordance with 4.5.2, the quantity of body assemblies which were welded during this shift, between this weld strength test and the earlier weld strength test (if applicable), shall be rejected.

4.4.3.3 Spring embrittlement (see Dwg. 9344042), Major defect. Five (5) springs shall be randomly selected from each heat treatment lot for this test. If any spring fails to meet the requirement, the heat treatment lot shall be rejected. The test shall be performed as specified in 4.5.3.

4.4.3.4 Hardness of spring (see Dwg. 9344042), Major defect. Five (5) springs shall be randomly selected from each heat treatment lot for this test. If any spring fails to meet the requirement, the heat treatment lot shall be rejected. The test shall be performed as specified in 4.5.4.

4.4.3.5 Hardness of gasket (see Dwg. 9386829), Major defect. Five (5) gaskets shall be randomly selected from each lot for this test. If any gasket fails to meet the requirement, the lot shall be rejected. The test shall be performed as specified in 4.5.5.

4.4.3.6 Air Pressure.

4.4.3.6.1 Air Pressure of unpainted cover assembly (see 3.6.1), Major defect. The cover assemblies shall be checked 100 percent. If any cover assembly fails to comply with the requirement, the cover assembly shall be rejected. The test shall be performed as specified in 4.5.6.1.

4.4.3.6.2 Air pressure of unpainted body assembly (body weldment) (see 3.6.2), Major defect. The body assemblies shall be checked 100 percent. If the body assembly fails to comply with the requirement, the body assembly shall be rejected. The test shall be performed as specified in 4.5.6.1.

4.4.3.6.3 Air pressure of painted container assembly (see Dwg. 9378166 as applicable), Major defect. Container assemblies shall be selected in accordance with MIL-STD-1235, continuous

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

sampling plan CSP-1, using Sample Frequency Code D with a value of i of 135 consecutive units. The test shall be performed as specified in 4.5.6.2.

4.4.3.6.3.1 Screw torque test. (See Dwg. 9378166), Major defect. The same containers used for the air pressure test of the container assembly (4.4.3.6.3) shall be subjected to this test as specified in 4.5.6.2.1.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with 4.4.2.1. and in 4.5. When Automated Acceptance Inspection Equipment is to be used, the provisions of MIL-A-70625 shall apply. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See section 6 of MIL-A-48078 and 6.3 herein.

4.5 Methods of inspection. (See 6.4)

4.5.1 Tensile strength of body material and weld. The tensile strength shall be determined in accordance with ASTM-E8.

4.5.2 Weld strength of rim to body. The strength of the weld shall be determined in accordance with ASTM-E8.

4.5.3 Spring embrittlement. The spring shall be repeatedly stretched with increasing loads until it does not return to its original free height. That point shall indicate minimum distortion. Any unit which fractures prior to extension to minimum distortion shall be classed defective.

4.5.4 Hardness of spring. The hardness of the spring shall be determined in accordance with ASTM-E18.

4.5.5 Hardness of gasket. The hardness shall be determined in accordance with ASTM-D2240.

4.5.6 Air pressure test.

4.5.6.1 Air pressure of unpainted cover assembly and unpainted body assembly. Subject the cover assembly and container body to the specified internal air pressure for the test time specified. For the cover assembly, apply the pressure when the cover assembly is assembled to a master body assembly (or its equivalent) equipped with a gasket. For the body assembly, apply the pressure when the body assembly is assembled to master cover (or equivalent) and gasket. The master cover and the master body assembly shall be provided with satisfactory means for applying and maintaining the pressure during the test and for showing evidence of leakage. Observation shall be made for a pressure drop exceeding the requirement. A cover assembly or body assembly which does not meet the requirements shall be classed defective.

4.5.6.2 Air pressure of painted container assembly. Subject the painted container assembly to an air pressure test as specified in the applicable container assembly drawing. A container assembly which does not meet the requirement shall be classed defective. When cover assemblies or body

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

weldments (container bodies) are procured separately, the contractor shall submit for Government approval, the test procedure that will be followed to meet the applicable test requirement.

4.5.6.2.1 Screw torque test. After the air pressure is performed and the screw is reapplied to the cover assembly, apply the minimum torque (see Dwg. 9378166). Any evidence of motion of the screw before reaching the minimum acceptable torque shall be cause for rejection of the container assembly being tested. Any container assembly which fails the screw torque test may be reworked and returned to the lot after passing the screw torque test.

5. PACKAGING

5.1 Packaging requirements. None required.

5.2 Packing. Packing shall be commercial. Metal ammunition containers shall be prepared in accordance with ASTM-D3951.

5.2 Marking. Shipping marking shall comply with ASTM-D3951 and the following additional instructions. No shipping marking shall be placed directly on the containers. Commercial shipping tags attached with wire shall be used unless otherwise specified. The following information shall be shown: Item name and model number, part number and revision, contract number, lot number and date, name and address of manufacturer. If containers are bundled, boxed or palletized, the gross weight and quantity shall be included. The above information may be placed on pallets or boxes by labeling or stenciling.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. This ’lightweight metal ammunition container is used for packing 105MM howitzer ammunition and 105MM tank ammunition.

6.2 Acquisition requirements. See MIL-A-48078.

6.3 Submission of inspection equipment for design approvals. See MIL-A-48078. Submit designs as required to: Commander, U.S. Army Armament Research, Development and Engineering Center, ATTN: AMSMC-QAR-I (D), Picatinny Arsenal, NJ 07806-5000. This address will be specified on the Contract Data Requirements List, DD Form 1423 in the contract. Unless otherwise specified, data item D1-R-1714 will apply.

6.4 Equivalent test methods. Prior approval of the Contracting Officer is required for use of equivalent test methods. A description of the proposed method should be submitted through the Contracting Officer to: Commander, U.S. Army Armament Research Development and Engineering Center, ATTN: AMSMC-QAR-Q (D), Picatinny Arsenal, NJ 07806-5000. This description should include but not be limited to the accuracy and precision of the method, test data demonstrating the accuracy and precision and drawings of any special equipment required.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

6.5 Submission of alternative inspection Provisions. Proposed alternative inspection provisions should be submitted by the contractor to the procuring contracting officer for evaluation and approval by the technical activity responsible for preparation of this specification.

6.6 Changes form previous issue. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

6.7 Subject term (keyword) listing.

Ammunition
Container
Howitzer
Packing
Pallet
Projectile, 105MM
Tank

Custodian:
Army – AR

Preparing activity:
Army – AR
(Project 8140 - 2009 – 003)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.