INCH-POUND

MIL-F-62265A(AT)
AMENDMENT 1
12 MARCH 1992

MILITARY SPECIFICATION

FILTER ELEMENT AND RELIEF VALVE, FLUID PRESSURE, HYDRAULIC (M-60 TANK SERIES)

This amendment forms a part of MIL-F-62265A(AT), dated 25 September 1990, and approved for use by the U.S. Army Tank-Automotive Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

3.4.4 Delete and substitute:

"3.4.4 Weight (see 4.7.1.2). The weight of the assembly, containing no hydraulic fluid, shall be approximately 1.5 pounds (per drawing 12257235) or 0.8 pounds (per drawing 12270316)."

3.5.2 Delete and substitute:

"3.5.2 Filtration. The filter element shall remove 97 percent minimum by weight of all contaminants larger than size specified in table I (see 4.7.2.2)."

PAGE 5

TABLE III, Line 1 Delete "12257235 .15 .15" and substitute

"12257235 0 .30"

AMSC N/A This document contains no deliverable data. FSC 4820
DISTRIBUTION STATEMENT A. Approved for public release, unlimited distribution.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:27Z
Check the source to verify that this is the current version before use.

PAGE 9

Table VII Delete and substitute:

" TABLE VII. Inspection applied to preproduction and initial production samples

Title and Sequence	Requirement	Method	Preproduction 1 2 3 4	Initial Production 1 2 3 4
Examinations				
Materials	3.3	visual	x x x	x x x x
Dimensional constraints	3.4.3	visual	x x x	x x x x
Packaging	5.0	visual		x
Tests				
Flow direction	3.4.2	4.7.1.1	x x x	x x x x
Weight	3.4.4	4.7.1.2	x x x	x x x x
Bubble point-alcohol	3.5.1	4.7.2.1.1	x x x x	x x x x
Bubble point-hydraulic fluid	3.5.1	4.7.2.1.2	x x x x	x x x x
Low temp. test	3.6.1	4.7.3.1.1	x x x x	x x x x
Vibration	3.6.2	4.7.3.2	x x x x	x x x x
Shock	3.6.3	4.7.3.3	x	x
Flow rate	3.5.3	4.7.2.3	x	x
Pressure drop	3.5.4	4.7.2.4	x	x
Dirt capacity	3.5.5	4.7.2.5	x	x
Collapse pressure	3.5.7	4.7.2.7	x	x
Flow fatigue	3.5.8	4.7.2.8	x	x
Filtration	3.5.2	4.7.2.2	x	x
Efficiency	3.5.6	4.7.2.6	x	x
Relief valve				
Cracking pressure	3.5.9.1	4.7.2.9.1	x	x
Flow capacity	3.5.9.2	4.7.2.9.2	x	x
Reseat pressure	3.5.9.3	4.7.2.9.3	x	x
Endurance	3.5.9.4	4.7.2.9.4	x x x x	x x x x

PAGE 12

4.7.1.2 Delete and substitute:

" 4.7.1.2 Weight. The assembly shall be weighed without hydraulic fluid and shall weigh approximately 1.5 pounds (12257235) or 0.8 pounds (12270316) maximum (see 3.4.4)."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:27Z
Check the source to verify that this is the current version before use.

PAGE 13

4.7.2.3 Delete and substitute:

"4.7.2.3 Flow Rate Determination. The flow for the assembly shall be determined in conjunction with 4.7.2.2 and shall be as specified in table I (see 3.5.3)."

PAGE 14

4.7.2.4 Delete and substitute:

"4.7.2.4 Pressure drop test. To determine compliance to the pressure drop across a clean assembly as specified in 3.5.4, the following procedure, or equivalent, shall be used with the relief valve blocked:

Hydraulic pressure, adjusted to provide rated flow, shall be applied to the assembly. Pressure shall be monitored on the inlet and outlet sides of the filter. The pressure drop across the assembly, less the housing pressure drop, shall be the differences between the inlet and outlet pressure and shall not exceed that specified in table I."

4.7.2.6 Delete "filter element" and substitute "assembly".

4.7.2.6 sub para d. Delete and substitute:

"d. Apply air pressure to force the fluid containing contaminant through the test assembly at rated flow."

4.7.2.6 sub para f. Delete "filter" and substitute "assembly".

PAGE 15

4.7.2.8 line 1 Delete "3.5.4" and substitute "3.5.8".

4.7.2.8 line 2 Delete "assembly" and substitute "relief valve".

4.7.2.8 line 8 Delete "filter element" and substitute "test assembly".

PAGE 16

4.7.2.9.1 Delete first two sentences and substitute:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:27Z
Check the source to verify that this is the current version before use.

"4.7.2.9.1 Cracking pressure determination. To determine conformance to 3.5.9.1, the filter element media shall be blocked (with contaminants, dummy filter, etc.) and the assembly installed in a suitable housing. Pressure shall be applied to the inlet port of the housing beginning with a pressure of 40 psi and increasing in increments of 20 psi, or less, until cracking pressure of the relief valve in the assembly being tested is reached."

PAGE 18

5.2 Delete "(see 3.4.6)".

6.2 e Delete "(see 4.2.2)".

PAGE 21

Figure 2 Delete "GN_2 Supply" and substitute "Air/GN_2 Supply".

Custodian:
Army - AT

Preparing Activity:
Army - AT

(Project4820-A078)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:27Z
Check the source to verify that this is the current version before use.