INCH-POUND

MIL-D-63197 (AR)
AMENDMENT 2
17 February 1995
SUPERSEDING
AMENDMENT 1
10 October 1980

MILITARY SPECIFICATION

DETONATOR, DELAY ELECTRIC: PA 506
PARTS FOR, AND LOADING, ASSEMBLING AND PACKING

This amendment forms a part of MIL-D-63197 (AR), dated 7 October 1977, and is approved for use by the U.S. Army Armament Research, Development and Engineering Center, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Beneficial Comments: Delete "SMCAR-BAC-S" and substitute "AMSTA-AR-EDE-S".

PAGE 3

3.7.2, Delete in its entirety and substitute:

"3.7.2 Cold temperature. The detonator assembly shall comply with the output requirements of 3.6.1 and time requirements of 3.6.3 after being conditioned at - 65° F, ± 5° for two hours, and tested as specified in 4.5.10.2."

3.7.3, Delete in its entirety and substitute:

"3.7.3 Hot temperature. The detonator assembly shall comply with the output requirements of 3.6.1 and time requirements of 3.6.3 after being conditioned at plus 160° F, ± 5° for two hours, and tested as specified in 4.5.10.3."

AMSC N/A FSC 1375
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:23Z
Check the source to verify that this is the current version before use.

PAGE 14

4.4.2.7, Major Defect 106:

Delete "or incorrect" and substitute "deformed or scratched".

Para/Ref, delete "Gage" and substitute "Visual".

Add new "Major Defect 115, Anvil spherical radius verification ...-- ...3.2 ...Gage/4.6."

* 4.4.2.7, Note (a), delete in its entirety and substitute:

"(a) The Functioning Time sample will consist of detonators tested for Major Defect 109, 112 and 113."

PAGE 16

* 4.5.9, Insert first sentence: "Two hundred (200) detonators from each lot shall be subjected to this test."

* 4.5.9.1, Delete first sentence, substitute with the following:

"Detonators subjected to this test shall be temperature conditioned as specified in 4.5.9, 4.5.10.2 or 4.5.10.3 as applicable."

PAGE 17

* 4.5.9.3, Delete "Two hundred (200)".

PAGE 18

* 4.5.10.2, Delete last two sentences and substitute the following:

"If any detonator fails to meet the output or time requirements, it shall be classified defective."

* 4.5.10.3, Delete last two sentences and substitute the following:

"If any detonator fails to meet the output or time requirements, it shall be classified defective."

4.6, Add new paragraph:

"4.6 Tool control of spherical radius. The contractor shall verify at the beginning and end of each detonator lot produced that the anvil used meets the spherical radius requirements of Dwg. 9311150. Non-compliance with the above requirements shall result in the rejection of the lot."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:23Z
Check the source to verify that this is the current version before use.

6.2: Delete "USAARADCOM, ATTN: DRDAR-QAA-I" and substitute "ARDEC, ATTN: AMSTA-AR-QAA-B."

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in this notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1375-0009)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:23Z
Check the source to verify that this is the current version before use.