INCH-POUND

MIL-D-70430 (AR)
AMENDMENT 3
2 MARCH 1990
SUPERSEDING
AMENDMENT 2
30 JUNE 1984

MILITARY SPECIFICATION

DECELERATOR, RAM AIR, PARTS AND CONTAINER ASSEMBLY

This amendment forms a part of Military Specification MIL-D-70430(AR), dated 12 September 1983, and is approved for use within the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

* 3.5, Delete in its entirety.

PAGE 4

* 4.3.1, Delete Scoop Assembly, Lower RAD Panel Assembly, RAD Packing Container in their entirety.

* TABLE I: Delete Scoop Assembly, Lower RAD Panel Assembly, RAD Packing Container in their entirety.

PAGE 7

* TABLE I: Under Complete RAD Assembly, delete RAD Integrity in its entirety.

PAGE 8

* TABLE I: Under RAD Container Assembly, add "RAD Integrity 50 3.4.1 4.5.1".

* Delete Thermal Shock in its entirety.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:25Z
Check the source to verify that this is the current version before use.

PAGE 10

4.4.2.1, Add Major 106, "106 Maximum diameter of radius blend .40% 3.4 Gage".

PAGE 11

* 4.4.2.2, Major 101 add "(a)" next to .40%.

* Add Note to note block "(a). Special Inspection Level S-4 of MIL-STD-105."

PAGE 12

* 4.4.2.3, Delete Majors 102 and 104 in their entirety.

* Add "(a)" next to .40% in four places.

* Delete Minor 201 in its entirety and substitute "201 Major diameter .40%(a) 3.4 Gage"

* Delete Minor 202 in its entirety and substitute "202 Flatness .40% 3.4 Gage"

* Delete Minor 203 in its entirety.

* Add note to note block "(a). Special Inspection Level S-4 of MIL-STD-105."

PAGE 13

* 4.4.2.4, Add "(a)" next to .40% and .65% in two places and five places, respectively.

Add note to note block "(a). Special Inspection Level S-4 of MIL-STD-105."

PAGE 14

* 4.4.2.5, Add Major 102, "102 Rivets improper .40% 3.4 Gage".

* Delete "100%" and substitute ".40%".

PAGE 15

* 4.4.2.6, Add "(a)" next to .65% in four places.

* Add note to note block "(a). Five units per cutting die per 60,000 pieces."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:25Z
Check the source to verify that this is the current version before use.

PAGE 16

* 4.4.2.7, Add "(a)" next to .65% in three places.

* Add note to note block "(a). Five units per cutting die per 60,000 pieces."

PAGE 17

* 4.4.2.8, Delete in its entirety.

PAGE 18

* 4.4.2.9, Delete in its entirety.

PAGE 19

* 4.4.2.10, Add "(a)" next to .65% in six places.

* Add note to note block "(a). Five units per cutting die per 20,000 pieces."

PAGE 20

* 4.4.2.11, Delete Majors 101, 102, 103, 104, 105, 106 and 112 in their entirety.

* Add Major 113, "113 Presence of RAD panel reinforcing .40% 3.4 Visual".

* Add "(a)" next to .40% in five places.

* Add Note to Note block "(a). Special Inspection Level S-4 of MIL-STD-105."

PAGE 21

* 4.4.2.12, Delete in its entirety.

PAGE 22

* 4.4.2.13, Delete Critical 1 in its entirety.

* Major 101, delete "Visual" and substitute "Visual/Gage".

* Add Major 102 "102 RAD Integrity 32 3.4.1 4.5.1"

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:25Z
Check the source to verify that this is the currentversion before use.

4.5.1, Delete "RAD Assembly Complete shall be brought to....to allow for internal pressure measurements" and substitute "The RAD shall be removed from its container and inflated to a peak pressure within a duration interval not to exceed 14.0 milliseconds by an inert gas which is exhausted by means of a solenoid valve from a lecture bottle (having an internal volume 27.5 ± 0.5 cu. in.) pressurized to 490 + 10 psi, ~~as described by drawing 600245~~. In preparation for the test, it will be required to machine the center of the upper RAD plate (P/N 933813) of the RAD Assembly Complete to accommodate the inflation input orifice (a 1/8 inch pipe fitting is normally sufficient). Pressure measurement of the lecture bottle shall be accomplished by means of suitable gage placed in the pneumatic circuit so as to allow direct pressure. Measurement of the inflation interval of the RAD Assembly Complete shall be accomplished by means of a suitable piezoelectric transducer which is positioned along the axis of one lobe of the lower RAD panel (P/N 9345150), a distance of 2.0 + 0.5 inches from center, and coupled to a suitable oscilloscope with trace storage capacity."

* In the first sentence of the first paragraph, delete "A sample consisting of 0.1% of a production lot" and substitute "A sample of 32 units per production lot".

* 4.5.2, Delete in its entirety.

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1330-A336)

Source: https://assist.dla.mil -- Downloaded: 202640-23T03:25Z
Check the source to verify that this is the current version before use.