MIL-F-48057B (AR)
AMENDMENT 3
2 September 1983
SUPERSEDING
AMENDMENT 2
1 September 1983

MILITARY SPECIFICATION

FUZE, ROCKET, PIBD, M438
SUB-ASSEMBLY WITH DETONATOR

This Amendment forms a part of Military Specification MIL-F-48057B (AR), dated 17 February 1981, and is approved for use by the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 5

3.4.2.2: Delete "ambient temperature" and substitute "any temperature between -40°F and +160°F".

PAGE 6

3.8.8: Delete in its entirety.

PAGE 8

4.3.1: Delete "11706267" and substitute "8883713" in two places.
Delete "11008392" and substitute "8883718" in two places.
Delete "11001692" and substitute "8883710" in two places.
Delete "11008394" and substitute "9260774".
Delete "11830063" and substitute "9260774".
Delete "11001687" and substitute "8883703" in two places.
Delete "11008395" and substitute "9260804" in two places.
Delete "11001689" and substitute "8883700" in two places.
Delete item "Outer Plate Assembly" in its entirety.
Delete "11706262" and substitute "9260776" in two places.
Delete "10" from Quantity for Escapement Assembly and Inner Plate Assembly and substitute "20".
Delete "80" from Quantity for Safety & Arming Device and substitute "120".

PAGE 9

4.3.1: Delete "25" from Quantity for Magnetic Impulse Generator Assembly, and substitute "30". Delete "32" from Sub-Assy w/Detonator and Fuze Components, and substitute "54".

Add: "Stud, Spring 8883721 8883721 10".

FSC 1340

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:11Z
Check the source to verify that this is the current version before use.

PAGE 11

TABLE I: Delete "S&A Position Check" in its entirety. In No. of Sample Units, delete "16" and substitute "27" in two places.

PAGE 14

TABLE 1: Delete "Dwg. 11001692" and substitute "Dwg. 8883710".
Delete "Dwg. 11001687" and substitute "Dwg. 8883703".
Delete "Dwg. 11001689" and substitute "Dwg. 8883700".
Delete "Dwg. 11008394 or 11830063" and substitute "Dwg. 9260774".
Delete "Push Off Test" and substitute "Load Test", 3 Places.
Delete "10" and substitute "20" for Escapement Assembly, 2 places.

PAGE 15

TABLE 1: Delete "Dwg. 11008395" and substitute "Dwg. 9260804".
Delete "10" and substitute "20", 2 places.

PAGE 16

TABLE 1: Delete "Examination and Test" for Outer Plate Assembly (Dwg. 11008400) in its entirety.

Delete "Dwg. 11706262" and substitute "Dwg. 9260776".
Delete "Shaft Torque Test" and "Pallet Lever Push Off Test" in their entirety and substitute the following three tests:

"Load Test of Lever Shaft	10	3.2	4.5.5.13"
"Load Test of Lever Pallet	10	3.2	4.5.5.8"
"Torque Test of Lever Shaft	10	3.2	4.5.5.7"

Delete "Non-Arm Test" in its entirety.

In No. of Sample Units, Delete "80" and substitute "120" in four places; Delete "40" and substitute "60(a,b)" in two places.

In Arm Time (27 g's) Test, Delete "4.5.11.3" and substitute "4.5.11.4".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:11Z
Check the source to verify that this is the current version before use.

In Arm Time (40 g's) Test, Delete "4.5.11.4" and substitute "4.5.11.5".

In Non-Arming Test, Delete "4.5.11.3" and substitute "4.5.11.2.1 or 4.5.11.2.2".

Add: Notes "a. 20 at 70°F ± 5°F; 20 at -40°F ± 5°F, 20 at 160°F ± 5°F" and "b: Temperature conditioning shall be 4 hours minimum, and each S&A shall be tested within 3 minutes of removal from extreme temperatures. Be advised that removing the S&A from the cold temperature environment prior to performing the centrifuge test may cause frost to form on the metal parts. This may have an effect on the test results due to attenuation of the acoustic signal of the arming mechanism, thus making it difficult to distinguish the arm signal from background noise. The contractor shall take appropriate action to alleviate this potential problem. One effective method has been to seal each S&A in a plastic bag prior to temperature conditioning. Bagged S&A's are then subjected to the centrifuge test. Another method has been to house the centrifuge inside the temperature conditioning chamber. S&A's are then tested inside the temperature conditioning chamber."

PAGE 18

TABLE 1: In No. of Sample Units, Delete "25" and substitute "30" in three places.

Delete "Dwg. 11706267" and substitute "Dwg. 8883713".
Delete "Dwg. 11008392" and substitute "Dwg. 8883718".
Add "Stud Spring, (Dwg. 8883721) Examination for Defects 10 3.2 4.4.2.24".

PAGE 25

4.4.2.6: Delete "Critical 3" in its entirety. Add "(Type I Only)" to Major 105 Examination.

PAGE 26

4.4.2.7: In No. of Sample Units, Delete "16" and substitute "32" in two places.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:11Z
Check the source to verify that this is the current version before use.

PAGE 27

4.4.2.8: Delete "11706267" and substitute "8883713" in two places.
Delete "11008394" and substitute "9260774".
Delete "11830063" and substitute "9260774".

PAGE 36

4.4.2.17: Delete "11001692" and substitute "8883710" in two places.
Delete "11008394" and substitute "9260774".
Delete "11830063" and substitute "9260774".
Delete Critical 1 in its entirety and substitute Critical 1 and Critical 2: "1 Maximum gap between gear and pinion 100% 3.2 Gage" and "2 Load test of excapement gear and pinion assembly 100% 3.2 4.5.5.6".

PAGE 37

4.4.2.18: Delete "11001687" and substitute "8883703" in two places.
Delete "11008394" and substitute "9260774".
Delete "11830063" and substitute "9260774".
Delete Critical 1 in its entirety and substitute Criticals 1 and 2:

"1	Maximum gap between gear and pinion	100%	3.2	Gage"
"2	Load test of No. 1 gear and pinion Assembly	100%	3.2	4.5.5.4"

PAGE 38

4.4.2.19: Delete "11001689" and substitute "8883700" in two places.
Delete "11008394" and substitute "9260774".
Delete "11830063" and substitute "9260774".
Delete Critical 1 in its entirety and substitute Criticals 1 and 2:

"1	Maximum gap between gear and pinion	100%	3.2	Gage"
"2	Load test of No. 2 gear and pinion Assembly	100%	3.2	4.5.5.5"

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:11Z
Check the source to verify that this is the current version before use.

PAGE 39

4.4.2.20: Delete "11706262" and substitute "9260776" in two places.
Delete "11008394" and substitute "9260774".
Delete "11830063" and substitute "9260774".
Delete Critical 1 in its entirety and substitute Criticals 1, 2 and 3:

"1	Maximum gap between lever and shaft	100%	3.2	Gage"
"2	Load test of lever shaft	100%	3.2	4.5.5.13"
"3	Load test of lever pallet	100%	3.2	4.5.5.8"

Delete "None Defined" and add Major 101:

"101	Torque test of lever shaft	100%	3.2	4.5.5.7".

PAGE 41

4.4.2.22: Delete "11008394" and substitute "9260774".
Delete "11830063" and substitute "9260774".

PAGE 42

4.4.2.23: Delete "11008395" and substitute "9260804" in two places.
Delete "11008394" and substitute "9260774".
Delete "11830063" and substitute "9260774".

PAGE 43

4.4.2.24: Delete in its entirety and substitute included Page 6 (Page 43).

PAGE 44

4.4.2.25: Delete Majors "107" and "109" in their entirety.

Major 110, Delete "4.5.11.4" and substitute "4.5.11.5".

Major 111, Delete "4.5.11.3" and substitute "4.5.11.4".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:11Z
Check the source to verify that this is the current version before use.

Quality Conformance Inspection

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8883721
4.4.2.24	Stud, Spring				NEXT HIGHER ASSEMBLY 11008389
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
Major					
101	Diameter of stud, min.		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.12	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:11Z
Check the source to verify that this is the current version before use.

PAGE 46

4.4.2.27: Major 101, Delete "(a)"; delete "4.5.11.3" and substitute "4.5.11.2.1 or 4.5.11.2.2".

Add "Major 103 Release pin improperly assembled (Type II Only) 100% 3.2 Visual".

PAGE 48

* 4.4.2.29: Delete Major 101 in its entirety. Major 102: Delete "14.5.12.2" and substitute "4.5.12.2".

PAGE 49

4.4.2.30: In No. of Sample Units, Delete "15" and substitute "30".

PAGE 50

4.4.2.31: Delete "11008392" and substitute "8883718" in two places.

PAGE 51

4.4.4.1.1: Delete "S&A position check" and substitute "Non-Arming Test".

4.4.4.1.2: Delete "4.5.10".

PAGE 52

4.4.4.2: Under VERIFIED INSPECTION, Delete "4.5.10 - S&A Position Check" and substitute "4.5.11.2 - Non-Arming Test".

PAGE 53

4.5.5.1: Delete "Apply a" and substitute "Apply the required". Delete "resistive" and substitute "required".

4.5.5.2: Delete "Apply a" and substitute "Apply the required". Delete "resistive" and substitute "required".

4.5.5.3: Delete "Apply a" and substitute "Apply the required". Delete "resistive" and substitute "required".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:11Z
Check the source to verify that this is the current version before use.

4.5.5.4: Delete in its entirety and substitute:

"4.5.5.4 Load test of No. 1 gear and pinion assembly. Apply the required axial load perpendicular to the No. 1 gear and in such a direction as to test the assembly of the No. 1 gear and pinion. The required force shall act against the No. 1 gear. Upon removal of the required force, the maximum permissible gap shall be inspected for compliance with the drawing requirement. Any No. 1 gear and pinion assembly that fails the requirement shall be classed defective and removed from the lot."

4.5.5.5: Delete in its entirety and substitute:

"4.5.5.5 Load test of No. 2 gear and pinion assembly. Apply the required axial load perpendicular to the No. 2 gear in such a direction as to test the assembly of the No. 2 gear and pinion. The required force shall act against the No. 2 gear. Upon removal of the required force, the maximum permissible gap shall be inspected for compliance with the drawing requirement. Any No. 2 gear and pinion assembly that fails the requirement shall be classed defective and removed from the lot."

4.5.5.6: Delete in its entirety and substitute:

"4.5.5.6 Load test of escapement gear and pinion assembly. Apply the required axial load perpendicular to the escapement gear and in such a direction as to test the assembly of the escapement gear and pinion. The required force shall act against the escapement gear. Upon removal of the required force, the maximum permissible gap shall be inspected for compliance with the drawing requirement. Any escapement gear and pinion assembly that fails the requirement shall be classed defective and removed from the lot."

4.5.5.7: Delete in its entirety and substitute:

"4.5.5.7 Torque test of lever shaft. A torque shall be applied between the lever and the lever shaft. Any lever shaft that does not comply with the drawing requirement shall be classed defective and removed from the lot."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:11Z
Check the source to verify that this is the current version before use.

4.5.5.8: Delete in its entirety and substitute:

"4.5.5.8 Load test of lever pallet. Apply the required axial load perpendicular to the lever and in such a direction as to test the assembly of the lever and the lever pallet. The required force shall act against the lever. Upon removal of the required force, the height of the lever pallet above the lever shall be inspected for compliance with the drawing requirement. Any lever pallet that fails the requirement shall be classed defective and removed from the lot."

4.5.5.9: Delete in its entirety and substitute:

"4.5.5.9 Load test of pillars. Apply the required axial load perpendicular to the inner plate and in such a direction as to test the assembly of the pillars to the inner plate and outer plate. The required force shall act against the inner plate. Any pillars that do not comply with the drawing requirement shall be classed defective."

4.5.5.10: Delete in its entirety and substitute:

"4.5.5.10 Load test of bridge rivet. Apply the required load perpendicular to the inner plate and into the bridge rivet from the side opposite the bridge. The required force shall act against the inner plate. Any bridge rivet that does not comply with the drawing requirement shall be classed defective."

4.5.5.11: Delete "Apply a" and substitute "Apply the required". Delete "resistive" and substitute "required".

4.5.5.12: Delete "Apply a" and substitute "Apply the required". Delete "resistive" and substitute "required".

Add 4.5.5.13:

"4.5.5.13 Load test of lever shaft. Apply the required axial load perpendicular to the lever and in such a direction as to test the assembly of the lever and shaft. The required force shall act against the lever. Upon removal of the required force, the maximum permissible gap shall be inspected for compliance with the drawing requirement. Any lever shaft that fails the requirement shall be classed defective and removed from the lot."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:11Z
Check the source to verify that this is the current version before use.

PAGE 55

4.5.10: Delete in its entirety.

PAGE 56

4.5.10: Delete paragraph starting with "Defect standards ..." from para 4.5.10 and add it to para 4.5.11.2.1.

4.5.11.1: Delete last four lines and substitute "specified "g" limits for the arming tests are reached. This test equipment, if housed within a temperature conditioning chamber, shall be capable of operation between -40°F and +160°F with a tolerance of ± 5°F. The acceleration tolerance shall be ± .10g. Time measuring equipment shall be accurate within ± 0.01 second."

4.5.11.2.1: Delete "containing a power supply striker and spring but no explosives" and substitute "completely assembled".

4.5.11.2.2: Delete in its entirety, except for title, and substitute "The device completely assembled shall be placed in the centrifuge and tested at 12g for five seconds. The device shall be tested in a spring-loaded fixture which simulates the MIG spring. The device shall meet the requirements of 3.3.1. Any S&A that fails to meet the requirement shall be classed defective."

4.5.11.3: Delete in its entirety.

4.5.11.4: Delete "4.5.11.2.1 or 4.5.11.2.2 except that the" and substitute "4.5.11.1. The".

PAGE 57

4.5.11.5: Delete "4.5.11.2.1 or 4.5.11.2.2 except that the" and substitute "4.5.11.1. The".

Add "and removed from the lot" to last sentence.

4.5.12.1: Delete second line and substitute "required in 3.4.2.3. Following helicopter vibration, the assemblies shall be temperature conditioned for a minimum of four hours, 15 at -40°F ± 5°F and 15 at +160°F ± 5°F. They shall then be assem-".

Add "One defective shall be cause for lot rejection."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:11Z
Check the source to verify that this is the current version before use.

PAGE 58

4.5.17: Delete in its entirety, except for title, and substitute "Following the helicopter vibration of 4.5.15, the units shall be temperature conditioned for a minimum of four hours, 24 at -40°F ± 5°F and 24 at +160°F ± 5°F. They shall then be tested as in 4.5.11.1. Arming time shall start upon setback weight release and shall stop at rotor detent. The arming time shall be recorded to the nearest millisecond using an acoustic pick-up which feeds the arming cycle noise signal to the recorder."

TABLE II: For "Over Max", delete "0" and "1" and substitute "1" and "2", respectively.

For "Firing", delete "0" and "1" and substitute "1" and "2", respectively.

Add "Note: If one reject occurs, the lot shall be accepted. If three or more rejects occur, the lot shall be rejected. If one reject occurs in both arming time over max and firing, a second sample of 48 subassemblies shall be tested. If the combined number of rejects in both samples is three or more, the lot shall be rejected."

PAGE 59

4.5.18: Delete "32" and substitute "64".

Delete the last four sentences and substitute "If three defects are found, the lot shall be accepted. If four or more fuzes fail to comply with the requirement specified, the lot shall be rejected."

6.3: Delete "US Army Armament Research and Development Command, ATTN: DRDAR-QAF-I" and substitute "Armament Research and Development Center, US Army Armament, Munitions and Chemical Command, ATTN: DRSMC-QAF-I(D)".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:11Z
Check the source to verify that this is the current version before use.

*The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1340-A669)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:11Z
Check the source to verify that this is the current version before use.