MILITARY SPECIFICATION

FUZES, ROCKET, M423, M427 and M433 LOADING, ASSEMBLING AND PACKING

This amendment forms a part of Military Specification MIL-F-50253A (AR), dated 10 November 1978, and is approved for use by the US Army Armament Research and Development Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1: PRODUCT AND PACKAGE DRAWINGS: Add "9260925 - Umbilical Test Set" Delete "9260701 - Fuze, Rocket, M433 with Booster and Booster Lead" and substitute "9260701 - Fuze, Rocket, M433".

PAGE 4

4.3.1: Delete "Fuze, Rocket, M433 with Booster and Booster Lead" and substitute "Fuze, Rocket, M433".

PAGE 5

* TABLE I: Delete "with Booster and Booster Lead".

PAGE 6

* TABLE I: Delete "with Booster and Booster Lead", two places.

PAGE 7

4.4.1: Delete "a. One metal parts lot from one manufacturer" and substitute "Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, each inspection lot of boostered fuzes shall contain:

"a. Fuzes bearing the same metal parts lot interfix number from one metal parts manufacturer"

FSC 1340

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:18Z
Check the source to verify that this is the current version before use.

PAGE 9

4.4.2.2, Major 105: Delete "0.40%" and substitute "100%".

PAGE 10

* 4.5.2: Delete in its entirety and substitute: "Umbilical Continuity Test.-Each fuze umbilical shall be connected to an Umbilical Test Set(9260925). Each umbilical must meet the acceptance requirements. Any umbilical that does not meet the acceptance requirements shall be classed as defective and removed from the lot.

PAGE 11

4.5.3.2, line 8: Delete "functional" and substitute "functioned".

4.5.3.3: Delete in its entirety and substitute: "M433 Fuze.-Live boosters will be assembled into a government-approved simulated M433 fuze, an M423 Fuze Assembly or an M427 Fuze Assembly. When a simulated M433 fuze is used, the test fixture must simulate an M433 explosive train in the armed condition. Functional (electrical) energy of not less than 750 ergs shall be applied to the detonator electrical contacts in the simulated test fixture. High order detonation shall be determined by a 0.25 inch minimum dent in a cylindrical witness block (1.5 inch minimum height by 2.0 inch minimum diameter of 2011-T3 aluminum). When M423/427 Fuze Assemblies are used, the test procedure of 4.5.3.2 applies.

"WARNING: This test is dangerous and must be performed behind a suitable barricade."

PAGE 12

* 4.5.4.2, Line 10: Add after "needed.", "Rounds containing M433 Fuzes shall be set to the superquick mode with a government approved setter design that represents the helicopter setter system."

PAGE 13

6.3: Delete "DRDAR-QAR-I" and substitute "DRDAR-QAF-I".

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:18Z
Check the source to verify that this is the current version before use.

was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
ARMY-AR

Preparing activity
ARMY-AR

(Project 1340-A621)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:18Z
Check the source to verify that this is the current version before use.