MIL-P-60574B(MU)
AMENDMENT 1
17 March 1972

MILITARY SPECIFICATION

PROJECTILE, HEP-T, 105MM, M393A2
METAL PARTS

This amendment forms a part of Military Specification MIL-P-60574B(MU) dated 1 November 1971.

Para. 2.1 drawings, add: A8648732 - Eddy Current Inspection System.

Para. 3.6 Delete "a. Permanent deformation greater than .010 inches on either the body diameter or bourrelet diameter of the projectile."

Para. 4.3.2.2 Delete Majors 101, 102 and 103 in their entirety and substitute:

"101.	Runout of pitch diameter of large internal thread, with pitch diameter of external thread, including front face of shoulder and bottom of large internal thread cavity	Gage
102.	Runout of large outside diameter with pitch diameter of external thread, including front face of shoulder	Gage
103.	Runout of pitch diameter of small internal thread with pitch diameter of external thread, including front face of shoulder and rear face	Gage"

Delete MAJOR characteristic 121. in its entirety.

Para. 4.3.2.4 Delete MAJOR's 101 through 109 in their entirety and substitute:

"101.	Runout of cavity forward of base plug thread with bourrelets	Gage
102.	Runout of forward rotating band with bourrelets	Gage
103.	Runout of rear rotating band with bourrelets	Gage
104.	Runout of pitch diameter of base plug thread with bourrelets including rear face	Gage
105.	True position of large counterbore with pitch diameter of thread	Gage
106.	True position of small counterbore with large counterbore	Gage

FSC 1315

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:45Z
Check the source to verify that this is the current version before use.

107.	Flatness of rear face	Gage
108.	Perpendicularity of rear face with pitch diameter of thread	Gage"

Para. 4.3.2.5 Add MAJOR characteristic 108.

"108. Paint on rear face Visual"

Delete MINOR characteristic 204. in its entirety.

Add the following paragraphs 4.3.3.1.2.6 and 4.4.2.a:

"Para. 4.3.3.1.2.6 Eddy Current inspection.-Each finish machine base plug shall be inspected by the eddy current method using standards prescribed by drawing A8648732. Failure of the base plug to meet the standard will be cause for rejection of the base plug.

Para. 4.4.2.a Eddy Current inspection.-The procedure for performing the Eddy current test will be as prescribed by drawing A8648732. Eddy current standards shall be used at a minimum of every 4 hours. The standards shall be used at the start of each day's production and at intervals of not over 4 hours of continuous operation. The contractor shall also prepare a detailed written standard operating procedure to include the testing and calibration procedure which must be reviewed and approved by the responsible technical agency."

Para. 5.2.2 insert after the word packed "Level C".

Para. 5.3.2 Delete "in accordance with paragraph 3.4", insert "Level C in accordance with paragraph 3.7".

Custodian:

Army - MU

Preparing Activity:

Army - MU(FA)

Project No. 1315-A239

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:45Z
Check the source to verify that this is the current version before use.