MILITARY
SPECIFICATION

MIL-R-55217 (EL)
Amendment 1
30 July 1963

RECORDER-PROCESSOR-VIEWER, RADAR MAPPING RO-166( )/UP

1. Paragraph 2.1 Documents.- Add the following under STANDARDS, MILITARY:

"MIL-STD-150 Photographic Lenses "

2. Paragraph 3.5.1 Lenses.-

a. In line 2, replace "have" with "produce".

b. Add the following to the end of the paragraph:

"The lenses shall be in accordance with Standard MIL-STD-150, Type VI."

3. Paragraph 3.5.2 Data chamber.- Replace "two inch" with "one inch".

4. Paragraph 3.5.2.1 Lamps.- Replace "flash lamp" with "lamps".

5. Paragraph 3.6.1 Film drive.- Delete the second sentence in its entirety.

6. Paragraph 3.6.2 Sensitized material (film).- Add the following to the end of the paragraph:

"The film shall not be light struck from an external source. (See 4.8) "

7. Paragraph 3.6.2.1 Processing.- Replace the first sentence with the following:

"Film, which has been processed by the equipment and subsequently fixed and washed (see 3.6) shall have a H and D curve corresponding to typical curves for SO-261 film from conventional processing."

8. Paragraph 3.6.2.2 Fogging.- Replace "(see 4.8)" with "(see 4.11)".

FSC 5841

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:38Z
Check the source to verify that this is the current version before use.

9. Paragraph 3.6.2.3 Density.- Replace the paragraph with the following:

"3.6.2.3 Density.- A density range of 1.5 or higher shall result from a log exposure range of 2.0 when tested at +21°C, ambient, or higher. When tested at +5° C, the density range shall be 1.2 or higher. (See 4.11)"

10. Paragraph 3.6.3 Exposure to view distance.- Delete the entire paragraph.

11. Paragraph 3.6.6.2 Internal.- Replace "30°" with "25 degrees".

12. Paragraph 3.7.2 Viewing hood.- Add "in accordance with the model" after "viewing hood".

13. Paragraph 3.9 Weight.- Replace the paragraph with the following:

"3.9 Weight.- The weight of the equipment, without the viewing hood but including solution and film, shall not exceed 54 pounds."

14. Paragraph 4.7 Film drive.- In second sentence, replace "processed, fixed and washed" with "processed by the equipment and fixed and washed".

15. Paragraph 4.8 Fogging.-

a. Replace title with "Light leakage (see 3.6.2).- "

b. Add "for 4 minutes at +20° C" after "D-19 developer, or equal"

c. Replace the next to last sentence with the following:

"Examine the film for any evidence of light struck."

16. Paragraph 4.11.1(d): Replace "filtered developer" with "filtered monobath".

17. Paragraph 4.11.1(k): Add "3.6.2.2 Fogging" to the listing.

18. Paragraph 4.12 Processing endurance.- Add "at maximum film speed" after "operated".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:38Z
Check the source to verify that this is the current version before use.