

FED. SUP CLASS
5940





(E)

DASH NO.	COLOR CODE	A DIA MIN	A DIA MAX	B DIA MIN	B DIA MAX	MIL-C-22520/5 CRIMPING DIE DASH NO. (REF)	DIE CLOSURE
-101	NO COLOR	.098	.104	.121	.127	-33	B
-128	BLUE	.125	.131	.147	.155	-35	B
-149	PURPLE	.146	.152	.176	.182	-37	B
-156	YELLOW	.153	.159	.190	.196	-39	B
-175	BLUE	.172	.178	.212	.218	-41	B
-187	ORANGE	.184	.190	.224	.230	-43	B
-194	RED	.191	.197	.223	.229	-43	B
-199	NO COLOR	.196	.202	.232	.238	-43	B
-205	YELLOW	.202	.208	.242	.248	-19	B
-219	GREEN	.216	.222	.247	.253	-19	B
-225	PURPLE	.222	.228	.253	.259	-45	B
-232	ORANGE	.229	.235	.260	.266	-45	B
-261	YELLOW	.258	.264	.294	.300	-19	A
-275	NO COLOR	.272	.278	.303	.309	-43	A
-281	PURPLE	.278	.284	.328	.334	-41	A
-287	BLUE	.284	.290	.324	.330	-41	A
-297	GREEN	.294	.300	.332	.338	-41	A
-312	YELLOW	.309	.315	.359	.365	-39	A
-327	NO COLOR	.324	.330	.369	.375	-37	A
-348	ORANGE	.345	.351	.391	.397	-35	A
-359	PURPLE	.356	.362	.396	.402	-33	A
-375	YELLOW	.372	.378	.403	.409	-47	
-405	RED	.402	.408	.450	.456	-23	
-415	BLUE	.412	.418	.460	.466	-23	
-460	NO COLOR	.457	.463	.507	.513	-53	
-500	GREEN	.497	.503	.547	.553	-21	A

REPLACED BY TWO-PIECE COMBINATION (REF)	
MS21981 INNER FERRULE DASH NO.	MS21980 OUTER FERRULE DASH NO.
-058	-128, -149, -156
-063	-156, -175
-080	-156, -175, -187
-101	-187, -194, -199
-115	-199, -205, -219
-134	-225, -232, -261
-156	-232, -261, -275
-175, -187	-287, -297
-205, -219	-312, -327, -348

NOTES:

(E) 1. UNLESS SPECIFIED OTHERWISE, DIMENSIONS IN INCHES.
(E) 2. MS21980 OUTER FERRULES ARE USED WITH MS21981 INNER FERRULE AS AN UNINSULATED REPLACEMENT.
(E) 3. METRIC EQUIVALENTS (TO THE NEAREST .01 mm) ARE GIVEN FOR GENERAL INFORMATION ONLY AND ARE BASED UPON 1 INCH = 25.4 mm.

REQUIREMENTS:

1. MATERIAL: COPPER OR BRASS ALLOY, ROCKWELL F65 MAXIMUM
2. FINISH: TIN PLATED, PER MIL-T-10727, TYPE 1. COLOR CODE IN ACCORDANCE WITH TABLE.
3. REMOVE ALL BURRS AND SHARP EDGES. CHAMFER OR ROUNDED EDGES ACCEPTABLE.
4. MIL-C-22520/5 CRIMPING DIES SHALL BE USED WITH M22520/5-01 BASIC CRIMPING TOOL (MIL-C-22520/5).

FOR DESIGN FEATURE PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER ACQUISITION DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.

(E) REVISED AND REDRAWN

APPROVED 12 Oct 65 REVISED (A) 20 Jan 65 (B) 1 Jul 65 (C) 16 Sept 68 (D) 9 Jul 1973 (E) 13 Aug 82

User activities: Army - Navy - MC USAF -

Review activities: Army - EC Navy - USAF - 11, 17, 99

This military standard is approved for use by all Departments & Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P.A. NAVY - AS Other Cust USAF - 85 ARMY -	TITLE: FERRULES, OUTER, UNINSULATED, SHIELD TERMINATING, TYPE I TWO-PIECE, CLASS I, FOR SHIELDED CABLE	MILITARY STANDARD MS 21980
ACQUISITION SPECIFICATION MIL-F-21608	SUPERSEDES:	SHEET 1 OF 2

DD FORM 1 MAR 72 672-1 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE. Project No. 5940-0943 PLATE NO. 23088

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:43Z
Check the source to verify that this is the current version before use.

REVIEWER SYMBOLS
Army -
Navy - EC
USAF - 11, 17, 99

USER SYMBOLS
Army -
Navy - MC
USAF -

"Review/user information is current as of the date of this document. For future coordination of changes to this document, draft circulation should be based on the information in the current DODISS."

This military standard is approved for use by all Departments & Agencies of the Department of Defense. Selection for all new engineering and design applications and for reprocure use shall be made from this document.

(E)

INCHES	mm	INCHES	mm
.015	0.38	.272	6.91
.098	2.49	.278	7.06
.104	2.64	.284	7.21
.121	3.07	.290	7.37
.125	3.18	.294	7.47
.127	3.23	.300	7.62
.131	3.33	.303	7.70
.146	3.71	.309	7.35
.147	3.73	.315	8.00
.152	3.86	.324	8.23
.153	3.89	.328	8.33
.155	3.94	.330	8.38
.159	4.04	.332	8.43
.172	4.37	.334	8.48
.176	4.47	.338	8.59
.178	4.52	.345	8.76
.182	4.62	.351	8.92
.184	4.67	.356	9.04
.190	4.83	.359	9.12
.191	4.85	.362	9.19
.196	4.98	.365	9.27
.197	5.00	.369	9.37
.202	5.13	.372	9.45
.208	5.28	.375	9.53
.212	5.38	.378	9.60
.216	5.49	.396	10.06
.218	5.54	.397	10.08
.222	5.64	.402	10.21
.223	5.66	.403	10.24
.224	5.69	.408	10.36
.228	5.79	.409	10.39
.229	5.82	.412	10.46
.230	5.84	.418	10.62
.232	5.89	.450	11.43
.235	5.97	.456	11.58
.238	6.05	.457	11.61
.242	6.15	.460	11.68
.247	6.27	.463	11.76
.248	6.30	.466	11.84
.250	6.35	.497	12.62
.253	6.43	.503	12.78
.258	6.55	.507	12.88
.259	6.58	.513	13.03
.260	6.60	.547	13.89
.264	6.71	.553	14.05
.266	6.76		

P.A.
NAVY — AS
Other Cust
USAF - 85
ARMY -

PROCUREMENT SPECIFICATION
MIL-F-21608

TITLE
FERRULES, OUTER, UNINSULATED, SHIELD TERMINATING, TYPE I TWO-PIECE, CLASS I, FOR SHIELDED CABLE

SUPERSEDES:

MILITARY STANDARD
MS 21980

SHEET 2 OF 2

DD FORM 1 MAR 72 672-1 (Coordinated)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

Project No. 5940-0943

PLATE NO. 23000

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:43Z
Check the source to verify that this is the current version before use.