HHH-C-002134A(Army-GL)
September 26, 1985
SUPERSEDING
HHH-C-002134(Army-GL)
October 6, 1983

INTERIM FEDERAL SPECIFICATION

CARROTS, GLAZED, THERMOSTABILIZED, TRAY PACK

This interim Federal specification was developed by U.S. Army Natick Research and Development Center, Natick, MA 01760-5014, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

1. SCOPE

1.1 Scope. This specification covers glazed carrots, thermostabilized in tray pack cans.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

TT-C-495	- Coatings, Exterior, for Tinned Food Cans
PPP-B-636	- Boxes, Shipping, Fiberboard

(Activities outside the Federal Government may obtain copies of Federal specifications, standards, and commercial item descriptions as outlined under General Information in the Index of Federal Specifications, Standards and Commercial Item Descriptions. The Index, which includes cumulative bimonthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

FSC 8940

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:44Z
Check the source to verify that this is the current version before use.

(Single copies of this specification, other Federal specifications, and commercial item descriptions required by activities outside the Federal Government for bidding purposes are available without charge from General Services Administration Business Service Centers in Boston, MA; New York, NY; Philadelphia, PA; Washington, DC; Atlanta, GA; Chicago, IL; Kansas City, MO; Fort Worth, TX; Houston, TX; Denver, CO; San Francisco, CA; Los Angeles, CA; and Seattle, WA.

(Federal Government activities may obtain copies of Federal standardization documents, and the Index of Federal Specifications, Standards and Commercial Item Descriptions from established distribution points in their agencies.)

Military Specifications:

MIL-L-1497 - Labeling of Metal Cans for Subsistence Items
MIL-L-35078 - Loads, Unit: Preparation of Nonperishable
- Subsistence Items; General Specification for

Military Standards:

MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-900 - Bacterial Standards for Starches, Flours, Cereals, Alimentary Pastes, Dry Milks and Sugars Used in the Preparation of Thermostabilized Foods for the Armed Forces

(Copies of Military specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Laws and Regulations:

U.S. Department of Health and Human Services

Federal Food, Drug, and Cosmetic Act and Regulations Promulgated Thereunder (21 CFR parts 1-199)

(Applications for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

U.S. Department of Agriculture (USDA)

U.S. Standards for Condition of Food Containers

(Application for copies should be addressed to the Director, Market Research and Development Division, Agricultural Marketing Service, U.S. Department of Agriculture, Washington, DC 20250.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:44Z
Check the source to verify that this is the current version before use.

U.S. Standards for Grades of Butter

(Application for copies should be addressed to Director, Dairy Division, Agricultural Marketing Service, U.S. Department of Agriculture, Washington, DC 20250.)

U.S. Standards for Grades of Canned Carrots

Regulations Governing Inspection and Certification of Processed Fruits and Vegetables, Processed Products Thereof, and Certain Other Processed Food Products

(Application for copies should be addressed to the Chief, Processed Products Branch, Fruit and Vegetable Division, Agricultural Marketing Service, U.S. Department of Agriculture, Washington, DC 20250.)

2.2 Other publications. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

Association of Official Analytical Chemists (AOAC)

Official Methods of Analysis of the Association of Official Analytical Chemists

(Application for copies should be addressed to the Association of Official Analytical Chemists, 1111 North 19th Street, Suite 210, Arlington, VA 22209.)

Environmental Protection Agency (EPA)

National Interim Primary Drinking Water Regulations

(Application for copies should be addressed to the Office of Drinking Water WH550, Environmental Protection Agency, Washington, DC 20460.)

(Industrial association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 First article. When specified, a sample shall be subjected to first article inspection (see 4.3, 6.1, and 6.3).

3.2 Ingredients. All ingredients shall be clean, sound, wholesome, and free from foreign material, evidence of rodent and insect infestation, extraneous material, off-odors, off-flavors, and off-colors.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:44Z
Check the source to verify that this is the current version before use.

3.2.1 Carrots, fresh. The fresh carrots shall be a variety suitable for canning. The fresh carrots shall be well trimmed, firm, clean, of typical color, smooth, and well formed. They shall be free from secondary new top growth, soft rot and damage caused by freezing, growth cracks, sunburn, pithiness, woodiness, internal discoloration, oil spray, dry rot, other diseases, insects, or other means. The diameter of each carrot shall be not less than 3/4 inch or more than 1-1/4 inch and the length shall be not less than 5 inches.

3.2.2 Sugar, brown, light. The brown sugar shall be partially refined cane or beet sugar. It shall be light brown in color and shall have a sweet, molasses-like flavor.

3.2.3 Sugar, white, granulated. Sugar shall be white, refined, granulated, cane or beet sugar, or a combination thereof. Sugar shall meet the bacterial requirements of MIL-STD-900.

3.2.4 Butter, lightly salted. The lightly salted butter shall be U.S. Grade A or better as defined in the U.S. Standards for Grades of Butter.

3.2.5 Starch, waxy maize, modified, The starch shall be white, odorless, finely pulverized, modified waxy maize starch for use in canned foods. The modified starch shall demonstrate initial viscosity development in the temperature range of 140° to 170°F and a typical viscosity (be fully hydrated) at common retort temperatures. It shall resist breakdown at low pH, under sheer stress, and conditions of cold storage. The starch shall be bland with essentially no cereal or starch taste and shall comply with MIL-STD-900.

3.2.6 Juice, lemon. Lemon juice shall be prepared from the unfermented juice obtained from fresh sound mature and thoroughly cleaned fruit of one or more of the high acid varieties of the species Citrus limon (limonia). Such lemon juice may be canned or frozen, single strength or concentrated.

3.2.7 Salt. Salt shall be white, refined sodium chloride with or without anticaking agents. Iodized salt shall not be used.

3.2.8 Water. Water used for formulation, ice making, and washing shall conform to the National Interim Primary Drinking Water Regulations.

3.3 Preparation and processing.

3.3.1 Carrot preparation. The carrots shall be washed thoroughly to remove soil and foreign material, and sorted to remove any which are diseased or otherwise damaged. The sound stock shall be peeled and trimmed to remove discolored, damaged, or undesirable portions. The peeled carrots shall be cut transversely to the longitudinal axis, into nominal 1-1/2 inch chunks. The carrot chunks shall be blanched in 190°F water for 3 minutes if blanching has not been accomplished during the peeling operation. The blanched carrots shall be immediately cooled in cold water before canning.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:44Z
Check the source to verify that this is the current version before use.

3.3.2 Syrup preparation. The syrup shall be formulated and prepared as follows:

Ingredient	Percent by weight
Water	50.64
Sugar, light brown	25.86
Sugar, granulated	6.80
Butter	10.00
Starch, waxy maize, modified	5.00
Lemon juice	0.85
Salt	0.85

Approximately 80 percent of the water shall be combined with the sugars, butter, lemon juice, and salt in the processing kettle and heated to approximately 140 to 145°F. A starch slurry shall be prepared using the remaining cold water and the starch. The starch slurry shall be added slowly with constant agitation to the sugar mixture and the final mixture heated to 185 to 190°F and held for approximately 5 minutes. Prior to filling, the volume of the final mixture shall be adjusted with water to compensate for evaporation loss. Each batch of prepared syrup shall be completely filled into the tray pack cans within 1 hour following syrup preparation.

3.4 Tray pack filling and sealing. Each tray pack can shall be filled with product so as to conform to the following requirements:

a. Sufficient weight of cut blanched carrots to meet the finished product requirements of 3.6 shall be placed in each tray pack can (see 5.1.1) and the can immediately filled with syrup to not less than 110 ounces of product.

b. The temperature of the syrup at the time of filling shall be not less than 190°F or not greater than 200°F.

c. The cans shall be hermetically sealed with a minimum of 10 inches (Hg) vacuum immediately after filling.

d. The tray pack cans shall be in the retort process within 2 hours after sealing.

3.5 Tray pack thermoprocessing. The filled and sealed tray pack cans shall be thermostabilized by retorting at 250°F or below until a sterilization value (F_o) of not less than 6.0 has been achieved.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:44Z
Check the source to verify that this is the current version before use.

3.6 Finished product requirements. The finished product shall comply with the following requirements:

a. There shall be for foreign material, such as but not limited to dirt, insects, insect parts, hair, wood, paper, paint, glass, or metal.

b. There shall be no foreign odor or flavor, such as but not limited to burnt, scorched, stale, sour, rancid, musty, or moldy.

c. There shall be no color foreign to the product.

d. The salt content shall be not greater than 1.0 percent.

e. The average net weight shall be not less than 110 ounces.

f. No individual can shall contain less than 108 ounces.

g. No individual can shall contain more than 66 ounces drained weight of carrots.

h. No individual can shall contain less than 56 ounces drained weight of carrots.

i. Carrots shall possess a sweet, slightly tart cooked flavor.

j. The texture of the carrots shall be firm but not hard, mushy, or fibrous.

k. The syrup shall be moderately thick, tan-yellow, and translucent and shall not be lumpy or watery.

l. Product shall not exhibit evidence of excessive heating (materially darkened or scorched).

m. The aggregate of all defective units shall not exceed 15.0 percent of all units.

n. The blemished and seriously blemished units shall not exceed 7.5 percent of all units.

o. The seriously blemished units shall not exceed 1.0 percent of all units.

3.6.1 Palatability. The product shall be equal to or better than the preproduction sample (see 6.1) in palatability and overall appearance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:44Z
Check the source to verify that this is the current version before use.

3.7 Plant qualification. The product shall be prepared, processed, and packaged in establishments meeting the requirements of Title 21, Code of Federal Regulations, Part 110, Current Good Manufacturing Practice in Manufacturing, Processing, Packaging or Holding of Human Foods, and the plant sanitation requirements of the appropriate Government inspection agency.

3.9 Federal Food, Drug, and Cosmetic Act. All deliveries shall conform in every respect to the provisions of the Federal Food, Drug, and Cosmetic Act, and regulations promulgated thereunder.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor's responsibility. Inspection and acceptance by the USDA shall not relieve the contractor of obligation and responsibility to deliver a product complying with all requirements of this specification. The contractor shall assure product compliance prior to submitting the product to the USDA for any inspection.

4.2 Inspection and certification. Product acceptability shall be determined by the USDA. The USDA will determine the degree of supervision necessary to assure compliance with the requirements of this specification.

4.3 First article inspection. When a first article is required (see 6.1), it shall be inspected in accordance with the quality assurance provisions of this specification and evaluated for overall appearance and palatability. Any failure to conform to the quality assurance provisions or any appearance or palatability failure shall be cause for rejection of the first article.

4.4 Component and material inspection. Components and materials shall be inspected in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or other applicable purchase document.

4.4.1 Ingredient and component examination. Conformance of ingredients and components to identity, condition and other requirements specified in 3.2 shall be certified by the ingredient supplier or ingredient manufacturer, or compliance be evident by examination of pertinent labels, markings, U.S. Grade certificates, certificates of analysis, or other such valid documents acceptable to the inspection agency. In addition, prior to use, each ingredient shall be examined organoleptically, as necessary, to determine conformance to the condition requirements. Any nonconformance to an identity, condition, or other requirement shall be cause for rejection of the ingredient or component lot or of any involved product.

4.5 In-process examination. In-process examination shall be performed to determine conformance to the preparation, processing, can interior coating, filling, sealing, and packing requirements. Any nonconformance revealed by

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:44Z
Check the source to verify that this is the current version before use.

actual examination or by review of records of time, temperature, and formulation or of other valid documents shall be cause for rejection of the involved product.

4.6 Tray pack inspection. The inspection lot shall include only tray packs produced in one workshift. The USDA reserves the right to separate the inspection lot into smaller inspection lots.

4.6.1 Net weight inspection. Randomly select 30 filled and sealed tray pack cans from the inspection lot and weigh separately. Subtract the average tare weight (determined by randomly selecting and weighing 30 empty tray pack cans and lids and dividing the total weight by 30) from the weight of each tray pack in the sample. The results shall be reported to the nearest 1 ounce. If the average net weight is less than 110 ounces or if the net weight of any individual can is less than 108 ounces, the lot shall be rejected.

4.6.2 Product inspection. The sample size shall be as indicated by the double sampling plan specified in table I. The tray pack cans shall be selected at random from the lot. The tray pack cans shall be heated at least 20 minutes in 200°F water, opened, and inspected for the defects listed in table II.

TABLE I. Double sampling plan for product inspection. 1/

Lot size (cans)	Sample size (No. of cans)	Cumulative sample	Acceptance number	Rejection number
0-3200	8	--	0	2
	8	16	1	2
3201-35000	13	--	0	3
	13	26	3	4

1/ a. If no defects are found in the first sample, the lot shall be accepted.

b. If the number of defects found in the first sample equals or exceeds the rejection number, the lot shall be rejected.

c. If the number of defects found in the first sample exceeds the acceptance number but is less than the rejection number, the second sample shall be inspected. Defects found in the first and second samples shall be combined and if the number of defects in the cumulative sample equals or exceeds the rejection number, the lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:44Z
Check the source to verify that this is the current version before use.

TABLE II. Product inspection 1/ 2/

Category	Defect
Major	
154	Drained weight of carrots in a can is more than 66 ounces. 3/
155	Drained weight of carrots in a can is less than 56 ounces. 3/
156	Carrots do not possess a sweet, slightly tart cooked flavor.
157	Carrots hard, mushy, or fibrous.
158	Syrup not moderately thick.
159	Syrup not tan-yellow in color.,
160	Syrup not translucent.
161	Syrup lumpy.
162	Product exhibits evidence of excessive heating (is materially darkened or scorched).
163	The aggregate of all defective units (carrots) exceeds 15.0 percent of all units. 4/
164	The blemished and seriously blemished units (carrots) exceeds 7.5 percent of all units. 4/
165	The seriously blemished units (carrots) exceeds 1.0 percent of all units. 4/

1/ The presence of foreign material (e.g., glass, dirt, insect parts, hair, wood, metal, etc.), foreign odor or flavor (e.g., burnt, scorched, moldy, rancid, sour, stale, etc.) or foreign color shall be cause for rejection of the lot.

2/ Product not equal to or better than the approved preproduction sample in palatability and overall appearance shall be cause for rejection of the lot. (This comparison shall be performed only when deemed necessary by an AMS agent.)

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:44Z
Check the source to verify that this is the current version before use.

3/ Drained weight shall be determined by heating closed container of product in 200°F water for approximately 20 minutes, pouring off free sauce and then pouring remaining contents into a flat bottom container. A minimum of three times the tray pack can's volume of 190° to 212°F water shall be added to the container so as to cover the contents. The contents and water shall be agitated so as to remove sauce without breaking up the carrot pieces. The contents shall then be poured into a U.S. Standard 1/4-inch sieve in a manner that will distribute the product over the sieve without breaking the carrot pieces. Sieve area shall be such that the distributed product does not completely cover all the openings of the sieve. The sieve shall be tilted at an approximate 45° angle and allowed to drain for 2 minutes before determining the drained weight by subtracting the sieve tare weight from the gross weight. The drained weights shall be reported to the nearest 1 ounce.

4/ The definitions for defective units shall be in accordance with the U.S. Standards for Grades of Canned Carrots.

4.6.3 Salt content testing. Nine tray packs shall be selected from the lot and distributed as follows:

- three for laboratory analysis
- three for submission to the contractor
- three for retention by the AMS agent as a reserve sample.

The three tray packs for laboratory analysis shall be individually tested for salt content in accordance with the Official Methods of Analysis of the Association of Official Analytical Chemists, except that preparation of the samples shall be as follows. The cans shall be opened and the entire contents of each can shall be separately blended in a Warning blender or equivalent. The lot shall be rejected if the salt content in any individual tray pack is greater than 1.0 percent. Results shall be reported to the nearest 0.1 percent. Analysis of reserve samples at the request of the contractor shall not be permitted unless the original laboratory analysis indicated that the involved lot will be rejected because of noncompliance with the salt content requirement. When the reserve sample is analyzed, the analyses for salt shall be made and will be considered final. Unused reserve samples shall be returned to the contractor for inclusion in subsequent lots.

4.7 Can condition examination. Examination of filled and sealed tray pack cans shall be in accordance with the United States Standards for Condition of Food Containers, except that inspection for labeling shall be in accordance with MIL-L-1497 (see 5.4).

4.8 Shipping container examination. Shipping containers shall be examined for defects in assembly, closure, and reinforcement (when applicable) in accordance with the appendix of PPP-B-636. In addition, the following defects shall be classified as follows: Major: National stock number, item description, contract number, or date of pack markings missing, incorrect, or

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:44Z
Check the source to verify that this is the current version before use.

illegible; Minor: (1) Other required markings missing, incorrect or illegible; (2) Interior packing with fiberboard liner or pads not as specified; (3) Reinforcement with nonmetallic strapping or tape is not used. (4) Height of box liner less than inside depth dimension of box by more than 1/8 inch or extends above top edge of box; (5) Length or width of pads less than box dimensions by more than 1/8 inch; (6) Arrangement or number of cans not as specified.

4.9 Unit load inspection. Inspection of unit loads shall be in accordance with the quality assurance provisions of MIL-L-35078.

5. PREPARATION FOR DELIVERY

5.1 Packaging. The product shall be packaged in accordance with level A or C as specified (see 6.1).

5.1.1 Level A. A size 1001 by 1206 by 200 tray pack can shall be filled with 110 ounces of food product, sealed, and thermoprocessed as specified in 3.4, 3.5 and 3.6. The base plate of the can shall be electrolytic chromium-plated steel and shall be of sufficient temper to protect the product during shipment and storage. The base plate weight of the body and end of each can shall be 90 pounds per base box. The entire inside area of the can shall be coated. Scratches or fractures shall not penetrate through the interior can coating. The interior can coating shall not peel or blister when in contact with the product. The interior can coating shall neither affect nor be affected by the packaged product. A certificate of conformance shall be furnished to certify the compliance with the interior can coating requirements. The can shall be coated over all on the outside with a coating conforming to type I or TT-C-495.

5.1.2 Level C. The product shall be packaged as specified in 5.1.1, except that the cans with commercial exterior coating will be acceptable.

5.2 Packing. The product shall be packed in accordance with level A, B or C as specified (see 6.1).

5.2.1 Level A packing. Four cans of product, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard box, constructed, and closed in accordance with style RSC-L, grade V2s of PPP-B-636. The cans shall be packed flat, four in depth within the box. The inside of each box shall be provided with a box liner and five fiberboard pads. The height of the box liner shall be equal to the full inside depth of the box (+0 inch, -1/8 inch). The pads shall be not less than 1/8 inch of the full length and width dimensions of the box and shall be fabricated of grade V3c fiberboard. The pads shall be placed between the cans and on the top and bottom of the stacked cans. Each fiberboard box shall be reinforced with nonmetallic strapping or pressure-sensitive adhesive filament reinforced tape in accordance with the appendix of

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:44Z
Check the source to verify that this is the current version before use.

PPP-B-636. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.1). Strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.2.2 Level B packing. Four cans of product, packaged as specified in 5.1, shall be packed as specified in 5.2.1, except the box shall be constructed of grade V3c or V4s fiberboard.

5.2.3 Level C packing. Four cans of product, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard box, constructed and closed in accordance with style RSC-L, class domestic, grade 275 of PPP-B-636. The cans shall be packed flat, four in depth within the box. The inside of each box shall be provided with a box liner and five fiberboard pads. The height of the box liner shall be equal to the full inside depth of the box (+0 inch, -1/8 inch). The pads shall be placed between the cans and on the top and bottom of the stacked cans. The pad dimensions shall be not less than 1/8 inch of the full length and width dimension of the box and shall be fabricated of the same material as the box.

5.3 Unit loading. When specified (see 6.1), the product, packed as specified in 5.2.2 and 5.2.3, shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified. When unit loads are strapped, the strapping shall be limited to nonmetallic strapping.

5.4 Labeling. Each tray pack can shall be labeled in accordance with MIL-L-1497. In addition, the name of product shall be marked, stamping is permitted, on one 1001 by 200 side of the can. The labeling shall be legible when examined in accordance with 4.7 after submerging the can in boiling water for 30 minutes. Paper labels are not permitted. Cans shall show the following statements:

Tray cans may be heated prior to serving or served at ambient temperature without heating. When heated, the following heating directions shall apply:

TO HEAT

a. To heat in water: Submerge unopened can in boiling water. Simmer gently 35 minutes. Avoid overheating to the point where internal pressure is evident (can shows evidence of bulging). Remove from water and open lid for serving. Caution: Use care when opening as pressure may have been generated within the can.

b. To heat in oven: Either punch several holes in lid of can or open can in usual manner leaving the loose lid in place to prevent moisture loss. Place in a 350°F oven for approximately 30 to 35 minutes until contents reach an internal temperature of 165°F.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:44Z
Check the source to verify that this is the current version before use.

WARNING: Do not place closed can in oven; as heating will increase internal pressure which may cause the can to burst.

YIELD

Approximately 25 servings of 1/2 cup each.

5.5 Marking.

5.5.1 Shipping containers. In addition to any special marking required by the contract, shipping containers shall be marked in accordance with MIL-STD-129.

5.5.2 Unit loads. Unit loads shall be marked in accordance with MIL-L-35078. In addition, the following precautionary markings in capital letters larger than other markings shall be included:

CAUTION: DO NOT STACK PALLETS IN TRANSIT OR MORE THAN TWO HIGH IN STORAGE.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

a. Title, number and date of this specification.
b. When a first article is required (see 3.1, 4.3, and 6.3).
c. Provisions for approved preproduction samples (see 3.6.1 and 6.3).
d. Level of packaging and packing required (see 5.1 and 5.2).
e. Type and class of unit load when unit loading is required (see 5.2.1 and 5.3).

6.2 Appropriate level of pack. Based on the conditions known or expected to be encountered during shipment, handling, and storage of the specific item being procured, the procuring activity should select the appropriate level of pack in accordance with the criteria established in AR 700-15/NAVSUPINST 4030.28/AFR 71-6/MCO 4030.33A/DLAR 4145.7.

6.3 First article inspection. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should include specific instructions in all acquisition documents regarding arrangements for inspection, selection, and approval of the first article.

Preparing activity:

Army - GL

Project No. 8940-A496

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:44Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
HHH-C-002134A(Army-GL	Carrots, Glazed, Thermostabilized, Tray PAck

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

NATICK OP, 20 Nov 84

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:44Z
Check the source to verify that this is the current version before use.