KKK-T-00728B (GSA-FSS)
November 22, 1976
Interim Revision of
Fed. Spec. KKK-T-728A
February 2, 1973

INTERIM FEDERAL SPECIFICATION

TRUCK, HAND, TWO-WHEELED (LIGHT DUTY) 300 POUND CAPACITY

This Interim Federal Specification was developed by the General Services Administration, Federal Supply Service, Washington, DC 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized the use of this Interim Federal Specification as a valid exception to Federal Specification KKK-T-728A, dated February 2, 1973.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers rigid frame and collapsible frame two-wheeled light duty hand trucks.

1.2 Classification.

1.2.1 Types and classes. Hand trucks covered by this specification shall be of the following types and classes as specified (see 6.2):

Type I - Rigid frame.

Class 1 - Light weight (aluminum or magnesium).
Class 2 - Medium weight (steel).

Type II - Collapsible frame.

Class 1 - Light weight (aluminum or magnesium).

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

PPP-B-636 - Boxes, Shipping, Fiberboard.
PPP-B-640 - Boxes, Fiberboard, Corrugated, Triple Wall.

Federal Standard:

Fed. Std. No. 123 - Marking for Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

PSC 3920

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specification:

MIL-P-116 - Preservation, Methods Of.

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., Traffic Department, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

3. REQUIREMENTS

3.1 Standard commercial product. All hand trucks shall, as a minimum, be in accordance with the requirements of this specification and shall be the manufacturer's current standard commercial product. Any features on the manufacturer's standard commercial product which are better than or in addition to those required by this specification and which are not specifically prohibited herein shall be included in the item being furnished. For purposes of this specification, standard commercial product is defined as a product which has been or will be sold on the commercial market through advertisments or manufacturers' catalogs or brochures; and represents the latest production items.

3.2 Materials. The frame of types I and II, class 1 trucks shall be made of aluminum or magnesium and be of tubular construction. The frame of type I, class 2 trucks shall be made of steel and be of tubular construction. Materials used for the other components of the truck shall be suitable for the purpose intended. All materials shall be free from defects or imperfections which may affect the appearance or serviceability of the trucks.

3.3 Wheels. Each truck shall be equipped with two wheels which are fabricated of steel, hard rubber, or suitable high impact plastic. The rated load capacity of each pair of wheels shall not be less than the test load requirements for the truck as specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.

3.3.1 Steel wheels. Steel wheels shall be provided with solid rubber tires which have a Shave Durometer hardness of not less than .70 on the A scale. The rubber tires shall have a thickness (i.e., wall height) of 1/4 ± .010 inch and a width across the tread and at the point of attachment to the wheel of 7/8 ± .030 inch. The diameter of the wheel including the rubber tire shall be 5 ± .250 inches.

3.3.2 Rubber wheels. Rubber wheels shall consist of a hard rubber disc with a softer rubber tread molded onto the disc. The wheel disc shall have a Shore Durometer hardness of not less than 70 nor more than 95 on the D scale. The wheel tread shall have a Shore Durometer hardness of not less than 70 nor more than 85 on the A scale. The width of the wheel at the hub and across the tread shall be 1-1/2 ± .055 inches. An oil impregnated powdered iron or powdered bronze bushing shall be molded into the center of the wheel. The diameter of the wheel, including both disc and tread, shall be 5 ± .250 inches.

3.4 Wheel bearings. Wheels shall be provided with either anti-friction or self-lubricating sleeve type bearings.

3.5 Handle. Each truck shall be provided with one or two handles. When provided with one handle, the handle shall be in the center of the truck. The handle shall be in the form of a suitable hand grip.

3.6 Vertical stability. The front end of the nose plates shall have a thin leveled loading edge to facilitate insertion under loads. The truck shall exhibit no tendency to tip over or tilt in a pronounced manner when examined in accordance with 4.3.1.

3.7 Type I trucks. The type I truck frame shall be of the rigid (noncollapsible) type. The frame shall consist of two side members, three or more cross members, nose plate, one or two handles, and wheel mounting brackets. Component frame members shall be joined together by bolts, rivets or welding. The overall dimensions of the truck shall be 46 ± 2.0 inches long by 14 ± 1.0 inches wide. The truck shall be equipped with a single nose plate which is a minimum of 10 inches front to back and a minimum of 14 inches wide.

3.7.1 Weights.

3.7.1.1 Class 1. The weight of type I, class 1 trucks shall not exceed 15 pounds.

3.7.1.2 Class 2. The weight of type I, class 2 trucks shall not exceed 25 pounds.

3.8 Type II truck. The type II truck frame shall be of the collapsible type. The frame shall consist of fixed and adjustable members to which shall be attached one or two handles, two functionally located nosepieces and two wheel mounting brackets. The two nosepieces, one on each side of the frame, shall be not less than 10 inches front to back when the truck is in the operation position. Component frame members shall be joined together by bolts, rivets, or welding. The frame shall be designed so that it can be extended or opened lengthwise and crosswise to its operation shape and can be folded or collapsed when not in use. A locking device shall be provided to secure and keep the frame rigid when in its extended or open position. The overall dimensions of the truck in its extended or open position shall not exceed 52 inches in length and not more than 13 inches in width at the widest position of the frame. The truck when folded or collapsed shall occupy a space not larger than 38 by 6 by 8 inches. Means shall be provided, such as straps, clamps, or latches, to secure the truck in its folded or collapsed position.

3.8.1 Weight. The weight of type II, class 1 trucks shall not exceed 15 pounds.

3.9 Truck capacity. The types I and II hand trucks shall have a working capacity of 300 pounds plus an overload safety factor of 100 pounds. Trucks shall show no evidence of damage or permanent deformation when tested in accordance with 4.3.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.

3.10 Welds. Welding, when applicable, shall be in accordance with good commerical practice and shall be sound and not have burnt holes, cracks, fractures, or incomplete fusions. The surfaces of parts to be welded shall be free from rust, scale, paint, grease, and other foreign matter.

3.11 Rivets. Rivets, when applicable, shall have full concentric heads, shall be flush to the joining member, and shall not be cracked, fractured, or broken.

3.12 Threaded fasteners. Bolts or other threaded fasteners used to join the various parts of the truck together shall be adequate in design and fabrication for the intended purposes. Bolt holes shall be accurately punched or drilled and shall have burrs removed. Washers or lock washers shall be provided in accordance with good commercial practice.

3.13 Finish. Type I, Class 2 hand trucks shall be suitably finished to inhibit corrosion. Unless a specific finish is specified (see 6.2), these trucks shall be plated or painted at the manufacturer's option. Plating shall be in accordance with good commercial practice. When a painted finish is supplied, the trucks shall have one coat of primer applied prior to painting. A durable, weatherproof paint shall be used. Unless otherwise specified in the contract or purchase order (see 6.2), any color normally furnished by the manufacturer on his commercial trucks will be acceptable.

3.14 Marking. Each hand truck shall be marked in a permanent manner with the manufacturer's name or with a trademark of such known character that the source of manufacture may be readily determined.

3.15 Instructions. The manufacturer shall furnish with each type II hand truck a pamphlet or leaflet giving complete instructions for extending or opening the truck and placing it in service and for collapsing or folding and securing the truck.

3.16 Workmanship. Workmanship shall be first class in every respect. The hand trucks shall be free from sharp edges, slivers, and burrs that may be injurious to personnel and any other defects affecting appearance and serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Inspection for acceptance. Inspection shall be made in accordance with the provisions set forth in MIL-STD-105, except where otherwise indicated hereinafter.

4.2.1 End product inspection.

4.2.1.1 Visual examination. The sample unit shall be one completely assembled end item. The inspection level shall be level II and the acceptable quality levels (AQL's) shall be 4.0 for major defects and 10.0 for total defects, expressed in terms of defects per hundred units. Defects shall be classified as outlined in table I for recording of inspection results and corrective action. Results shall be kept available for review by the Government inspectors.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects

Examine	Defects	Classification Major	Minor
Finish	Type of finish not as specified; blistered, peeled, chipped, or area of no film or thin film.	X	
Material	Component not fabricated of the specified material.	X	
Design	Any characteristic not in accordance with the specified requirements.	X	
Construction and workmanship	Part missing or not specified type or size.	X	
	Damage or defects affecting serviceability or durability.	X	
	Damage or defects not affecting serviceability or durability.		X
	Sharp burr, sliver, or sharp edge that may be injurious to personnel or may affect serviceability.	X	
	Type II truck difficult to extend and collapse.		X
Welding (when applicable)	Missing, incomplete, burn holes, cracked, fractured, or otherwise not fused.	X	
Bolts, nuts, screws, studs, and other types of thread fasteners (when applicable).	Missing, not type specified, broken, stripped, or fractured.	X	
	Not properly tightened.		X
Assembly	Component not properly assembled or secured but not affecting serviceability.		X
	Component not properly assembled or secured affecting serviceability.	X	
	Unit perceptibly out of square or alignment.	X	
Marking	Missing, incomplete, or not legible.		X

4.2.1.2 Dimensional examination. Examination shall be made of the end item to determine compliance with dimensional requirements. Any dimension that exceeds the specified tolerance shall be classified a defect. The inspection level shall be S-2 with an acceptable quality level (AQL) of 6.5 defects, expressed in defects per hundred units.

4.2.1.3 Sampling for tests. A random sample of hand trucks shall be taken from each inspection lot in accordance with MIL-STD-105 at inspection level S-3 for tests of 4.3. If any truck fails any of the tests, the lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:46Z
Check the source to verify that this is the currentversion before use.

4.3 Tests.

4.3.1 Stability. The truck shall be placed in a position resting on its wheels and nose plate on a level surface. All outside support shall be removed from the truck and observation shall be made for conformance to 3.6.

4.3.2 Load bearing and transporting. The nose plate of the truck shall be inserted under a 400 pound load. The load shall be lifted from the floor by applying the necessary force on the handle(s) of the truck. The loaded truck shall be rolled in normal working position a distance of 100 feet three times. On each trip the trucks shall be rolled over three 1/2 by 3 inch wood strips which are secured in a flat position on the test surface. The strips shall be generally parallel and 3 inches apart. The truck is to be rolled at a minimum speed of 3 miles per hour (4.4 feet per second). Upon completion of the three runs, the truck shall be placed in a horizontal position on the floor and the 400 pound load shall be placed on the truck bed at the center. After a period of 1 minute, the truck shall be unloaded and visually examined for damage or deformation (see 3.9).

4.4 Inspection of preparation for delivery requirements. An inspection shall be made to determine that packaging, packing, and marking requirements of section 5 of this specification are complied with. Defects shall be scored in accordance with table II. For examination of contents the sample unit shall be one shipping container fully prepared for delivery selected just prior to the closing operations. Defects of closure listed shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and the AQL shall be 4.0 defects per hundred units.

TABLE II. Classification of preparation for delivery defects

Examine	Defects
Markings (exterior and interior)	Omitted; incorrect; illegible; or improper size, location, sequence, or method of application.
Materials	Any component missing or damaged.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose strapping, inadequate stapling. Bulging or distortion of container.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A, B, or C as specified (see 6.2).

5.1.1 Level A. Each truck shall be preserved in accordance with MIL-P-116, method II.

5.1.2 Level B. Each truck shall be packaged in a close-fitting box conforming to PPP-B-636, class domestic, style optional. Blocking and bracing shall be provided to prevent movement during shipment and storage. The box shall be closed in accordance with the appendix to the box specification. The gross weight shall not exceed the weight limitations of the box specification.

5.1.3 Level C. Each truck shall be preserved and packaged in accordance with the manufacturer's standard practice, providing that this insures protection for the trucks during shipment and provides for safe delivery to their destination.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. Trucks of like description, packaged as specified in 5.1, shall be packed in a close-fitting box conforming to PPP-B-636, class weather resistant, or PPP-B-640, class 2. The boxes shall be closed in accordance with the appendix to the box specification. The gross weight of the box shall not exceed the weight limitations of the applicable box specification. Strapping shall be in accordance with the appendix to the applicable box specification.

5.2.2 Level B. When specified (see 6.2), trucks of like description, packaged as specified in 5.1, shall be packed in a close-fitting box conforming to PPP-B-636, class domestic, style optional. The box shall be closed in accordance wtih the appendix to the box specification. The gross weight shall not exceed the weight limitations of the box specification.

5.2.3 Level C. Trucks, preserved and packaged as specified in 5.1.3, shall be packed in containers that will assure carrier acceptance and safe arrival at destination in compliance with the National Motor Freight Classication rules and the Uniform Freight Classification rules.

5.3 Marking. Marking shall be in accordance with 5.3.1 or 5.3.2 as specified (see 6.2).

5.3.1 Civil agencies. Packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.3.2 Military agencies. Packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The hand trucks covered by this specification are intended for use in trucking boxes and other flat freight in such areas as offices, hospitals, stores, shops, and warehouses and are also intended for use on delivery trucks.

6.2 Ordering data. Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Type and class required (see 1.2.1).
(c) If a specific finish is required (see 3.13).
(d) If a specific color of paint is required (see 3.13).
(e) Level of preservation and packaging required (see 5.1).
(f) Level of packing required (see 5.2).
(g) When packing is required for level B (see 5.2.2).
(h) Whether civil or military marking is required (see 5.3.1 and 5.3.2).

MILITARY CUSTODIANS:

Army - ME
Navy - YD
Air Force - 84

Review activities:

Army - GL, SM

MILITARY COORDINATING ACTIVITY:

Army - ME

PREPARING ACTIVITY: GSA - FSS

GSA DC 77-3158

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.