KKK-T-728A
February 2, 1973
SUPERSEDING
Int. Fed. Spec. KKK-T-00728(GSA-FSS)
May 13, 1964

FEDERAL SPECIFICATION

TRUCK, HAND, TWO-WHEELED (LIGHT DUTY)
300 POUND CAPACITY

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers rigid frame and collapsible frame two-wheeled light duty hand trucks.

1.2 Classification.

1.2.1 Types and classes. Hand trucks covered by this specification shall be of the following types and classes as specified (see 6.2):

Type I - Rigid frame.
Class 1. - Light weight (aluminum or magnesium).
Class 2 - Medium weight (steel).

Type II - Collapsible frame.
Class 1 - Light weight (aluminum or magnesium).

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

QQ-P-416 - Plating, Cadmium (Electrodeposited).
PPP-B-585 - Boxes, Wood, Wirebound.
PPP-B-591 - Boxes, Shipping, Fiberboard, Wood-Cleated.
PPP-B-601 - Boxes, Wood, Cleated-Plywood.
PPP-B-621 - Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636 - Boxes, Shipping, Fiberboard.
PPP-B-640 - Boxes, Fiberboard, Corrugated, Triple Wall.

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)



Source: https://assist.dla.mil -- Downloaded: 202610-26T12:46Z
Check the source to verify that this is the current version before use.

Military Specification:

MIL-P-116 - Preservation, Methods Of.

Military Standards:

MIL-STD-165 - Sampling Procedures and Tables for inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in confection with specific procurment functions should be obtained from the procuring agency or as directed by the contracting officer.)

2.2 Other publications. The following documents from a pert of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of incitation for bids or request for proposal shall apply.

National Bureau of Standards.

Handbook: H28-Screw--Thread Standards for Federal Services.

(Class may be obtained from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

Unfirom Classification committee, agent:

Uniform Freight Classification.

{Application for copies should be addressed to the Uniform Classification Committe, Room 1106, 22 South Riverside Plaza, Chicago, IL 60606. )

National Motor Freight Traffic Associatio, Incorporated, Agent:

National Motor Freight Classification.

(Application far copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, NW, Washington, DC 20036.)

3. REQUIREMENTS

3.1 Standard product. Hand trucks covered by this Specification shall be the manufacturer's standard commercial product except for those modifications or changes required in order to comply with this specification.

3.2 Materials. The frame of types I and II, class trucks shall be made of alumimum or magnesium and be of tubular construction. The frame of type I, class 2 trucks shall be made of steel and be of tubular construction. Materials used for the other components of the truck stall be suitable for the purpose intended. All materials shell be free from defects or imperfections which may affect the l ppearame or serviceability of the trucks.

3.3 Wheels. Each truck shall be equipped with two robber tired steel wheels or two solid rubber wheels. The rated load capacity of each pair of wheels shall be not less than the test load requirements of the truck as specified herein.

3.3.1 Steel wheels. Steel wheels shall be provided with solid rubber tires hawing a thickness of not less than 1/4-inch and a width of not less than 7/8-inch. The wheel diameter, including the rubber tire, shall be not less than 5 inches.

3.3.2 Solid rubber wheels. Solid rubber -sheds shall consist of a hard rubber disc with a softer robber tread molded on the disc. Tine wheel disc shall have a Shore Durometer hardness of not less than 55 nor more than 65 an the D scale. The wheel tread shall have a Durometer hardness of not less that at nor more than 90 on the A scale. The width of ‘the wheel at the center or hub and across the tread shall be not less than 1-1/2 inches. The diameter of the wheel shall be not less that 5 inches. An all impregnated powdered iron or powdered bronze bushing shall be molded into the center of the wheel.

3.4 Wheel bearings. The wheels shall be provided with either anti-friction or self lubricating sleeve type bearings.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.

3.5 Handle. Each truck shall be provided with one or two handles. When provided with one handle, the handle shall be in the center of the truck. The handle shall be in the form of a suitable hand grip.

3.6 Nose plate. The front end of the nose plates shall have a thin beveled loading edge to facilitate insertion under loads. The truck shall steal upright on a level floor when resting on its nose plate and wheels.

3.7 Type I trucks. The type I truck frame shall be of the rigid (non-collapsible) type. The frame shall consist of two side members, three or more cross members, nose plate, one or two handles, and wheel mounting brackets. Component frame members shall be. joined together by bolts, rivets or welding. The overall dimensions of the truck shall be approximately 46 inches long by 14 inches wide. The truck shall be equipped with a single noes plate minimum 10 inches front to back and 14 inches tide.

3.7.1 Weights.

3.7.1.1 Class 1. The weight of type I, class 1 trucks shall not exceed 15 pounds.

3.7.1.2 Class 2. The weight of type I, class 2 trucks shall not exceed 25 pounds.

3.8 Type II truck. The type II truck shall be of the collapsible type. The frame shall consist of fixed and adjustable members to which shall be attached one or two handles, two functionally located nosepieces and the wheel mounting brackets. The two nosepieces, one on each side of the frame, shall be not less than 10 inches front to back when the truck is in the operation position. Component frame members shall be joined together by bolts, rivets, or welding. The frame shall he designed so that it cm be extended or opened lengthwise and crosswise to its operation shape and can be folded or collapsed when not in use. A locking device shall be provided to secure and keep the frame rigid when in its extended or open position. The overall dimensions of the truck in its extended or open position shall not exceed 52 inches in length and not more than 13 inches in width at the widest position Of the frame. The truck when folded or collapsed shall occupy a space not larger than 38 by 6 by 8 inches. Means shall be provided, such as straps, clamps, or latches, to secure the truck in its folded or collapsed position.

3.8.1 Weight. The weight of type II, class 1 trucks shall not exceed 15 pounds.

3.9 Truck capacity. The types I and II hand trucks shall have a working capacity of 300 pounds plus an overload safety factor of 100 pounds.

3.10 Performance. The hand truck shall be capable of picking up on the nose plate a load of 400 pounds (see 3.) and transporting such load over concrete or wood floors and sills normally encountered in warehouses and loading platforms without sustaining any damage or permanent deformation.

3.11 Welds. Welding, when applicable, shall be in accordance with good commercial practice and shall be sound and not have burnt holes, cracks, fractures, or incomplete fusions. The surfaces of parts to be welded shall be free from rust, scale, paint, grease, and other foreign matter.

3.12 Rivets. Rivets, when applicable, shall have full concentric heads, shall be flush to the joining member, and shall not be cracked, fractured, or broken.

3.13 Threaded fasteners. All screw threads, when applicable, shall comply with the National Bureau of Standards Handbook H28. Unified screw threads shall be used in lieu of American National screw threads and non-unified American Standard screw threads. Boltholes shall be accurately punched or drilled and shall have burrs removed. dashers or lockwashers shall be provided in accordance with good commercial practice and all bolts, nuts, and screws shall be tight.

3.14 Finish. Type I, class 2 hand trucks shell be either cadmium plated or painted as specified (see 6.2). When cadmium plated, plating shall be in accordance with QQ-P-416, type II, class 3. When painted the truck shall be finished with one coat of primer prior to painting. A durable weatherproof paint shall be used and unless otherwise specified in the contract or order (see 6.2), any color normally furnished by the manufacturer will be acceptable.

3.15 Marking. Each hand truck shall be marked in a permanent manner with the manufacturer's name or with a trademark of such known character that the source of manumfacture may be readily determined.

3.16 Instructions. The manufacturer shall furnish with each type II hand truck a pamphlet or leaflet giving complete instructions for extending or opening the truck and placing it in service and for collapsing or folding and securing the truck.

3.17 Workmanship. Workmanship shall be first class in every respect. The hand trucks shall be free from sharp edges, slivers, and burrs that may be injurious to personnel and any other defects affecting appearance and serviceability.



Source: https://assist.dla.mil -- Downloaded: 2026t0-26T12:46Z
Check the source to verify that this is the current version before use.

## 4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirments as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Inspection for acceptance. Inspection shall be the in accordance with the previsions set forth in MIL-STD-105, except where otherwise indicated herinafter.

4.2.1 Inspection of materials and comments. n accordance with 4.1, the supplier is responsible for insuring that components and materials used were manufactured, tested, and inspected in accordance with the specified requirements or referenced subsidiary specifications and standards to the extent specified herein or, if none, in accordance with this specification.

4.2.2 Intermediate visual and dimensional examination. The intermediate product or assemblies which cannot be checked or measured after final assembly shall be examined at various stages of manufacture for compliance with this specification. Examination shall be made at an appropriate intermediate station for defects in construction, workmanship, dimensions, and material. Any deviation from specified requirements shall be classified a defect.

4.2.3 End product inspection.

4.2.3.1 Visual examination. The sample unit shall be one completely assembled end item. The inspection level shall be level II and the acceptable quality levels (AQL) shall be 4.0 for major defects and 10.0 for total defects, expressed in terms of defects per hundred units. Defects shall be classified as outlined in table I for recording of inspection results and corrective action. Results shall be kept available for reviev by the Government inspectors.

TABLE I. Classification of defects

| Examine | Defect | Classification Major | Classification Minor |
|---|---|---|---|
| Finish | Type of finish not as specified; blistered, peeled, chipped, or area of no film or thin film. | | X |
| | Not finished where required. | X | |
| Material | Component not fabricated of the specified material. | X | |
| Design | Any characteristic not in accordance with the specified requirements. | X | |
| Construction and workmanship, general (applicable to all components and assemblies) | Part missing or not specified type or size. | X | |
| | Fractured, split, punctured, dented, deteriorated, bowed, malformed, or otherwise impaired affecting serviceability. | X | |
| | Defective or otherwise damaged but not affecting serviceability. | | X |
| | Misplaced, loose, or not in proper alignment affecting serviceability. | X | |
| | Sharp burr, sliver, or sharp edge that may be injurious to personnel or may affect serviceability. | X | |
| | Operation omitted or not properly performed affecting serviceability. | X | |
| | Operation omitted or not properly performed but not affecting serviceability. | | X |
| | Type II truck difficult to extend and collapse. | | X |
| | Not connected or joined as specified or poorly accomplished, affecting serviceability. | X | |
| Welding (when applicable) | Not type specified, missing, incomplete, burn holes, cracked, fractured, or otherwise not fused. | X | |



Source: https://assist.dla.mil -- Downloaded: 202610-26T12:46Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects (cont'd)

| Examine | Defect | Classification Major | Minor |
|---|---|---|---|
| Bolts, nuts, screws, studs, and other types of threaded fasteners (when applicable). | Missing, not type specified, broken, stripped, fractured, or loose. | X | |
| Lubrication | Not lubricated where required. | X | |
| | Insufficiently lubricated. | | X |
| Assembly | Component not properly assembled or secured but not affecting serviceability. | | X |
| | Component not properly assembled or secured affecting serviceability | X | |
| | Unit perceptibly out of square or alignment. | X | |
| Marking | Missing, incomplete, or not legible. | | X |

4.2.3.2 Dimensional examination. Examination shall be made of the end item to determine compliance with dimensional requirements. Any dimension that exceeds the specified tolerance shall be classified a defect. The inspection level shall be S-2 with an acceptable quality level (AQL) of 6.5 defects, expressed in defects per hundred units.

4.2.3.3 Sampling for tests. A random sample of hand trucks shall be taken each inspection lot in accordance with MIL-STD-105 at inspection level S-3 for tests of 4.3. If any truck falls any of the tests, the lot shall be rejected.

4.3 Tests.

4.3.1 Stability. The truck shall be placed on its noes plate and wheels on a level floor to determine that it stands upright in conformance to 3.6.

4.3.2 Nose plate loading. The nose plate shall be placed under a 400 pound load and the load lifted from the floor by applying the necessary force on one truck handle. The truck shall be examined for any damage and permanent deformation to determine conformance to 3.10.

4.3.3 Static loading. With the truck resting in a horizontal position on the floor, a 400 pound load shall be placed on truck bed at the center of the truck and the truck examined for any damage and permanent deformation.

4.3.4 Load transporting. A 400 pound load shall be placed on the truck and the truck rolled in normal working position a distance of 100 feet three times. On each trip the truck shall be rolled over three 1/2 by 3 inch wood strips lying flat and hold stationary on the floor with the strips spaced 3 inches apart. The truck shall be rolled at a speed of not less than 3 miles per hour (4.4 feet per second). At the end of the run the truck shall be examined for any damage and permnent deformation.

4.4 Inspection of preparation for delivery requirements. An inspection shall be made to determine that packaging, packing and marking requirements of section 5 of this specification are complied with. Defects shall be scored in l ccordanoa with table II. For examination of contents the sample unit shall be one shipping container fully prepared for delivery selected just prior to the closing operations. Defects of closure listed shall be examined on shipping containers fully prepared for delivery. The lot sise shall be the number of shipping containers in the end item inspection lot. The inspection level shall be II and the AQL shall be 4.0 defects per hundred units.

TABLE II. Classification of preparation for delivery defects

| Examine | Defect |
|---|---|
| Markings (exterior and interior) | Omitted; incorrect; illegible; or improper size, location, sequence, or method of application. |
| Materials | Any component missing, or damaged. |
| Workmanship | Inadequate application of components such as incomplete closure of container flaps, loose strapping, inadequate stapling. Bulging or distortion of container. |



Source: https://assist.dla.mil -- Downloaded: 202610-26T12:46Z
Check the source to verify that this is the current version before use.

## 5. PREPARATION MOVEMENT

5.1 Preservation and packaging. Preservation and packaging shall be level A, B, or C as specified (see 6.2).

5.1.1. Level A. Each truck shall be preserved and packaged in accordance with MIL-P-116, Method III.

5.1.2 Level B. Each truck shall be packaged in a close-fitting box conforming to PP-B-636, class domestic. Blocking and bracing shall be provided. The box shall be closed in aaccordance with the. appendix to the box specification. The gross weight shall not exceed the weight limitations of the box specification.

5.1.3 Level C. Each truck shall in preserved and packaged in accordance with the manufacturer's standard practice, providing that this insures protection for the trucks during shipment and provides for safe delivery to their destination.

5.2 Packing. Packing shall be level A, B or C as specified (see 6.2).

5.2.1 Level A. Type I trucks or like description or type II trucks (collapsed to the minimum size) of like description shall be packed in a close-fitting box conformable to PPP-B-585, class 3, PPP-B-591, class II, PPP-B-601, overseas type, PPP-B-621, class 2, PPP-B-636, class weather resistant, or PPP-B-640, class. 2. Blocking and bracing shall be provided. The fiberboard boxes shall be closed in accordance with the appendix to the box specification. The grass weight of the triple wall fiberboard box and the wood boxes shall not exceed approximately 200 pounds. The gross weight of the PPP-B-636 fiberboard box shall not exceed the weight limitations of the box specification. Strapping shall be in accordance with the appendix to the applicable box specification.

5.2.2 Level B. Type I trucks of like description or type II trucks (collapsed to the minimum side) of like description shall be packed in a close-fitting box conforming to PPP-B-636, class domestic. Blocking and bracing shall be provided. The box shall be closed in accordance with the appendix to the box Specification. The gross gross weight shall not exceed the weight limitations of the box specification. For Army shipments only rely, the box shall conform to PPP-B-636, class weather resistant.

5.2.2 Level C. The trucks, preserved and packaged as specified in 5.?.?, shall be packed in containers that will assure carrier acceptance and safe arrival at description in compliance with the Uniform Freight Classfication and the National Motor Freight Classification. Unless otherwise specified (see 6.2), fiberboard boxes used for Army shipments shall be in accordance with PPP-B-636, class weather resistant.

5.3 Marking.

5.3.1 Civil agencies. In addition to markings required by the contract or order (see 6.2), the packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.3.2 Military agencies. In addition to markings required by the contract or order ( sec 6.2), the packages and shipping containers shall be marked in accordance with MIL-STD-129.

## 6. NOTES

6.1 Intended use. The hand trucks covered by this specification are intended for use in trucking boxes and other flat freight in such areas as offices, hospitals, stores, shops, and warehouses and are also intended for use on delivery trucks.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents.

(a) Title, number, and date of this specification.
(b) Type and class required (see 1.2.1).
(c) Whether type I, class 2 hand trucks shall be plated or painted (see 3.14).
(d) Color if different. from 3.14.
(e) Level of packaging required (see 5.1).
(f) Level of packing required (see 5.2).
(g) When class domestic fiberboard boxes shall be used for Army shipments.
(h) [illegible]



Source: https://assist.dla.mil -- Downloaded: 202610-26T12:46Z
Check the source to verify that this is the current version before use.

MILITARY CUSTODIANS:

Army-ME
Navy - YD
Air Force - 84

Review activities:

Army - GL, SM

MILITARY COORDINATING ACTIVITY:

Army - ME

Preparing activity:

GSA FS3

U. S. GOVERNMENT PRINTING OFFICE : 1973 O - 514-177 ( 369 )

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 10 cents each.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:46Z
Check the source to verify that this is the current version before use.